Axis Communicatio	ons			JANU	ARY-2024
Product Name	High volume order	Status	Product Number US	Standard Lead Time	Product Category
2N AC - BOX PC	10		01672-001	2	2N Access Control and Intercoms
2N AU - BLUETOOTH	5	Discontinued	01368-001	2	2N Access Control and Intercoms
2N AU - RJ45 CONNECTOR CABLE	5		01371-001	2	2N Access Control and Intercoms
2N AU 2.0 COMBI BLUETOOTH RFID NFC SEC	20	Discontinued	01851-001	2	2N Access Control and Intercoms
2N AU 2.0 COMBI KEYPAD RFID NFC SEC	10	Discontinued	01852-001	2	2N Access Control and Intercoms
2N AU 2.0 COMBI RFID 125kHz 13MHz NFC SEC	5	Discontinued	01850-001	2	2N Access Control and Intercoms
2N AU - RFID 125kHz 2G	10		02137-001	2	2N Access Control and Intercoms
2N AU 2.0 RFID 125k/13M NFC SEC 2G	15		02146-001	2	2N Access Control and Intercoms
2N AU 2.0 - 13.56MHz NFC SEC, 2G	5		02142-001	2	2N Access Control and Intercoms

		Discontinued	00440.004	•	
2N AU 2.0 - RFID 13.56MHz NFC,2G	5	Discontinued	02143-001	2	2N Access
					Control and
					Intercoms
2N AU 2.0 Touch keypad	20		02262-001	2	2N Access
					Control and
					Intercoms
2N AU 2.0 Fingerprint reader	5		02263-001	2	2N Access
					Control and
					Intercoms
2N AUM - RFID 13.56 MHz, NFC READY	10	Discontinued	02393-001	2	2N Access
					Control and
					Intercoms
2N AU M 13.56 MHz NFC	10		02909-001	2	2N Access
					Control and
					Intercoms
2N AUM-RFID 13.56MHz&125kHz	5	Discontinued	02394-001	2	2N Access
	_				Control and
					Intercoms
2N AU M 125kHz 13.56MHz NFC	5		02910-001	2	2N Access
	, i i i i i i i i i i i i i i i i i i i			-	Control and
					Intercoms
2N AUM-BT&13MHz, 125kHz, NFC	20	Discontinued	02395-001	2	2N Access
ZN AOM-DIQISMINZ, IZSKNZ, NFC	20	Discontinueu	02395-001	2	Control and
					Intercoms
					intercoms
2N AU M BT&RFID125kHz 13.56MHz NFC	20		02911-001	2	2N Access
ZN AU M BIARFIDIZSKIZ 13.50MHZ NFC	20		02911-001	2	Control and
					Intercoms
	15	Discontinued	00000 004	2	
2N AUM-TOUCH KEY&13M,125k, NFC	15	Discontinued	02396-001	2	2N Access Control and
					Intercoms
2N AU M KPD&RFID 125k 13.56M NFC	15		02912-001	2	2N Access
	10		02012-001	2	Control and
					Intercoms
2N Access Unit M Flush Box	5		02940-001	2	2N Access
	5		02940-001	2	Control and
					Intercoms
2N Access Unit M mounting spacer	5		02932-001	2	2N Access
2N Access onit m mounting spacer	5		02932-001	2	
					Control and
			00775 004		Intercoms
2N AU2.0 KPD&RFID125,13.56secNFC	5		02775-001	2	2N Access
					Control and
					Intercoms
2N AU2.0 KPD&RFID125,13.56NFC	5		02774-001	2	2N Access
					Control and
					Intercoms
2N AU2.0 BLE RFID125,13.56secNFC	10		02773-001	2	2N Access
					Control and
					Intercoms
2N AU2.0 BLE RFID125,13.56NFC	5		02772-001	2	2N Access
					Control and
					Intercoms
2N AU2.0 KPD,BLE&RFID125,13secNFC	5		02777-001	2	2N Access
					Control and
					Intercoms
2N AU2.0 KPD,BLE&RFID125,13.56NFC	5		02776-001	2	2N Access
· · · · · · · · · · · · · · · · · · ·				-	Control and
					Intercoms
		1			

2N IP AUDIO KIT	10	04526 004	2	
	10	01526-001	2	2N Access Control and
				Intercoms
2N IP AUDIO KIT - MIC & SPK SET	5	01478-001	2	2N Access
	5	01478-001	2	Control and
				Intercoms
2N IP AUDIO KIT - BUTTON	5	01479-001	2	2N Access
2N IP AUDIO KIT - BUTTON	5	01479-001	2	2N Access Control and
				Intercoms
2N IP AUDIO KIT - SPEAKER	5	02571-001	2	
IZN IP AUDIO KIT - SPEARER	5	02571-001	2	2N Access Control and
				Intercoms
2N IP AUDIO KIT - MICROPHONE	5	02570-001	2	
	5	02570-001	2	2N Access
				Control and
		04057.004	•	Intercoms
2N IP BASE - CAM BLACK	30	01357-001	2	2N Access
				Control and
		04050 004	•	Intercoms
2N IP BASE - 125kHz RFID	5	01358-001	2	2N Access
				Control and
		04050 004	•	Intercoms
2N IP BASE - 13.56MHz RFID	5	01359-001	2	2N Access
				Control and
	45	04000.004	•	Intercoms
2N IP BASE - BACKPLATE	15	01360-001	2	2N Access
				Control and
				Intercoms
2N IP BASE DOUBLE BUTTON	5	02017-001	2	2N Access
				Control and
				Intercoms
2N IP Base Single button	5	02228-001	2	2N Access
				Control and
		00000.004		Intercoms
2N IP BASE UPPER METAL FIXTURE	5	02362-001	2	2N Access
				Control and
				Intercoms
2N IP BASE SEALING	5	02402-001	2	2N Access
				Control and
ANUS FORCE A RTN US CAM DIGT		04004.004		Intercoms
2N IP FORCE - 1 BTN, HD CAM, PICT.	20	01334-001	2	2N Access
				Control and
		04005-004		Intercoms
2N IP FORCE - 1 BTN, PICT.	5	01335-001	2	2N Access
				Control and
		04000.004		Intercoms
2N IP FORCE - 1 BTN	10	01336-001	2	2N Access
				Control and
	400	04007.004		Intercoms
2N IP FORCE - 1 BTN + HD CAM	100	01337-001	2	2N Access
				Control and
		04000.004	^	Intercoms
2N IP FORCE - 1 BTN + KEYPAD	5	01338-001	2	2N Access
				Control and
				Intercoms
2N IP FORCE - 1 BTN + HD CAM + KPD	20	01339-001	2	2N Access
				Control and
				Intercoms

2N IP FORCE - 2 BTN + HD CAM	20	01340-001	2	2N Access
				Control and Intercoms
2N IP FORCE - 2 BTN	5	01241 004	2	
2N IP FORCE - 2 BIN	5	01341-001	2	2N Access Control and
2N IP FORCE - 4 BTN	10	01242.001	2	Intercoms
2N IP FORCE - 4 BIN	10	01342-001	2	2N Access
				Control and
2N IP FORCE - 4 BTN + HD CAM	45	01242.001	0	Intercoms
2N IP FORCE - 4 BIN + HD CAM	15	01343-001	2	2N Access
				Control and
2N IP FORCE - 125kHz RFID	15	01211 001	2	Intercoms
	15	01344-001	2	2N Access
				Control and
				Intercoms
2N IP FORCE - SAFETY SCREWS	15	01345-001	2	2N Access
ZN IF FORCE - SAFETT SCREWS	15	01345-001	2	Control and
				Intercoms
2N IP FORCE - 13.56MHZ SEC RFID	5	01730-001	2	2N Access
ZN IF FORCE - 13.30MINZ SEC RFID	5	01/30-001	2	Control and
				Intercoms
				intercoms
2N IP FORCE TORX SCREW BLACK	5	01735-001	2	2N Access
	, , , , , , , , , , , , , , , , , , ,		-	Control and
				Intercoms
2N IP FORCE FRAME	5	01734-001	2	2N Access
	, , , , , , , , , , , , , , , , , , ,	01104 001	-	Control and
				Intercoms
2N IP FORCE PANEL4 BUTTONS	5	01736-001	2	2N Access
	•		-	Control and
				Intercoms
2N IP FORCE PANEL 1 BUTTON	5	01737-001	2	2N Access
			_	Control and
				Intercoms
2N IP FORCE PANEL 1 BTN PICTOGRAMS	5	01738-001	2	2N Access
				Control and
				Intercoms
2N IP FORCE PANEL 1 BTN KEYPD READY	5	01739-001	2	2N Access
				Control and
				Intercoms
2N IP FORCE PANEL 2 BTN CARD READER	5	01740-001	2	2N Access
				Control and
				Intercoms
2N IP FORCE/SAFETY - FLUSH BOX	10	01348-001	2	2N Access
				Control and
				Intercoms
2N IP FORCE/SAFETY - PLASTER BOX	10	01349-001	2	2N Access
				Control and
				Intercoms
2N IP FORCE/SAFETY - ADD.SWITCH	15	01350-001	2	2N Access
				Control and
				Intercoms
2N IP FORCE/SAFETY - GOOSENECK	20	01351-001	2	2N Access
				Control and
				Intercoms

			-	
2N IP FORCE/SAFETY - INST. ADAPTER	15	01352-001	2	2N Access
				Control and
				Intercoms
2N IP FORCE /SAFETY - DBL GOOSENECK	5	01550-001	2	2N Access
				Control and
				Intercoms
2N IP FORCE SAFETY SET OF BUSHINGS	5	01733-001	2	2N Access
				Control and
				Intercoms
2N IP FORCE SECURE DOOR	10	01976-001	2	2N Access
				Control and
				Intercoms
2N IP FORCE KEYPAD	5	01873-001	2	2N Access
				Control and
				Intercoms
2N IP Force Induction loop	5	02338-001	2	2N Access
				Control and
				Intercoms
2N IP SAFETY - 1 BTN	15	01353-001	2	2N Access
				Control and
				Intercoms
2N IP SAFETY - 2 BTN	5	01354-001	2	2N Access
				Control and
				Intercoms
2N IP SAFETY - RED BTN	10	01355-001	2	2N Access
				Control and
				Intercoms
2N IP SAFETY - FRAME	5	01356-001	2	2N Access
			-	Control and
				Intercoms
2N IP SAFETY PANEL 1 BUTTON	5	01870-001	2	2N Access
			-	Control and
				Intercoms
2N IP SAFETY PANEL INFO/SOS	5	01871-001	12	2N Access
				Control and
				Intercoms
2N IP SAFETY TORX SCREWS	5	01872-001	2	2N Access
			-	Control and
				Intercoms
2N IP SAFETY BLUE BUTTON	5	01869-001	2	2N Access
	, i i i i i i i i i i i i i i i i i i i		-	Control and
				Intercoms
2N IP SOLO - FLUSH MOUNT	15	01300-001	2	2N Access
	10	01000-001	-	Control and
				Intercoms
2N IP SOLO - SURFACE MOUNT	100	01301-001	2	2N Access
	100	01301-001	2	Control and
				Intercoms
2N IP SOLO - SURFACE MOUNT BLACK	E0	01202.001	2	
ZIN IF JULU - JUKFACE WUUNT DLACK	50	01302-001	2	2N Access
				Control and Intercoms
	15	04202.004	0	
2N IP SOLO - FLUSH MOUNT BLACK	15	01303-001	2	2N Access
				Control and
				Intercoms
2N IP SOLO - FLUSH BACKBOX	30	01304-001	2	2N Access
				Control and
				Intercoms

2N IP SOLO - BACKPLATE	100	01305-001	2	2N Access
ZN IF SOLO - BACKPLATE	100	01303-001	2	Control and
				Intercoms
2N IP SOLO GLASS MOUNT	10	02078-001	2	2N Access
		02070-001	2	Control and
				Intercoms
2N IP SOLO SURFACE BLACK WO CAMERA	5	02202-001	2	2N Access
	J J	02202-001	-	Control and
				Intercoms
2N IP SOLO SURFACE WO CAMERA	10	02203-001	2	2N Access
		02200-001	-	Control and Intercoms
2N IP SOLO FLUSH BLACK WO CAMERA	5	02204-001	2	2N Access
		02204-001	-	Control and Intercoms
2N IP SOLO FLUSH WO CAMERA	5	02205-001	2	2N Access
2N IF SOLO FLUSH WO CAMERA	5	02203-001	2	Control and Intercoms
2N IP STYLE FLUSH BOX	10	02405-001	2	2N Access
				Control and
				Intercoms
2N IP STYLE SURFACE CHASSI	20	02406-001	2	2N Access
				Control and
				Intercoms
2N MAIN UNIT, SEC, IP65 IP STYLE	20	02407-001	2	2N Access
				Control and
				Intercoms

2N IP Style sec screen protector	5	02719-001	2	2N Access Control and Intercoms
2N IP STYLE SCREEN PROTECTOR	5	02743-001	2	2N Access Control and
2N IP UNI MIC GASKET	5	01862-001	2	Intercoms 2N Access Control and Intercoms
2N IP UNI FRONT PANEL 1 BUTTON	5	01864-001	2	2N Access Control and Intercoms
2N IP UNI PANEL 2 BUTTON	5	01865-001	2	2N Access Control and Intercoms
2N IP UNI PANEL 1 BUTTON	5	01866-001	2	2N Access Control and Intercoms
2N IP UNI FRONT SCREWS	5	01867-001	2	2N Access Control and Intercoms
2N IP UNI SPEAKER CABLE	5	01861-001	2	2N Access Control and Intercoms
2N IP UNI MICROPHONE	5	01863-001	2	2N Access Control and Intercoms
2N IP UNI FLUSH BOX	5	01868-001	2	2N Access Control and Intercoms
2N IP VARIO TUBE	5	01882-001	2	2N Access Control and Intercoms
2N IP VARIO TUBE SEALING	5	01883-001	2	2N Access Control and Intercoms
2N IP VARIO COVER 1 BUTTON	5	01884-001	2	2N Access Control and Intercoms
2N IP VARIO COVER 1 BUTTON/KEYPAD	5	01885-001	2	2N Access Control and Intercoms
2N IP VARIO COVER 3 BUTTON/READER	5	01886-001	2	2N Access Control and Intercoms
2N IP VARIO COVER 3 BUTTON/KEYPAD	5	01887-001	2	2N Access Control and Intercoms
2N IP VARIO COVER 6 BUTTON/READER	5	01888-001	2	2N Access Control and Intercoms

2N IP VARIO COVER 6 BUTTON/KEYPAD	5	04880 004	2	
ZN IP VARIO COVER 6 BUTTON/RETPAD	5	01889-001	2	2N Access Control and
				Intercoms
2N IP VARIO MICROPHONE	5	01879-001	2	2N Access
	5	018/9-001	2	Control and
				Intercoms
2N IP VARIO WAGO TERMINAL	5	01880-001	2	2N Access
ZN IF VARIO WAGO TERMINAL	5	01880-001	2	Control and
				Intercoms
2N IP VARIO KEYPAD	5	01881-001	2	2N Access
	5	01001-001	2	Control and
				Intercoms
2N IP VARIO SPEAKER	5	01878-001	2	2N Access
	Ŭ		-	Control and
				Intercoms
2N IP VARIO COVER 6 BUTTON/DISPLAY	5	01890-001	2	2N Access
	Ŭ	01050-001	-	Control and
				Intercoms
2N IP VARIO COVER 8 BTN EXTENDER	5	01891-001	2	2N Access
	Ŭ		-	Control and
				Intercoms
2N IP VARIO COVER 16 BTN EXTENDER	5	01892-001	2	2N Access
			-	Control and
				Intercoms
2N IP VARIO BACK PANEL	5	01893-001	2	2N Access
	-			Control and
				Intercoms
2N IP VARIO FRONT 1 BUTTON COVER	5	01894-001	2	2N Access
				Control and
				Intercoms
2N IP VARIO FRONT 1 BUTTON KEYPAD	5	01895-001	2	2N Access
				Control and
				Intercoms
2N IP VARIO FRONT 3 BUTTON COVER	5	01896-001	2	2N Access
				Control and
				Intercoms
2N IP VARIO FRONT 3 BUTTON KEYPAD	5	01897-001	2	2N Access
				Control and
				Intercoms
2N IP VARIO FRONT 6 BUTTON COVER	5	01898-001	2	2N Access
				Control and
				Intercoms
2N IP VARIO FRONT 6 BUTTON KEYPAD	5	01899-001	2	2N Access
				Control and
				Intercoms
2N IP VARIO CAMERA SUPPORT	5	01900-001	2	2N Access
				Control and
				Intercoms
2N IP VARIO CAMERA HOLDER	5	01901-001	2	2N Access
				Control and
				Intercoms
2N IP VARIO CAMERA COVER	5	01902-001	2	2N Access
				Control and
				Intercoms
2N IP VARIO CAMERA BLIND COVER	5	01903-001	2	2N Access
				Control and
				Intercoms

2N IP VERSO - INFOPANEL	10		01252-001	2	2N Access
	10		01202-001	2	Control and
					Intercoms
2N IP VERSO - KEYPAD	20		01253-001	2	2N Access
	20		01200-001	2	Control and
					Intercoms
2N IP VERSO - KEYPAD BLACK	15		01254-001	2	2N Access
	15		01234-001	2	Control and
					Intercoms
2N IP VERSO - I/O	15		01257-001	2	2N Access
	15		01237-001	2	Control and
					Intercoms
2N IP VERSO - 5 BUTTONS	15		01258-001	2	2N Access
	15		01230-001	2	Control and
					Intercoms
2N IP VERSO - WIEGAND	50		04050 004	2	
ZN IP VERSU - WIEGAND	50		01259-001	2	2N Access Control and
					Intercoms
	40		04000 004	•	2N Access
2N IP VERSO - TAMPER SWITCH	10		01260-001	2	2N Access Control and
					Intercoms
2N IP VERSO - BLIND PANEL	10		04264 004	2	
2N IP VERSO - BLIND PANEL	10		01261-001	2	2N Access Control and
					Intercoms
2N IP VERSO - INDUCTION LOOP	5		04000 004	2	
2N IP VERSO - INDUCTION LOOP	5		01263-001	2	2N Access
					Control and Intercoms
2N IP VERSO - BLUETOOTH	5	Discontinued	01266-001	2	2N Access
ZN IP VERSU - BLUETUUTH	5	Discontinued	01200-001	2	Control and
					Intercoms
2N IP VERSO - EXTENSION CABLE 1M	10		04267 004	<u> </u>	
ZN IP VERSU - EXTENSION CABLE TWI	10		01267-001	2	2N Access Control and
					Intercoms
2N IP VERSO - EXTENSION CABLE 3M	5		04269 004	2	2N Access
ZN IF VERSO - EXTENSION CABLE SW	5		01268-001	2	Control and
					Intercoms
2N IP VERSO - BLIND BUTTON	5		01270-001	2	2N Access
ZN IF VERSO - BLIND BUTTON	5		01270-001	2	Control and
					Intercoms
2N IP VERSO - MAIN WO CAMERA	15		01271-001	2	2N Access
ZN IF VERSO - MAIN WO CAWERA	15		01271-001	2	Control and
					Intercoms
2N IP VERSO - MAIN WO CAMERA BLACK	10		01272-001	2	2N Access
ZN IP VERSU - MAIN WU CAMERA BLACK	10		01272-001	2	Control and
2N IP VERSO - MAIN W CAMERA	200		01272 004	2	Intercoms
ZIN IF VEROU - MAIN W CAMERA	200		01273-001	2	2N Access
					Control and
			04074 004		Intercoms
2N IP VERSO - MAIN W CAMERA BLACK	70		01274-001	2	2N Access
					Control and
					Intercoms

2N IP VERSO 2.0 - MAIN W CAMERA	100		02907-001	2	2N Access Control and Intercoms
2N IP VERSO 2.0 - MAIN W CAMERA BLACK	100		02908-001	2	2N Access Control and Intercoms
2N IP VERSO - TOUCH DISPLAY	60		01275-001	2	2N Access Control and Intercoms
2N IP VERSO - TOUCH KEYPAD	15		01277-001	2	2N Access Control and Intercoms
2N IP VERSO - FINGERPRINT	10		01276-001	2	2N Access Control and Intercoms
2N IP VERSO - EXTENSION CABLE 5M	5		01269-001	2	2N Access Control and Intercoms
2N IP VERSO BLIND BUTTON BLACK	10		01523-001	2	2N Access Control and Intercoms
2N IP VERSO COMBI BLUETOOTH RFID SEC.	70	Discontinued	01639-001	2	2N Access Control and Intercoms
2N IP VERSO COMBI KEYPAD RFID SEC.	10	Discontinued	01638-001	2	2N Access Control and Intercoms
2N LTE VERSO - MAIN W CAMERA	5		01792-001	2	2N Access Control and Intercoms
2N LTE VERSO - MAIN W CAMERA BLACK	5		01791-001	2	2N Access Control and Intercoms

	- I	04040.004		
2N LTE VERSO EXTERNAL ANTENNA	5	01943-001	2	2N Access
				Control and Intercoms
	45	04075 004		
2N IP VERSO SECURE DOOR	15	01975-001	2	2N Access
				Control and
				Intercoms
2N IP VERSO WEDGE FOR 2 MODULES	20	01940-001	2	2N Access
				Control and
				Intercoms
2N IP VERSO - BLIND MODULE COVER	5	02043-001	2	2N Access
				Control and
				Intercoms
2N IP VERSO AND SOLO - REFLECTOR	5	02058-001	2	2N Access
				Control and
				Intercoms
2N IP SOLO WEDGE BACKPLATE	20	02077-001	2	2N Access
				Control and
				Intercoms
2N IP VERSO - SPEAKER COVER BLACK	5	02055-001	2	2N Access
				Control and
				Intercoms
2N IP VERSO - RFID READER COVER	5	02056-001	2	2N Access
				Control and
				Intercoms
2N IP VERSO - CLAMP BETWEEN MODULES	5	02057-001	2	2N Access
				Control and
				Intercoms
2N IP VERSO BLUETOOTH READER COVER	5	02063-001	2	2N Access
				Control and
				Intercoms
2N VERSO/SOLO TERMINAL 2 PIN 10X	5	02093-001	2	2N Access
				Control and
				Intercoms
2N VERSO/SOLO TERMINAL 3 PIN 10X	5	02092-001	2	2N Access
				Control and
				Intercoms
2N IP Verso - RFID 125kHz 2G	15	02140-001	2	2N Access
				Control and
				Intercoms
2N IP Verso - RFID 13MHz NFC SEC 2G	10	02141-001	2	2N Access
				Control and
				Intercoms
2N LTE Verso – debug LAN MODULE	5	02284-001	2	2N Access
				Control and
				Intercoms
2N IP VERSO OSDP MODUL	50	02577-001	2	2N Access
				Control and
				Intercoms
2N VersoKBD&BLE&RFID125,13,sec,NFC	10	02782-001	2	2N Access
				Control and
				Intercoms
2N VersoKBD&BLE&RFID125,13,NFC	10	02781-001	2	2N Access
				Control and
				Intercoms

	50	02444.004	2	
2N IP VERSO BT&RFID 125k&13.56M	50	02444-001	2	2N Access Control and
				Intercoms
2N VersoBLE&RFID125kHz,13.56MHz,NFC	5	02778-001	2	2N Access
ZN VEISOBLEARFIDIZSKHZ, IS.SOWHZ, NFC	5	02778-001	2	Control and
				Intercoms
2N VersoKPD&RFID125,13.56,NFC	5	02779-001	2	2N Access
2N VEISORF DARFID 125, 15.50, NFC	5	02//9-001	2	Control and
				Intercoms
2N IP VERSO TOUCHKEY&RFID 125&13	20	02443-001	2	2N Access
	20	02445-001	2	Control and
				Intercoms
2N IP VERSO - 1M FLUSH FRAME	15	01278-001	2	2N Access
	15	01270-001	2	Control and
				Intercoms
2N IP VERSO - 1M FLUSH FRAME BLACK	15	01279-001	2	2N Access
ZN IF VERSO - IM FEUSH FRAME BLACK	15	01279-001	2	Control and
				Intercoms
2N IP VERSO - 2M FLUSH FRAME	20	01280-001	2	2N Access
	20	01200-001	2	Control and
				Intercoms
2N IP VERSO - 2M FLUSH FRAME BLACK	20	01281-001	2	2N Access
	20	01201-001	2	Control and
				Intercoms
2N IP VERSO - 3M FLUSH FRAME	10	01282-001	2	2N Access
	10	01202-001	-	Control and
				Intercoms
2N IP VERSO - 3M FLUSH FRAME BLACK	5	01283-001	2	2N Access
	J J	01200-001	-	Control and
				Intercoms
2N IP VERSO - 1M FLUSH BOX	20	01284-001	2	2N Access
	20	01204 001	-	Control and
				Intercoms
2N IP VERSO - 2M FLUSH BOX	50	01285-001	2	2N Access
			-	Control and
				Intercoms
2N IP VERSO - 3M FLUSH BOX	10	01286-001	2	2N Access
				Control and
				Intercoms
2N IP VERSO - 1M SURFACE FRAME	50	01287-001	2	2N Access
				Control and
				Intercoms
2N IP VERSO - 1M SURFACE FRAME BL.	30	01288-001	2	2N Access
				Control and
				Intercoms
2N IP VERSO - 2M SURFACE FRAME	125	01289-001	2	2N Access
				Control and
				Intercoms
2N IP VERSO - 2M SURFACE FRAME BL.	50	01290-001	2	2N Access
				Control and
				Intercoms
2N IP VERSO - 3M SURFACE FRAME	20	01291-001	2	2N Access
				Control and
				Intercoms
2N IP VERSO - 3M SURFACE FRAME BL.	20	01292-001	2	2N Access
				Control and
				Intercoms

2N IP VERSO - 1M BACKPLATE	30	04202 004	2	2N A00000
	30	01293-001	2	2N Access Control and
				Intercoms
2N IP VERSO - 2M BACKPLATE	90	01204 001	2	
ZN IP VERSU - ZM BACKPLATE	90	01294-001	2	2N Access Control and
				Intercoms
2N IP VERSO - 3M BACKPLATE	20	01005 001	2	
ZN IP VERSO - SM BACKPLATE	20	01295-001	2	2N Access Control and
2N IP VERSO - 2x2M BACKPLATE	5	01296-001	2	Intercoms 2N Access
ZN IF VERSO - ZXZIVI BACKFEATE	5	01290-001	2	Control and
				Intercoms
2N IP VERSO - 3x2M BACKPLATE	5	01297-001	2	2N Access
	J	01237-001	2	Control and
				Intercoms
2N IP VERSO - 2x3M BACKPLATE	5	01298-001	2	2N Access
	J	01230-001	2	Control and
				Intercoms
2N IP VERSO - 3x3M BACKPLATE	5	01299-001	2	2N Access
	J J	01205-001	-	Control and
				Intercoms
2N IP VERSO - 1M GANG PLATE	20	01524-001	2	2N Access
	20	01024 001	-	Control and
				Intercoms
2N IP VERSO - 2M GANG PLATE	15	01525-001	2	2N Access
		0.010 001	-	Control and
				Intercoms
2N ANNUAL APARTMENT SUBS MY2N	0	02683-001	0	2N Access
			•	Control and
				Intercoms
2N ANNUAL DEVICE SUBS MY2N	0	02682-001	0	2N Access
	, , , , , , , , , , , , , , , , , , ,	02002 001	Ū	Control and
				Intercoms
				intereenie
2N AC Advanced LIC	0	02309-001	0	2N Access
				Control and
				Intercoms
		00040-004		01.4
2N AC Pro LIC	0	02310-001	0	2N Access
				Control and
				Intercoms
2N AC Unlimited LIC	0	02311-001	0	2N Access
		V2011-001	0	Control and
				Intercoms

2N AC Advanced to Pro LIC	0		02312-001	0	2N Access Control and Intercoms
2N AC Pro to Unlimited LIC	0		02313-001	0	2N Access Control and Intercoms
2N AC Attendance Monitoring LIC	0	Description changed	02314-001	0	2N Access Control and Intercoms
2N PICard Commander LIC	0		02722-001	0	2N Access Control and Intercoms
2N PLUGIN FOR OnGuard	0		02624-001	0	2N Access Control and Intercoms

2N PLUGIN FOR CCure	0	02625-001	0	2N Access Control and Intercoms
2N PLUGIN FOR Symmetry	0	02922-001	0	2N Access Control and Intercoms
2N IDT 2.0 - MEETING ROOM LICENSE	0	02171-001	0	2N Access Control and Intercoms
2N IP INTERCOM AND SIP AUDIO- INFORMACAST	0	01381-001	2	2N Access Control and Intercoms
MIFARE RFID SMART CARD 13.56MHz	150	01384-001	2	2N Access Control and Intercoms
MIFARE RFID SMART KEY FOB 13.56MHz	350	01385-001	2	2N Access Control and Intercoms
2N SECURITY RELAY	175	01386-001	2	2N Access Control and Intercoms
2N WIEGAND ISOLATOR	5	01387-001	2	2N Access Control and Intercoms
2N MAGNETIC DOOR CONTACT	5	01388-001	2	2N Access Control and Intercoms
WIEGAND 125 kHz RFID CARD READER	5	01389-001	2	2N Access Control and Intercoms
WIEGAND 13.56 MHz RFID CARD READER	5	01390-001	2	2N Access Control and Intercoms

2N INDUCTION LOOP	5		01391-001	2	2N Access
					Control and
					Intercoms
2N INDUCTION LOOP - POWER SUPPLY	5		01393-001	2	2N Access
					Control and
					Intercoms
PoE INJECTOR WITHOUT CABLE	5	Discontinued	01394-001	2	2N Access
					Control and
					Intercoms
EMARINE RFID PROX CARD 125kHz	60		01395-001	2	2N Access
					Control and
					Intercoms
EMARINE RFID PROX KEY FOb 125kHz	200		01396-001	2	2N Access
					Control and
					Intercoms
WEB RELAY - 1 OUTPUT, 1 INPUT	20		01397-001	2	2N Access
					Control and
					Intercoms
WEB RELAY - 4 OUTPUTS, 0 INPUT, PoE	20		01398-001	2	2N Access
					Control and
					Intercoms
USB RFID READER 125kHz	5	Discontinued	01399-001	2	2N Access
					Control and
	_			-	Intercoms
USB RFID READER 13MHz & 125kHz	5		01400-001	4	2N Access
					Control and
	_				Intercoms
USB FINGERPRINT READER	5		01401-001	2	2N Access
					Control and
					Intercoms
USB BLUETOOTH READER	5		01402-001	2	2N Access
					Control and
	10		04400-004		Intercoms
PoE INJECTOR WITH CABLE	10		01403-001	2	2N Access
					Control and
					Intercoms
2N 2WIRE - SET WITH US PLUG	175		01404-001	2	2N Access
					Control and
USB SEC RFID READER 13MHz & 125kHz	40		04507.004		Intercoms
USB SEC RFID READER 13MHZ & 125KHZ	10		01527-001	2	2N Access Control and
					Intercoms
VERSO/SOLO SPEAKER COVER,5x	5		01640-001	2	2N Access
VERSO/SOLO SPEARER COVER,5X	5		01040-001	2	Control and
					Intercoms
VERSO/SOLO CAMERA WINDOW,5x	5		01641-001	2	2N Access
	5		01041-001	2	Control and
					Intercoms
VERSO WINDOW NON-CAMERA,5x	20		01642-001	2	2N Access
	20		01042-001	4	Control and
	1				Intercoms
VERSO/SOLO REFLECTOR,2N LOGO,5x	5		01643-001	2	2N Access
	5		010-3-001	2	Control and
					Intercoms
VERSO/SOLO BUTTON NAMETAG,10x	5		01644-001	2	2N Access
	5		01044-001	4	Control and
					Intercoms
	1				

VERSO FLUSH/SURFACE LOWER FIX,5x	5	01645-001	2	2N Access
VERSOTEDST#SORTAGE LOWER TIX,5x	5	01043-001	2	Control and
				Intercoms
SOLO FLUSH/SURFACE LOWER FIX,5x	5	01646-001	2	2N Access
	Ŭ	01040 001	-	Control and
				Intercoms
VERSO/SOLO FLUSH TOP FIX,5x	5	01647-001	2	2N Access
	Ŭ		-	Control and
				Intercoms
VERSO/SOLO SURFACE TOP FIX,5x	5	01648-001	2	2N Access
			-	Control and
				Intercoms
VERSO BUS SHORT,80MM,10x	5	01649-001	2	2N Access
,				Control and
				Intercoms
VERSO BUS SHORT,220MM,10x	5	01650-001	2	2N Access
			_	Control and
				Intercoms
VERSO MICROPHONE SET,10x	5	01651-001	2	2N Access
			_	Control and
				Intercoms
FORCE/SAFETY SPEAKER 1W	5	01652-001	2	2N Access
				Control and
				Intercoms
FORCE/SAFETY GASKET FOR MIC,5x	5	01654-001	2	2N Access
	-			Control and
				Intercoms
FORCE/SAFETY MIC WITH CABLE,5x	5	01655-001	2	2N Access
				Control and
				Intercoms
FORCE BUTTON NAMETAG,5x	5	01656-001	2	2N Access
				Control and
				Intercoms
FORCE PLASTIC BUTTON ON PCB,5x	5	01657-001	2	2N Access
				Control and
				Intercoms
FORCE 1 BUTTON BOARD,1x	5	01658-001	2	2N Access
				Control and
				Intercoms
FORCE 1 BUTTON BOARD, PICTOGRAM,5x	5	01659-001	2	2N Access
				Control and
				Intercoms
FORCE 2 BUTTONS BOARD,1x	5	01660-001	2	2N Access
				Control and
				Intercoms
FORCE 4 BUTTON BOARD,1x	5	01661-001	12	2N Access
				Control and
				Intercoms
FORCE/SAFETY SPEAKER10W 4pcs	5	01653-001	2	2N Access
				Control and
				Intercoms
2N U-SHAPED FRAME IP BASE BLACK	5	02041-001	2	2N Access
				Control and
				Intercoms
2N NVT PL-08 SWITCH 2 ADAPTERS	5	02318-001	2	2N Access
				Control and
				Intercoms

-		00040.004		
5		02319-001	2	2N Access
				Control and Intercoms
-		00445-004		
5		02445-001	2	2N Access Control and
-		00700 004		Intercoms
5		02788-001	2	2N Access Control and
				Intercoms
5		02787 001	2	2N Access
5		02707-001	2	Control and
				Intercoms
125		02087-001	2	2N Answering
				Units
40		02088-001	2	2N Answering Units
5		01741-001	2	2N Access Control and
40		04005 004		Intercoms
				2N Answering Units
20		01936-001	2	2N Answering Units
	5 40	5 5 5 125 40 5 40 5 40 5 40 5 40	5 02445-001 5 02788-001 5 02787-001 125 02087-001 40 02088-001 5 01741-001 40 01935-001	5 02445-001 2 5 02788-001 2 5 02787-001 2 125 02087-001 2 40 02088-001 2 5 01741-001 2 40 01935-001 2

2N INDOOR TALK BLACK	30	01698-001	2	2N Answering Units
2N INDOOR TALK WHITE	5	01699-001	2	2N Answering Units
2N INDOOR FLUSH BOX	100	01700-001	2	2N Answering Units
2N INDOOR SURFACE INSTALLATION BOX	20	02320-001	2	2N Answering Units
2N INDOOR DESK STAND	200	02039-001	2	2N Answering Units
2N CLIP, ETHERNET	125	02892-001	2	2N Answering Units

2N CLIP DESK STAND	30		02905-001	2	2N Answering Units
2N CLIP 1-GANG INSTALLATION PLATE	50		02906-001	2	2N Answering Units
2N IP PHONE D7A	30		02660-001	2	2N Answering Units
2N USB CAMERA FOR 2N IP PHONE D7A	5		02659-001	2	2N Answering Units
2N IP PHONE D7A WALL MOUNT BRACKET	5		02530-001	2	2N Answering Units
GXV3370 IP PHONE	10	Discontinued	01695-001	2	2N Answering Units
2N Grandstream GXV-3350 - VoIP	10		02240-001	2	2N Answering Units
GXV3240 IP PHONE	5	Discontinued	01422-001	2	2N Answering Units
2N IDT 2.0 POE BLACK	40		01668-001	2	2N Answering Units
2N IDT 2.0 POE WHITE	15		01669-001	2	2N Answering Units
2N IDT 2.0 POE WIFI BLACK	10	Discontinued	01670-001	2	2N Answering Units
2N IDT 2.0 POE WIFI WHITE	10	Discontinued	01671-001	2	2N Answering Units
2N IDT - DESK STAND BLACK	40		01425-001	2	2N Answering Units
2N IDT - DESK STAND WHITE	10		01426-001	2	2N Answering Units
2N IDT - POWER SUPPLY FLUSH	5		01423-001	2	2N Answering Units

2N SIP MIC	10	01208-001	4	2N Audio
2N SIP SPEAKER - HORN	5	01433-001	2	2N Audio
2N SIP SPEAKER - WALL MOUNTED, W	5	01432-001	2	2N Audio
2N SIP SPEAKER - WALL MOUNTED, B	5	01431-001	2	2N Audio
2N IP AUDIO POWER SUPPLY - US PLUG	5	01435-001	2	2N Audio
AXIS TA1601 Mounting Plate	15	02687-001	2	Access Control
AXIS TA1801 Top Cover	5	02688-001	4	Access Control
AXIS TA1901 DIN Rail Clip 10PCS	5	02685-021	4	Access Control

AXIS TA1902 Connector Kit	5	02686-001	4	Access Control
AXIS TA4701 Access Card 100P	10	02303-001	2	Access Control
AXIS TA4201 Weathershield	5	02532-001	4	Access Control
AXIS TA4401 BRAILLE LABEL 10P	5	02533-001	2	Access Control
AXIS TA4702 Key Fob 50P	10	02304-001	2	Access Control

	-	1	04700 004	4	
AXIS TA8201 RECESSED MOUNT	5		01762-001	4	Access Control
AXIS TA8601 CONDUIT ADAPTER 3/4 NPS	10		01763-001	4	Access Control
AXIS TA8501 PHYSICAL TAMPERING SW	10		01962-001	4	Access Control
AXIS A8105-E FLUSH MOUNT	10	Discontinued	5801-481	2	Access Control
AXIS A9801 SECURITY RELAY	30		5801-141	4	Access Control
MOUNT KIT CODEBLUE/A8004	5	Discontinued	5507-471	4	Access Control
AXIS TI8901 FACE PLATE REPLACEMENT	5		02070-001	4	Access Control
AXIS TI8603 Conduit Adapter 3/4"NPS	5		02233-001	4	Access Control
AXIS TI8602 WALL MOUNT BACK BOX	125		02066-001	2	Access Control
AXIS TI8202 RECESSED MOUNT	10		02067-001	2	Access Control

AXIS TI8203 ADAPTER PLATE	10		02503-001	4	Access Control
AXIS TI8904 INDUCTION LOOP	10		02673-001	4	Access Control
AXIS TA1802 Top Cover	10		02699-001	4	Access Control
AXIS TI8204 Recessed Mount White	70		02561-001	2	Access Control
AXIS TI8204 Recessed Mount Black	20		02562-001	2	Access Control
AXIS A1601	60	Discontinued	01507-001	2	Access Control

AXIS A1210 Network Door Controller	60	02368-001	2	Access Control
AXIS A1210-B Network Door Controller	50	02369-001	2	Access Control
AXIS A1214 Door Controller Kit	10	02684-001	2	Access
AXIS A1610 Network Door Controller	150	02653-001	2	Control
				Control
AXIS A1610-B Network Door Controller	70	02654-001	2	Access Control

AXIS A1001 Network Door Controller	100	Discontinued	0540-001	2	Access Control
					Control
	5	Discontinued	0540.004	4	A
AXIS A1001 BULK 10PCS Network Door Controller	5	Discontinued	0540-021	4	Access Control
Controller					Control
AXIS Door Controller Extension	0		02896-001	0	Access
					Control

AXIS A9188 NETWORK I/O RELAY MODULE 80 0820-001 4 Access Control AXIS A9161 NETWORK I/O RELAY MODULE 60 0821-001 4 Access Control
AXIS A9161 NETWORK I/O RELAY MODULE 60 0821-001 4 Access
AXIS A9188-VE NETWORK I/O RELAY MODULE 10 0831-001 4 Access
Control

	475	00000 004		A
AXIS A8207-VE MKII	175	02026-001	4	Access Control
AXIS I8016-LVE	175	01995-001	2	Access Control
AXIS I8116-E White	250	02408-001	2	Access Control

	~~	00/00 00/	^	
AXIS I8116-E Black	90	02409-001	2	Access Control
AXIS A4020-E Reader	70	02144-001	2	Access Control
				Control
AXIS A4120-E Reader with Keypad	50	02145-001	2	Access
				Control

	^	<u>г г</u>	00504 004	<u> </u>	A
AXIS BARCODE READER	0		02524-001	0	Access
					Control
AXIS 4IN1 SECURITY SCREWDRIVER	20		5507-711	2	Accessory
			04007 004		
AXIS Q17 FRONT WINDOW KIT B	5		01687-001	4	Accessory
	5		5503-741	4	Accessory
GASKET A CABLE 3,5-7MM 10PCS	5		5503-741	4	Accessory
ACC TOOL STEEL STRAP	5	╂─────┤	21776	4	Accessory
AUG IUUL SIEEL SIKAP	5		21//0	4	Accessory
AXIS GASKET M16 5-8 MM 10PCS	5		01785-001	4	Accessory
AND GASKET WITO 3-0 WIWI TUPUS	5		01/03-001	4	Accessory
GASKET B M20 CABLE 6-13MM 10PCS	5		5503-751	4	Accessory
GASKET D WIZU GADLE 0-TSWIWI TUPCS	5		5503-751	4	Accessory
GASKET C M25 CABLE 8-17MM 10PCS	5		5503-791	4	Accessory
AXIS TQ3901 Gasket M20 Cable	5		02277-001	4	Accessory
AND I WOOD I GOSKEL WIZU GODIE	5		02211-001	4	Accessory
	40		5503 764	A	Accessory
CABLE GLAND A M20 5PCS	10		5503-761	4	Accessory

GASKET C M20 10PCS	20		5505-941	4	Accessory
					,
CABLE GASKET M20 3MM 10PCS	5		5506-421	4	Accessory
LENS TOOLKIT P39XX-R 4 PCS	10		5506-441	4	Accessory
CABLE GLAND A M25 5PCS	5		5503-831	4	Accessory
CABLE GLAND A M25 5FCS CABLE GLAND M20x1.5 RJ45 5PCS	10		5503-951	2	Accessory
CABLE GLAND MZUX 1.3 K043 JF CS	10		0000-001	2	Accessory
AXIS M3025-VE LENS M12 6MM	5	Discontinued	5504-551	4	Accessory
LENS M12 6MM F1.9 4PCS	5		01960-001	4	Accessory
LENS M12 16MM F1.8 4PCS	5		01961-001	4	Accessory
LENS M12 12MM F1.6 4P	10		01780-001	4	Accessory
LENS M12 12MM F 1.0 4F	5		01781-001	4	Accessory
LENS M12 16MM F1.8 4P	5		01812-001	4	Accessory
LENS M12 6MM F2.0 4P	15		01813-001	4	Accessory
AXIS WEATHERSHIELD K	10		5507-121	4	Accessory
				•	, lococory
LENS M12 6MM 5PCS	10	Discontinued	5801-771	4	Accessory
LENS M12 2.8 MM F1.2 10P	5		01860-001	4	A000000m/
LENS M12 2.6 MM F1.2 10P	5		01000-001	4	Accessory
ACC LENS M12 6MM F1.6 10 PCS	5		5504-961	4	Accessory
ACC LENS M12 8MM F1.6 10 PCS	5		5504-971	4	Accessory
					_

ACC LENS M12 3.6MM F2.0 10PCS	5		5506-011	4	Accessory
ACC LENS MIZ S.OMIM FZ.U TUFCS	5		5506-011	4	Accessory
AXIS LENS M12 2.1MM F2.2 10PCS	5		5901-371	4	Accessory
AXIS LENS M12 2.1 MM F1.8 IR 10P	5		02006-001	4	Accessory
AXIS LENS M12 3.6 MM F1.8 IR 10P	5		02007-001	4	Accessory
AXIS LENS M12 6.0 MM F1.9 IR 10P	5		02008-001	4	Accessory
AXIS LENS M12 8.0 MM F1.8 IR 10P	5		02009-001	4	Accessory
LENS M12 16MM 5PCS	10	Discontinued	5801-781	4	Accessory
ACC LENS M12 MEGAPIXEL 6PCS	5		5506-431	4	Accessory
THEIA LENS CS VARIF 1.8-3MM DC-IRIS	10		5503-161	4	Accessory
LENS FUJINON CS 2.2-6MM DC-IRIS B	5	Discontinued	5800-781	4	Accessory
LENS CS VARIF 9-40MM DC-IRIS D/N	5		5503-171	4	Accessory
LENS CS VARIF 9-40MM P-IRIS D/N	5		5504-901	4	Accessory

LENS COMPUTAR CS 12.5-50MM DC-IRIS	10		5800-791	4	Accessory
LENS COMPUTAR CS 12.5-50MM P-IRIS	5		5800-801	4	Accessory
LENS COMPUTAR i-CS 2.8-8.5MM	20		5901-101	4	Accessory
LENS FUJINON C CS 8-80MM DC	5	Discontinued	5506-991	4	Accessory
RICOM 2MP LENS DC-IRIS 8-26MM F0.9	5		01577-001	4	Accessory
LENS CS 12-50 MM F1.4 P-IRIS 8MP	10		01690-001	4	Accessory
LENS I-CS 9-50 MM F1.5 8MP	40		01727-001	4	Accessory
Lens i-CS 3.9-10 mm F1.5 8 MP	5		01576-001	4	Accessory
Lens CS 2.8 - 13 mm F1.4 DC-Iris 5 MP	5		01775-001	4	Accessory
AXIS TM3808-E Skin Cover Black 4P	5		02219-001	2	Accessory
LENS CS 3-10.5 MM DC-IRIS 2 MP	5		01774-001	4	Accessory
AXIS LENS CLOTH 10PCS AXIS LENS CLOTH 50PCS	5		5502-661 5502-721	4	Accessory Accessory
SURVEILLANCE STICKER ENG 10PCS	5		5502-811	4	Accessory
SURVEILLANCE STICKER ENG 50PCS	5		5502-821	4	Accessory
RADAR DETECTION STICKER EN 10PCS	5		01551-001	4	Accessory

AXIS WEATHERSHIELD KIT C	5	5504-881	4	Accessory
	, C	0004 001	-	Accessery
AXIS PT IR ILLUMINATOR KIT C	10	5801-901	4	Accessory
AXIS T99 ILLUMINATOR BRACKET KIT A	5	01181-001	4	Accessory
			•	houseny
AXIS WASHER KIT B	5	5507-701	4	Accessory
AXIS TQ6905-E WASHER KIT	5	02241-001	4	Accessory
AXIS BIRD CONTROL SPIKE 10P	70	5801-121	4	Accessory
				-
AXIS SAFETY WIRE 3M 5P	80	5801-971	2	Accessory
	10	04550.004		Access
AXIS F7301 CABLE BLACK 1M 4PCS	10	01552-001	2	Accessory

AXIS F7315 CABLE WHITE 15M 4PCS	70	5506-821	4	Accessory
AXIS P13 WEATHERSHIELD EXTENSION A	5	01692-001	4	Accessory
M12(F)-RJ45(M) CABLE 0.5M (1.6FT)	10	01793-001	4	Accessory
AXIS TM1803 WEATHERSHIELD EXTENSION	5	02061-001	2	Accessory
AXIS TV5901 Control Board Adapter	5	02256-001	4	Accessory
TP6901-E ADAPTER BRACKET P56	5	02458-001	4	Accessory
AXIS TD4801 Sunshield 4pcs	10	02098-001	4	Accessory
AXIS TQ6906-E Protection Ring	5	02691-001	4	Accessory
AXIS TP3818-E CASING BLACK	20	02478-001	4	Accessory

AXIS TU6004-E CABLE 8M	300	02250-001	2	Accessory
			_	,,
AXIS TU6004-E CABLE 30M	70	02252-001	2	Accessory
	10	02202-001	-	Accessory
AXIS TU6004-E CABLE 1M 4P	20	02249-001	2	Accessory
	20	02245-001	2	Accessory

AXIS TU6004-E CABLE 8M 4P	30	02251-001	2	Accessory
			_	,
AXIS TU6005 PLENUM CABLE 8M	30	 02266-001	2	Accessory
	50	02200-001	2	Accessory
AXIS TU6005 PLENUM CABLE 20M	40	02267-001	2	Accessory

AXIS TU6002 RIGHT-ANGLE SMA ADP 10P	10	02470-021	4	Accessory
AXIS TU6003 Conn Kit FAKRA 10P	10	02468-021	4	Spare Part
AXIS TU6006 Conn Kit FAKRA 10P	5	02469-021	4	Spare Part
AXIS TU6009 CONN 6-PIN 2.5MM 10P	10	02795-021	4	Accessory
	10	02/00 021	-	Accessery
		00704 004	4	A
AXIS TU6008 CONN 5-PIN 2.5MM 10P	5	02794-021	4	Accessory
AXIS TP6902-E ADAPTER BRACKET	5	02854-001	4	Accessory
		 02647-001		
AXIS TU9004 Wireless Dongle	30	02647-001	2	Accessory
AXIS TU6007-E CABLE 1M 4P	50	02793-001	2	Accessory

AXIS TU6007-E CABLE 8M	300	02790-001	2	Accessory
			-	,,
AXIS TU6007-E CABLE 8M 4P	70	02791-001	2	Accessory
AXIS TS3901 Rail Extensions	10	02528-001	2	Accessory
AXIS TU6011 Mains Cable	70	02867-004	2	A a a a a a i i i
AAIS 106011 Mains Cable	70	02007-004	2	Accessory
AXIS TU6011 Mains Cable 10 pcs	5	02867-024	2	Accessory
AXIS T92E05 PROTECTIVE HOUSING	5	0344-001	4	Accessory
		0344-001	4	Accessory

AXIS T92E20 OUTDOOR HOUSING	10	0433-001	4	Accessory
	10	0400 001	-	Accessory
AXIS T92F10 OUTDOOR HOUSING 6PCS	100	5801-531	4	Accessory
AXIS TQ1809-LE HOUSING T92G	5	02322-001	2	Accessory
AXIS T93C10 OUTDOOR HOUSING	5	5507-681	2	Accessory
AXIS T93C EXTENSION KIT	5	5901-471	4	Accessory
AXIS T93F05 PROTECTIVE HOUSING	5	5900-261	4	Accessory
<u> </u>				

	-	1	5000 074	4	A
AXIS T93F10 OUTDOOR HOUSING 24VAC/12- 24VDC	5		5900-271	4	Accessory
AXIS T93F20 OUTDOOR HOUSING POE	5		5900-281	4	Accessory
	5	Discontinued	5506-491	4	A
AXIS T93G05 PROTECTIVE HOUSING	5	Discontinued	5506-491	4	Accessory
AXIS SUNSHIELD A	5		5504-941	4	Accessory
AXIS T98A15-VE SURVEILLANCE CABINET	30		5900-151	4	Accessory
AXIS T98A16-VE SURVEILLANCE CABINET	5		5900-161	4	Accessory
AXIS T98A16-VE SURVEILLANCE CABINET	5		5900-161	4	Accessory
AXIS T98A16-VE SURVEILLANCE CABINET	5		5900-161	4	Accessory
AXIS T98A16-VE SURVEILLANCE CABINET	5		5900-161	4	Accessory
AXIS T98A16-VE SURVEILLANCE CABINET	5		5900-161	4	Accessory
AXIS T98A16-VE SURVEILLANCE CABINET	5		5900-161	4	Accessory
AXIS T98A16-VE SURVEILLANCE CABINET	5		5900-161	4	Accessory
AXIS T98A16-VE SURVEILLANCE CABINET	5		5900-161	4	Accessory
AXIS T98A16-VE SURVEILLANCE CABINET	5		5900-161	4	Accessory

AXIS T98A17-VE SURVEILLANCE CABINET	15		5900-171	4	Accessory
				•	, lococory
AXIS T98A18-VE SURVEILLANCE CABINET	40		5900-181	4	Accessory
AAIS 190A10-VE SURVEILLANCE CADINET	40		5900-161	4	Accessory
AXIS T98A19-VE SURVEILLANCE CABINET	5	Discontinued	5900-321	4	Accessory
AXIS T98A SUNSHIELD	5		5503-551	4	Accessory
AXIS CABINET LOCK A	10		5505-651	4	Accessory
					-
CORRIDOR FORMAT BRACKET A	5		5504-931	4	Accessory
	-				,
CORRIDOR FORMAT BRACKET B	5		5506-381	4	Accessory

AXIS T92E CAMERA HOLDER PLATE C	5		5505-331	4	Accessory
AXIS T92E CAMERA CHANGE KIT A	5		5505-341	4	Accessory
AXIS TQ1808-VE SURVEILLANCE CABINET	15		02359-001	4	Accessory
AXIS TP3826-E housing	40		02672-001	4	Accessory
AXIS M3044-V/45-V/46-V VIEW PROT 5P	5	Discontinued	5507-441	4	Accessory
AXIS M3024/25/26/27 COVER WHT 10PCS	5	Discontinued	5504-071	4	Accessory
AXIS M3024/25/26/27 COVER BLK 10PCS	5	Discontinued	5504-061	4	Accessory
AXIS M30 SKIN COVER A BLACK 4P	5	Discontinued	01463-001	4	Accessory
AXIS M30 CASING A BLACK 5P	15	Discontinued	5507-431	4	Accessory
AXIS M30 SM DETECT CASING A 5P	5	Discontinued	5901-151	4	Accessory
AXIS M30 COVER RING A BLACK 4P	5	Discontinued	01492-001	2	Accessory
AXIS M42 SMOKED DOME A 4P	15		01608-001	4	Accessory
AXIS M55 SMOKED DOME A	10		01607-001	4	Accessory

5		02236-001	4	
5		02236-001	4	Access
				Accessory
5		5506-161	4	Accessory
5		5505-991	4	Accessory
10		5506-001	2	Accessory
5	Discontinued	5505-861	4	Accessory
5		5507-421	4	Accessory
5	Discontinued	5801-401	4	Accessory
10	Discontinued	5801-411	4	Accessory
10	Discontinued	5506-021	2	Accessory
5	Discontinued	5503-151	2	Accessory
5	Discontinued	01546-001	4	Accessory
5	Discontinued	01547-001	4	Accessory
5	Discontinued	5800-761	4	Accessory
30		5506-151	4	Accessory
10	Discontinued	01157-001	4	Accessory
	5 5 5 5 5 10 10 5 5 5 5 5 30	SImage: second seco	5	5 5505-991 4 5 5505-991 4 10 5506-001 2 5 Discontinued 5505-861 4 5 Discontinued 5507-421 4 5 Discontinued 5801-401 4 5 Discontinued 5801-401 4 10 Discontinued 5801-401 4 10 Discontinued 5506-021 2 5 Discontinued 5503-151 2 5 Discontinued 01546-001 4 5 Discontinued 01546-001 4 5 Discontinued 5800-761 4 30 Iscontinued 5800-761 4

AXIS Q35-LVE SKIN COVER A BLACK 2P	5	Discontinued	01529-001	4	Accessory
AXIS Q35 SMOKED DOME A 5PCS	5	Discontinued	01183-001	4	Accessory
AXIS Q3517-SLVE NYLON DOME 2P	5	Discontinued	01585-001	4	Accessory
AXIS Q36-VE SMOKED DOME	5		5801-501	4	Accessory
AXIS Q37 SMOKED DOME A	5	Discontinued	5901-431	4	Accessory
AXIS TQ6810 HARD COATED SMOKED DOME	20		02401-001	4	Accessory
AXIS TQ6811-E DOME CL HYDROPHILIC	5		02576-001	4	Accessory
AXIS Q60-S SMOKED DOME A	5		5504-791	4	Accessory
AXIS Q6114-E/15-E CLEAR DOME	5	Discontinued	5507-281	4	Accessory
AXIS Q6114-E/15-E CLEAR DOME 5P	5	Discontinued	5506-521	4	Accessory
AXIS Q8414-LVS SMOKED DOME 5P	5	Discontinued	5506-301	4	Accessory
AXIS TM3801 BLACK CASING 4P	50	Discontinued	01854-001	2	Accessory
AXIS TM3803 BLACK CASING 4P	10	Discontinued	01744-001	2	Accessory
AXIS TM3804 SM DETECT CASING C 4P	5	Discontinued	01745-001	4	Accessory
AXIS TM3805 VANDAL CASING C 4P	5	Discontinued	01746-001	4	Accessory
AXIS TM3807 BLACK CASING 4P	20		01918-001	4	Accessory

AXIS TM3809-E SKIN COVER BLACK 4P	5	02334-001	4	Accessory
AXIS TM3818 CASING BLACK 4p	30	02578-001	2	Accessory
AXIS TP3801 BLACK CASING 4P	10	01623-001	4	Accessory
AXIS TP3801-E BLACK CASING 4P	20	01626-001	4	Accessory
AXIS TP3802 SMOKED DOME 4P	30	01624-001	4	Accessory
AXIS TP3802-E SMOKED DOME 4P	10	01627-001	4	Accessory
AXIS TP3806 DOME COVER BLACK 4P	5	02005-001	4	Accessory
AXIS TP3808 DOME COVER BLACK 4P	5	02004-001	4	Accessory
AXIS TP3813-E Ventless Metal Casing	5	02237-001	2	Accessory
AXIS TP3814-E BLACK DOME CASING	15	02244-001	4	Accessory
AXIS TP3815-E SMOKED DOME	10	02391-001	2	Accessory
AXIS TP3817-E CASING BLACK	5	02357-001	4	Accessory
AXIS TP3816-E CASING BLACK 4P	10	Discontinued 02355-001	4	Accessory
AXIS TP3820 CASING BLACK 4P	10	02492-001	4	Accessory
AXIS TP3820-E CASING BLACK 4P	5	02496-001	4	Accessory

10		02408 001	A	A
10		02498-001	4	Accessory
15		02356-001	4	Accessory
20		02512-001	2	Accessory
10	Discontinued	01816-001	4	Accessory
20		01817-001	4	Accessory
10	Discontinued	01947-001	2	Accessory
10		02399-001	2	Accessory
5	Discontinued	5500-201	4	Accessory
				_
5		5500-601	4	Accessory
	20 10 20 10 10	152010Discontinued1020202010Discontinued105Discontinued	1502356-0012002512-00110Discontinued01816-0012001817-0012001817-00110Discontinued10Discontinued10Discontinued10Discontinued10Discontinued10Discontinued10Discontinued10Discontinued10Discontinued10Discontinued10Discontinued10Discontinued10Discontinued10Discontinued10Discontinued10Discontinued10Discontinued	15 02356-001 4 20 02512-001 2 10 Discontinued 01816-001 4 20 01817-001 4 20 01817-001 4 10 Discontinued 01947-001 2 10 Discontinued 01947-001 2

	T	1		
AXIS TP3823-E WEATHERSHIELD BL 2P	5	02629-001	4	Accessory
AXIS TM5801 DOME COVER BLACK	5	02428-001	4	Accessory
AXIS TP3824-E DOME SMOKED 4P	30	02550-001	4	Accessory
AXIS TM3815-E DOME SMOKED 4P	5	02618-001	4	Accessory
AXIS TP3819-E DOME SMOKED	20	02480-001	4	Accessory
AXIS TP3825-E WEATHERSHIELD BLACK	20	02584-001	4	Accessory
AXIS TF1803-RE LENS PROTECTOR 4P	10	02435-001	4	Accessory
AXIS TF1802-RE LENS PROTECTOR 4P	10	02434-001	4	Accessory
AXIS TF1801-R LENS HOOD 4P	5	02213-001	4	Accessory

AXIS TP3827 Clear Dome Cover 10p	5	02701-021	4	Accessory
AXIS TP3830 Top Cover Black 10p	5	02702-021	4	Accessory
AXIS TQ3809-E Dome Smoked	20	02804-001	2	Accessory
AXIS TQ3811-E Casing	5	02828-001	2	Accessory
AXIS TM3814-E Skin Cover Black 4P	10	02573-001	2	Accessory
AXIS TM3821 CASING BLACK 4P	10	02731-001	2	Accessory
AXIS TM3819 CASING BLACK 4P	10	02819-001	4	Accessory
AXIS TM3820 VANDAL CASING 4P	10	02820-001	4	Accessory
AXIS TQ6813 HARD COATED CLEAR DOME	5	02938-001	4	Accessory
AXIS TQ6814 HARD COATED SMOKED DOME	5	02939-001	4	Accessory
AXIS TP3833-E Dome Casing Black	5	02871-001	2	Accessory
AXIS TP3832-E Dome Smoked	5	02872-001	2	Accessory
AXIS TQ1001-E WALL MOUNT	15	02325-001	4	Accessory
AXIS TQ1301-E POLE MOUNT 50-150mm	5	02343-001	4	Accessory
AXIS TQ1303-E CORNER MOUNT	5	02648-001	4	Accessory

AXIS TQ1918 ADAPTER M20x1.5-3/4 NPT	5		02762-001	4	Accessory
ECP081208 PS 24V UL	5		5801-931	12	Accessory
EX POLE BRACKET XF40	5		5507-191	12	Accessory
EX WALL MOUNT XF40	10		5507-201	12	Accessory
EX POLE MOUNT XF40	5		5507-221	12	Accessory
WALL MOUNT D201-S XPT	10	Discontinued	01521-001	2	Accessory
WALL MOUNT EXCAM XF	5		01569-001	6	Accessory
EXCAM XF WIPER BLADE 10 PACK	5		01930-001	6	Accessory

FRONT GLASS PROTECTIVE FILM F101-A	5	02029-001	2	Accessory
EXCONNECTION RAIL 8-PORT POE++	5	02747-001	12	Accessory
AXIS TQ1920 ADAPTER M25x1.5-1/2 NPT	5	02798-001	4	Accessory
AXIS TQ1921 ADAPTER M20x1.5-1/2 NPT	5	02797-001	4	Accessory
AXIS TQ1925 ADAPTER M25x1.5-M20x1.5	5	02799-001	4	Accessory
AXIS TQ1812-E WEATHERSHIELD	5	02387-001	4	Accessory
AXIS TQ1814-E WEATHERSHIELD	5	02801-001	4	Accessory
AXIS TQ1922-E SWIVEL JOINT	5	02802-001	4	Accessory
AXIS TQ1923-E WIPER BLADE 5P	5	02803-001	4	Accessory
AXIS TQ1924-E WASHER NOZZLE	5	02800-001	4	Accessory
AXIS TU6012 CONN 2-PIN 7.62 ST	5	02824-001	4	Accessory
AXIS TU6013 CONN 2-PIN 5.08 ST	5	02823-001	4	Accessory
AXIS TU6014 CONN 6-Pin 3.81 ST	5	02825-001	4	Accessory

AXIS 1.5" NPS/NPT MALE COUPLER	90		01706-001	2	Accessory
AXIS T8640 WALL MOUNT BRACKET	10		5026-411	4	Accessory
AXIS T8640 DIN RAIL CLIP	20		5026-431	4	Accessory
AXIS T8642 MOUNTING KIT A	5	Discontinued	5506-291	4	Accessory
AXIS T8640 RACK MOUNT BRACKET	10		5026-421	4	Accessory
AXIS T91A02 DIN RAIL CLIP 77MM	15		5017-027	4	Accessory
AXIS T91A02 DIN RAIL CLIP 86MM	10		5017-028	4	Accessory
AXIS T91A03 DIN RAIL MOUNT	20		5503-194	4	Accessory
AXIS T91A04 CAMERA HOLDER 3/4" NPS	60		5017-041	2	Accessory
AXIS T91A05 CAMERA HOLDER 1.5" NPS	10		5017-051	2	Accessory
AXIS T91A06 PIPE ADAPTER 3/4-1.5"	250		5503-091	2	Accessory
AXIS T91A10 MOUNTING KIT	100		5507-331	2	Accessory
	100			-	Accessory
AXIS T91A11 STAND WHITE	80		5017-111	4	Accessory
					-

			-	
AXIS T91A13 THREADED CEIL MOUNT 10P	5	01464-001	4	Accessory
AXIS T91A23 TILE GRID CEIL MNT 4P	125	01612-001	2	Accessory
AXIS T91A33 LIGHT TRACK MNT 4P	10	01467-001	4	Accessory
AXIS T91A33 LIGHT TRACK MNT BLK 4P	5	01474-001	4	Accessory
AXIS T85 RACK MOUNT KIT A AXIS T91B21 STAND BLACK	15 10	01232-001 5506-621	4	Accessory Accessory
AXIS T91B21 STAND WHITE	20	5506-611	2	Accessory
AXIS T91A27 POLE MOUNT 10PCS	5	5503-971	4	Accessory
AXIS T91B47 100-410MM	500	01164-001	2	Accessory

	•	04405 004	•	
AXIS T91B47 50-150MM	0	01165-001	2	Accessory
AXIS T91B57 POLE MOUNT 100-410MM	250	01470-001	2	Accessory
AXIS T91B57 POLE MOUNT GREY	40	01446-001	4	Accessory
AXIS T91B67 POLE MOUNT 65-165MM	450	01473-001	2	Accessory
AXIS T91M47 POLE MOUNT	5	01149-001	2	Accessory
AXIS TD9301 OUTDOOR MIDSPAN POLE MOUNT	5	01951-001	4	Accessory
AXIS T91D61 WALL MOUNT	1600	5504-821	2	Accessory
AXIS T91E61 WALL MOUNT	1100	5506-481	2	Accessory

AXIS T91G61 WALL MOUNT	650		5506-951	2	Accessory
			01111001		
AXIS T91G61 WALL MOUNT GREY	80		01444-001	4	Accessory
AXIS TS2901 APPLIANCE STAND	5		02035-001	4	Accessory
	·			•	riceccory
AXIS T91H61 WALL MOUNT	750		5507-641	2	Accessory
AXIS T91F61 WALL MOUNT STAINLESS STEEL	10		5506-681	4	A
					Accessory
AXIS T91L61 WALL-AND-POLE MOUNT	175	Discontinued	5801-721	4	Accessory

AXIS T91K61 WALL MOUNT	5	Discontinued	5901-401	4	Accessory
AXIS T94J01A WALL MOUNT	40		5901-331	4	Accessory
AXIS T94J01A WALL MOUNT GREY	10		01445-001	4	Accessory
AXIS T91D62 TELESCOPIC PARAPET MNT	300		5507-271	2	Accessory
AXIS T91D62 ADAPTER MOUNTING BRACKET	15		5507-501	4	Accessory
AXIS T91B62 PARAPET MOUNT	60	Discontinued	5504-631	2	Accessory

AXIS T91B50 TELESCOPIC CEIL MNT	450	5507-451	2	Accessory
	100		-	<i>i</i> lococoly
AXIS T91B51 CEILING MOUNT	450	5507-461	2	Accessory
AXIS T91B52 EXTENSION PIPE 30 CM	175	5507-491	2	Accessory
AXIS 191852 EXTENSION FIFE 50 CM	175	5507-491	2	Accessory
AXIS T91B52 EXTENSION PIPE 100 CM	200	5507-481	2	Accessory
AXIS T91B53 TELESCOPIC CEIL MNT 2P	125	01189-001	2	Accessory
AXIS T91B63 CEILING MOUNT	150	5504-641	2	Accessory
				-
AXIS T91A64 BRACKET CORNER	1400	5017-641	2	Accessory
				-
	-			I

AXIS T91F67 POLE MOUNT STAINLESS STEEL	10		5506-691	4	Accessory
AXIS T91A6 PIPE SEAL 1PCS	10		5503-781	2	Accessory
AXIS T93C WALL-POLE CONDUIT BACKBOX	5		5901-421	2	Accessory
AXIS T94A01C ATTACHMENT KIT	20		5901-301	2	Accessory
	20			-	Accessery
AXIS T94A01D PENDANT KIT	1000		5502-431	2	Accessory
AXIS T94A02D PENDANT KIT	10	Discontinued	5901-411	4	Accessory
AXIS T94A01F CEILING BRACKET	10		5506-181	4	Accessory
AXIS T94A02F CEILING BRACKET	10		5801-601	4	Accessory
AND 194AUZP CEILING BRACKET	10		5001-001	4	Accessory
AXIS T94A01L RECESSED MOUNT	30		5505-721	4	Accessory
AXIS T94A02L RECESSED MOUNT	125		5506-171	2	Accessory
AXIS T94A04L RECESSED MOUNT	15	Discontinued	5801-611	4	Accessory
AND 134AU4L RECESSED MOUNT	10	Discontinued	5001-011	4	ACCESSOLY

AXIS T94B02D PENDANT KIT 10PCS	10		01159-001	4	Accessory
	10			-	Accessivy
AXIS T94B02D PENDANT KIT	400		5507-361	2	Accessory
AXIS T94B02D PENDANT KIT BLACK	70		01185-001	2	Accessory
AXIS T94B05L RECESSED MOUNT	5	Discontinued	01150-001	2	Accessory
AXIS T94B03L RECESSED MOUNT	5		5801-861	4	Accessory
AXIS T94B02M J-BOX/GANG BOX PLATE	800		5801-421	2	Accessory
AXIS T94B01P CONDUIT BACK BOX	250		5507-401	2	Accessory
AXIS T94C01L RECESSED MOUNT	80		01242-001	4	Accessory
					,
AXIS T94C01M J-BOX/GANG BOX PLATE	80		01243-001	4	Accessory

AXIS T94C01U UNIVERSAL MOUNT	90		01244-001	4	Accessory
AXIS T94D01S MT BRACKET FL WT 10PCS	5		5504-911	4	Accessory
AXIS T94D02S MT BRACKET CU WT 10PCS	5		5504-921	4	Accessory
AXIS T94F01D PENDANT KIT	30		5503-881	2	Accessory
AXIS TM1902 Stand Mount 4 pcs	15		02853-001	4	Spare Part
AXIS T94F02D PENDANT KIT	10	Discontinued	5900-021	2	Accessory
AXIS T94F01M J-BOX/GANG BOX PLATE	60		5503-921	2	Accessory
AXIS T94F01P CONDUIT BACK BOX	450		5504-041	2	Accessory
AXIS T94G01P CONDUIT BACK BOX	60		5505-181	2	Accessory
AXIS T94K01D PENDANT KIT	1000		5505-081	2	Accessory
AXIS T94M01D PENDANT KIT	200		5505-091	2	Accessory

AXIS T94M02L RECESSED MOUNT	30	01156-001	2	Accessory
			-	,,
AXIS T94N01D PENDANT KIT	2500	01513-001	2	Accessory
AXIS T94N02D Pendant Kit	300	02076-001	2	Accessory
AXIS T94N01G POLE MOUNT	60	5901-341	4	Accessory
AXIS T94N01L RECESSED MOUNT	80	01514-001	2	Accessory
AXIS T94P01B CORNER BRACKET	10	5504-711	2	Accessory
		0004-711	2	Accessory
AXIS T94P01L RECESSED MOUNT	250	01172-001	2	Accessory
				· · · · · · · · · · · · · · · · · · ·
AXIS T94Q01A WALL MOUNT	5	5505-241	4	Accessory

AXIS T94Q01F CEILING AND COLUMN MNT	40		5507-591	4	Accessory
					-
AXIS T94R01B CORNER BRACKET	175		5507-601	2	Accessory
AXIS TQ1601-E CONDUIT BACK BOX	175		02336-001	2	Accessory
AXIS T94S01L RECESSED MOUNT	10	Discontinued	5507-671	2	Accessory
		Diocontantaoa		-	/
AXIS T94S01L RECESSED MOUNT 10P	5	Discontinued	5901-361	2	Accessory
	-				, , ,
AXIS T94S02L RECESSED MOUNT	100	Discontinued	01462-001	4	Accessory
	1			I	L

AXIS T94S01P CONDUIT BACK BOX	350		01190-001	2	Accessory
AXIS TQ1602-E CONDUIT BACK BOX	175		02421-001	2	Accessory
AXIS T94T01D PENDANT KIT	900	Discontinued	5505-871	2	Accessory
AXIS T94T02D PENDANT KIT	350		01461-001	2	Accessory
AXIS T94U01D PENDANT KIT	10		5506-651	4	Accessory
AXIS T94U02D PENDANT KIT	10		5506-661	4	Accessory
AXIS T94V01C DUAL CAMERA MOUNT	30		01457-001	4	Accessory
	400		04505 004		
AXIS T94V02D PENDANT KIT	100	Discontinued	01505-001	4	Accessory

AXIS T94V01D PENDANT KIT	5	Discontinued	5801-431	4	Accessory
AXIS T94X01A WALL MOUNT 6PCS	100		5801-541	4	Accessory
AXIS T94Y01G POLE MOUNT 6PCS	100		5801-551	4	Accessory
AXIS T95A64 BRACKET CORNER	10		5010-641	4	Accessory
AXIS T95A67 BRACKET POLE	30		5010-671	4	Accessory
WALL MOUNT AXIS PS24	5		5000-011	4	Accessory
AXIS PS-24 Pole bracket	5		21764	4	Accessory
AXIS T91A03 DIN RAIL CLIP 5PCS	30		5800-511	4	Accessory
AXIS MIDSPAN DIN CLIP A	5		5503-931	4	Accessory
AXIS P33 MOUNTING BRACKET	50		5502-401	2	Accessory
P1214/-E MOUNT KIT EXC HOUS 5-P	5		5800-461	4	Accessory
	·				
AXIS P33XX-VE ¾INPS CONDUIT ADAPTER	30	Discontinued	5503-711	2	Accessory
AXIS TQ1904 MOUNTING BRACKET	10		02451-001	4	Accessory

AXIS P33XX-VE ¾INPS COND ADPT 4P	5	Discontinued	5503-721	4	Accessory
AXIS P33XX-VE ¾" NPS ADAPT	30	Discontinued	5503-131	2	Accessory
AXIS RETROFIT KIT FOR T94S01L 4P	5		01982-001	4	Accessory
AXIS RETROFIT KIT T94K01L/02L 4P	10		02002-001	4	Accessory
AXIS P33-VE Pendant Kit	300	Discontinued	5502-321	2	Accessory
ADAPTER AXIS 209 TO M31/P39 50 PCS	5		5503-192	4	Accessory
AXIS P33XX-VE CABLE COVER 4 PCS	5	Discontinued	5503-731	4	Accessory
AXIS ACI COND ADAP 3/4" U-SHAPE 30MM 5PCS	50		5505-191	4	Accessory
AXIS ACI CONDUIT BRACKET A 5P	40	Discontinued	5505-971	4	Accessory
AXIS ACI CONDUIT ADAPTER 1/2"-3/4" A 2P	70		5505-541	4	Accessory
AXIS ACI COND ADAP 1/2 " U-SHAPE 20MM 5P	10		5505-521	4	Accessory
AXIS ACI COND ADAP 1/2"-3/4" NPS 2P	5		5505-591	4	Accessory

AXIS ACI CONDUIT ADAPTER 3/4" NPS 2P	200		5505-641	4	Accessory
AXIS RACK SLIDE RAILS A	5	Discontinued	5504-781	4	Accessory
					_
AXIS F7308 CABLE BLACK 8M 4PCS	5		5506-921	4	Accessory
AXIS F8401 CLEAR LENS PROTECTOR 5PCS	10		5505-841	4	Accessory
AXIS F8202 STRAIGHT MT BRACKET 5PCS	5		5505-821	2	Accessory
AXIS F8203 FIXED MT BRACKET 5PCS	10		5505-831	2	Accessory
AXIS F8211 PINHOLE TRIM RING 10PCS	5		5507-101	4	Accessory
AXIS F8212 TRIM RING 10PCS	5		5507-111	4	Accessory
AXIS F8205 BULLET ACCESSORY	10		5506-211	2	Accessory
AXIS F8225 PINHOLE ACCESSORY	10		5506-531	2	Accessory
AXIS F8235 FISHEYE ACCESSORY	10		5506-541	4	Accessory
AXIS F92A01 BLACK HEIGHT S. HOUSING	20		01630-001	2	Accessory
	20		01000-001	L	Accessory

AXIS F92A01 SILVER HEIGHT S. HOUSI~	20	01631-001	2	Accessory
AXIS T91R61 WALL MOUNT	30	01516-001	4	Accessory
AXIS TD4601 ACI Conduit Bracket 5pcs	5	02281-001	4	Accessory
AXIS TM3001 TILT MOUNT	20	01748-001	4	Accessory
AXIS TM3101 PENDANT WALL MOUNT	80	01742-001	2	Accessory
AXIS TM3101 PENDANT WALL MNT BLACK	5	01917-001	4	Accessory
AXIS TM3201 RECESSED MOUNT	125	01856-001	2	Accessory
AXIS TM3204 RECESSED MOUNT	15	02425-001	4	Accessory
AXIS TM3205 RECESSED MOUNT	20	02381-001	2	Accessory

AXIS TM3208 RECESSED MOUNT	60	02449-001	2	Accessory
AXIS TM3209 RECESSED MOUNT	70	02454-001	2	Accessory
AXIS TM3210 RECESSED MOUNT	20	02817-001	2	Accessory
AXIS TM3211 RECESSED MOUNT	15	02818-001	2	Accessory
AXIS TP1601 ADAPTER PLATE	50	02083-001	2	Accessory
AXIS TP3101 PENDANT WALL MOUNT	5	01783-001	2	Accessory
AXIS TP3103-E PENDANT KIT	1400	02548-001	2	Accessory
AXIS TP3201 RECESSED MOUNT	500	01757-001	2	Accessory

	00	00450.004		
AXIS TP3201-E RECESSED MOUNT	90	02452-001	2	Accessory
AXIS TP3202 RECESSED MOUNT	125	01983-001	2	Accessory
AXIS TP3203 RECESSED MOUNT	30	02509-001	2	Accessory
AXIS TP3601 3/4" CONDUIT ADAPTER 4P	100	01804-001	2	Accessory
AXIS TP3603 CONDUIT BACK BOX	250	02025-001	2	Accessory
AXIS TP3701 J-BOX & POLE ADAPTER	70	01743-001	4	Accessory
AXIS TP3905 CONDUIT ADAPTER 1" 4P	5	02388-001	4	Accessory
AXIS TP8101 PENDANT KIT	5	02019-001	4	Accessory
AXIS TP8201 RECESSED MOUNT	5	02020-001	4	Accessory
AXIS TP3602 1/2" CONDUIT ADAPTER 4P	30	01805-001	4	Accessory

AXIS TP3902 RETROFIT KIT 4P	5	01807-001	2	Accessory
AXIS TQ3101-E PENDANT KIT	250	02107-001	4	Accessory
AXIS TQ3102 PENDANT KIT	90	02108-001	4	Accessory
AXIS TQ3201-E RECESSED MOUNT	15	02136-001	4	Accessory
AXIS TQ6501-E PARAPET MOUNT	70	02110-001	2	Accessory
AXIS TQ9601 CONDUIT TOP BOX	60	01818-001	4	Accessory
AXIS TQ6901-E ADAPTER BRACKET 4P	15	02111-001	4	Accessory
AXIS TS3001 Recorder Mount	10	02081-001	2	Accessory
AXIS TQ6201-E RECESSED MOUNT	5	02102-001	4	Accessory
AXIS TQ1501-E CRANE TRAFFIC MOUNT	15	02384-001	2	Accessory

AXIS TM3206 RECESSED MOUNT	20	02382-001	2	Accessory
			-	, lococory
AXIS TM3207 RECESSED MOUNT	40	02383-001	2	Accessory
AXIS TF9902 SURFACE MOUNT	30	02360-001	4	Accessory
AXIS TF9903 DIN RAIL CLIP	10	02361-001	4	Accessory
		02301-001	-	Accessory
AXIS TM5601 CONDUIT BACK BOX	10	02427-001	4	Accessory
AXIS TD3901 Strain Relief 2P	10	02285-001	4	Accessory
		00000.004		
AXIS TD3902 Connector Kit	5	02302-001	2	Accessory
AXIS TP1602-E Conduit Back Box	20	02712-001	4	Accessory
	40	02214-001		A
AXIS TF1902-RE MOUNTING BRACKET 4P	40	02214-001	4	Accessory
	•			

AXIS TF1202-RE RECESSED MOUNT 4P	20	02216-001	4	Accessory
	10	00017-001		
AXIS TF1203-RE RECESSED MOUNT 4P	10	02217-001	4	Accessory
AXIS TF1901-RE SWIVEL MOUNT 4P	20	02212-001	4	Accessory
AXIS TF1201-RE RECESSED MOUNT 4P	30	02433-001	4	Accessory
AXIS TQ1003-E Wall Mount	20	02567-001	2	Accessory

AXIS TQ3103-E PENDANT KIT	40	02855-001	2	Accessory
AXIS TQ3202-E RECESSED MOUNT	10	02856-001	2	Accessory
AXIS TM4101 PENDANT KIT	20	02837-001	4	Accessory
AAIS IM4IUT PENDANT KIT	20	02037-001	4	Accessory
AXIS TM4201 RECESSED MOUNT 4P	20	02836-001	4	Accessory
AXIS TP5201-E RECESSED MOUNT	20	02830-001	2	Accessory
AXIS TP4601-E Conduit Back Box	30	02750-001	4	Accessory
	30	02730-001	-	Accessory
AXIS TQ3601-E CONDUIT BACK BOX	50	02913-001	4	Accessory
AXIS TP3004-E Wall Mount Black	100	02923-001	2	Accessory

AXIS TP3105-E Pendant Kit Black	60		02924-001	2	Accessory
AXIS TP3106-E Pendant Kit Black	80		02925-001	2	Accessory
AXIS TP3301-E Pole Mount Black	60		02961-001	2	Accessory
AXIS TP3204-E RECESSED MOUNT	175		02873-001	2	Accessory
	1400	New	02411-001	2	A
AXIS TQ5001-E Wall/Pole Mount	1400	New	02411-001	2	Accessory
AXIS TP1001-E Wall/Pole Mount	200	New	02851-001	2	Accessory

5	01226-001	4	Accessory
			-
5	01227-001	4	Accessory
10	02575-001	10	Accessory
			,,
		-	
20	02222-001	2	Audio Systems
			Oyotomo
5000	02223-001	4	Audio
			Systems
5	02556-001	2	Audio
		-	Systems
_	20	10 02575-001 20 02222-001 5000 02223-001	10 02575-001 10 10 02575-001 10 20 02222-001 2 5000 02223-001 4

AXIS TC1603 TILE BRIDGE 2P	50	02555-001	2	Audio Systems
AXIS TC1602 CONDUIT ADAPTER 5P	5	02557-001	4	Audio Systems
AXIS TC1901 WIRE KIT 5P	5	02558-001	4	Audio Systems
AXIS TC1902 Ceiling Speaker Gasket 5P	5	02720-001	4	Audio Systems
AXIS TC1903 Ceiling Speaker Gasket 5P	5	02721-001	4	Audio Systems
AXIS AUDIO MANAGER CENTER 1Y ELIC	0	02246-001	0	Audio Systems

		-	00000 001	•	A !!
AXIS AUDIO MANAGER PRO - E-LICENSE	0		02062-001	0	Audio
					Systems
AXIS C7050 MK III	5		02723-004	2	Audio
	5		02/23-004	2	
					Systems
	-	Discontinued	00074 004	4	A
AXIS AUDIO MANAGER PRO C7050 MK II	5	Discontinued	02071-004	4	Audio
					Systems

AXIS AUDIO MANAGER PRO C7050	5 850	Discontinued	01519-004	2	Audio Systems Audio
					Systems
AXIS C1004-E NETW CAB SPEAKER BLACK	10		0923-001	2	Audio Systems

AXIS C1004-E NETW CAB SPEAKER WHITE	15	0833-001	2	Audio Systems
AXIS C1410 NETWORK MINI SPEAKER	100	01916-001	2	Audio Systems

AXIS C1210-E NETWORK CEILING SPEAKER	125	02324-001	2	Audio
	.20		_	Systems
				-
AXIS C1211-E NETWORK CEILING SPEAKER	125	02323-001	2	Audio
AXIS C1211-E NETWORK CEILING SPEAKER	125	02323-001	2	Audio Systems
AXIS C1211-E NETWORK CEILING SPEAKER	125	02323-001	2	Audio Systems
AXIS C1211-E NETWORK CEILING SPEAKER	125	02323-001	2	Audio Systems
AXIS C1211-E NETWORK CEILING SPEAKER	125	02323-001	2	Audio Systems
AXIS C1211-E NETWORK CEILING SPEAKER	125	02323-001	2	Audio Systems
AXIS C1211-E NETWORK CEILING SPEAKER	125	02323-001	2	Audio Systems
AXIS C1211-E NETWORK CEILING SPEAKER	125	02323-001	2	Audio Systems
AXIS C1211-E NETWORK CEILING SPEAKER	125	02323-001	2	Audio Systems
AXIS C1211-E NETWORK CEILING SPEAKER	125	02323-001	2	Audio Systems
AXIS C1211-E NETWORK CEILING SPEAKER	125	02323-001	2	Audio Systems
AXIS C1211-E NETWORK CEILING SPEAKER	125	02323-001	2	Audio Systems
AXIS C1211-E NETWORK CEILING SPEAKER	125	02323-001	2	Audio Systems
AXIS C1211-E NETWORK CEILING SPEAKER	125	02323-001	2	Audio Systems
AXIS C1211-E NETWORK CEILING SPEAKER	125	02323-001	2	Audio Systems
AXIS C1211-E NETWORK CEILING SPEAKER	125	02323-001	2	Audio Systems
AXIS C1211-E NETWORK CEILING SPEAKER	125	02323-001	2	Audio Systems
AXIS C1211-E NETWORK CEILING SPEAKER	125	02323-001	2	Audio Systems
AXIS C1211-E NETWORK CEILING SPEAKER	125	02323-001	2	Audio Systems
AXIS C1211-E NETWORK CEILING SPEAKER	125	02323-001	2	Audio Systems
AXIS C1211-E NETWORK CEILING SPEAKER	125	02323-001	2	Audio Systems
AXIS C1211-E NETWORK CEILING SPEAKER	125	02323-001	2	Audio Systems
AXIS C1211-E NETWORK CEILING SPEAKER	125	02323-001	2	Audio Systems
AXIS C1211-E NETWORK CEILING SPEAKER	125	02323-001	2	Audio Systems

AXIS C1510 NETWORK PENDANT SPEAKER	15	02389-001	2	Audio Systems
AXIS C1511 NETWORK PENDANT SPEAKER	5	02390-001	2	Audio Systems
AUDIO CEILING TILE KIT US	40	02378-004	2	Audio Systems

	1			
AUDIO CEILING TILE KIT CAM READY US	40	02379-004	2	Audio
				Systems
	50	02380-001	2	Audio
AXIS C1610-VE	50	02380-001	2	Audio
				Systems
AXIS TC1703 Mesh Cover 5p	5	02559-001	4	Audio
	5	020001	1	
				Systems

AVIO TO4704 Mach Cover En	-		00500 004	4	Audia
AXIS TC1704 Mesh Cover 5p	5		02560-001	4	Audio Systems
AXIS C8033 NETWORK AUDIO BRIDGE	60	Discontinued	01025-001	2	Audio Systems
AXIS C8310 Volume Controller	40		02741-001	2	Audio Systems
AXIS C8110 NETWORK AUDIO BRIDGE	60		02370-001	2	Audio Systems

AXIS C8210 NETWORK AUDIO AMP	15	01558-001	2	Audio Systems
AXIS XPQ1785	10	02278-001	4	Camera

AXIS P1468-XLE	50	02534-001	4	Camera

AXIS XFQ1656	10		02462-001	4	Camera
D201-S XPT Q6075	5	Discontinued	01926-001	2	Camera

XF40-Q1785 -50 C UL	10		02189-001	12	Camera
	-				
AXIS M1045-LW	20	Discontinued	0812-004	2	Camera
					-
AXIS M1055-L BOX CAMERA	70		02349-001	2	Camera

AXIS M1065-L	450	Discontinued	0811-001	2	Camera
AXIS M1065-LW	70	Discontinued	0810-004	4	Camera
	10	Discontinued	0010 004	-	Guilleru
AXIS M1075-L BOX CAMERA	500		02350-001	2	Camera

Camera
Camera

AXIS M1135 MK II	250		02483-001	2	Camera
AXIS M1135 MK II i-CS	10		02580-001	2	Camera
	-				
AXIS M1135 BAREBONE	5	Discontinued	01768-041	4	Camera

AXIS M1135-E	40	Discontinued	01772-001	4	Camera
AXIS M1135-E MK II	200		02485-001	2	Camera

AXIS M1137 20 Discontinued 01769-001 4 Camera	AXIS M1135-E MK II i-CS	10		02622-001	2	Camera
AXIS M1137 20 Discontinued 01769-001 4 Camera						
AXIS M1137 20 Discontinued 01769-001 4 Camera						
AXIS M1137 20 Discontinued 01769-001 4 Camera						
AXIS M1137 20 Discontinued 01769-001 4 Camera						
AXIS M1137 20 Discontinued 01769-001 4 Camera						
AXIS M1137 20 Discontinued 01769-001 4 Camera						
AXIS M1137 20 Discontinued 01769-001 4 Camera						
AXIS M1137 20 Discontinued 01769-001 4 Camera						
AXIS M1137 20 Discontinued 01769-001 4 Camera						
AXIS M1137 20 Discontinued 01769-001 4 Carnera						
AXIS M1137 20 Discontinued 01769-001 4 Camera						
AXIS M1137 20 Discontinued 01769-001 4 Camera						
AXIS M1137 20 Discontinued 01769-001 4 Camera						
AXIS M1137 20 Discontinued 01769-001 4 Camera						
AXIS M1137 20 Discontinued 01769-001 4 Camera						
AXIS M1137 20 Discontinued 01769-001 4 Camera						
AXIS M1137 20 Discontinued 01769-001 4 Camera						
AXIS M1137 20 Discontinued 01769-001 4 Camera						
AXIS M1137 20 Discontinued 01769-001 4 Camera						
	AXIS M1137	20	Discontinued	01769-001	4	Camera

AXIS M1137 MK II I-CS 5 02581-001 2 Camera AXIS M1137 BULK 10PCS 5 Discontinued 01768-021 2 Camera AXIS M1135 BULK 10PCS 5 Discontinued 01768-021 2 Camera	AXIS M1137 MK II	60		02484-001	2	Camera
AXIS M1135 BULK 10PCS 5 Discontinued 01768-021 2 Camera						
AXIS M1135 BULK 10PCS 5 Discontinued 01768-021 2 Camera						
AXIS M1135 BULK 10PCS 5 Discontinued 01768-021 2 Camera						
AXIS M1135 BULK 10PCS 5 Discontinued 01768-021 2 Camera						
AXIS M1135 BULK 10PCS 5 Discontinued 01768-021 2 Camera						
AXIS M1135 BULK 10PCS 5 Discontinued 01768-021 2 Camera						
AXIS M1135 BULK 10PCS 5 Discontinued 01768-021 2 Camera						
AXIS M1135 BULK 10PCS 5 Discontinued 01768-021 2 Camera						
AXIS M1135 BULK 10PCS 5 Discontinued 01768-021 2 Camera						
AXIS M1135 BULK 10PCS 5 Discontinued 01768-021 2 Camera						
AXIS M1135 BULK 10PCS 5 Discontinued 01768-021 2 Camera						
AXIS M1135 BULK 10PCS 5 Discontinued 01768-021 2 Camera						
AXIS M1135 BULK 10PCS 5 Discontinued 01768-021 2 Camera						
AXIS M1135 BULK 10PCS 5 Discontinued 01768-021 2 Camera						
	AXIS M1137 MK II i-CS	5		02581-001	2	Camera
	AXIS M1135 BULK 10PCS	5	Discontinued	01768-021	2	Camera
IAXIS M1137 BAREBONE 5 Discontinued 01769-041 4 Camera						
	AXIS M1137 BAREBONE	5	Discontinued	01769-041	4	Camera

AXIS M1137-E	20	Discontinued	01773-001	4	Camera
AXIS M1137-E MK II	60		02486-001	2	Camera

AXIS M1137-E MK II i-CS	5		02623-001	2	Camera
AXIS M2025-LE	350	Discontinued	0911-001	4	Camera

AXIS M2025-LE BLACK	30	Discontinued	0988-001	4	Camera
	50	Discontinueu	0300-001	-	Camera
AXIS M2025-LE BULK 10PCS	5	Discontinued	0911-021	2	Camera
AXIS M2026-LE MK II	250	Discontinued	01049-001	2	Camera
AXIS M2026-LE MK II BLACK	20	Discontinued	01050-001	2	Camera
	-				
	<u> </u>				
AXIS M2026-LE Mk II BULK 10PCS	5	Discontinued	01049-021	4	Camera
AXIS M2026-LE Mk II BLACK BULK 10PCS	5	Discontinued	01050-021	4	Camera
		Discontinued	01000-021		Gamera
				1	

AXIS M2035-LE	800	02124-001	2	Camera
AXIS M2035-LE Black	70	02131-001	2	Camera
	10	02101-001	2	Gamera

AXIS M2035-LE 8 MM	20	02132-001	2	Camera
AXIS M2035-LE 8 MM BLACK	5	02133-001	4	Camera

AXIS M2036-LE	550	02125-001	2	Camera
AXIS M2036-LE Black	90	02134-001	2	Camera

AXIS P1245	300	0926-001	2	Camera
			_	
AXIS P1265	125	0927-001	2	Camera
AXIS P1275	30	0928-001	2	Camera

AXIS P1375	40	01532-001	2	Camera
AXIS P1375 BAREBONE	5	01532-031	4	Camera

AXIS P1375-E	100	01533-001	2	Camera
AXIS P1375-E BAREBONE	5	01533-031	4	Camera

AXIS P1375-E	100	41533-001	2	Camera
AXIS P1375-E BAREBONE	5	41533-031	4	Camera
	Ŭ	 	т 	ounioru

AXIS P1377	10	01808-0	001 2	Camera
AXIS P1377 BAREBONE	10	01808-0)31 2	Camera

AXIS P1377-LE	50	01809-001	2	Camera
AXIS P1377-LE BAREBONE	10	01809-031	2	Camera
	10	01003-001	۲	Gainera

AXIS P1377-LE	50	41809-001	2	Camera
AXIS P1377-LE BAREBONE	10	 41809-031	2	Camera
	10	71003-051	۲	Gainera

AXIS P1368-E	10	Discontinued	01109-001	4	Camera
		Discontinued	01100-001	-	Gamera
AXIS P1368-E BAREBONE	5	Discontinued	01109-031	4	Camera
AXIS P1378	15		01810-001	2	Camera
	-				
AXIS P1378 BAREBONE	10		01810-031	2	Camera

AXIS P1378-LE	50	Description changed	01811-001	2	Camera
AXIS P1378-LE BAREBONE	10		01811-031	2	Camera

AXIS P1378-LE	50	41811-001	2	Camera
AXIS P1378-LE BAREBONE	10	41811-031	2	Camera

AXIS P1445-LE	60	Discontinued	01506-001	4	Camera
AXIS P1455-LE-3 L. P. Verifier Kit	40	Discontinued	02235-001	4	Camera

mera

AXIS P1455-LE 29 mm	60	Discontinued	02095-001	4	Camera
AXIS P1465-LE	350		02339-001	2	Camera
				-	

AXIS P1465-LE 29 mm	200		02340-001	2	Camera
AXIS P1447-LE	400	Discontinued	01054-001	2	Camera
	400	Discontinued	01004-001	-	Gamera

AXIS P1467-LE	550		02341-001	2	Camera
AXIS P1448-LE	350	Discontinued	01055-001	4	Camera
AXIS P1448-LE	350	Discontinued	01055-001	4	Camera
AXIS P1448-LE	350	Discontinued	01055-001	4	Camera
AXIS P1448-LE	350	Discontinued	01055-001	4	Camera
AXIS P1448-LE	350	Discontinued	01055-001	4	Camera
AXIS P1448-LE	350	Discontinued	01055-001	4	Camera
AXIS P1448-LE	350	Discontinued	01055-001	4	Camera
AXIS P1448-LE	350	Discontinued	01055-001	4	Camera
AXIS P1448-LE	350	Discontinued	01055-001	4	Camera
AXIS P1448-LE	350	Discontinued	01055-001	4	Camera
AXIS P1448-LE	350	Discontinued	01055-001	4	Camera
AXIS P1448-LE	350	Discontinued	01055-001	4	Camera
AXIS P1448-LE	350	Discontinued	01055-001	4	Camera
AXIS P1448-LE	350	Discontinued	01055-001	4	Camera
AXIS P1448-LE	350	Discontinued	01055-001	4	Camera
AXIS P1448-LE	350	Discontinued	01055-001	4	Camera
AXIS P1448-LE	350	Discontinued	01055-001	4	Camera
AXIS P1448-LE	350	Discontinued	01055-001	4	Camera
AXIS P1448-LE	350	Discontinued	01055-001	4	Camera
AXIS P1448-LE	350	Discontinued	01055-001	4	Camera
AXIS P1448-LE	350	Discontinued	01055-001	4	Camera

AXIS P1468-LE	400		02342-001	2	Camera
AXIS Q1615 Mk III	20	Discontinued	02051-001	2	Camera
	20	Discontinucu	02001 001	-	Guineru

AXIS Q1615-LE Mk III	50		02064-001	2	Camera
AXIS Q1615 Mk III BAREBONE	5	Discontinued	02051-041	2	Camera
N//0.010/7					
AXIS Q1645	10	Discontinued	01222-001	4	Camera
	1			1	

AXIS Q1645 BARE BONE	5	Discontinued	01222-041	4	Camera
AXIS Q1645-LE	5	Discontinued	01223-001	4	Camera
AXIS Q1647	5	Discontinued	01051-001	4	Camera

AXIS Q1647-LE	10	Discontinued	01052-001	4	Camera
AXIS Q1656	20		02164-001	2	Camera

AXIS Q1656-B	5	02164-031	4	Camera

AXIS Q1656-LE	30	02168-001	2	Camera

AXIS Q1656-BLE	5	02442-031	4	Camera

AXIS Q1656-BE	5	02168-031	4	Camera

AXIS Q1656-DLE	15	02420-001	2	Camera

AXIS Q1659 35MM F/2	5	Discontinued	0963-001	4	Camera
AXIS Q1715 BLOCK CAMERA	10		02220-001	2	Camera

AXIS Q1700-LE	70	01782-001	2	Camera
AXIS Q1785-LE	10	01161-001	4	Camera
AND GIVES-LE	10	01101-001	4	Califera

AXIS Q1786-LE	20	01162-001	4	Camera

XIS Q1798-LE	40	01702-001	2	Camera

AXIS Q1805-LE	200	02504-001	2	Camera

175	To be launched	02506-001	2	Camera
350		0913-001	2	Camera
	350			

AXIS FA1125 SENSOR UNIT	175	0914-001	2	Camera
AXIS FATT25 SENSOR UNIT	175	0914-001	2	Calliera
AXIS FA3105-L EYEBALL SENSOR UNIT	175	01026-001	2	Camera
AXIS FASTUS-L ETEBALL SENSOR UNIT	175	01020-001	2	Califera
AXIS FA4115 SENSOR UNIT	60	04004 004	2	
AXIS FA4115 SENSOR UNIT	60	01001-001	2	Camera
AXIS FA51 MAIN UNIT	60	02196-001	2	Camera
AND FADT MAIN UNIT	00	02196-001	<u> </u>	Camera

AXIS FA51 MAIN UNIT 10PCS	50	02196-021	2	Camera
AXIS FA51-B MAIN UNIT 10PCS	5	02196-041	4	Camera

AVIS EAEA MAINI LINIT	E	0070 004	2	Comoro
AXIS FA54 MAIN UNIT	5	0878-004	2	Camera
AXIS P8815-2 3D Ppl Counter BK	10	01787-001	4	Camera
AXIS P8815-2 3D Ppl Counter WH	20	01786-001	4	Camera
AXIS F9114 MAIN UNIT	200	01991-001	2	Camera

AXIS F9114-B MAIN UNIT	10	01991-031	2	Camera
AXIS F9104-B MAIN UNIT	20	 02192-031	2	Camera
			-	Gamora

AXIS F9111 MAIN UNIT	200	01990-001	2	Camera
AXIS F2115-R VARIFOCAL SENSOR	60	02639-001	2	Camera

AXIS F2135-RE FISHEYE SENSOR	250	02641-001	2	Camera
AXIS F2105-RE STANDARD SENSOR	250	02640-001	2	Camera

AXIS F2105-RE STANDARD BULK 8P	40	02640-021	2	Camera
AXIS F2115-R VARIFOCAL BULK 8P	10	 02639-021	2	Camera

AXIS F2135-RE FISHEYE BULK 8P	30	02641-021	2	Camera
AXIS F7225-RE Pinhole	50	02363-001	2	Camera
		02000 001	-	ounieru
AXIS F7225-RE Pinhole BULK 8 PCS	20	02363-021	2	Camera
			-	

AXIS F4105-LRE	125		02364-001	2	Camera
AXIS F4105-LRE BULK 8 PCS	20		02364-021	2	Camera
AXIS M3015	175	Discontinued	01151-001	2	Camera

AXIS M3016	70	Discontinued	01152-001	4	Camera
AXIS M3046-V 2.4mm	10	Discontinued	0806-001	4	Camera
AXIS M3064-V	750	Discontinued	01716-001	2	Camera
AXIS M3065-V	1200	Discontinued	01707-001	2	Camera

AXIS M3075-V	200	Discontinued	01709-001	4	Camera
AXIS M3066-V	500	Discontinued	01708-001	2	Camera
	500	Discontinueu	01700-001	2	Gaillera
AXIS M3047-P	125	Discontinued	0808-001	4	Camera

AXIS M3048-P	80	Discontinued	01004-001	4	Camera
AXIS M3067-P	400	Discontinued	01731-004	2	Camera
AXIS M3085-V	2500		02373-001	2	Camera

AXIS M3086-V	2000		02374-001	2	Camera
AXIS M3088-V	450		02375-001	2	Camera
	400		02070-001	-	Califera
AXIS M3026-VE	5	Discontinued	0547-001	4	Camera

AXIS M3037-PVE	30	Discontinued	0548-001	4	Camera
AXIS M3058-PLVE	250	Discontinued	01178-001	2	Camera
			••••••	_	
AXIS M3077-PLVE	175		02018-001	2	Camera
				1	I

AXIS M3104-L	15	Discontinued	0865-001	4	Camera
AXIS M3104-LVE	5	Discontinued	0866-001	4	Camera
AXIS M3105-L	80	Discontinued	0867-001	4	Camera
		Discontinued	0007-001		Gamera
AXIS M3106-LVE MK II	50	Discontinued	01037-001	4	Camera

XIS M3115-LVE	750		01604-001	2	Camera
XIS M3116-LVE	500		01605-001	2	Camera
XIS M3205-LVE	600	Discontinued	01517-001	2	Camera

AXIS M3206-LVE	700	Discontinued	01518-001	2	Camera
AXIS M3215-LVE	450		02371-001	2	Camera

AXIS M3216-LVE	500	02372-001	2	Camera
			_	
AXIS M4215-V	200	02676-001	2	Camera
	200	02070 001	-	Guinera
AXIS M4215-LV	300	02677-001	2	Camera

AXIS M4216-V	450	02112-001	2	Camera
			_	
AXIS M4216-LV	550	02113-001	2	Camera
	550	02113-001	2	Califiera
AXIS M4218-V	90	02678-001	2	Camera

AXIS M4218-LV	100	02679-001	2	Camera
AXIS M4308-PLE	250	02100-001	2	Camera

AXIS M4317-PLVE	750	02510-001	2	Camera
AXIS M4318-PLVE	1000	02511-001	2	Camera
	1000	02511-001	2	Califera

AXIS M4327-P	5	02636-004	2	Camera
AXIS M4328-P	5	02637-004	2	Camera

AXIS P3235-LVE	5	Discontinued	01199-001	4	Camera
AXIS P3245-LV	3000	Discontinued	01592-001	4	Camera

AXIS P3245-LVE 22 MM	200	Discontinued	02047-001	4	Camera
AXIS P3247-LV	2000	Discontinued	01595-001	2	Camera

AXIS P3247-LVE	1200	Discontinued	01596-001	2	Camera
AXIS P3248-LV	500	Discontinued	01597-001	4	Camera

AXIS P3255-LVE	90	02099-001	2	Camera
AXIS P3265-V	2500	02326-001	2	Camera
AAIS P3205-V	2500	02326-001	2	Camera

AXIS P3265-LV	3000	02327-001	2	Camera
AXIS P3265-LVE	3000	02328-001	2	Camera

AXIS P3245-V	3000	Discontinued	01591-001	2	Camera
AXIS P3265-LVE 22 mm	150		02333-001	2	Camera

AXIS P3267-LV	1200	02329-001	2	Camera
AXIS P3267-LVE	1600	02330-001	2	Camera

AXIS P3245-VE	850	Discontinued	01594-001	2	Camera
AXIS P3268-LV	600		02331-001	2	Camera

AXIS P3245-LVE	3000	Discontinued	01593-001	4	Camera
AXIS P3268-LVE	850		02332-001	2	Camera
	050		02332-001	2	Gamera
	1				

			1 1
Discontinued	01058-001	2	Camera
Discontinued	01970-001	2	Camera
	Discontinued		

AXIS P4705-PLVE Panoramic Camera	1600	02415-001	2	Camera
	1000	02416-001		0
AXIS P4707-PLVE Panoramic Camera	1000	02416-001	2	Camera
AXIS P3719-PLE	400	01500-001	2	Camera

AXIS P3727-PLE	150	02218-001	2	Camera
	150	02218-001	2	Calliera
AXIS P3735-PLE	2500	02633-001	2	Camera
AXIS P3737-PLE	2000	02634-001	2	Camera
AXIS P3738-PLE	550	02635-001	2	Camera
AND FJ/JOFLE	550	02033-001	2	Califera

AXIS P3807-PVE	350	Discontinued	01048-004	2	Camera
AXIS P3818-PVE	450		02060-001	2	Camera

AXIS P3827-PVE	1200		02450-001	2	Camera
				-	
AXIS P3904-R Mk II	5		01078-001	4	Camera
	5		01070-001	-	Gamera
AXIS P3904-R MK II BULK 10PCS	5		01078-021	4	Camera
AXIS P3904-R MK II BULK 50 PCS	10		01078-031	4	Camera
AAIS P3904-R MR II BULK 50 PCS	10		01078-031	4	Camera
AXIS P3375-V	350	Discontinued	01060-001	4	Camera
AXIS P3904-R Mk II M12	5		01071-001	4	Camera
AXIS P3904-R MK II M12 BULK 10PCS	5		01071-021	4	Camera
	Ŭ		01071-021	-	Gamera
	- 1		1		1

AXIS P3375-LV	100	Discontinued	01062-001	4	Camera
	5		04074 024	4	Comoro
AXIS P3904-R MK II M12 BULK 50PCS	5		01071-031	4	Camera
AXIS P3905-R Mk II	30		01072-001	4	Camera
AXIS P3375-VE	100	Discontinued	01061-001	4	Camera
AXIS P3905-R MK II BULK 10PCS	5		01072-021	4	Camera
AXIS P3905-R MK II BULK 50 PCS	5	}	01072-031	4	Camera
				-	
AXIS P3905-R Mk II M12	10		01073-001	4	Camera
	10		01073-001	4	Callela

AXIS P3905-R MK II M12 BULK 10 PCS	5		01073-021	4	Camera
AXIS P3905-R MK II M12 BULK 50 PCS	5		01073-031	4	Camera
AXIS P3905-R MK II BAREBONE 10P	5		01072-041	4	Camera
AXIS P3915-R Mk II	15	Discontinued	01074-001	2	Camera
AXIS P3915-R MK II BULK 10 PCS	5	Discontinued	01074-021	2	Camera
AXIS P3915-R MK II BULK 50 PCS	5	Discontinued	01074-031	2	Camera
AXIS P3915-R Mk II M12	10	Discontinued	01075-001	2	Camera
AXIS P3915-R MK II M12 BULK 10 PCS	5	Discontinued	01075-021	2	Camera
AXIS P3915-R MK II M12 BULK 50 PCS	5	Discontinued	01075-031	2	Camera
AXIS P3905-R MK II M12 BAREBONE 10P	5		01073-041	4	Camera

AXIS P3925-R	15	01920-001	2	Camera
AXIS P3925-R BULK 10P	5	01920-021	2	Camera
AXIS P3925-R M12	10	01933-001	4	Camera

AXIS P3925-R M12 BULK 10P	5	01933-021	4	Camera
	5	01900-021		Gamera
			-	-
AXIS P3925-LRE	30	02090-001	2	Camera
AXIS P3925-LRE M12	10	02091-001	2	Camera

AXIS P3935-LR 125 01919-001 2 Camera AXIS P3935-LR 600 Discontinued 01598-001 2 Camera AXIS P3248-LVE 600 Discontinued 01598-001 2 Camera AXIS P3935-LR BULK 10P 5 01919-021 2 Camera
AXIS P3935-LR BULK 10P 5 01919-021 2 Camera
AXIS P3935-LR BULK 10P 5 01919-021 2 Camera
AXIS P3935-LR BULK 10P 5 01919-021 2 Camera
AXIS P3935-LR BULK 10P 5 01919-021 2 Camera
AXIS P3935-LR BULK 10P 5 01919-021 2 Camera
AXIS P3935-LR BULK 10P 5 01919-021 2 Camera
AXIS P3935-LR BULK 10P 5 01919-021 2 Camera
AXIS P3935-LR BULK 10P 5 01919-021 2 Camera
AXIS P3935-LR BULK 10P 5 01919-021 2 Camera
AXIS P3935-LR BULK 10P 5 01919-021 2 Camera
AXIS P3935-LR BULK 10P 5 01919-021 2 Camera
AXIS P3935-LR BULK 10P 5 01919-021 2 Camera
AXIS P3935-LR BULK 10P 5 01919-021 2 Camera
AXIS P3935-LR BULK 10P 5 01919-021 2 Camera
AXIS P3935-LR BULK 10P 5 01919-021 2 Camera
AXIS P3935-LR BULK 10P 5 01919-021 2 Camera
AXIS P3935-LR BULK 10P 5 01919-021 2 Camera
AXIS P3935-LR BULK 10P 5 01919-021 2 Camera
AXIS P3935-LR BULK 10P 5 01919-021 2 Camera

AXIS P3935-LR M12	30	01932-001	4	Camera
AAIS F3933-LR WIZ	30	01932-001	4	Calliera
AXIS P3935-LR M12 BULK 10P	5	01932-021	4	Camera
	-			
AXIS P9106-V BRUSHED STEEL	60	01553-001	2	Camera
	465	 	<u> </u>	
AXIS P9106-V WHITE	100	01620-001	2	Camera

AXIS Q3527-LVE	10	Discontinued	01565-001	2	Camera
	400		00054 004	2	
AXIS Q3536-LVE 9MM DOME CAMERA	400		02054-001	2	Camera

I				Camera
300		02225-001	2	Camera
	300	300	300 02225-001	300 02225-001 2

AXIS Q3538-SLVE DOME CAMERA	60	02463-001	4	Camera

AXIS Q3626-VE	40	02616-004	2	Camera
AXIS Q3628-VE	100	02617-004	2	Camera

AXIS Q3819-PVE	350		01819-001	2	Camera
AXIS Q9216-SLV STEEL	90		01766-001	2	Camera
AXIS Q9216-SLV WHITE	125		01767-001	2	Camera
AXIS Q8414-LVS METAL	50	Discontinued	0709-001	4	Camera
					ounoru

AXIS Q8414-LVS WHITE	20	Discontinued	0710-001	4	Camera
AXIS P3245-LVE-3 L. P. Verifier Kit	10	Discontinued	02234-001	4	Camera
		Diocontinuou			Gamora

AXIS P3265-LVE-3 L.P- Verifier Kit	20	02812-001	4	Camera
AXIS M3057-PLR Mk II DOME CAMERA	30	02457-001	4	Camera
AXIS P3905-R MK III	80	02670-001	2	Camera
AXIS P3905-R MK III M12	80	02671-001	2	Camera

10	02670-021	2	Camera
10	02671-021	2	Camera
60	02501-001	2	Camera
15	02502-001	2	Camera
10	02501-021	2	Camera
	02001 021	-	Guineru
5	02502-021	2	Camera
	10 60 15 10 10 10	10 02671-021 10 02501-001 60 02501-001 15 02502-001 10 02501-021	10 02671-021 2 10 02501-001 2 60 02501-001 2 15 02502-001 2 10 02501-021 2

AXIS M4317-PLR	30	02833-001	2	Camera
AXIS M4318-PLR	20	02834-001	2	Camera

AXIS P3268-SLVE	70		02710-001	4	Camera
AXIS Q8615-E 50HZ	5	Discontinued	02516-001	4	Camera

AXIS Q8615-E 60HZ	20	Discontinued	02517-001	4	Camera
	200		00400 004	0	0.0000
AXIS M5000-G US	200		02188-004	2	Camera
AXIS M5054	60	Discontinued	01079-001	2	Camera
AXIS M5074	80		02345-001	2	Camera
			1	1	

AXIS M5075-G	150		02347-004	2	Camera
	250		04440 004		
AXIS M5525-E 60HZ	350		01146-001	2	Camera
AXIS P5654-E 60HZ	80	Discontinued	01759-001	4	Camera
AXIS P5654-E Mk II 60 Hz	150	New	02915-001	2	Camera
				_	
AXIS P5655-E 60HZ	550		01682-004	2	Camera
L	ļ	1			L

AXIS P5676-LE 60 Hz	200	02414-001	2	Camera
AXIS Q6010-E 60HZ	175	01981-001	2	Camera
AXIS Q6100-E 60HZ	200	01711-001	2	Camera

AXIS Q6074 60HZ 15 01968-004 2 Came	
AXIS Q6074-E 60HZ 90 01974-004 2 Came	ra
AXIS Q6075 60HZ 60 01750-004 2 Came	ra

	350	01752 004	2	Camara
AXIS Q6075-E 60HZ		01752-004		Camera
AXIS Q6078-E 60HZ	60	02148-004	2	Camera
AXIS Q6135-LE 60HZ	600	01959-004	2	Camera

AXIS Q6135-LE 60 Hz NM	5	New	01959-301	2	Camera
AXIS Q6128-E 60HZ	70	Discontinued	0799-004	2	Camera
AXIS Q6215-LE 60HZ	175	Discontinued	01442-004	2	Camera
		US Only			
AXIS Q6215-LE 60HZ	175	Discontinued	01442-018	2	Camera
	175	Discontinued	01772-010		Janiera
		Canada Only			

AXIS Q6225-LE 60Hz	150	02317-004	2	Camera
AXIS Q6315-LE 60 Hz	300	01925-004	2	Camera

AXIS Q6318-LE 60 Hz	125		02447-004	2	Camera
			•=••••	-	
AXIS V5925 60 Hz	90		01966-004	2	Camera
AXIS V5938 60 Hz	10		02023-004	2	Camera
	-				
AXIS Q6075-SE 60 Hz	10	Discontinued	02239-001	4	Camera
				-	

AXIS Q8752-E 35 MM 30 FPS	5	01838-001	10	Camera

AXIS Q8752-E ZOOM 30 FPS	10	01841-001	4	Camera
AXIS Q8641-E 35MM 30 FPS 24V	5	01119-001	11	Camera
AAIS Q0041-E SSIVIIVI SU FFS 24V	5	01119-001		Calliera

AXIS Q8642-E 60MM 30 FPS 24V	5		01121-001	11	Camera
AXIS Q8741-E 35MM 30 FPS 24V	5	Discontinued	0824-001	4	Camera

AXIS Q8741-LE 35MM 30 FPS 24V	5	Discontinued	01013-001	4	Camera
AXIS Q8742-E ZOOM 30 FPS 24V	5	Discontinued	0830-001	4	Camera

AXIS Q8742-E 35MM 30 FPS 24V	5	Discontinued	0828-001	4	Camera
AXIS Q8742-LE 35MM 30 FPS 24V	5	Discontinued	01017-001	4	Camera

AXIS Q8742-LE ZOOM 30 FPS 24V	5	Discontinued	01019-001	4	Camera

AXIS P1280-E 2.2 MM 8.3 FPS	5	02114-001	4	Camera

AXIS P1280-E 4MM 8.3 FPS	5	0940-001	3	Camera
	-		_	
AXIS P1290-E 4 MM 8.3 FPS	5	01168-001	12	Camera

AXIS Q1941-E 7MM 30 FPS	10	Discontinued	0786-001	4	Camera
AXIS Q1951-E 7mm 30 fps	40		02150-001	2	Camera

AXIS Q1941-E 13MM 30 FPS	5	Discontinued	0787-001	4	Camera
AXIS Q1951-E 13mm 30 fps	10		02152-001	2	Camera

AXIS Q1941-E 19MM 30 FPS	5	Discontinued	0877-001	4	Camera
AXIS Q1951-E 19mm 30 fps	20		02154-001	2	Camera

AXIS Q1941-E 35MM 30 FPS	5	Discontinued	0788-001	4	Camera
AXIS Q1951-E 35mm 30 fps	20		02156-001	2	Camera
	20		02130-001	2	Califera

AXIS Q1941-E 60MM 30 FPS	5	0789-001	10	Camera
	-		-	
AXIS Q1941-E PT MOUNT 7MM 30 FPS	5	0973-001	11	Camera
AXIS QIS41-E FI MOUNT / MIM SU FFS	5	0975-001		Calliera

AXIS Q1941-E PT MOUNT 13MM 30 FPS	5	0974-001	11	Camera
AXIS Q1941-E PT MOUNT 19MM 30 FPS	5	0979-001	11	Camera

AXIS Q1941-E PT MOUNT 35MM 30 FPS	5	0975-001	11	Camera
AXIS Q1941-E PT MOUNT 60MM 30 FPS	5	 0977-001	11	Camera
	0	0377-001		Gamera

AXIS Q1942-E 10MM 30 FPS	5	Discontinued	0916-001	4	Camera
AXIS Q1952-E 10mm 30 fps	10		02158-001	2	Camera

AXIS Q1942-E 19MM 30 FPS	5	Discontinued	0918-001	4	Camera
AXIS Q1952-E 19mm 30 fps	10		02160-001	2	Camera
				-	Guinora
		I			

AXIS Q1952-E 35mm 30 fps	10	02162-001	2	Camera
AXIS Q1942-E 60MM 30 FPS	5	0922-001	4	Camera

AXIS Q1942-E PT MOUNT 10MM 30 FPS	5	0981-001	11	Camera
AXIS Q1942-E PT MOUNT 19MM 30 FPS	5	0983-001	11	Camera

AXIS Q1942-E PT MOUNT 35MM 30 FPS	5	0985-001	11	Camera
AXIS Q1942-E PT MOUNT 60MM 30 FPS	5	0987-001	11	Camera

AXIS Q1961-TE 7mm 30 fps	10	02174-001	4	Camera
AXIS Q1961-TE 13mm 30 fps	5	02176-001	4	Camera

AXIS Q2101-TE 7 mm 8.3 fps	5	02649-001	10	Camera

AXIS Q2101-TE 7 mm 30 fps	5	02650-001	4	Camera

AXIS Q2101-TE 13 mm 8.3 fps	5	02651-001	10	Camera

AXIS Q2101-TE 13 mm 30 fps	5	02652-001	4	Camera

AXIS Q2101-TE 19 mm 8.3 fps	5	02668-001	10	Camera

AXIS Q2101-TE 19 mm 30 fps	5		02669-001	4	Camera
AXIS Q2901-E 9MM 8.3 FPS	10	Discontinued	0645-001	4	Camera

AXIS Q2901-E PTMOUNT 9MM 8.3 FPS	5	Discontinued	0646-001	4	Camera
	-				
AXIS Q2901-E 19MM 8.3 FPS	5	Discontinued	0647-001	4	Camera
					
AXIS Q2901-E PTMOUNT 19MM 8.3 FPS	5	Discontinued	0648-001	4	Camera

AXIS FA1080-E 2.2MM 8.3 FPS	5	02089-001	4	Camera
AXIS FA1080-E 4MM 8.3 FPS	5	01728-001	4	Camera

AXIS FA4090-E 4MM 8.3 FPS	5		01729-001	12	Camera
CANON PLE. REC MOUNT KIT SR30-P-VB	5	Discontinued	1065C001	9	Canon
CANON CEILIN MOUNT COV S SS40-S-VB	5	Discontinued	4962B001	9	Canon
CANON CEILIN MOUNT COV B SS40-B-VB	5		4962B002	9	Canon
CANON INDOOR DOME HOUSING DR41-C-VB	5		6816B001	9	Canon
CANON INDOOR DOME HOUSING DR41-S-VB	10		6816B002	9	Canon
CANON SURFACE MOUNT SPACER SS30-VB	5	Discontinued	9920B001	9	Canon
CANON PA-V18 US	5		8362B001	9	Canon
CANON PENDANT CAP PC30VE-VB	5	Discontinued	1736C001	9	Canon
CANON CONDUIT BOX CB30VE-VB	5	Discontinued	1735C001	9	Canon
CANON CEILIN MOUNT COV W SS40-W-VB	5		4962B005	9	Canon
	-			-	
					I

CANON NETWORK CAMERA VB-S910F	5		1389C001	9	Canon
CANON NETWORK CAMERA VB-S30D Mkli	5	Discontinued	2545C001	2	Canon
CANON NETWORK CAMERA VB-S31D Mkii	5	Discontinued	2546C001	9	Canon
	0	Discontinued	20400001	5	Gallon
CANON NETWORK CAMERA VB-S32D	5		5717C001	9	Canon

CANON NETWORK CAMERA VB-M50B	5		1064C001	9	Canon
	C C			Ū	ounon
CANON NETWORK CAMERA VB-M44B	5	Discontinued	2542C002	2	Canon
CANON NETWORK CAMERA VB-M44S	5	Discontinued	2542C001	2	Canon
CANON NETWORK CAMERA VB-H45B	30	Discontinued	2541C002	2	Canon

CANON NETWORK CAMERA VB-H45S	5	Discontinued	2541C001	2	Canon
	Ŭ	Discontinued	20410001	-	ounon
CANON NETWORK CAMERA VB-H47W	5		5715C001	9	Canon
CANON NETWORK CAMERA VB-H47B	100		5715C002	9	Canon
CANON NETWORK CAMERA VB-M46W	5		5716C001	9	Canon

		1			
CANON NETWORK CAMERA VB-M46B	10		5716C002	9	Canon
AXIS P7701	100	Discontinued	0319-004	2	Encoder Decoder
AXIS P7701 VIDEO DEC BB BULK 20PCS	5	Discontinued	0319-051	4	Encoder Decoder
AXIS P7701 VIDEO DECODER BARE BONE	5	Discontinued	0319-041	4	Encoder Decoder
AXIS T8705 VIDEO DECODER	5	Discontinued	01186-004	2	Encoder Decoder
AXIS D1110 VIDEO DECODER 4K	350		02282-001	2	Encoder Decoder
AXIS M7104 VIDEO ENCODER	40		01679-001	2	Encoder Decoder

AXIS P7216 VIDEO ENCODER 20 Discontinued 0542-004 2 Encoder Decoder AXIS P7304 VIDEO ENCODER 60 01680-001 2 Encoder Decoder AXIS M7116 150 02036-004 2 Encoder Decoder
AXIS M7116 150 02036-004 2 Encoder
AXIS P7316 Video Encoder 50 02037-004 2 Encoder
Decoder
AXIS 291 1U VIDEO SERV RACK 5 0267-004 2 Encoder
AXIS 291 10 VIDEO SERV RACK 5 0267-004 2 Encoder Decoder

AXIS S3008 Mk II 2 TB	70	02764-004	2	Recorder
AXIS S3008 Mk II 4 TB	70	02765-004	2	Recorder
AXIS S3008 Mk II 8 TB	20	02766-004	2	Recorder
	20	02/00/004	-	Recorder

AXIS S3016 8 TB	15	02527-004	2	Recorder
		 00054 004		Deserves
AXIS S3016 16 TB	20	02351-004	2	Recorder

AXIS S3016 32 TB	10	02352-004	2	Recorder
AXIS S3008 2 TB	50	02105-004	2	Recorder
AXIS S3008 4 TB	20	02046-004	2	Recorder
AND 0000 4 10	20	V2V40-VV4	<u> </u>	Recorder
L		ļ		

AXIS S3008 8 TB	10	02135-004	2	Recorder
AXIS S2108	15	02403-004	2	Recorder
AXIS S2208	40	01580-004	2	Recorder
	15	01581-004	2	Booorder
AXIS S2212	15	01561-004	2	Recorder

AXIS S2216	20	01582-004	2	Recorder
	20	01002-004	2	Recorder
AXIS S2224	15	01583-004	2	Recorder
	15	01303-004	2	Recorder
AXIS S1216 TOWER 8 TB	10	02694-004	2	Recorder
AAIS SIZIO TOWER & IB	10	02694-004	2	Recorder

AXIS S1216 RACK 8 TB	20	02895-001	2	Recorder
AXIS S1232 RACK 16 TB	15	02537-001	2	Recorder

AXIS S1232 RACK 32 TB	15	02538-001	2	Recorder
AXIS S1232 TOWER 32 TB	10	02536-004	2	Recorder

AXIS S1264 RACK 24 TB	10	02539-001	2	Recorder
AXIS S1264 RACK 64 TB	15	02540-001	2	Recorder

AXIS S1264 RACK 144 TB	5	02541-001	2	Recorder
AXIS S1296 RACK 96 TB	10	02542-001	2	Recorder

AXIS S1296 RACK 192 TB	5	02543-001	2	Recorder
AXIS S9301	15	02693-004	2	Recorder
AXIS S9302	15	02692-004	2	Recorder

AXIS S1116 MT	20	Discontinued	01617-001	4	Recorder
AXIS S1116 RACKED	5		01618-001	4	Recorder
	, , , , , , , , , , , , , , , , , , ,				ricoordor
AXIS S1132	15	Discontinued	01613-001	4	Recorder

AXIS S1132 TOWER 32 TB	5	Discontinued	02079-004	2	Recorder
AXIS S1132 TOWER 64 TB	5	Discontinued	02080-004	2	Recorder
		Discontin	04644 004		Deserter
AXIS S1148 24TB	20	Discontinued	01614-001	4	Recorder

AXIS S1148 140TB	10	Discontinued	01616-001	4	Recorder
AXIS S9101 Mk II	10	Discontinued	01985-004	4	Recorder
AXIS S9201 MKII	5	Discontinued	01691-001	4	Recorder
Axis Professional Services Token	0		02130-001	0	Services

AXIS DEVICE MANAGER EXTEND	0	02643-001	0	Software
	^	0222.000		Cothurses
ACAP AXIS PERIMETER DEFENDER 1 E- LICENSE	0	0333-608	0	Software
ACAP AXIS PERIMETER DEFENDER 10 E-	0	0333-609	0	Software
LICENSE				

AXIS PERIMETER DEFENDER PTZ 1P ELIC	0	01725-001	0	Software
AXIS H. 264 50-user decoder license pack	10	0160-050	4	Software
AXIS H.264 +AAC decoder 50-user decoder license pack	5	0160-060	4	Software
AXIS PEOPLE COUNTER E-LICENSE	0	01147-011	0	Software

AXIS LICENSE PLATE VERIFIER 1P E-LICENSE	0		01574-001	0	Software
	-			-	
AXIS STORE REPORTER 1Y ELICENSE	0		02473-001	0	Software
CANON H.264 ADDITIONAL USER LICENSE	0		9552B003	0	Software
CANON H.264/H.265 ADDITIONAL USER	0		9552B004	0	Software
LICENSE	U		3 002DUU4	U	Soltware
-					
		1			

	0	0970 040	٥.	Software
ACS CORE DEVICE E-LICENSE	0	0879-010	0	Software
ACS UNIVERSAL DEVICE E-LICENSE	0	0879-020	0	Software
ACS 4 TO UNIVERSAL UPG E-LICENSE	0	0879-040	0	Software
ACS CORE TO UNIVERSAL UPG E-LICENSE	0	0879-030	0	Software

5	Discontinued	01438-001	4	Spare Part
15		02574-001	2	Accessory
5	Discontinued	5800-731	4	Spare Part
5	Discontinued	5800-741	4	Spare Part
5	Discontinued	5800-711	4	Spare Part
5	Discontinued	5800-721	4	Spare Part
10		5801-841	4	Spare Part
10		01567-001	4	Spare Part
5	Discontinued	01153-001	2	Spare Part
5	Discontinued	01950-001	4	Spare Part
5	Discontinued	01922-001	4	Spare Part
5		01923-001	4	Spare Part
5		01239-001	4	Spare Part
5	Discontinued	5800-111	4	Spare Part
15		01606-001	4	Spare Part
5	Discontinued	5506-131	2	Spare Part
5	Discontinued	5504-991	4	Spare Part
30	Discontinued	5700-321	4	Spare Part
10	Discontinued	5700-311	4	Spare Part
20	Discontinued	5700-341	4	Spare Part
	15 10 10	15Discontinued5Discontinued5Discontinued5Discontinued10International10International5Discontinued5Discontinued5Discontinued5Discontinued5Discontinued5Discontinued10International5Discontinued10Discontinued11Discontinued12Discontinued13Discontinued10Discontinued10Discontinued	15 Discontinued 5800-731 5 Discontinued 5800-731 5 Discontinued 5800-741 5 Discontinued 5800-711 5 Discontinued 5800-721 10 5801-841 10 10 S801-841 10 10 S801-841 11 10 Discontinued 01567-001 5 Discontinued 01153-001 5 Discontinued 01922-001 5 Discontinued 01922-001 5 Discontinued 01923-001 5 Discontinued 5800-111 5 Discontinued 5800-111 5 Discontinued 5800-111 5 Discontinued 5800-111 5 Discontinued 5801-11 5 Discontinued 5901-131 5 Discontinued 5700-321 30 Discontinued 5700-311 10 Discontinued 5700-311 <	15 02574-001 2 5 Discontinued 5800-731 4 5 Discontinued 5800-741 4 5 Discontinued 5800-711 4 5 Discontinued 5800-721 4 10 5801-841 4 10 5801-841 4 10 5801-701 4 10 5801-841 4 10 01567-001 4 5 Discontinued 01153-001 2 5 Discontinued 01922-001 4 5 Discontinued 01922-001 4 5 Discontinued 01923-001 4 5 Discontinued 5800-111 4 15 Discontinued 5800-111 4 5 Discontinued 5800-131 2 5 Discontinued 5506-131 2 5 Discontinued 5700-321 4 30 Discontinued

SPR AXIS P3346-V DOME KIT	5		5700-911	4	Spare Part
SPR AXIS P3346-VE DOME KIT	10		5700-921	4	Spare Part
AXIS P3364-LV DOME KIT	5	Discontinued	5800-691	4	Spare Part
AXIS P3364-LVE DOME KIT	10	Discontinued	5800-681	4	Spare Part
AXIS P33 SEMI-SMOKED DOME A 4PCS	5		01548-001	4	Spare Part
AXIS P33 CLEAR DOME A 4PCS	5		01549-001	4	Spare Part
AXIS P3707-PE CLEAR DOME KIT	5		5801-521	2	Spare Part
AXIS P37 CLEAR DOME KIT A	10	Discontinued	01515-001	2	Spare Part
SPR TOP COVER AXIS P39-R 10 PCS	5		5801-111	4	Spare Part
AXIS P54 CLEAR DOME	5		5800-771	4	Spare Part
AXIS P5512-E DOME KIT	5	Discontinued	5800-281	4	Spare Part
AXIS TP3809 DOME COVER WHITE 4P	5		02010-001	4	Spare Part
AXIS TQ6803 HARD-COATED CLEAR DOME	5		01814-001	4	Spare Part
AXIS TQ6806 HARD-COATED CLEAR DOME	5		01771-001	4	Spare Part
AXIS TQ6807 CLEAR DOME COVER	40	Discontinued	01946-001	2	Spare Part
AXIS TQ6809 HARD COATED CLEAR DOME	30		02398-001	2	Spare Part

AXIS TQ6810 HARD COATED CLEAR DOME	30		02400-001	4	Spare Part
AXIS TM3810-E DOME CLEAR 4P	5		02424-001	4	Spare Part
AXIS TQ9801 CLEAR DOME	5		02050-001	4	Spare Part
AXIS TP5801-E Clear Dome	70		02280-001	4	Spare Part
AXIS Q3505-V CLEAR DOME 5P	5	Discontinued	5505-611	4	Spare Part
AXIS Q35 CLEAR DOME A 5PCS	5		01180-001	4	Spare Part
AXIS Q3505-VE CLEAR DOME 5P	5	Discontinued	5505-631	4	Spare Part
AXIS Q36-VE CLEAR DOME	5		5801-511	4	Spare Part
AXIS Q37 CLEAR DOME A	5	Discontinued	5507-311	4	Spare Part
AXIS Q6000-E CLEAR DOME	5		5506-641	4	Spare Part
AXIS Q603X HD DOME KIT	10		5700-811	4	Spare Part
AXIS Q3517-SLVE CLEAR DOME 2P	5		01584-001	4	Spare Part
AXIS Q60-E/C SMOKED DOME D	10	Discontinued	5503-961	4	Spare Part
AXIS Q60-S CLEAR DOME A	5		5700-751	4	Spare Part
AXIS Q8414-LVS CLEAR DOME 5P	5	Discontinued	5506-331	4	Spare Part
AXIS A8105-E CLEAR DOME 5PCS	5		5801-471	2	Spare Part
AXIS TA8801 CLEAR DOME COVER 5P	5		01764-001	4	Spare Part

AXIS TP3801 WHITE CASING 4P	5	01799-001	4	Spare Part
AXIS TP3801-E WHITE CASING 4P	5	01800-001	4	Spare Part
AXIS TP3802 CLEAR DOME 4P	5	01625-001	4	Spare Part
AXIS TP3802-E CLEAR DOME 4P	10	01629-001	4	Spare Part
AXIS TP3803-E CLEAR DOME	5	02197-001	4	Spare Part
AXIS TP3807 DOME COVER WHITE 4P	5	02011-001	4	Spare Part
AXIS TP3823-E WEATHERSHIELD 2P	10	02490-001	4	Spare Part
AXIS TP3820 CASING WHITE 4P	5	02491-001	4	Spare Part
AXIS TP3820-E CASING WHITE 4P	5	02495-001	4	Spare Part
AXIS TP3821-E CASING WHITE 4P	5	02497-001	4	Spare Part
AXIS TP3824-E DOME CLEAR 4P	5	02549-001	4	Spare Part
AXIS TP3812-E TOP CASING	5	02210-001	4	Spare Part
AXIS TP3002-E MOUNTING BRACKET 4P	5	02551-001	4	Spare Part

AXIS TP3003-E MOUNTING BRACKET 4P	5	02552-001	4	Spare Part
AXIS TP3815-E CLEAR DOME COVER	10	02392-001	2	Spare Part
AXIS TQ3802-E COVER WEATHERSHIELD	5	02273-001	4	Spare Part
AXIS TQ3803-E COVER TOP	5	02275-001	4	Spare Part
AXIS TQ3001-E MOUNTING BRACKET 5P	5	02515-001	2	Spare Part
AXIS TQ3807-E DOME CLEAR 5P	5	02513-001	2	Spare Part
AXIS TQ3808-E WEATHERSHIELD 5P	5	02514-001	2	Spare Part
AXIS TM5801 DOME COVER WHITE	5	02429-001	4	Spare Part
AXIS TM3818 CASING WHITE 4p	5	02579-001	4	Spare Part
AXIS TM3815-E DOME CLEAR 4P	5	02619-001	4	Spare Part
AXIS TP3819-E DOME CLEAR	15	02479-001	4	Spare Part
AXIS TP3825-E WEATHERSHIELD WHITE	15	02585-001	4	Spare Part
AXIS TQ3809-E Dome Clear	5	02805-001	2	Spare Part
AXIS TM3821 CASING WHITE 4P	5	02730-001	4	Spare Part
AXIS TM3819 CASING WHITE 4P	5	02821-001	4	Spare Part
AXIS TI8903 Clear Dome 5P	5	02563-001	4	Spare Part

5		02831-001	4	Spare Part
5		02874-001	2	Spare Part
		02011001	-	opuror ure
5	Discontinued	5500-491	4	Spare Part
5		01439-001	4	Spare Part
5	Discontinued	5901-211	4	Spare Part
5		5505-161	4	Spare Part
5		01198-001	4	Spare Part
10		5503-991	4	Spare Part
5		5800-121	4	Spare Part
5	Discontinued	5506-311	4	Spare Part
5	Discontinued	5506-321	4	Spare Part
5		5800-351	4	Spare Part
80		01472-001	2	Spare Part
100		01471-001	2	Spare Part
	5 5 5 5 5 5 5 5 5 5 5 5 5 80	5Discontinued5Discontinued5Discontinued5Discontinued10	5 02874-001 5 Discontinued 5500-491 5 Discontinued 01439-001 5 Discontinued 5901-211 5 Discontinued 5901-211 5 Discontinued 5901-211 5 Discontinued 5901-211 5 01198-001 01198-001 5 01198-001 5503-991 10 5503-991 5503-991 5 Discontinued 5506-311 5 Discontinued 5506-311 5 Discontinued 5506-321 5 S800-351 5800-351 80 01472-001 1472-001	5 Discontinued 5500-491 4 5 Discontinued 5500-491 4 5 Discontinued 01439-001 4 5 Discontinued 5901-211 4 5 Discontinued 5505-161 4 5 Discontinued 5503-991 4 5 Discontinued 5506-311 4 5 Discontinued 5506-321 4 5 Discontinued 5800-351 4 80 01472-001 2 2

STAINLESS STEEL STRAPS 1450MM 1 PAIR	60	Discontinued	5800-811	2	Spare Part
SPR AXIS P3343-VE SCREW KIT	5	Discontinued	5700-351	4	Spare Part
SPR AND P3343-VE SCREW NIT	5	Discontinued	5700-351	4	Spare Part
SPR AXIS P3343/-V SCREW KIT	5	Discontinued	5700-301	4	Spare Part
AXIS T94B02S MOUNTING BRACKET 5P	5	Discontinued	5901-281	4	Spare Part
AXIS T94F01S MOUNTING BRACKET	5		5505-171	4	Spare Part
AXIS T94G01S MOUNTING PLATE	10		5506-081	4	Spare Part
AXIS T94K01S MOUNTING BRACKET 4P	5	Discontinued	5505-551	4	Spare Part
AXIS T94M01S MOUNTING BRACKET 4P	5	Discontinued	5505-561	4	Spare Part
AXIS T94S01S MOUNTING BRACKET 4P	5	Discontinued	5506-061	4	Spare Part
AXIS T94T01S MOUNTING BRACKET 4P	5	Discontinued	5506-071	4	Spare Part
AXIS T94T02S MOUNTING BRACKET	5		01566-001	4	Spare Part
MOUNTING BRACKET AXIS P33XX-VE	5	Discontinued	5700-691	4	Spare Part
AXIS T94V01S MOUNTING BRACKET	5		5801-911	4	Spare Part
AXIS 3/4" CONDUIT LOCKNUT A 4P	5		01512-001	4	Spare Part
AXIS T94U02S MOUNTING BRACKET	5		5506-671	4	Spare Part
AXIS T94F02S MOUNTING BRACKET	5	Discontinued	5507-131	4	Spare Part
AXIS TP3001 MOUNTING BRACKET 4P	5		01806-001	4	Spare Part
AXIS TP3001-E MOUNTING BRACKET 4P	5		01801-001	4	Spare Part

AXIS TQ3902 MOUNT BRACKET	5		02274-001	4	Spare Part
AXIS TM2801 WEATHER SHIELD KIT	5		02588-001	4	Spare Part
AXIS TM1001 Wall Mount 5 pcs	20		02852-001	2	Spare Part
AXIS TQ3002-E Mounting Bracket	5		02829-001	2	Spare Part
AXIS P91 CLEAR DOME A 2P	5		01621-001	4	Spare Part
AXIS P91 SKIN COVER A BRUSHED STEEL	10		01622-001	4	Spare Part
RJ12 PLUG SHIELDED 10 PCS	5		01182-001	4	Spare Part
ACC MAINS ADAPTOR PS-P	5		5500-704	4	Spare Part
AXIS MAINS ADAPTER 12V DC 40W	5		01509-001	4	Spare Part
AXIS MAINS ADAPTER 48V DC 90W	5		01508-001	4	Spare Part
MAINS CABLE IEC-C13	10		5800-201	4	Spare Part
AXIS PATCH CABLE A 200MM 6PCS	5		5506-451	4	Spare Part
CABLE GLAND A M16 5PCS	5		5800-961	4	Spare Part
AXIS P3367-VE CASING KIT	5	Discontinued	5800-601	4	Spare Part
CONN KIT AXIS P1311	5		5500-851	2	Spare Part
CONN KIT AXIS Q7404	5	Discontinued	5700-161	4	Spare Part
AXIS TM3807 WHITE CASING 4P	5		02074-001	4	Spare Part
LENS M12 2.8MM F2.0 10PCS	5		5801-921	4	Spare Part

AXIS T93F TOP COVER	5		5505-891	4	Spare Part
	5		5505-051	-	Spare Fait
LENS CS 2.8-8MM F1.2 DC-I MP	5	Discontinued	5700-881	4	Spare Part
LENS CS VF 2.8-8MM F1.2 P-IRIS	5		5800-671	4	Spare Part
LENS CS VF 2.8-8MM F1.2 DC-IR	5	Discontinued	5800-661	4	Spare Part
AXIS LENS FUJINON CS 2.8-8MM P-IRIS	5		5506-721	4	Spare Part
LENS CS 2.8-8.5MM P-IRIS	5		5801-491	4	Spare Part
LENS CS 2.9-8.2MM F1.4 DC SVGA	5	Discontinued	5700-871	4	Spare Part
LENS CS 4-10MM P-IRIS	5	Discontinued	5801-011	4	Spare Part
AXIS LENS TAMRON C 4-13MM DC-IRIS	5		5506-731	4	Spare Part
TAMRON 5MP LENS P-IRIS 8-50 MM F1.6	50		01469-001	4	Spare Part
LENS CS 2.8 - 10 MM F1.2 P-IRIS 2MP	5		01949-001	4	Spare Part
LENS M12 2.8 MM F1.6 IR 10P	5		02012-001	4	Spare Part
LENS M12 2.9MM F2.0 1P	5		02065-001	4	Spare Part
LENS CS 3.9 - 10 MM F1.5 P-IRIS 8MP	5		02094-001	4	Spare Part
AXIS Q872x-E SUNSHIELD KIT	5	Discontinued	5800-321	4	Spare Part
SPR BRACKET KIT AXIS Q60XX/P55XX	10		5700-851	4	Spare Part
SPR CONN KIT AXIS Q7401	5	Discontinued	5500-831	2	Spare Part
SPR CONN PUSH PULL PLUG IDC-8 IP67	350		5700-371	2	Spare Part
NETWORK CABLE WITH GASKET 5M	100		5700-331	2	Spare Part
AXIS Q60XX-C MULTI CONNECT CABLE 7M	5	Discontinued	5800-821	4	Spare Part

AXIS T91G61/T91L61 SCREW KIT	15		5901-391	2	Spare Part
AXIS P5544 LENS KIT	5		5800-401	4	Spare Part
AXIS T96B05 FRONT KIT 5 PCS	5		5506-851	4	Spare Part
AXIS Q60XX-C COOLING MODULE	20		5800-501	4	Spare Part
AXIS T8005 POWER SUPPLY 5V 5W USB	5		5901-191	4	Spare Part
SPR POWER SUPPLY 1U 300W BL. FRONT	5		5800-861	4	Spare Part
AXIS T93G TOP COVER	5	Discontinued	5506-971	4	Spare Part
AXIS T92G FRONT WINDOW KIT A	5		01578-001	4	Spare Part
AXIS T92G WEATHERSHIELD KIT A	5		01579-001	4	Spare Part
AXIS T92G20 CAMERA HOLDER	5		01954-001	4	Spare Part
AXIS SUNSHIELD B	5		5800-971	4	Spare Part
AXIS SUNSHIELD C	5		5800-981	4	Spare Part
SUNSHIELD AXIS Q603X-E	5		5700-951	4	Spare Part
AXIS Q6010-E Solo kit	50		02221-001	2	Spare Part
AXIS Q62 IMPACT PROTECTION BRACKET	5		01600-001	4	Spare Part

	-				
AXIS Q62 FRONT WINDOW KIT A	5	Discontinued	01601-001	4	Spare Part
AXIS Q62 WIPER KIT A 4P	5		01602-001	4	Spare Part
AXIS Q62 IR WINDOW KIT A	5		01603-001	4	Spare Part
SUNSHIELD KIT T92E	5		5700-941	4	Spare Part
AXIS P33 WEATHERSHIELD KIT A	5	Discontinued	01701-001	4	Spare Part
AXIS P38 WEATHERSHIELD KIT A	10	Discontinued	01499-001	2	Spare Part
AXIS Q35 WEATHERSHIELD KIT A	5	Discontinued	01179-001	4	Spare Part
AXIS WEATHERSHIELD KIT D	5	Discontinued	5506-761	4	Spare Part
AXIS WEATHERSHIELD KIT E	5	Discontinued	5506-751	4	Spare Part
AXIS WEATHERSHIELD KIT M	5	Discontinued	5507-321	4	Spare Part
AXIS WEATHERSHIELD KIT N	5	Discontinued	5801-851	4	Spare Part
AXIS WEATHERSHIELD KIT Q	5	Discontinued	5801-451	4	Spare Part
AXIS WEATHERSHIELD KIT R	5	Discontinued	01238-001	4	Spare Part
WEATHERSHIELD KIT P3343/44-VE	5	Discontinued	5800-011	4	Spare Part

WEATHERSHIELD KIT P3346/67-VE	10	Discontinued	5800-021	4	Spare Part
AXIS TP3805 WEATHERSHIELD 2P	20		01628-001	4	Spare Part
AXIS TP3904 CLAMP BRACKET MOUNT	5		02337-001	4	Spare Part
FRONT GLASS KIT AXIS T92E20/21	10		5700-831	4	Spare Part
ELECTRONIC KIT AXIS T92E20	10		5700-971	4	Spare Part
AXIS T92E EXTENSION KIT	5	Discontinued	5506-101	4	Spare Part
AXIS M20 FRONT KIT A	5	Discontinued	5901-291	4	Spare Part
AXIS P13 WEATHERSHIELD KIT A	5		01693-001	4	Spare Part
AXIS P13-E TOP COVER A	5		01694-001	4	Spare Part
AXIS P14 FRONT KIT C	5	Discontinued	01761-001	4	Spare Part
AXIS P14 WEATHERSHIELD A	5		01717-001	4	Spare Part
AXIS TP1801-E Front Window Kit	5		02292-001	4	Spare Part

AXIS TP1802-E Front Window Kit 29mm	5		02412-001	2	Accessory
AXIS Q17 FRONT WINDOW KIT A	5		01686-001	4	Spare Part
AXIS Q17 FRONT WINDOW KIT C	5		01971-001	4	Spare Part
AXIS Q1798-LE WEATHERSHIELD	5		01972-001	4	Spare Part
AXIS Q1765-LE FRONT KIT	5	Discontinued	5801-101	4	Spare Part
SPR FAN CASSETTE AXIS Q7920	5		5800-851	4	Spare Part
AXIS T98A05 CABINET DOOR	5		5800-521	4	Spare Part
AXIS T98A06 CABINET DOOR	5		5800-531	4	Spare Part
AXIS T98A07 CABINET DOOR	5		5800-541	4	Spare Part
AXIS T98A08 CABINET DOOR	5		5800-551	4	Spare Part
AXIS T98A09 CABINET DOOR	5	Discontinued	5800-871	4	Spare Part
AXIS P135X CONN KIT	5	Discontinued	5800-381	4	Spare Part
AXIS T8123/4-E MIDSPAN SPARE KIT	5	Discontinued	5800-371	4	Spare Part
FRONT KIT 60MM AXIS Q872X-E	5	Discontinued	5800-311	4	Spare Part
FRONT KIT 35MM AXIS Q872X-E	5	Discontinued	5800-301	4	Spare Part
PT IR ILLUMINATOR KIT B	20	Discontinued	5800-921	4	Spare Part

AXIS Q86 FRONT KIT A	5	Discontinued	01440-001	4	Spare Part
	_				
AXIS Q86 WIPER KIT A 5P	5	Discontinued	01441-001	4	Spare Part
AXIS Q86-E LIGHT SENSOR BOX 120 V	5	Discontinued	5505-771	4	Spare Part
AXIS Q8665-LE BASE UNIT 24V AC	5	Discontinued	5801-191	4	Spare Part
AXIS Q8665-E BASE UNIT 120 V AC	5	Discontinued	5801-181	4	Spare Part
AXIS Q8631-E/32-E HOUSING TOP	20	Discontinued	5801-291	4	Spare Part
AXIS Q8665 HOUSING TOP	5	Discontinued	5801-281	4	Spare Part
AXIS Q8631/32/65 SUNSHIELD	5	Discontinued	5801-311	4	Spare Part
AXIS Q8665 WIPER	5	Discontinued	5801-201	4	Spare Part
AXIS Q8721-E/22-E BASE	5	Discontinued	5800-951	4	Spare Part
AXIS TM1802 TOP COVER KIT	5		01779-001	2	Spare Part
AXIS WEATHERSHIELD S	5		01496-001	4	Spare Part
AXIS WIPER KIT B	5	Discontinued	01688-001	4	Spare Part
AXIS CONNECTOR A 2P2.5 STR 10PCS	5		5505-261	4	Spare Part
AXIS CONNECTOR A 4P2.5 STR 10PCS	5		5800-891	4	Spare Part
AXIS CONNECTOR A 6P2.5 STR 10PCS	5		5505-271	4	Spare Part
AXIS CONNECTOR A 2P3.81 STR 10PCS	5		5800-901	4	Spare Part
AXIS CONNECTOR A 3P3.81 STR 10PCS	5		5505-281	4	Spare Part
AXIS CONN A 4P3.81 STR IN/OUT 10P	5		5505-291	4	Spare Part
AXIS CONNECTOR A 4P3.81 STR 10PCS	5		5505-251	4	Spare Part
AXIS CONNECTOR A 2P5.08 STR 10PCS	5		5505-301	4	Spare Part

SPR 5 PORT GB ETHERNET SWITCH KIT	5	Discontinued	5800-881	2	Spare Part
AXIS Q1765 FOOT CHASSIS	5		5506-091	4	Spare Part
AXIS ADAPTER RJ45 MALE TO MALE	5		5506-891	4	Spare Part
AXIS ACI CONDUIT COVER A 10PCS	5		01175-001	4	Spare Part
AXIS TP1903 PCBA Housing T92	5		02243-001	4	Spare Part
AXIS TP3903-E FRONT WINDOW	5		02211-001	4	Spare Part
AXIS TP3811 Weathershield	5		02075-001	2	Spare Part
AXIS TQ1801 WEATHERSHIELD	5		01760-001	4	Spare Part
AXIS TQ1802 WEATHERSHIELD	5		02014-001	4	Spare Part
AXIS TQ1803 FRONT WINDOW KIT	5		02015-001	4	Spare Part
AXIS TQ1804-E TOP COVER WITH WIPER	5		02193-001	4	Spare Part
AXIS TQ1804-BE TOP COVER	5		02430-001	4	Spare Part
AXIS TQ1806 WEATHERSHIELD	10		02268-001	4	Spare Part
AXIS TQ1810-E FRONT KIT	5		02426-001	4	Spare Part
AXIS TQ1906-E FRONT WINDOW KIT	5		02417-001	4	Spare Part
AXIS TQ1907-E FRONT WINDOW KIT	5		02418-001	4	Spare Part
AXIS TQ6902-E WEATHER SHIELD	5		02104-001	4	Spare Part

AXIS TQ6808-E HARD-COAT CLEAR DOME	5	02103-001	4	Spare Part
AXIS TQ8809-E WIPER KIT	5	02231-001	4	Spare Part
AXIS TQ8801-E Top Cover	5	02229-001	10	Spare Part
AXIS TQ8802-E Top Cover Zoom	5	02230-001	10	Spare Part
AXIS TI8902 GLASS REPLACEMENT KIT	5	02069-001	4	Spare Part
LENS I-CS 1/1.8" 3.9-10 mm F1.5	10	02367-001	4	Spare Part
LENS CS 4-10MM F0.9	5	02448-001	4	Spare Part
AXIS TM2001 MOUNT BRACKET	5	02586-001	4	Spare Part
AXIS TM2802 FRONT KIT A	5	02587-001	4	Spare Part
AXIS TQ1807-VE CABINET DOOR	5	02358-001	4	Spare Part
AXIS TQ6812-E Solo Kit	50	02655-001	4	Spare Part

AXIS TP3828-E Dome Cover White	15		02477-001	4	Spare Part
LENS M12 2MM F2.0	5		02466-001	4	Spare Part
LENS M12 3.1MM F2.0	5		02465-001	4	Spare Part
AXIS TP1803-E Front Window Kit	5		02713-001	4	Spare Part
AXIS TP1804-E Front Window Kit	5		02714-001	4	Spare Part
AXIS TU6001 CONN 3-PIN 3.81MM 10P	20		02464-021	4	Spare Part
AXIS TQ8901-E Wiper Kit	5	Discontinued	02661-001	4	Spare Part
AXIS TQ8803-E Front Kit	5	Discontinued	02531-001	4	Spare Part
AXIS TQ1502-E Front Window Kit	5		02717-001	13	Spare Part
AXIS TQ3810-E Weathershield	5		02806-001	4	Spare Part
LENS I-CS 3.5-10 MM F1.8	5		02638-001	4	Spare Part
AXIS TP3907 Clamp Bracket Mount 10P	5		02931-021	2	Spare Part

		0.074	4 004	Cranera Darré
AXIS TS3902 RAIL KIT	5	0274	4-001 4	Spare Part
AXIS Mains Adapter 48V DC 180W	5	0276	7-001 4	Spare Part
AXIS DEVICE MICROPHONE A	20	0157	5-001 4	System Accessory
AXIS T8351 MK II MICROPHONE 3.5MM	125	0156	0-001 2	System Accessory
AXIS T8355 DIGITAL MICROPHONE	100	0156	1-001 4	System Accessory
AXIS TP3901 MICROPHONE KIT	125	0179	8-001 2	System Accessory
AXIS TP3906 MICROPHONE KIT	5	0254	7-001 4	System Accessory

AXIS DEVICE MICROPHONE B	10	01963-001	4	System
				Accessory
AXIS TU1001-VE Microphone	20	02269-001	2	System
	20	02209-001	2	Accessory
AXIS TU1002-VE MICROPHONE KIT	5	02082-001	4	System
				Accessory
AXIS TU1001-V Microphone	30	02270-001	2	System
				Accessory
POE SPLITTER 5V	100	02044-001	4	System
				Accessory
AXIS POE MIDSPAN 8-PORT	5	5012-004	4	System
				Accessory
AXIS POE MIDSPAN 16-PORT	5	5012-014	4	System Accessory
				Accessory
AXIS T8120 15W MIDSPAN 1-PORT	250	5026-204	2	System
				Accessory
AXIS T8120 15W MIDSPAN 10PCS	5	5026-224	2	System
				Accessory
· · · · · · · · · · · · · · · · · · ·	•			

AXIS T8607 MEDIA CONV SWITCH 24VDC	5	5901-271	4	System Accessory
AXIS 30W MIDSPAN	500	02172-004	2	System Accessory
AXIS 30 W MIDSPAN AC/DC	80	02208-001	4	System Accessory
AXIS 90 W MIDSPAN AC/DC	20	02209-001	4	System Accessory
AXIS 30W OUTDOOR MIDSPAN	20	01944-001	2	System Accessory
AXIS T8611 SFP MODULE LC.LX	100	5801-801	2	System Accessory
AXIS T8612 SFP MODULE LC.SX	60	5801-811	2	System Accessory
AXIS T8613 SFP MODULE 1000BASE-T	10	5801-821	4	System Accessory
AXIS T8134 MIDSPAN 60W	400	5900-334	2	System Accessory
AXIS T8144 60W INDUSTRIAL MIDSPAN	150	01154-001	2	System Accessory

AXIS TU8002-E 90 W MIDSPAN	30		02453-001	2	System Accessory
AXIS T8125 AC 24V MIDSPAN 60W	30	Discontinued	5900-251	4	System Accessory
POWER SUPPLY DIN CP-D 12/2.1 25W	20		5505-731	4	System Accessory
POWER SUPPLY DIN CP-D 24/4.2 100 W	10		01169-001	4	System Accessory
POWER SUPPLY PS24 240 W	10		01170-001	2	System Accessory
AXIS T8127 60 W SPLITTER 12/24 V DC	40		5500-001	2	System Accessory
POWER SUPPLY DIN PS24 480W	30		01677-001	4	System Accessory
AXIS POWER SUPPLY DIN PS56 240W	40		01726-001	4	System Accessory
AXIS T8129 POE EXTENDER	200		5025-281	2	System Accessory
AXIS T8129-E OUTDOOR POE EXTENDER	150		01148-001	4	System Accessory
ACC CABLE I/O AUDIO 5M P3343-VE	5	Discontinued	5502-331	4	System Accessory

AXIS LONG RANGE POE EXTENDER KIT	50	01857-001	4	System Accessory
AXIS DIGITAL AUDIO EXTENSION KIT	10	01590-001	4	System Accessory
AXIS AUDIO EXTENSION CABLE B 5M	70	01589-001	4	System Accessory
AXIS T8516 PoE+ NETWORK SWITCH	20	5801-694	4	System Accessory
AXIS T8524 POE+ NETWORK SWITCH	70	01192-004	4	System Accessory
TERMINAL BLOCK TO 3.5MM AUDIO EXT	60	01714-001	2	System Accessory
AXIS MULTICABLE A I/O AUDIO PWR 1M	5	5505-031	4	System Accessory
AXIS T8640 POE+ OVER COAX ADAP	50	5026-401	2	System Accessory
AXIS MULTICABLE A I/O AUDIO PWR 5M	5	5505-021	4	System
AXIS T8641 POE+ OVER COAX BASE	10	5028-411	4	Accessory System Accessory
AXIS MULTICABLE B I/O AUDIO PWR 2.5M	5	5505-511	4	System Accessory
AXIS T8642 POE+ OVER COAX DEVI	10	5027-421	4	System Accessory

AXIS MULTICABLE C I/O AUDIO PWR 1M	15		5506-201	2	System Accessory
AXIS T8643 POE+ OVER COAX COMPACT	10		01468-001	4	System Accessory
AXIS MULTICABLE C I/O AUDIO PWR 5M	20		5506-191	4	System
AXIS T8645 PoE+ COAX COMPACT KIT	20		01489-001	4	Accessory System
					Accessory
AXIS T8646 POE+ OVER COAX BLADE	5	Discontinued	5026-461	4	System Accessory
AXIS T8646 POE+ OVER COAX BLADE KIT	5	Discontinued	5026-471	4	System Accessory
AXIS OUTDOOR RJ45 CABLE 5M	20		5502-731	2	System Accessory
AXIS OUTDOOR RJ45 CABLE 15M	20		5504-731	4	System Accessory
AXIS Q60XX-C MULTI CONNECT CABLE 12M	5	Discontinued	5504-651	4	System Accessory

AXIS CABLE 24 VDC/24-240 VAC 22M	5		5801-741	4	System Accessory
NETWORK CABLE COUPLER INDOOR	125		5503-771	2	System Accessory
NETWORK CABLE COUPLER INDOOR SLIM	30		5503-272	4	System Accessory
ELECTRICAL SAFETY KIT A 120VAC	20	Discontinued	5503-521	4	System Accessory
AXIS T98A15-VE MEDIA CONVERTER CABINET A (120 V AC)	5		5505-351	4	System Accessory
AXIS T98A16-VE MEDIA CONVERTER CABINET A (120 V AC)	5		5505-361	4	System Accessory
AXIS T98A17-VE MEDIA CONVERTER CABINET A (120 V AC)	5		5505-371	4	System Accessory
AXIS T98A18-VE MEDIA CONVERTER CABINET A (120 V AC)	10		5505-381	4	System Accessory

AXIS T98A19-VE MEDIA CONVERTER CABINET	5	Discontinued	5505-391	4	System
A (120 V AC)	J	Discontinued	0000-001	-	Accessory
ACC MAINS ADAPTOR AXIS PS24	5		5000-001	4	System
					Accessory
AXIS T8008 PS24	5		5801-701	4	System
					Accessory
AXIS T8051 Power Converter AC/DC to DC	100	Discontinued	5505-051	4	System
				-	Accessory
					_
AXIS TU8001 Ethernet Surge Protector	175		02315-001	2	System
					Accessory
AXIS T8061 ETHERNET SURGE PROTECTOR	250		5801-641	2	System
					Accessory
CONNECTOR M12 MALE 4P 10PCS	5		5502-131	4	System
					Accessory
AXIS 10-PIN PUSH-PULL SYSTEM CONN	10		5506-251	4	System
					Accessory
RJ45 FIELD CONNECTOR 10 PCS	5		01996-001	4	System
					Accessory
AXIS STEREO-TO-MONO ADAPTER	5		5801-681	2	System
AND STEREU-IU-MUNU ADAPTER	5		189-1005	2	System Accessory
					, 10000001 y

AXIS POWER CABLE 24 V 7m (23ft)	5	02198-001	4	System
AXIS FOWER CABLE 24 V /III (2311)	5	02198-001	4	Accessory
				Accessory
AXIS TD8902 SFP+ MODULE LC.SR.X	10	02631-001	4	System
AXIS TDOSUZ SFF+ MODULE LC.SK.X	10	02031-001	4	Accessory
				Accessory
AXIS TD8901 SFP+ MODULE LC.LR.X	10	02630-001	4	System
				Accessory
POWER SUPPLY DIN PS56 480 W	30	02632-001	4	System
				Accessory
AXIS T8154 60W SFP MIDSPAN	175	02740-004	2	System
				Accessory
AXIS TU8004 90 W Midspan	90	02783-001	4	System
				Accessory

AXIS SURVEILLANCE CARD 64 GB	700	5801-951	2	System Accessory
AXIS SURVEILLANCE CARD 64 GB 10P	60	5801-961	2	System Accessory
AXIS SURVEILLANCE CARD 128 GB	600	01491-001	2	System Accessory
AXIS SURVEILLANCE CARD 128 GB 10P	50	01678-001	2	System Accessory
				,

AXIS SURVEILLANCE CARD 256GB	250	02021-001	2	System Accessory
AXIS SURVEILLANCE CARD 256GB 10PCS	20	02021-021	2	System Accessory
AXIS SURVEILLANCE CARD 512GB	125	02365-001	2	System Accessory

AXIS SURVEILLANCE CARD 512GB 10PCS	10	02365-021	2	System
	10	02000-021	-	Accessory
				, ,
AXIS SURVEILLANCE CARD 1TB	80	02366-001	2	System
				Accessory
				-
AXIS SURVEILLANCE CARD 1TB 10PCS	10	02366-021	2	System
		01000 011	-	Accessory
				,,
SURVEILLANCE HARD DRIVE 4TB	5	 01858-001	2	System
	5	01000-001	-	
				Accessory

SURVEILLANCE HARD DRIVE 6TB	10		01859-001	2	System Accessory
ENTERPRISE HARD DRIVE 4TB	5		02471-001	2	Recorder
ENTERPRISE HARD DRIVE 8TB	10		02472-001	2	Recorder
AXIS T8312 KEYPAD	5	Discontinued	5020-201	4	System Accessory
AXIS T8604 MEDIA CONVERTER SWITCH	20		5027-041	2	System Accessory

AXIS T8606 MEDIA CONV SWITCH 24VDC	15		5901-261	4	System Accessory
AXIS T8331 PIR MOTION DETECTOR	5	Discontinued	5506-931	4	System Accessory
AXIS T8331-E PIR MOTION DETECTOR	10	Discontinued	5506-941	4	System Accessory
AXIS T8341 PIR MOTION SENSOR	5	Discontinued	01202-004	2	System Accessory
AXIS T8342 DOOR/WINDOW SENSOR	5	Discontinued	01203-004	2	System Accessory
AXIS T8343 ALERT BUTTON	5	Discontinued	01204-004	2	System Accessory
AXIS T8344 POWER ON/OFF PLUG	5	Discontinued	01205-004	2	System Accessory
AXIS T8353A MICROPHONE 3.5MM	10		5032-531	2	System Accessory
AXIS T8353 MOUNT	5		5505-041	4	System
AXIS T8415 WIRELESS INSTALLATION TOOL	20		5506-231	2	Accessory System Accessory
AXIS T8415 WIRELESS INST TOOL KIT	20		5506-881	2	System Accessory
AXIS P55/Q60 MULTI CONN CABLE 5M	5		5502-491	4	System Accessory
AXIS T8415 INSTALLATION BAG	5		5506-871	2	System Accessory
AXIS INSTALLATION TOOL BATTERY 12V3.4Ah	15		5506-551	2	System Accessory
ACC MAINS ADAP PS-P T-C	10		5502-261	4	System Accessory
AXIS INSTALLATION CHARGER ADAPTOR 12V1A	5		5506-561	2	System Accessory

AXIS P8221	50	Discontinued	0321-004	4	System Accessory
AXIS D3110 Connectivity Hub	90		02232-001	2	System Accessory
AXIS T8006 PS12	10		5030-064	4	System Accessory
NETWORK CABLE COUPLER IP66	30		5503-431	2	System Accessory
ACC MAINS ADAP PS-K TERM-CONN	5		5503-681	4	System Accessory
AXIS T8003 PS57	20		5029-034	4	System Accessory
AXIS T8007 PS24	10		5503-104	4	System Accessory
AXIS T8008 PS12	5		5503-661	4	System Accessory
AXIS T8085 PS57 500W 1U	5		5504-864	4	System Accessory

AXIS T90C20 FIXED DOME IR-LED	5	5024-201	4	System Accessory
AXIS T90D20 IR-LED	10	01210-001	4	System
				Accessory
AXIS T90D20 POE IR-LED	20	01211-001	4	System Accessory
AXIS T90D25 W-LED	5	01215-001	4	System Accessory
AXIS T90D25 POE W-LED	5	01216-001	4	System Accessory
AXIS T90D30 IR-LED	10	01212-001	4	System Accessory

AXIS T90D30 POE IR-LED	15	01213-001	4	System Accessory
				hooocity
AXIS T90D35 W-LED	10	01217-001	4	System Accessory
AXIS T90D35 POE W-LED	5	01218-001	4	System Accessory
				,
AXIS T90D40 IR-LED	10		4	Quature
AXIS 190040 IR-LED	10	01214-001	4	System Accessory
AXIS WL LENS B 120 DEG	5	5505-681	4	System Accessory
AXIS IR LENS B 120 DEG	5	5505-701	4	System
	10	5505-691	4	Accessory System
AXIS WL LENS C 120 DEG	10	2202-031	4	Accessory
AXIS IR LENS C 120 DEG	5	5505-711	4	System Accessory
AXIS IR LENS D 120 DEG	10	01235-001	4	System Accessory

AXIS T90B REMOTE CONTROL	5	5800-931	4	System Accessory
AXIS T90 WALL-AND-POLE MOUNT AXIS T90 SINGLE BRACKET	50	01219-001	4	System Accessory System
		01220-001	4	Accessory
AXIS T90 MULTI BRACKET	5	01221-001	4	System Accessory
AXIS DOOR SWITCH A	5	5503-841	4	System Accessory
AXIS DOME INTRUSION SWITCH C	10	01802-001	4	System Accessory
MAINS CABLE ANGL C13-OPN 0.5M	5	5506-244	4	System Accessory
AXIS FIXED BOX IR ILLUMINATOR KIT A	10	01534-001	4	System Accessory
AXIS TQ1901-E IR ILLUMINATOR KIT	5	02194-001	4	System Accessory
AXIS I/O INDICATION LED 4P	5	01765-001	4	System Accessory

AXIS CAMERA HEATER POWER SUPPLY	50	02040-001	4	System Accessory
AXIS TQ1902-E IR ILLUMINATOR KIT	5	02195-001	4	System Accessory
AXIS TM3812 Tamper-resistant Cover	10	02565-001	4	System Accessory
AXIS TM3817 TAMPER-RESISTANT COVER	5	02572-001	4	System Accessory
AXIS TM1901 WIRELESS KIT	70	02627-004	2	System Accessory

AXIS D4100-E NETWORK STROBE SIREN	200		01942-001	2	System Device
AXIS D2110-VE	80		01564-001	4	System Device
AXIS D2210-VE Radar White	20	To be launched	02955-001	2	System Device

AXIS D2210-VE Radar Black	100	To be launched	02770-001	2	System Device
AXIS D8004 UNMANAGED POE SWITCH	40		02101-004	2	System Device
AXIS T8504-E OUTDOOR POE SWITCH	10		01449-001	2	System Device
AXIS T8504-R INDUSTRIAL POE SWITCH	60		01633-001	4	System Device
AXIS D8208-R INDUSTRIAL PoE++ SWITCH	50		02621-001	4	System Device

AXIS T8508 POE+ NETWORK SWITCH	40		01191-004	4	System Accessory
					Accessory
	-				
AXIS P8221 BULK 10PCS	5	Discontinued	0321-021	4	System Device
AXIS T6101 MKII Audio and I/O Interface	125		02553-001	2	System Device
AXIS T6112 MKII Audio and I/O Interface	80		02554-001	2	System Device
AXIS TW1100 Clip Mount 5P	5		02126-001	2	Wearables
AXIS TW1101 MOLLE Mount 5P	5		02127-001	4	Wearables
AXIS TW1102 Magnet Mount 5P	5	Discontinued	02128-001	2	Wearables

5		02129-001	4	Wearables
30		02437-001	4	Wearables
5		02582-001	4	Wearables
5	New	02689-001	2	Wearables
5	New	02690-001	4	Wearables
5		01952-001	2	Wearables
10		02242-001	4	Wearables
	30 5 5 5 5	30 5 5 5 8 8 9 8 9 8 9 9 9 9 9 9 9 9 9 9 9	30 02437-001 30 02582-001 5 02582-001 5 New 5 New 5 02689-001 5 New 5 01952-001 5 01952-001	30 02437-001 4 30 02582-001 4 5 02582-001 4 5 New 02689-001 2 5 New 02690-001 4 5 New 02690-001 2 5 New 02690-001 2

AXIS TW1201 BW MINI CUBE SENSOR WHITE	5	02260-001	4	Wearables
AXIS TW1900 ADHESIVE PICATINNY RAIL 5P	5	02031-001	2	Wearables
AXIS TW1901 CABLE HOLDER 5P	5	02030-001	2	Wearables
AXIS TW1902 LENS PROTECTOR 5P	5	02032-001	2	Wearables
AXIS TW1904 Body Worn Mount Flight	5	02191-001	4	Wearables
······································	•			
AXIS TW1905 MINI CUBE MAGNET MOUNT 5P	5	02261-001	4	Wearables
AXIS TW1906 Battery Replacement Kit 5P	5	02725-001	4	Wearables
Parts in 1000 Battery Replacement Att or		VE1 20-001	7	1160105165

AXIS TW8100 RACK MOUNT	5		02321-001	4	Wearables
AXIS W100 BODY WORN CAMERA	70	Discontinued	01722-001	2	Wearables
AXIS W100 BODY WORN CAMERA 24P	5	Discontinued	01722-021	4	Wearables
	L				

AXIS W101 BODY WORN CAMERA BLACK	125	02258-001	2	Wearables
AXIS W101 BODY WORN CAMERA WHITE		02259-001		Meanshire
AXIS W101 BODY WORN CAMERA WHITE	10	02259-001	2	Wearables
AXIS W101 BODY WORN CAMERA BLK 24P	5	02258-021	2	Wearables
	1			

AXIS W110 BODY WORN CAMERA GRAY	60	New	02644-004	2	Wearables
AXIS W110 BODY WORN CAMERA BLACK	60	New	02680-004	2	Wearables
AXIS W110 Gray 5 pcs	5	New	02644-024	2	Wearables

AXIS W110 Black 5 pcs	5	New	02680-024	2	Wearables
AXIS Body Worn Live	0		02724-001	0	Wearables

AXIS Case Insight US 1year BWC Lic	0	02084-001	0	Wearables
AXIS Case Insight US 1y Storage 1TB	0	02291-001	0	Wearables
AXIS Case insight US Ty Storage TTB	U	02291-001	U	wearables

AXIS Case Insight USGOV 1year BWC Lic	0	02287-001	0	Wearables
, in the second s			-	
AXIS Case Insight USGOV 1y Storage 1TB	0	02294-001	0	Wearables

AXIS Case Insight CA 1year BWC Lic	0	02295-001	0	Wearables
AXIS Case Insight CA 1y Storage 1TB	0	02297-001	0	Wearables

AXIS W800 SYSTEM CONTROLLER	10		01964-004	2	Wearables
AXIS W700 DOCKING STATION 1 BAY	5		01723-004	2	Wearables
AXIS W701 DOCKING STATION 8 BAY	10		01724-004	2	Wearables
AXIS W702 DOCKING STATION 1 BAY	5	New	02645-004	2	Wearables
AXIS W703 DOCKING STATION 8 BAY	5	New	02646-004	2	Wearables
AXIS W400 Body Worn Activation Kit	10		02877-001	4	Wearables

, USD						
			r			
Product Description		MSRP		EAN Code US	Weight (lbs)	Width in
The 2N® Access Commander Box is an ultra	\$	624.00		8595159505961	2.20	3.11
compact computer with pre-installed 2N® Access Commander – software designed for						
access control configuration and 2N devices						
management. It is ready to use, plug and play						
solution which requires only a power supply						
and an Ethernet cable to be connected to the						
computer. It is perfectly optimised for small						
and medium-size installations with up to 500 2N IP intercoms/Access Units and 7000 users.						
ZN IF Intercoms/Access onits and 7000 users.						
2N Access Unit - Bluetooth. Comes without	\$	510.00		8595159511399	0.49	1.26
frame and/or flush box - those are from IP						
Verso. 2N Access Unit - RJ45 connector cable	\$	12.00		8505150507644	0.09	5.20
ZIN ACCESS UNIT - KJ40 CONNECTOR CADIE	φ	12.00		8595159507644	0.09	5.20
2N Access Unit 2.0 – Bluetooth & RFID 125kHz,	\$	920.00		8595159515052	0.31	4.41
13.56MHz secured card reader, reading PACS						
ID + UID, NFC ready, support of HID iClass secured.						
The unit is equipped with the RJ45 connector,						
no need to use 01371-001 2N AU - RJ45						
CONNECTOR CABLE accessories anymore.						
2N Access Unit 2.0 – Touch keypad & RFID	\$	805.00		8595159515076	0.31	4.41
25kHz, 13.56MHz secured card reader, reading	•					
PACS ID + UID, NFC ready, support of HID						
iClass secured.						
The unit is equipped with the RJ45 connector,						
no need to use 01371-001 2N AU - RJ45 CONNECTOR CABLE accessories anymore.						
CONTECTOR CABLE accessores anymore.						
2N Access Unit 2.0 - RFID 125kHz, 13.56MHz	\$	732.00		8595159515038	0.31	4.41
secured card reader, reading PACS ID + UID,						
NFC ready, support of HID iClass secured.						
The unit is equipped with the RJ45 connector,						
no need to use 01371-001 2N AU - RJ45						
CONNECTOR CABLE accessories anymore.						
2N Access Uni 2.0 - RFID 125kHz, second	\$	472.00		8595159516172	0.51	1.18
generation with better reading distance/time						
2N Access Unit - RFID 125kHz/13.56MHz NFC,	\$	605.00		8595159515120	0.31	1.18
second generation with better reading						
distance/time, reads PACS ID	*	E 44 00		9505450545400	0.04	4.40
2N Access Unit - RFID 13,56MHz NFC secured (reads PACS ID), second generation with better	\$	541.00		8595159515106	0.31	1.18
reading distance/time						

2N Access Uni 2.0 - RFID 13.56MHz, second	\$	454.00	8595159515090	0.31	1.18
generation with better reading distance/time					
	•				
2N Access Unit 2.0 touch keypad	\$	384.00	8595159514970	0.31	1.18
2N Access Unit 2.0 Eingernrint reader	\$	763.00	8595159514963	0.31	1.18
2N Access Unit 2.0 Fingerprint reader	φ	763.00	0595159514965	0.31	1.10
2N Access Unit in mullion design. RFID	\$	390.00	8595159515366	0.60	2.72
13.56MHz. Suitable for door frame installation.	Ψ	000.00	0000100010000	0.00	2.12
Replacement of 02393-001 with 3m long	\$	447.00	8595159523231	0.90	2.80
Ethernet cable	Ŧ				
2N Access unit in mullion desing. RFID with	\$	519.00	8595159515380	0.60	2.72
13.56MHz and 125kHz. Suitable for door frame	Ŧ				
installation.					
Replacement of 02394-001 with 3m long	\$	555.00	8595159523248	0.90	2.80
Ethernet cable					
2N Access unit in mullion design. Combo	\$	676.00	8595159515397	0.60	2.72
reader with BT and RFID 13.56MHz and 125kHz.					
Suitable for door frame installation.					
Replacement of 02395-001 with 3m long	\$	723.00	8595159523255	0.90	2.80
Ethernet cable					
2N Access Unit mullion. Combo unit touch	\$	623.00	8595159515410	0.60	2.72
keypad and RFID 13.56MHz and 125kHz.					
Suitable for door frame installation.					
Replacement of 02396-001 with 3m long	\$	667.00	8595159523262	0.90	2.80
Ethernet cable					
					1
Flush mounting accessory for 02909-001, 02910-	\$	35.00	8595159515434	0.31	1.18
001, 02911-001, and 02912-001					
	Ļ	-		-	
Spacer mounting accessory for 02909-001,	\$	35.00	8595159515441	0.31	1.18
02910-001, 02911-001, and 02912-001					
	-				
2N AU2.0 READER, Keyboard, RFID 125kHz,	\$	805.00	8595159515168	0.51	1.18
13,56Mhz, NFC, secured, PICard					
	^	001.00	0505450545454	0 = 1	4.10
2N AU2.0, READER, Keyboard, RFID 125kHz,	\$	681.00	8595159515151	0.51	1.18
13,56 Mhz, NFC, PICard					
	*	000.00	0505450545444	0.54	4.40
2N AU2.0 READER, Bluetooth, RFID 125kHz,	\$	920.00	8595159515144	0.51	1.18
13,56Mhz, NFC, secured, PICard					
	¢	904.00	8505450545427	0.54	4 4 0
2N AU 2.0 READER, BLE, RFID 125kHz, 13,56Mhz, NFC, PICard	\$	804.00	8595159515137	0.51	1.18
13,00WIIZ, NFC, PICARU					
	\$	1 1 4 0 0 0	8505150521466	0.54	1 4 0
2N AU 2.0 READER, BLE, RFID 125kHz, 13,56Mhz, NFC, secured, PICard	Þ	1,140.00	8595159521466	0.51	1.18
13,50mmz, NEC, Secureu, Ficaru					
2N AU 2.0, Keypad, Bluetooth, RFID 125kHz,	\$	974.00	8595159521459	0.51	1.18
13,56Mhz, NFC, PICard	φ	514.00	0090109021409	0.51	1.10

2N IP Audio Kit – SIP module for embedded installation	\$ 387.00		0.88	10.00
2N IP Audio Kit - microphone & speaker set	\$ 46.00	8595159503653	0.10	0.59
2N IP Audio Kit - stainless steel backlit button	\$ 35.00	8595159503646	0.04	3.94
2N IP Audio Kit - speaker	\$ 20.00	8595159502731	0.10	3.31
2N IP Audio Kit - microphone	\$ 20.00	8595159502724	0.10	2.99
2N IP Base - camera, black frame	\$ 839.00	8595159509884	1.37	11.42
2N IP Base - 125kHz RFID card reader	\$ 103.00	8595159509365	0.11	4.92
2N IP Base - 13.56MHz RFID card reader, reads UID	\$ 165.00	8595159509266	0.11	4.92
2N IP Base - backplate for easier surface installation	\$ 69.00	8595159509259	0.66	10.83
2N IP Base double button spare part	\$ 26.00	8595159514550	0.20	1.18
2N IP Base - single button spare part	\$ 24.00	8595159514543	0.11	1.18
Spare part - metal fixture for 2N IP Base, 10 pcs	\$ 45.00	8595159517681	0.11	0.39
2N IP Base spare part - antenna cover sealing, 10 pcs	\$ 49.00	8595159517728	0.10	0.79
2N IP Force - 1 button + HD camera + pictograms + 10W speaker, card reader ready	\$ 1,599.00	8595159506630	4.59	6.81
2N IP Force - 1 button + pictograms + 10W speaker, card reader ready	\$ 1,237.00	8595159507590	4.45	6.81
2N IP Force - 1 button + 10W speaker	\$ 1,151.00	8595159500263	4.43	6.81
2N IP Force - 1 button + HD camera + 10W speaker	\$ 1,559.00	8595159506647	4.63	6.81
2N IP Force - 1 button + keypad + 10W speaker	\$ 1,276.00	8595159502045	4.94	6.81
2N IP Force - 1 button + HD camera + keypad + 10W speaker	\$ 1,571.00	8595159506616	4.96	6.81

2N IP Force - 2 buttons + HD camera + 10W speaker, card reader ready	\$ 1,576.00	8595159506661	4.65	6.81
2N IP Force - 2 buttons + 10W speaker, card reader ready	\$ 1,174.00	8595159506784	4.59	6.81
2N IP Force - 4 buttons + 10W speaker	\$ 1,264.00	8595159504544	4.81	6.81
2N IP Force - 4 button + HD camera + 10W speaker	\$ 1,588.00	8595159506685	4.83	6.81
2N IP Force - 125kHz card reader. Includes Wiegand interface, 2 logical inputs, 2 output relays and tamper switch.	\$ 144.00	8595159500959	0.22	0.98
2N IP Force - safety screws, torx with pin	\$ 14.00	8595159507712	0.07	1.02
2N IP Force - 13.56MHz secured card reader, NFC ready, Reads UID + PACS ID, support of HID iClass secured. Includes Wiegand interface, 2 logical inputs, 2 output relays and tamper switch	\$ 317.00	8595159515304	0.15	0.98
2N IP Force Torx 4 screws black for the front panel - 5 packages of screws	\$ 22.00	8595159513812	0.07	0.39
2N IP Force Frame for the main unit - 1 pc	\$ 31.00	8595159513805	0.40	1.57
2N IP Force front panel with 4 buttons - 1pc	\$ 135.00	8595159513829	0.55	1.57
2N IP Force front panel with 1 button - 1pc	\$ 96.00	8595159513836	0.35	1.57
2N IP Force front panel with 1 button and pictograms -	\$ 117.00	8595159513843	0.33	1.57
2N IP Force front panel with 1 button ready for keypad - 1pc	\$ 99.00	8595159513850	0.29	1.57
2N IP Force front panel with 2 buttons ready for card reader - 1pc	\$ 125.00	8595159513867	0.37	1.57
2N IP Force and Safety - Brick flush mounting box	\$ 108.00	8595159500362	2.71	4.45
2N IP Force and Safety - Plasterboard flush mounting box	\$ 97.00	8595159500379	1.19	2.76
2N IP Force and Safety - Additional switch + Tamper switch.	\$ 58.00	8595159500942	0.44	5.83
2N IP Force and Safety - Gooseneck stand, height 120cm/47in	\$ 333.00	 8595159505473	23.41	9.06

2N IP Force and Safety - Installation adapter for Code Blue and Talkaphone	\$ 125.00	8595159505664	4.48	11.02
2N IP Force and Safety - Gooseneck stand double, 45" / 80"	\$ 624.00	8595159513546	46.30	15.98
2N IP Force and Safety set of bushing for ethernet cable -5 pcs	\$ 64.00	8595159513799	0.93	1.57
2N IP Force Secure Door set - contains additional switch + tamper (01350-001) and Security Relay (01386-001)	\$ 132.00	8595159515649	0.49	2.76
2N IP Force keypad - 1pc	\$ 94.00	8595159513775	0.35	1.18
Induction loop for 2N IP Force. Main unit with RFID window has to be used together with this accessory.	\$ 146.00	8595159517377	0.20	5.20
2N IP Safety - 1 button + 10W speaker	\$ 1,134.00	8595159500737	4.17	6.81
2N IP Safety - 2 buttons + 10W speaker	\$ 1,164.00	8595159506562	4.19	6.81
2N IP Safety - red emergency button + 10W speaker	\$ 1,164.00	8595159507026	4.14	6.81
2N IP Safety - metal frame (orange color)	\$ 40.00	8595159500874	0.40	0.79
	\$ 40.00	8595159514130	0.26	0.28
	\$ 45.00	8595159514147	0.26	0.28
	\$ 16.00		0.73	0.39
2N IP Safety quick dial button with blue backlight - 5pcs	\$ 229.00	8595159514123	0.29	1.18
2N IP Solo - flush mount	\$ 1,268.00	8595159505589	1.52	1.42
2N IP Solo - surface mount	\$ 1,237.00	8595159505602	1.63	1.42
2N IP Solo - surface mount, black	\$ 1,237.00	8595159505565	1.63	1.42
2N IP Solo - flush mount, black	\$ 1,268.00	8595159505541	1.52	1.42
2N IP Solo - backbox for flush installation	\$ 29.00	8595159505527	0.44	0.20

2N IP Solo - backplate for easier surface installation	\$ 58.00	8595159511528	0.37	1.06
Backplate for glass mount, has to be shipped together with 01305-001 backplate	\$ 23.00	8595159515878	0.11	0.39
2N IP Solo black without camera for surface mount. The intercom is suitable for residential and commercial installation where camera is not required and IP Verso without camera has too big footprint, usually indoor (however intercom has IP54 rating and its perfectly suitable for outdoor installation).	\$ 676.00	8595159515861	1.61	1.42
2N IP Solo without camera for surface mount. The intercom is suitable for residential and commercial installation where camera is not required and IP Verso without camera has too big footprint, usually indoor (however intercom has IP54 rating and its perfectly suitable for outdoor installation).	\$ 676.00	8595159515854	1.61	1.42
2N IP Solo black without camera for flush mount. The intercom is suitable for residential and commercial installation where camera is not required and IP Verso without camera has too big footprint, usually indoor (however intercom has IP54 rating and its perfectly suitable for outdoor installation).	\$ 707.00	8595159515847	1.61	1.42
2N IP Solo without camera for flush mount. The intercom is suitable for residential and commercial installation where camera is not required and IP Verso without camera has too big footprint, usually indoor (however intercom has IP54 rating and its perfectly suitable for outdoor installation).	\$ 707.00	8595159515830	1.61	1.42
2N IP style flush box. Accessories for the IP Style main unit 02407-001.	\$ 205.00	8595159517490	3.31	2.28
2N IP Style surface installation box. Accessory for 2N IP Style main unit 02407-001.	\$ 97.00	8595159517506	1.41	1.42
2N IP Style - 10 inch touchscreen intercom with IP65 and IK08. Embedded RFID reader 125kHz+13.56MHz (reads iClass PACS ID), embedded BT access control and full HD camera with WDR. Suitable for both surface (02406-001) and flush (02405-001) installation.	\$ 4,150.00	8595159517513	6.20	2.80

2N IP Style main unit, secured, with installed antibacterial protector - 10 inch touchscreen intercom with IP65 and IK08. Embedded RFID reader 125kHz+13.56MHz (reads iClass PACS ID), embedded BT access control and full HD camera with WDR. Suitable for both surface (02406-001) and flush (02405-001) installation.	\$ 4,350.00	8595159522487	4.70	2.80
2N IP Style screen protector, accessory	\$ 130.00	8595159522852	0.40	0.79
	\$ 24.00	8595159514451	0.26	0.28
	\$ 42.00	8595159514475	0.46	0.28
	\$ 44.00	8595159514482	0.46	0.28
	\$ 43.00	8595159514499	0.46	0.28
	\$ 26.00	8595159514512	0.07	0.39
2N IP Uni speaker with cable, 4 pcs	\$ 44.00	8595159514444	0.15	1.06
2N IP Uni microphone with cable, 10 pcs	\$ 47.00	8595159514468	0.24	7.56
2N IP Uni flush box for in-wall installation, 1 pc	\$ 28.00	8595159514529	0.42	6.46
	\$ 15.00	8595159514215	0.02	0.39
	\$ 12.00	8595159514222	0.02	0.39
	\$ 40.00	8595159514239	0.40	1.38
	\$ 40.00	8595159514246	0.40	1.38
	\$ 42.00	8595159514253	0.37	1.38
	\$ 42.00	8595159514260	0.37	1.38
	\$ 44.00	8595159514277	0.37	1.38

	\$ 44.00	8595159514284	0.37	1.38
2N IP Vario microphone with cable, 5 pcs	\$ 15.00	8595159514178	0.02	1.06
2N IP Vario wago terminal for ethernet and lock connection, 5 pcs	\$ 20.00		0.07	0.39
2N IP Vario keypad, 1 pc	\$ 20.00	8595159514192	0.07	0.39
2N IP Vario speaker with holder and sealing, 5 pcs	\$ 25.00	8595159514161	0.15	1.06
2N IP Vario front metal cover with 6 button and display cut-out, 1 pc	\$ 44.00	8595159514291	0.37	1.38
2N IP Vario front metal cover for 8 button extender, 1 pc	\$ 44.00	8595159514307	0.33	4.33
2N IP Vario front metal cover for 16 button extender, 1 pc	\$ 44.00	8595159514314	0.37	1.38
2N IP Vario backbox, black plastic chassis, 5 pcs	\$ 25.00		1.63	12.40
2N IP Vario plastic front cover for 1 button, 1 pc	\$ 30.00	8595159514338	0.29	4.33
2N IP Vario plastic front cover for 1 button and keypad, 1 pc	\$ 75.00	8595159514345	0.37	1.38
2N IP Vario front plastic cover for 3 buttons, 1 pc	\$ 30.00	8595159514352	0.37	1.38
2N IP Vario front plastic cover for 3 buttons and keypad	\$ 75.00	8595159514369	0.37	1.38
2N IP Vario front plastic panel for 6 buttons, 1 pc	\$ 45.00	8595159514376	0.37	1.38
2N IP Vario plastic front cover with 6 buttons and keypad	\$ 90.00	8595159514383	0.37	1.38
2N IP Vario plastic camera support, 5 pcs	\$ 8.00	8595159514390	0.02	0.39
2N IP Vario plastic camera holder, 5 pcs	\$ 8.00	8595159514406	0.02	2.76
2N IP Vario camera cover, 5 pcs	\$ 10.00	8595159514413	0.02	2.76
2N IP Vario cover for w/o camera version, 5 pcs	\$ 10.00	8595159514420	0.02	0.39

2N IP Verso - Infopanel	\$ 114.00	8595159503899	0.44	5.00
2N IP Verso - Keypad	\$ 280.00	8595159504292	0.79	5.20
2N IP Verso - Keypad, black	\$ 280.00	8595159509532	0.95	5.20
2N IP Verso - 2 inputs and 2 output relays. This module is installed beneath other modules.	\$ 69.00	8595159504339	0.11	1.26
2N IP Verso - 5 buttons	\$ 136.00	8595159504346	0.51	5.20
2N IP Verso - Wiegand. This module is installed beneath other modules.	\$ 103.00	8595159504360	0.11	1.26
2N IP Verso - Tamper switch. This module is installed beneath other modules.	\$ 47.00	8595159504377	0.04	5.20
2N IP Verso - Blind panel	\$ 26.00	8595159504612	0.26	5.20
2N IP Verso - Induction loop	\$ 256.00	8595159507699	0.24	5.31
2N IP Verso - Bluetooth	\$ 352.00	8595159508825	0.44	5.20
2N IP Verso - Extension cable 1m	\$ 22.00	8595159504735	0.09	0.47
2N IP Verso - Extension cable 3m	\$ 23.00	8595159508580	0.15	9.33
2N IP Verso - Blind button. Covers one button, on the main unit or 5 button module.	\$ 25.00	8595159504957	0.04	0.28
2N IP Verso - Main unit without camera	\$ 684.00	8595159503813	0.99	1.38
2N IP Verso - Main unit without camera, black	\$ 684.00	8595159509556	0.99	1.38
2N IP Verso - Main unit with camera	\$ 1,213.00	8595159503820	0.99	1.22
2N IP Verso - Main unit with camera, black	\$ 1,213.00	8595159509563	1.04	1.22

2N IP VERSO 2.0 Main unit with camera, Nickel The main intercom unit has a Full HD camera and one button. You can connect up to 30 modules to it, and it's designed with flexibility in mind! Mount it on the wall, flush with the wall, or even on glass - just choose the correct mounting accessory.	\$ 1,490.00	8595159517544	1.10	1.18
2N IP VERSO 2.0 Main unit with camera, Black The main intercom unit has a Full HD camera and one button. You can connect up to 30 modules to it, and it's designed with flexibility in mind! Mount it on the wall, flush with the wall, or even on glass - just choose the correct mounting accessory.	\$ 1,490.00	8595159517551	1.10	1.18
2N IP Verso - Touch display	\$ 899.00	8595159504353	0.62	5.20
2N IP Verso - Touch keypad	\$ 235.00	8595159511559	0.79	5.20
2N IP Verso - Fingerprint	\$ 604.00	8595159508443	0.49	5.20
2N IP Verso - Extension cable 5m	\$ 30.00	8595159511726	0.31	6.69
2N IP Verso - Blind button. Covers one button, on the main unit or 5 button module. Black	\$ 25.00	8595159513300	0.13	2.99
2N IP Verso – Bluetooth & RFID reader (125kHz, secured 13.56MHz UID+PACS ID, NFC), support of HID iClass secured.	\$ 759.00	8595159513386	0.79	5.00
2N IP Verso – Touch keypad & RFID reader (125kHz, secured 13.56MHz UID+PACS ID, NFC), support of HID iClass secured.	\$ 623.00	8595159513379	0.79	5.00
LTE intercom - no wired data connection, connects to the network via LTE. Requires data LTE SIM card (MicroSIM size) and external power supply such as 01435-001. The internal antenna occupies position of one module, if you intend to use additional modules with the main unit, use the external antenna 01943-001.	\$ 1,290.00	8595159511948	0.99	10.00
LTE intercom - no wired data connection, connects to the network via LTE. Requires data LTE SIM card (MicroSIM size) and external power supply such as 01435-001. The internal antenna occupies position of one module, if you intend to use additional modules with the main unit, use the external antenna 01943-001.	\$ 1,290.00	8595159511955	0.99	10.00

Accessories for 2N LTE Verso for places with poor LTE coverage.	\$ 29.00		8595159511962	0.09	0.39
2N IP Verso Secure Door set - contains I/O module (01257-001), tamper switch (01260-001) and Security Relay (01386-001)	\$ 178.00	-	8595159515632	0.49	2.76
2N IP Verso and LTE Verso 2 module wedge backplate, 25°, helps to cover blind spots of the camera	\$ 41.00	ľ	8595159515663	0.40	2.01
Plastic blind module cover for IP Verso, 5 pcs	\$ 52.00	ſ	8595159513942	0.40	1.77
2N IP Verso and Solo – Reflector with 2N logo black, 5 pcs	\$ 76.00	ľ	8595159513935	0.10	0.39
25° gradient mounting backplate	\$ 32.00	ſ	8595159515656	0.31	4.69
Speaker cover, black, 5 pcs	\$ 85.00	Ī	8595159513898	0.40	5.00
Front plastic cover of Verso RFID reader, 5pcs	\$ 70.00		8595159514666	0.20	1.10
Metal clamps for connection of Verso modules backboxes together, 20pcs	\$ 47.00	ľ	8595159514024	0.20	4.29
Plastic bluetooth reader cover	\$ 71.00	Ī	8595159514673	0.21	1.30
2N IP Verso/Solo - green 2 PIN terminal for input/output, 10 pcs	\$ 18.00	Ī	8595159516578	0.11	0.39
2N IP Verso/Solo - green 3 PIN terminal for relay and 12V input, 10 pcs	\$ 20.00	ſ	8595159516585	0.11	0.39
2N IP Verso - RFID 125kHz, second generation with better reading distance/time.	\$ 189.00	Ī	8595159516547	0.40	5.20
2N IP Verso - RFID 13.56MHz NFC, second generation with better reading distance/time, reads PACS ID	\$ 312.00	Ī	8595159516219	0.40	5.20
A debug module for 2N LTE Verso that is compatible with all sold LTE Versos. It includes a RJ-45 port that can be used for local access to the intercom for troubleshooting in case of mobile network issues.	\$ 63.00		8595159516943	0.11	1.69
OSDP module for integration into 3rd party access control system. OSDP module is compatible with IP Verso, IP Style and Access Unit 2.0.	\$ 115.00		8595159517476	0.11	4.61
2N IP VERSO READER , Keyboard, BLE, RFID 125kHz, 13,56Mhz, NFC, secured, PICard	\$ 909.00	Ī	8595159521480	0.40	5.31
2N IP VERSO READER, Keyboard, BLE, RFID 125kHz, 13,56Mhz, NFC, PICard	\$ 740.00	ľ	8595159521473	0.40	5.31

2N IP VERSO READER, BLE, RFID 125kHz, 13,56Mhz, secured, PICard	\$ 759.00	8595159515960	0.40	5.31
2N IP VERSO READER, BLE, RFID 125kHz, 13,56Mhz, NFC, PICard	\$ 573.00	8595159515946	0.40	1.18
2N IP VERSO READER, Keyboard, RFID 125kHz, 13,56Mhz,NFC, PICard	\$ 500.00	8595159515939	0.40	1.18
IP VERSO READER, Keyboard, RFID 125kHz, 13,56Mhz, NFC, PICard	\$ 623.00	8595159515953	0.40	5.31
2N IP Verso - 1 module flush frame	\$ 86.00	8595159503837	0.88	6.65
2N IP Verso - 1 module flush frame, black	\$ 86.00	8595159509419	0.88	6.65
2N IP Verso - 2 modules flush frame	\$ 97.00	8595159503844	1.32	0.91
2N IP Verso - 2 modules flush frame, black	\$ 97.00	8595159509433	1.32	0.91
2N IP Verso - 3 modules flush frame	\$ 97.00	8595159503851	1.52	14.88
2N IP Verso - 3 modules flush frame, black	\$ 97.00	8595159509457	1.26	14.88
2N IP Verso - 1 module flush box	\$ 29.00	8595159504667	0.44	1.93
2N IP Verso - 2 modules flush box	\$ 36.00	8595159504674	0.73	1.97
2N IP Verso - 3 modules flush box	\$ 37.00	8595159504681	0.95	14.96
2N IP Verso - 1 module surface frame	\$ 63.00	8595159503868	0.66	5.20
2N IP Verso - 1 module surface frame, black	\$ 63.00	8595159509471	0.55	5.20
2N IP Verso - 2 modules surface frame	\$ 80.00	8595159503875	1.39	1.18
2N IP Verso - 2 modules surface frame, black	\$ 80.00	8595159509495	1.39	1.18
2N IP Verso - 3 modules surface frame	\$ 115.00	8595159503882	1.74	1.26
2N IP Verso - 3 modules surface frame, black	\$ 130.00	8595159509518	1.61	1.26

2N IP Verso - 1 module backplate for surface installation	\$ 58.00	8595159507132	0.46	1.18
2N IP Verso - 2 modules backplate for surface installation	\$ 64.00	8595159507149	0.77	1.38
2N IP Verso - 3 modules backplate for surface installation	\$ 74.00	8595159507156	1.06	13.82
2N IP Verso - 2x2 modules backplate for surface installation	\$ 94.00	8595159507163	1.63	1.02
2N IP Verso - 3x2 modules backplate for surface installation	\$ 130.00	8595159507170	2.18	1.02
2N IP Verso - 2x3 modules backplate for surface installation	\$ 125.00	8595159507187	2.14	13.98
2N IP Verso - 3x3 modules backplate for surface installation	\$ 159.00	8595159507194	3.00	1.02
2N IP Verso - 1 module backplate for surface installation on a 2-gang backbox	\$ 50.00	8595159512983	3.97	5.98
2N IP Verso - 2 modules backplate for surface installation on a 2-gang backbox	\$ 58.00	8595159512990	8.82	12.01
My2N Mobile Video 12 month subscription voucher for ONE apartment (up to 4 user devices assigned per apartment). A single voucher is generated for multiple apartments per My2N site on the same order, however vouchers for multiple My2N Sites need to be ordered separately.	\$ 40.00			
My2N Mobile Video 12 month subscription voucher for one user device. A single voucher is generated for multiple user devices per My2N site on the same order, however vouchers for multiple My2N Sites need to be ordered separately.	\$ 27.00			
2N Access Commander – Advanced licence. Allows management of up to 30 devices and 300 users with access to Advanced features.	\$ 720.00			
2N Access Commander – Pro licence. Allows management of up to 100 devices and 1000 users with acces to Pro features	\$ 1,560.00			
2N Access Commander – Unlimited licence. Allows management of unlimited devices and users* and access to Pro features. (*Unlimited within limitations of software interface: Approx 2000 devices)	\$ 3,600.00			

2N Access Commander – Upgrade Advanced to	\$ 1,020.00			
Pro licence. Pro license allows management of				
up to 100 devices and 1000 users with access				
to Pro features.				
2N Access Commander – Upgrade Pro to	\$ 2,220.00			
Unlimited licence. Unlimited license allows				
management of unlimited devices and users*				
and access to Pro features. (*Unlimited within				
limitations of software interface: Approx 2000				
devices)				
2N Access Commander – Add-on Attendance	\$ 600.00			
Monitoring license. This activates attendance				
monitoring for all users included in the present				
license type. It should be used only with				
Access Commander 2.4 or higher.				
PICard Commander is 2N's unique	\$ 900.00			
cryptographic software, providing Protected				
Identity Credentials, built on the popular Mifare				
DESFire technology. The license for this				
software is generated using the SN of a				
compatible USB reader (non-secured - 01400-				
001, secured - 01527-001). The software can				
then only be used with the licensed USB				
reader.				
The line of the total free between ON	<u>* 1 100 00</u>			
The license activates the interface between 2N	\$ 1,190.00			
IP Intercoms and LeneIS2 OnGuard. 2N PLUGIN				
FOR OnGuard enables the communication				
between 2N IP Intercoms and OnGuard, an				
access control system from LenelS2. The				
integration allows the OnGuard users to				
monitor and manage intercoms through one				
comprehensive security platform. Operators				
can place or terminate a call between their				
desktop station and selected remote intercom				
with a single click in the OnGuard interface. It is also possible to monitor 2N devices and use				
•				
intercom events to trigger actions in OnGuard.				

Wiegand	•			0.00	,
External 125 kHz EMarine RFID card reader, Wiegand External 13.56MHz Mifare RFID card reader,	\$	108.00	8595159511832 8595159511849	0.57	4.76 2.36
2N Magnetic door contact	\$	23.00		0.04	2.56
2N Wiegand Isolator	\$	171.00	8595159501413	0.26	0.98
2N Security Relay	\$	165.00	8595159500935	0.07	1.77
Mifare RFID smart key fob 13.56MHz	\$	6.00	8595159511481	0.01	1.18
Mifare RFID smart card 13.56MHz	\$	6.00	8595159511474	0.02	3.35
2N IP Intercom and SIP AudioLicense - Informacast License	\$	97.00		0.00	0.00
License key for the 2N® INDOOR TOUCH 2.0 enabling the 2N® MEETING ROOM app feature.	\$	380.00			
Symmetry, an access control system from AMAG. The integration allows the Symmetry users to monitor and manage intercoms through one comprehensive security platform. Operators can place or terminate a call between their desktop station and selected remote intercom with a single click in the Symmetry interface.					
The license activates the interface between 2N IP Intercoms and AMAG Symmetry™ Access Control. 2N PLUGIN FOR Symmetry enables the communication between 2N IP Intercoms and	\$	1,190.00			
are executed through the graphical maps or in the device tree in C•CURE 9000. The integration provides continuous 24/7 monitoring of the 2N IP intercoms and event reporting in C•CURE 9000. Intercom events can be further linked with actions in C•CURE 9000					
between 2N IP Intercoms and C•CURE 9000, an access control system from Tyco. The CCure users can monitor and control the 2N IP intercoms through the C•CURE 9000 user interface. Call commands between intercoms					
The license activates the interface between 2N IP Intercoms and C•CURE 9000. 2N PLUGIN FOR CCure enables the communication	\$	1,190.00			

2N External induction loop for IP Intercom	\$ 193.00	8595159506722	0.71	7.87
2N Power supply for the induction loop	\$ 46.00	8595159506982	0.18	1.77
PoE injector PSA16U-480(POE), external PoE; 1port 15.4W ACDC - without cable	\$ 60.00	8595159511887	0.93	2.76
Proximity Card Emarine 125kHz	\$ 6.00	8595159594101	0.02	0.04
Proximity Key Fob Emarine 125kHz	\$ 6.00	8595159594125	0.01	0.20
Web IP Relay - 1 output, 1 input	\$ 295.00	8595159511504	0.44	1.57
	\$ 375.00	8595159511511	0.35	1.57
External RFID Reader 125kHz EMarine (USB interface)	\$ 71.00	8595159598475	0.35	4.53
External RFID Reader 13.56MHz + 125kHz (USB interface)	\$ 365.00	8595159511870	0.29	1.65
External fingerprint reader (USB interface)	\$ 273.00	8595159505909	0.37	0.12
External Bluetooth reader (USB interface)	\$ 31.00	8595159512976	0.00	0.04
PoE injector PSA16U-480(POE), external PoE; 1port 15.4W ACDC - with US cable	\$ 71.00	8595159501987	1.06	6.46
2N 2Wire - set of 2 adaptors and power source for the US plug	\$ 380.00	8595159504834	1.46	6.46
2N RFID secured reader 13.56MHz + 125kHz (USB interface), This USB reader reads the card serial number (CSN) and also secured PACs ID from HID smart cards	\$ 469.00	8595159513553	0.29	10.98
2N IP Verso and Solo speaker cover - plastic cover of speaker on the main unit - 5pcs	\$ 68.00	8595159513881	0.35	3.31
2N IP Verso and Solo camera window- camera version -plastic cover on the main unit - 5pcs	\$ 45.00	8595159513904	0.18	33.07
2N IP Verso camera window- non-camera version -plastic cover on the main unit - 5pcs	\$ 50.00	8595159513911	0.18	3.31
2N IP Verso and Solo Reflector with 2N logo - plastic part under the camera - 5pcs	\$ 62.00	8595159513928	0.40	3.31
2N IP Verso and Solo button nametag - plastic button with nametag - 10pcs	\$ 90.00	8595159513959	0.29	33.07

2N IP Verso Flush and surface bottom fixture - metal fixture to hold the frame - 5pcs	\$ 45.00	8595159513966	0.13	3.94
2N IP Solo Flush and surface bottom fixture - metal fixture to hold the frame - 5pcs	\$ 40.00	8595159513973	0.15	3.94
2N IP Verso and Solo Flush mount upper fixtrue - metal part to hold the frame - 5pcs	\$ 40.00	8595159513980	0.15	3.94
2N IP Verso and Solo Surface mount upper fixture - metal part to hold the frame - 5pcs	\$ 35.00	8595159513997	0.33	3.94
2N IP Verso bus short, 80mm - vbus cabel to connect the modules - 10pcs	\$ 45.00	8595159514000	0.04	3.94
2N IP Verso bus short, 220mm - vbus cabel to connect the modules - 10pcs	\$ 55.00	8595159514017	0.09	2.76
2N IP Verso microphone set - microphone with cable to 3 module extension - 10pcs	\$ 70.00	8595159514031	0.07	3.94
2N IP Force and Safety Speaker 1W, 16 Ohm, 77mm - 1pc	\$ 30.00	8595159513737	0.15	3.27
2N IP Force and Safety Gasket for microphone - 5pcs	\$ 16.00	8595159513751	0.00	3.94
2N IP Force and Safety microphone with cable - 10pcs	\$ 152.00	8595159513768	0.02	3.94
2N IP Force and analog Force Button namateg to plastic part - 5pcs	\$ 25.00	8595159513782	0.00	3.94
2N IP Force and analog Force Plastic clear button on the PCB board - 10pcs	\$ 22.00	8595159513874	0.57	11.42
2N IP Force and analog Force 1 button board - 1pc	\$ 30.00	8595159514055	0.15	3.27
2N IP Force and analog Force 1 button board, pictograms - 1pc	\$ 30.00	8595159514062	0.15	1.06
2N IP Force and analog Force 2 buttons board - 1pc	\$ 35.00	8595159514079	0.15	3.27
2N IP Force and analog Force 4 buttons board - 1pc	\$ 40.00	8595159514086	0.15	3.27
2N IP Force and Safety Speaker 10W, 4 Ohm, 76mm - 4pcs	\$ 65.00	8595159513744	2.34	6.46
U-shaped black front frame for 2N IP Base	\$ 60.00	8595159514536	0.36	1.30
NVT phybridge 2 wire to ethernet convertor. The package contains 8 port switch unit and 2 adaptors. Other adaptors can be purchased as SKU 02319-001 (pack with 6 adaptors).	\$ 1,077.00	8595159517599	2.60	2.80

Sixpack of NVT adaptors compatible with NVT switch 02318-001. Solution for 2wire to ethernet conversion.	\$ 828.00	8595159517605	0.40	2.99
PoE+ (802.3at) injector	\$ 80.00	8595159518930	1.10	2.40
2N Fobs, Mifare Desfire EV3, capacity 4K, package 10pcs, PICard	\$ 124.00	8595159522975	0.40	0.79
2N Cards, Mifare Desfire EV3, capacity 4K, package 10pcs, PICard	\$ 78.00	8595159522968	0.04	0.79
7" touchscreen answering unit with a wide viewing angle. The tempered glass surface and award-winning design are the perfect choices for any luxury residential project. The 2N Indoor View requires the 2N Indoor Flush Box (01700-001) or the 2N Indoor Desk Stand (02039-001) for an installation.	\$ 656.00	8595159515793	1.19	9.61
7" touchscreen answering unit with a wide viewing angle. The tempered glass surface and award-winning design are the perfect choices for any luxury residential project. The 2N Indoor View requires the 2N Indoor Flush Box (01700-001) or the 2N Indoor Desk Stand (02039-001) for an installation.	\$ 656.00	8595159515809	1.19	9.61
Buttons extender for the 2N IP Phone D7A (02660-001).	\$ 289.00	6938818301672	1.32	8.27
The 2N® Indoor Compact is an indoor answering unit designed especially for the residential market. Installation by connecting a single UTP cable and configuration via a web interface guarantees that integrators can put the unit into operation quickly and easily. Users will be impressed by the minimalist design, tempered glass surface, 4.3" colour display, sound in HD quality and intuitive controls. A simply elegant solution for video communication.	\$ 488.00	8595159513478	1.10	9.69
The 2N® Indoor Compact is an indoor answering unit designed especially for the residential market. Installation by connecting a single UTP cable and configuration via a web interface guarantees that integrators can put the unit into operation quickly and easily. Users will be impressed by the minimalist design, tempered glass surface, 4.3" colour display, sound in HD quality and intuitive controls. A simply elegant solution for video communication.	\$ 488.00	8595159513485	1.10	9.69

2N Indoor Talk PoE – Black Elegant answering unit with HD sound. The design of the 2N® Indoor Talk answering unit will suit every flat or home. The aesthetic appearance of this product was achieved by using a glass surface and striking backlighting of its icons. However, we placed particular emphasis on selecting the highest-quality audio components in order to achieve a high- quality sound. This means you can talk to visitors outside as if they were standing right next to you. Invite them in and press the icon to open the door from the comfort of your home. The 2N Indoor Talk Black requires the 2N Indoor Flush Box (01700-001) for installation.	\$ 354.00	8595159513454	1.30	2.40
2N Indoor Talk PoE – White Elegant answering unit with HD sound. The design of the 2N® Indoor Talk answering unit will suit every flat or home. The aesthetic appearance of this product was achieved by using a glass surface and striking backlighting of its icons. However, we placed particular emphasis on selecting the highest-quality audio components in order to achieve a high- quality sound. This means you can talk to visitors outside as if they were standing right next to you. Invite them in and press the icon to open the door from the comfort of your home. The 2N Indoor Talk White requires the 2N Indoor Flush Box (01700-001) for installation.	\$ 354.00	8595159513461	1.30	2.40
2N Indoor answering unit flush installation box, required for the 2N® Indoor View (02087-001 or 02088-001), 2N® Indoor Compact (01935-001 or 01936-001) and 2N® Indoor Talk (01698-001 or 01699-001).	\$ 28.00	8595159513560	0.40	2.80
2N Indoor answering unit surface installation box, required for the 2N® Indoor View (02087- 001 or 02088-001), 2N® Indoor Compact (01935- 001 or 01936-001) and 2N® Indoor Talk (01698- 001 or 01699-001).	\$ 28.00	8595159517483	0.71	3.90
2N Indoor desk stand is intended for the 2N® Indoor Compact (01935-001 or 01936-001) or the 2N® Indoor Talk (01698-001 or 01699-001) answering units. There is no need to use the flush box (01700- 001).	\$ 55.00	8595159516165	0.40	5.71
4" video IP indoor station, surface mounted	\$ 359.00	8595159522456	0.71	1.81

Optional desk stand for the 2N Clip 02892-001	\$ 30.00	8595159522951	0.20	2.80
Optional accessory for the 2N Clip 02892-001 that allows its surface installation over the flush mounted single-gang electrical box	\$ 19.00	8595159523224	0.31	1.18
7" touchscreen IP phone, Android OS based.	\$ 709.00	6938818307667	3.99	5.12
USB camera module for the 2N IP Phone D7A (02660-001). It enables bi-directional video calls with the 2N IP Style intercom (02407-001 or 02521-001).	\$ 119.00	6938818301795	0.20	1.61
Wall mount bracket for the 2N IP Phone D7A (02660-001).	\$ 14.00	8595159521176	0.20	5.91
Grandstream GXV 3370 Multimedia IP phone with 7" touch screen, Android, Wifi, PoE	\$ 614.00	6947273702528	4.06	14.02
Grandstream GXV 3350 Multimedia IP phone with 5" digital color LCD (1280x720), Android, Wifi, PoE, tiltable camera Peripherals: HDMI- out, USB, headset jack, EHS	\$ 447.00	6947273702917	3.79	9.61
Grandstream GXV 3240 Multimedia IP phone with 4.3" digital color LCD, Android, Wifi, PoE	\$ 385.00	6947273701552	8.27	9.41
2N® Indoor Touch 2.0 - PoE Black	\$ 831.00	8595159513034	2.65	12.60
2N® Indoor Touch 2.0 - PoE White	\$ 831.00	8595159513041	2.65	12.60
2N® Indoor Touch 2.0 - PoE Wi-Fi Black	\$ 998.00	8595159513058	2.65	12.60
2N® Indoor Touch 2.0 - PoE Wi-Fi White	\$ 998.00	8595159513065	2.65	12.60
2N Indoor Touch - Desk stand black	\$ 120.00	8595159511450	3.55	10.83
2N Indoor Touch - Desk stand white	\$ 120.00	8595159511467	3.70	10.83
2N Indoor Touch External power supply, 12V 2A DC, flush mounted	\$ 109.00	8595159505817	0.82	1.57

2N SIP Mic allows paging to several zones with a simple push of a button. It is ideal for live or pre-recorded announcements. It has a built-in audio-management server for configuration, which means less equipment as well as flexible, easy and cost-efficient installation. The network microphone console has 12 buttons that can be configured with actions of your choice. 2N SIP Mic's 12 buttons give you a smart paging solution for up to 12 zones, and if your system grows you can easily connect the microphone console to a PBX system thanks to support for SIP. The microphone is based on open standards and connects to standard networks using PoE.	\$ 1,133.00	8595159511429	3.44	6.89
2N SIP Speaker - Horn (outdoor SIP based active hornspeaker)	\$ 588.00	8595159509181	11.46	9.84
2N SIP Speaker - Loudspeaker Set,wall mounted (SIP based active speaker)	\$ 522.00	8595159508177	6.88	9.65
2N SIP Speaker - Loudspeaker Set, wall mounted (SIP based active speaker)	\$ 522.00	8595159508184	13.12	9.65
2N IP Audio Power Supply - US plug	\$ 78.00	8595159503301	0.88	1.69
AXIS TA1601 Mounting Plate is compatible with AXIS TQ1808-VE Surveillance Cabinet and AXIS A1210-B Network Door Controller to build 4 door controller kit - AXIS A1214 Network Door Controller Kit	\$ 59.00	7331021081666	3.09	1.06
AXIS TA1601 Mounting Plate is included in AXIS A1214 Network Door Controller Kit.				
 AXIS TA1801 Top Cover is compatible with AXIS A1210-B Network Door Controller, ideal for installations that need a full enclosure for extra protection or in plenum spaces. AXIS TA1801 Top Cover is included in AXIS A1210 Network Door Controller. 	\$ 39.00	7331021081673	0.77	5.12
AXIS TA1901 DIN Rail Clip is for standard 35mm DIN rail, and compatible with Axis network door controller and network I/O relay modules.	\$ 49.00	7331021083011	0.61	3.94

Change compositions for Avia concertant	¢	00.00	 7004004004050	0.55	4.40
Spare connectors for Axis access control products including network door controllers, readers, and network I/O relay modules. AXIS TA1902 Access Control Connector Kit includes 20pcs of 2pos, 20pcs of 4pos, 10pcs of 6pos, 10pcs of 8pos terminal block	\$	99.00	7331021081659	0.55	4.13
connectors for Axis network door controller and network I/O relay modules, and 10pcs of 4pos terminal block connector for AXIS A4010- E Reader and AXIS A4120-E Reader with Keypad.					
Contactless MIFARE® DESFire® EV2 2K smart card that uses advanced radio frequency identification (RFID) technology to deliver secure and reliable physical access to premises. The card is made of 100% recycled PET-G. One bulk pack comes with 100 cards.	\$	649.00	7331021075764	1.15	3.70
AXIS TA4201 Weathershield, accessory to AXIS A4120-E Reader with Keypad, to protect reader from extreme conditions, such as accumulation of encrusting snow or ice. Glass-fiber reinforced, and UV resistant plastic offers robustness for use in harsh outdoor environment, and easy on the environment with PVC/BCR/CFR free.	\$	29.00	7331021079083	0.44	2.44
AXIS TA4401 Braille Label, easy to install accessory to AXIS A4120-E Reader with Keypad, for assisting with keypad entry to sight limited. With the optimized visually impaired reader mode to avoid inadvertent PIN input. UV resistant material offers robustness for use in harsh outdoor environment. And easy on the environment with PVC/BCR/CFR free. One bulk pack comes with 10 units.	\$	169.00	7331021079090	0.11	3.54
Contactless MIFARE® DESFire® EV2 2K key fob that uses advanced radio frequency identification (RFID) technology to deliver secure and reliable physical access to premises. The key fob is made of impact-resistant matt polycarbonate and ultrasonically welded in a stainless steel frame, making it stable and durable, with IP67 and IK09 rating – perfect for carrying on a keyring. One bulk pack comes with 50 key fobs.	\$	649.00	7331021075771	0.79	3.15

Recessed mount offering neat and easy installation of the AXIS A8207-VE Network Video Door Station. Multiple mounting and wiring options along with a robust construction makes it suitable for most situations and wall	\$ 129.00	7331021067455	2.84	14.37
types. Cable protection attachment bracket for AXIS A8207-VE Network Video Door Station Compatible with 3/4" Conduits	\$ 89.00	7331021067462	0.81	11.42
AXIS TA8501 Physical Tampering Switch is an accessory to be used when the AXIS A8105-E Network Video Door Station is combined with the AXIS A9801 Security Relay. This accessory is a fix to the known issue of the integrated accelerometer showing false tampering alerts.	\$ 15.00	7331021069855	0.11	6.02
Nice and easy recessed mount of AXIS A8105-E Network video door station suitable for most wall types.	\$ 79.00	7331021053243	0.95	6.50
AXIS A9801 Security relay box offer an easy and cost efficient way to improve security for doors controlled by an Axis network video door station. The product bridges the connection between door station and door lock and is placed on the secure side of the door. If an intruder attempt to tamper with the door station to access the door lock wires, AXIS A9801 Security relay will cut the connection and ensure that the door remains securely locked.	\$ 129.00	7331021049352	0.22	4.53
Stainless steel adapter plate for mounting AXIS A8004-VE Network Video Door Station in Code Blue emergency stanchions and call boxes, combining intelligent video surveillance with emergency communication in a single device. The adapter plate is compatible with all Code Blue help points, suitable for new deployments and retrofitting existing installations.	\$ 119.00	7331021054981	1.68	8.66
Stainless steel face plate replacement sold as a spare part for AXIS I8016-LVE Network Video Intercom. It enables easy on-site replacement in case the original plate has been damaged or vandalized.	\$ 199.00	7331021071902	0.71	6.30
Cable protection attachment bracket for AXIS I8016-LVE Network Video Intercom, compatible with 3/4" Conduits.	\$ 34.00	7331021075146	0.44	4.13
Wall mount to be used together with AXIS I8016 LVE Network Video Intercom. Highly robust with IK10 and IP69 rating.	\$ 159.00	7331021071865	1.50	5.51
Recessed mount offering neat installation of AXIS I8016-LVE Network Video Intercom. Multiple mounting and wiring options along with a robust construction makes it suitable for most situations and wall types.	\$ 49.00	7331021071872	0.66	5.51

Stainless steel adapter plate for mounting AXIS I8016-LVE Network Video Intercom in Code Blue® and Talkaphone® emergency stations and help points. Suitable for new deployments and retrofitting existing installations, it combines intelligent video surveillance with emergency communication—all in a single device.	\$ 149.00	7331021078475	2.27	8.46
AXIS TI8904 Induction loop enhances the current features set of AXIS I8016-LVE Network Video Intercom to transmit audio from the intercom to a person's hearing aid. This accessory is hidden in the AXIS TI8202 Recessed Mount or AXIS TI8602 Wall Mount and only visible by a t-coil sign sticker on the face plate of AXIS I8016-LVE. By eliminating the need for an external power supply or additional configuration on the intercom, a quick and reliable installation can be ensured	\$ 129.00	7331021081482	0.19	4.13
AXIS TA1802 Top Cover is compatible with AXIS A1610-B Network Door Controller, ideal for installations that need a full enclosure for extra protection or in plenum spaces. AXIS TA1802 Top Cover is included in AXIS A1610 Network Door Controller.	\$ 39.00	7331021081956	1.23	8.66
Nice and easy recessed mount of AXIS I8116-E Network Video Intercom suitable for most wall types.	\$ 89.00	7331021079410	0.93	6.30
Nice and easy recessed mount of AXIS I8116-E Network Video Intercom suitable for most wall types.	\$ 89.00	7331021079427	0.93	6.30
With door controllers from Axis, you install one smart, independent device by each door to create a scalable access control system. The open platform allows you to mix and match best-of-breed software and hardware, and enables easy integration with other systems such as video surveillance, intrusion detection, and time and attendance. AXIS A1601 Network Door Controller is ideal for advanced access management in mid-sized and large, multi-site installations using third-party software (no embedded Entry Manager software). It has a powerful processor, expanded storage and memory, relays, and I/O ports. AXIS A1601 is powered by PoE+ and can also power connected equipment.	\$ 759.00	7331021064287	2.99	9.45

A compact edge-based one door controller, suitable for plenum spaces, all powered by one	\$ 459.00	7331021076488	1.87	5.00
PoE cable. It is fully integrated within Axis end- to-end solutions, this scalable product is optimized for both small and large installations and supports flexible authentication using different types of credentials. Furthermore, with built-in cybersecurity features, it prevents unauthorized access and safeguards your system.				
The barebone version of A1210, a compact edge-based one door controller, suitable for installation anywhere. It's possible to stack units, ideal for installation in small spaces such as existing or newly installed cabinets. Fully integrated within Axis end-to-end solutions, it's optimized for both small and large installations and supports flexible authentication using different types of credentials.	\$ 429.00	7331021076495	1.23	6.85
This all-in-one, out-of-the-box-ready kit can control up to four doors. It includes four AXIS A1210-B units enclosed in AXIS TQ1808-VE, a robust, vandal-resistant IK10- and NEMA 4x- rated cabinet. Fully integrated within Axis end- to-end solutions, it offers fast and easy installation	\$ 1,999.00	7331021081635	20.06	11.22
This advanced and robust door controller includes everything needed to control two doors–all powered by one PoE cable, featuring four reader connections as well as two Form C relays to power the onboard lock. You can store up to 250k credentials and 250k event logs on the device itself. With built-in cybersecurity features, this smart door controller can internally handle all tasks related to door access—even if the network is down.	\$ 759.00	7331021081154	2.91	10.24
Barebone version of A1610 Network Door Controller. Sold without a top cover, it offers easy installation with Axis or 3rd party cabinet. This advanced door controller includes everything needed to control two doors–all powered by one PoE cable, featuring four reader connections as well as two Form C relays to power the onboard lock. You can store up to 250k credentials and 250k event logs on the device itself. With built-in cybersecurity features, this smart door controller can internally handle all tasks related to door access—even if the network is down.	\$ 729.00	7331021081161	2.07	10.24

AXIS A1001 Network Door Controller is an open, non-proprietary platform for access management. The controller is installed by each door and data is automatically synchronized between the controllers in the system. The controller supports most Wiegand and RS 485 OSDP readers. The unit comes with a built-in software for basic access management for up to 33 controllers as well as an open API to meet the requirements for larger and more advanced installations. The plenum rated controller is designed for wall or ceiling mount indoors and supports Power over Ethernet IEEE 802.3af Class 3. It is fitted with 14 configurable input/outputs and 5 power outputs for door accessories including fault/tamper detection and support for Uninterruptible Power Supply (UPS).	649.00	7331021008021	1.67	8.86
AXIS A1001 Network Door Controller is an open, non-proprietary platform for access management. The controller is installed by each door and data is automatically synchronized between the controllers in the system. The controller supports most Wiegand and RS 485 OSDP readers. The unit comes with a built-in software for basic access management for up to 33 controllers as well as an open API to meet the requirements for larger and more advanced installations. The plenum rated controller is designed for wall or ceiling mount indoors and supports Power over Ethernet IEEE 802.3af Class 3. It is fitted with 14 configurable input/outputs and 5 power outputs for door accessories including fault/tamper detection and support for Uninterruptible Power Supply (UPS).	6,490.00	7331021008038	14.55	14.17
Single unit e-license for AXIS Door Controller Extension This AXIS Camera Application Platform (ACAP) based application empowers Axis network door controllers to support additional features or integrations to extend the capability of the door controller. For example, wireless locks integration to support up to additional 16x wireless doors per door controller.	\$ 199.00			

AXIS A9188 Network I/O Relay Module is an intelligent module with 8 configurable I/Os and 8 form C relays and supports supervised inputs. Open API, including VAPIX, for software integration. High level of integration with AXIS A1001 Network Door Controller for elevator control for floor management etc. Supported by AXIS Video Hosting System, AXIS Camera Station and third party partner software. The module provides 12 and 24 V DC output to I/O devices and can extend the functionality of any Axis product where you need additional I/Os or relays. Powered by PoE+ or 12 and 24 V DC input	\$ 599.00	7331021049895	1.65	6.50
AXIS A9161 Network I/O Relay Module has 6 configurable I/Os with supervised inputs and a relay. The module reacts on inputs, such as signals from PIR motion detectors or switches, to trigger actions. Supplying power to I/O devices, it can extend the functionality of Axis products where additional I/Os or relays are needed. Its enclosure makes installation easy and flexible. -6 I/Os and 1 form C relays -12 and 24 V DC output/input or PoE+ -Based on Axis open plattforms, VAPIX and ACAP -Used with AXIS Camera station or third-party software	\$ 299.00	7331021049901	1.50	6.50
AXIS A9188-VE Network I/O Relay Module comes with AXIS T98A15-VE Surveillance Cabinet making it outdoor-ready, vandal- resistant, and UL294-approved. With its 8 configurable I/Os and relays, its open platform enables a high level of integration with AXIS A1001 Network Door Controller and other facility systems. -8 I/Os with supervised inputs and 8 form C relays -UL294-approved with cabinet AXIS T98A15-VE Surveillance Cabinet -12 and 24 V DC output/input or PoE+ -Open API, support for VAPIX, ACAP -Used with AXIS Camera station or third-party software	\$ 899.00	7331021050112	10.32	11.81

AXIS A8207-VE Network Video Door Station combines a fully featured 6MP security camera with high-quality, two-way audio communication and remote entry control. It also has an integrated RFID access control reader. By providing both surveillance, visitor management, and employee accessibility, AXIS A8207-VE increases the efficiency while keeping down the number of devices at the door. Analytics, such as motion or sound- based detection, is supported. Based on open standards and with several hardware interfaces, AXIS A8207-VE easily integrates with other systems and solutions and is prepared for future needs. Interaction is intuitive and accessible, with an inductive loop for hearing aid.	\$ 1,599.00	7331021071070	3.64	11.61
AXIS I8016-LVE Network Video Intercom is a compact and highly robust network intercom for two-way communication, video and remote entry control. with exceptional audio quality, including echo and noise cancellation, and a 5MP camera with invisible IR night vision and 140° FOV, the unit offers reliable 24/7 identification and remote entry control also in the most demanding situations. Based on open IP standards and interfaces such as ONVIF, PoE and SIP, AXIS I8016-LVE Network Video Intercom offers great integration possibilities and is a perfect complement to any video surveillance system.	\$ 1,199.00	7331021070561	2.29	5.91
AXIS I8116-E is a small and powerful network video intercom. It operates as a communication device and full-fledged security camera at the same time, providing 5MP video, audiovisual identification, two-way communication and remote entry control as an intrinsic part of video surveillance. Open standards such as ONVIF and Session Initiation Protocol (SIP) in combination with its small size, give unique opportunities for system design, integration and installation. Wide Dynamic Range (WDR) and efficient noise cancellation ensure uncompromised performance in demanding situations, such as strong backlight or surrounding noise.	\$ 899.00	7331021076884	1.10	4.33

AXIS I8116-E is a small and powerful network	\$ 899.00	7331021076891	1.10	4.33
video intercom. It operates as a communication				
device and full-fledged security camera at the same time, providing 5MP video, audiovisual				
identification, two-way communication and				
remote entry control as an intrinsic part of				
video surveillance. Open standards such as				
ONVIF and Session Initiation Protocol (SIP) in combination with its small size, give unique				
opportunities for system design, integration				
and installation. Wide Dynamic Range (WDR)				
and efficient noise cancellation ensure				
uncompromised performance in demanding				
situations, such as strong backlight or surrounding noise.				
surrounding noise.				
AXIS A4020-E Reader is designed to perfectly match Axis network door controllers and Axis	\$ 219.00	7331021073524	0.40	6.50
credentials.				
Ideal for use in harsh environments both				
indoors and outdoors, it features a mullion-				
mount design to fit perfectly in narrow spaces				
and door frame installations. It supports most				
types of smart RFID card standards with 13.56MHz credential technologies and includes				
out-of-the-box support for Open Supervised				
Device Protocol (OSDP). Packed with built-in				
cybersecurity features, it helps prevent				
unauthorized access and safeguards your				
system. Furthermore, this smart reader supports Secure Communication Protocol				
(SCP) enabling secure communications and				
connections.				
COOL European Community				
COO: European Community				
AXIS A4120-E Reader with Keypad, offers	\$ 359.00	7331021073531	0.77	5.91
secure and seamless entry, designed to				
perfectly match Axis network door controllers and Axis credentials. IP66, IK07 ratings for use				
in harsh environments and				
the intuitive touch keypad offers unlimited				
touches. It supports most types of smart RFID				
card standards with 13.56MHz technologies				
and includes out-of-the-box support for Open Supervised Device Protocol (OSDP) and Secure				
Channel Protocol (SCP).				
COO: European Community				

Single unit e-license for AXIS Barcode Reader	\$	199.00			
Convenient and cost-effective, AXIS Barcode Reader seamlessly turns Axis intercom or camera into a QR code reader for reliable credential or access control management. This IP- and AXIS Camera Application Platform (ACAP)-based application is fully integrated with AXIS Camera Station Secure Entry for					
reliable QR code entry for visitors. Visit www.axis.com for supported products and application download.					
The AXIS 4-in-1 Security Screwdriver Kit is a great tool for installing Axis products. The kit features two double-sided insert bits type that match Axis products using tamper resistant torx and standard philips head. The kit comes with a quick-release, non-slip rubber handle, and a velcro-sealed polyester pouch with belt clip. Insert bits material in chrome vanadium (TR10+PH1) and in stainless steel (TR20+TR30).	\$	39.00	7331021060340	0.49	6.50
Accessory front window assembly in polycarbonate for AXIS Q1785/86-LE, IK10 rated. Not recommended for installation that requires more than 22x optical zoom.	\$	59.00	7331021066472	0.26	7.09
M20 Gasket for cable diameter 3,5mm to 7mm. 10 pcs.	\$	29.00	7331021003712	0.09	4.33
Tool for steel strap tensioning. For use with 21764 and AXIS T91A67	\$	145.00	667026008146	3.09	3.74
IP66 cable gasket for M16 holes (max 17mm). By using the included CONNECTOR GUARD A over the RJ45 connector, you do not need to re- terminate the network cable which gives a much faster and more secure installation. Suitable for cable diameters between 5-8mm. Black color. 10 pieces (bulk pack).	\$	29.00	7331021067691	0.09	3.94
M20 Gasket for cable diameter 6-13mm, 10 pcs.	\$	29.00	7331021003729	0.09	4.33
M20 Gasket for cable 8-17mm, 10 pcs.	\$	29.00	7331021003767	0.11	4.33
10 cable gaskets compatible with Q3819-PVE, Q1951-E, Q1952-E. 10 pcs of 2013186 GASKET CABLE 21,5x4 and 1 pcs of 1327329 TOOL	\$	29.00	7331021075610	0.14	2.76
MOUNTING RJ45 E1.	¢	0.00	7331021003736	0.45	5.04
M20 cable gland, 5 pcs.	\$	9.00	1331021003136	0.15	5.91

This gasket is specially made for flexible and easy installation. By using the included CONNECTOR GUARD A over the RJ45	\$	29.00	7331021045286	0.07	3.94
connector, you do not need to re-terminate the					
network cable wich gives a much faster and					
more secure installation.					
Made for M20 holes and cables from 5 to 15mm					
in outer diameter. 10 pcs.					
M20 gasket for small cables like I/O and audio	\$	29.00	7331021047372	0.08	4.13
cables. 10 pcs					
Tool kit for simplifying adjustment of viewing	\$	29.00	7331021047488	0.13	3.94
direction and focus setting. Compatible with					
AXIS P39xx-R cameras with the standard lens					
and the 2.8 mm accessory lens. Content: Lens					
tool, Allen key and Opening tool. 4 pcs of each.					
M25 Cable gland, 5 pcs.	\$	29.00	7331021003774	0.24	5.91
				-	
M20 cable gland for RJ45. Ease of installation, no need of cutting the cable.	\$	29.00	7331021004894	0.19	5.91
Optional lens for AXIS M3025-VE, 6mm.	\$	49.00	7331021006171	0.12	4.13
Including focus ring.	φ	49.00	7331021000171	0.12	4.15
Accessory lens 6 mm, F1.9 with M12 thread and	\$	79.00	7331021069831	0.13	4.13
built in IR-cut filter for AXIS F1005-E and	φ	79.00	7551021009051	0.15	4.15
FA1105. Tool for removing the standard lens is					
included. 4 Pcs.					
Accessory lens 16 mm, F1.8 with M12 thread	\$	79.00	7331021069848	0.18	4.13
and built in IR-cut filter for AXIS F1005-E and	Ŧ			0110	
FA1105. Tool for removing the standard lens is					
included. 4 Pcs.					
LENS M12 12MM F1.6 Q6100-E, Q6010-E	\$	109.00	7331021067646	0.22	6.50
LENS M12 25MM F2.4 4P Q6100-E	\$	109.00	7331021067653	0.22	6.50
LENS M12 16MM F1.8 Q6010-E Q6100-E	\$	109.00	7331021068148	0.22	6.50
LENS M12 6MM F2.0 Q6010-E Q6100-E	¢ \$	109.00	7331021068155	0.22	6.50
	φ \$	39.00	7331021051539	0.32	2.28
Weathershield for AXIS P14 Series designed for use in rainy and windy environments.	φ	39.00	7331021051539	0.32	2.20
use in rainy and windy environments.					
Accessory M12 6mm lens for AXIS Q6000-E	\$	109.00	7331021055797	0.24	6.50
Mkll 5pcs	φ	109.00	7551021055797	0.24	0.50
Megapixel lens 2.8 mm, F1.2 with M12 thread	\$	219.00	7331021068735	0.40	6.30
for AXIS P39-R Series that provides 110°	Ť				
horizontal FOV and excellent low light					
performance. Coated with IR-cut filter. 10					
pieces bulk pack.					
Megapixel lens 6 mm, F1.6 with M12 thread for	\$	219.00	7331021044197	0.44	6.50
AXIS P39-R Series that provides 52° horizontal					
FOV with these cameras. With IR filter. 10					
pieces.					
Megapixel lens 8 mm, F1.6 with M12 thread for	\$	219.00	7331021044203	0.44	6.50
AXIS P39-R Series that provides 40° horizontal					
FOV with these cameras. With IR filter. 10					
pieces.					

Megapixel lens 3.6 mm, F2.0 with M12 thread for AXIS P39-R Series that provides 87°	\$	219.00	7331021045644	0.49	6.50
horizontal FOV with these cameras. With IR					
filter. 10 pieces. Can be used as a spare part for					
AXIS P39-R or as a wider FOV option for P3905-					
RE.					
Megapixel lens 2.1mm, F2.2 with M12 thread for	\$	219.00	7331021060012	0.24	4.33
AXIS P39-R Series that provides 147° horizontal	Ψ	215.00	7001021000012	0.24	4.00
FOV with these cameras. With IR filter. 10					
pieces. Lens tool included.					
p					
2.1 mm accessory lens, F1.8 with M12 thread,	\$	199.00	7331021070684	0.35	6.30
without IR-cut filter for day/night cameras with	Ŧ			0.00	0.00
removable IR cut filter. Compatible with AXIS					
P3925-R and AXIS P3935-LR. 10 pcs. Lens tool					
included.					
3.6 mm accessory lens, F1.8 with M12 thread,	\$	199.00	7331021070691	0.40	6.30
without IR-cut filter for day/night cameras with	Ψ	100.00		0.70	0.00
removable IR cut filter. Compatible with AXIS					
P3925-R and AXIS P3935-LR. 10 pcs. Lens tool					
included.					
6.0 mm accessory lens, F1.9 with M12 thread,	\$	199.00	7331021070707	0.44	6.30
without IR-cut filter for day/night cameras with	Ψ	155.00	7331021070707	0.44	0.50
removable IR cut filter. Compatible with AXIS					
P3925-R and AXIS P3935-LR. 10 pcs. Lens tool					
included.					
8.0 mm accessory lens, F1.8 with M12 thread,	\$	199.00	7331021070714	0.44	6.30
without IR-cut filter for day/night cameras with	φ	199.00	7331021070714	0.44	0.30
removable IR cut filter. Compatible with AXIS					
P3925-R and AXIS P3935-LR. 10 pcs. Lens tool					
included.					
Accessory M12 16mm lens for AXIS Q6000-E	\$	99.00	7331021055803	0.24	6.50
Accessory M12 Tomm lens for AXIS Q0000-E Mkll 5pcs	Þ	99.00	7331021055603	0.24	6.50
2 pieces each of 2.8 mm (F2.0), 6 mm (F1.6) and	\$	159.00	7331021047471	0.26	6.50
8 mm (F1.6) Megapixel lenses with M12 thread.	Ψ	155.00	7551021047471	0.20	0.50
For use with AXIS P39-R cameras. Includes					
lens tools.					
Barrel distortion corrected and IR corrected	\$	309.00	7331021036611	0.22	4.72
wideangle lens for cameras up to 5 mega pixel	φ	309.00	1331021030011	0.22	4.72
resolution. Compatible with e.g. AXIS M1114/-E,					
AXIS P1353/-E, P1354/-E, P1355/-E, P1357/-E,					
AXIS P1353/-E, P1354/-E, P1355/-E, P1357/-E, AXIS Q1602/-E, Q1604/-E, Q1614/-E, Q1615/-E.					
					1
Varifocal IR-corrected lens with DC-Iris.	\$	149.00	7331021007000	0.40	4.72
Compatible with e.g. AXIS P1353/-E, P1354/-E,	Ψ	149.00	1331021007000	0.40	4.72
P1355/-E, P1357/-E, AXIS P1353/-E, P1354/-E,					
1 1000/-L, F 1007/-L, AND Q1002/-E, Q1004/-E.					
Varifocal IR-corrected lens for cameras up to 5	\$	279.00	7331021036628	0.24	4.72
mega pixel resolution. Compatible with e.g.	Ψ	213.00	1001021000020	0.24	7.12
AXIS M1114/-E, P1354/-E, P1355/-E, P1357/-E,					
Q1602/-E, Q1604/-E.					
Q1002/-E, Q1004/-E.					
Varifocal IR-corrected P-iris tele lens	\$	279.00	7331021041691	0.37	4.72
compatible with AXIS AXIS P1355/-E, P1357/-E,	Ψ	219.00	1331021041031	0.37	4.72
AXIS Q1602/-E, Q1604/-E, Q1614/-E, Q1615/-E.					

\$ 269.00		7331021007017	0.40	4.72
\$ 269.00		7331021007024	0.40	4.72
\$ 249.00		7331021057739	0.44	4.72
\$ 349.00		7331021051003	0.68	4.72
\$ 549.00		7331021065154	1.46	4.72
\$ 299.00		7331021066526	0.49	4.72
\$ 449.00		7331021067004	0.80	5.20
\$ 299.00		7331021065147	0.44	4.72
\$ 79.00		7331021067585	0.40	4.72
\$ 89.00		7331021074996	0.66	6.50
\$ 69.00		7331021067578	0.31	4.72
\$ 49.00		7331021030909	0.33	6.50
				6.50
\$ 8.00		73310210333320	0.07	8.07
\$ 59.00		7331021033337	0.31	8.07
\$ 8.00		7331021064904	0.05	8.66
\$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$	 \$ 269.00 \$ 249.00 \$ 349.00 \$ 549.00 \$ 549.00 \$ 299.00 \$ 299.00 \$ 449.00 \$ 79.00 \$ 79.00 \$ 69.00 	\$ 269.00 \$ 249.00 \$ 349.00 \$ 549.00 \$ 549.00 \$ 299.00 \$ 299.00 \$ 299.00 \$ 299.00 \$ 69.00 \$ 69.00 \$ 69.00 \$ 449.00 \$ 59.00	\$ 269.00 7331021007024 \$ 249.00 7331021057739 \$ 349.00 7331021051003 \$ 549.00 7331021065154 \$ 299.00 7331021066526 \$ 299.00 7331021066526 \$ 299.00 7331021067004 \$ 299.00 7331021065147 \$ 79.00 7331021065147 \$ 89.00 7331021067585 \$ 89.00 7331021067578 \$ 69.00 7331021030909 \$ 49.00 7331021033320 \$ 59.00 7331021033337	\$ 269.00 7331021007024 0.40 \$ 249.00 7331021057739 0.44 \$ 349.00 7331021051003 0.68 \$ 549.00 7331021065154 1.46 \$ 299.00 7331021066526 0.49 \$ 299.00 7331021066526 0.49 \$ 299.00 7331021065147 0.80 \$ 299.00 7331021065147 0.44 \$ 79.00 7331021067585 0.40 \$ 89.00 7331021067585 0.40 \$ 89.00 7331021067578 0.31 \$ 69.00 7331021031456 1.10 \$ 49.00 7331021033337 0.31

Heavy duty outdoor weathershield for wall mounted AXIS fixed dome cameras. Designed to protect the dome from rain, snow and sun. The underside of the cover is coated with matte black anti-reflective coating, for suitable use with camera's built-in IR LEDs.	\$ 69.00	7331021041233	1.07	6.97
850nm IR LED illuminator kit compatible with AXIS T99A Positioning Units for visual cameras. Kit includes one pair of IR illuminators, one metal mounting bracket, and three different diverging lenses. Note: this is the same illuminator kit as used in AXIS Q8685- LE PTZ Network Camera.	\$ 1,949.00	7331021056534	11.24	17.32
Bracket kit for installing a pair of compatible illuminators to Axis positioning cameras and positioning units. Designed for use with AXIS Q8685-E and AXIS T99A10. Compatible with selected T90 white-LED and IR-LED illuminators. Includes fitting brackets, illuminator connectors, screws, washers, cable glands and cable ties. Illuminators sold separately.	\$ 219.00	7331021061729	5.45	10.43
Washer kit for spraying cleaning fluid on the windows of AXIS positioning cameras and positioning units. The kit contains a 23 litre tank, pump for delivery up to 11m (36ft), tube, nozzle and custom-made mounting bracket for the nozzle.	\$ 1,079.00	7331021060067	15.98	12.80
Washer kit for spraying cleaning fluid on the windows of AXIS positioning cameras and positioning units. The kit contains a 23 litre tank, pump for delivery up to 11m (36ft), tube, nozzle and custom-made mounting bracket for the nozzle. This washer kit compatible with Q6215 and as well requires seperate ordering of T6101 I/O since Q6215 does not have I/O.	\$ 1,189.00	7331021075221	17.53	12.99
Bird control spikes made of flexible UV- resistant polymer preventing birds from landing on cameras or mounts. Each module has five spikes and can be mounted on flat or curved surfaces using the pre-mounted adhesive or cable ties (not included). The modules can be connected lengthwise and/or widthwise to cover a larger area. 10 pcs.	\$ 39.00	7331021049338	0.41	4.72
Stainless steel safety wire 3 m (10 ft) long, with a fixed loop in one end and an adjustable loop with a plated brass wire lock in the other. Suitable for both indoor and outdoor use.	\$ 49.00	7331021057036	0.53	4.92
Black cable with RJ12 and micro USB connectors for indoor Sensor Units. Length 1 m (39 in.) 4 pcs.	\$ 29.00	7331021064911	1.32	5.91

AVIS E7245 comes in peaks of four 45 m (40 ft)	¢	100.00	7224024040464	0.49	7 40
AXIS F7315 comes in packs of four. 15-m (49 ft.) white cable with an RJ12 connector for connection to an AXIS F1004 Sensor Unit or AXIS FA-series sensors.	\$	109.00	7331021049161	2.43	7.48
AXIS P13 Weathershield Extension A for AXIS P1375-E. For mounting on AXIS P13 Series camera providing additional protection against rain, snow and sunlight.	\$	49.00	7331021066625	1.06	12.60
M12 D-Code 4-pin (Female) to RJ45 (Male) Ethernet cable, CAT5E. Length: 0.5m (1.6ft). Cable outer diameter: 6.2mm (0.25"). Color: Black. Outdoor UV and sunlight resistant. Tested operational for shock and vibration according to requirements for rolling stock and ground vehicle installations. Compatible with all Axis network video products with female RJ45 Ethernet port 802.3af and 802.3at (up to 30W).	\$	49.00	7331021067745	0.18	5.12
weathershield extension over M1135/37-E where entire top cover kit not wanted (TM1802)	\$	49.00	7331021071766	0.32	6.30
AXIS TV5901 Control Board Adapter is a cable to connect AXIS V5925 and AXIS V5938 to joystick, keypad and other controllers supporting VISCA protocol.	\$	39.00	7331021075405	0.13	5.51
Adapter bracket that allows Axis P56-series to be connected to Q6100. The material is PC+ABS Cycoloy C6600 GY8D352 and comes in Axis White.	\$	49.00	7331021077737	0.26	5.91
AXIS TD4801 Sunshield is the perfect accessory for when AXIS D4100-E Network Strobe Siren is used in conditions where sunlight would shine directly on the device. It is easy to mount, without the need to take AXIS D4100-E down. The accessory comes in a 4 pack.	\$	89.00	7331021072510	2.16	10.24
Additional protective ring for AXIS Q6215-LE and AXIS Q6225-LE. The purpose of it is to stop rain, melt water, sleet and snow from entering the gap between the moving parts in sub-zero environments, preventing the pan axle to be frozen solid. Pan movement protection instead. Protects against water, and large pieces from entering the gap.	\$	39.00	7331021081703	0.20	6.30
AXIS TP3818-E Casing Black, is a black casing and is offered as an optional accessory for AXIS P4705-PLVE and P4707-PLVE. Does not include dome.	\$	49.00	7331021078123	0.44	5.51

AXIS TU6004-E Cable 8m is a 8m (26ft) cable used for the 2nd generation F-series. It has rugged connectors. A FAKRA connector on one side (connecting to the F91 main units) and a SMA connector on the other side (connecting to the F21, F72 and F4105-LRE sensors). AXIS TU6004-E Cable 8m is outdoor rated and complies with IP66 and IP6K9K. It has a 5mm (0,2 in) diameter and a 40mm (1,6 in) bending radius. AXIS TU6004-E Cable 8m can be shorten and re- crimped on the FAKRA side only thanks to AXIS TU6003 Conn kit FAKRA, 10P (sold separately).	\$ 29.00	7331021075351	0.84	8.27
AXIS TU6004-E cable 30m is a 30m (98ft) cable used for the 2nd generation F-series. It has rugged connectors. A FAKRA connector on one side (connecting to the F91 main units) and a SMA connector on the other side (connecting to the F21, F72 and F4105-LRE sensors). AXIS TU6004-E Cable 30m is outdoor rated complying with the IP66 and IP6K9K standards. It has a 5mm (0,2 in) diameter and a 40mm (1,6 in) bending radius. AXIS TU6004-E Cable 30m can be shorten and re-crimped on the FAKRA side only thanks to AXIS TU6003 Conn kit FAKRA, 10P (sold separately).	\$ 99.00	7331021075375	2.91	10.24
AXIS TU6004-E Cable 1m 4P is a bulk pack of 4x 1m (3ft) cables used for the F-series. TU6004- E Cable 1m has rugged connectors. A FAKRA connector on one side (connecting to the F91 main units) and a SMA connector on the other side (connecting to the F21, F72 and F4105-LRE sensors). AXIS TU6004-E Cable 1m is outdoor rated and complies with the IP66 and IP6K9K standards. It has a 5mm (0,2 in) diameter and a 40mm (1,6 in) bending radius. AXIS TU6004-E Cable 1m can be shorten and re- crimped on the FAKRA side only thanks to AXIS TU6003 Conn kit FAKRA 10P (sold separately).	59.00	7331021075344	0.53	6.30

 AXIS TU6004-E Cable 8m 4P is a bulk pack of 4x 8m (26ft) cables used for the F-series. TU6004-E Cable 8m has rugged connectors. A FAKRA connector on one side (connecting to the F91 main units) and a SMA connector on the other side (connecting to the F21, F72 and F4105-LRE sensors). AXIS TU6004-E Cable 8m is outdoor rated and complies with the IP66 and IP6K9K standards. It has a 5mm (0,2 in) diameter and a 40mm (1,6 in) bending radius. AXIS TU6004-E cable 8m can be shorten and recrimped on the FAKRA side only thanks to AXIS TU6003 Conn kit FAKRA, 10P (sold separately). 	\$ 99.00	7331021075368	3.79	6.89
AXIS TU6005 Plenum Cable 8m is a 8m cable (26ft) used for the 2nd generation) F-series. It has rugged connectors. A FAKRA connector on one side (connecting to the F91 main units) and a SMA connector on the other side (connecting to the F21, F72 and F4105-LRE sensors). AXIS TU6005 Plenum Cable 8m is indoor plenum rated cable. It has a 4mm (0,16 in) diameter and a 32mm (1,3 in) bending radius. AXIS TU6005 Plenum Cable 8m can be shorten and re-crimped on the FAKRA side only thanks to AXIS TU6005 Plenum Cable 8m is only available for the US market.	\$ 99.00	7331021075504	0.75	9.88
 AXIS TU6005 Plenum Cable 20m is a 20m (65 ft) cable used for the 2ng generation F-series. It has rugged connectors. A FAKRA connector on one side (connecting to the F91 main units) and a SMA connector on the other side (connecting to the F21, F72 and F4105-LRE sensors). AXIS TU6005 Plenum Cable 20m is indoor plenum rated cable. It has a 4mm (0,16 in) diameter and a 32mm (1,3 in) bending radius. AXIS TU6005 Plenum Cable 20m can be shorten and re-crimped on the FAKRA side only thanks to AXIS TU6006 Conn kit FAKRA 10P (sold separately). AXIS TU6005 Plenum Cable 20m is only available for the US market. 	\$ 199.00	7331021075511	1.76	10.63

AXIS TU6002 Right Angle SMA ADP 10p is a bulk pack of 10x 90° angle angle adapters. The accessory is an accessory of the AXIS F21 sensors. The 90° angle adapter helps installing a sensor in tight space without bending AXIS TU6004, AXIS TU6007 and AXIS TU6005 cable and potentially damaging it.	\$8	9.00	7331021077935	0.13	2.68
AXIS TU6003 Conn Kit FAKRA 10p is a bulk pack of 10x replacement FAKRA connectors. In this kit, you have all the necessary accessories to re-crimp AXIS TU6004-E Cable with the new FAKRA connector. AXIS TU6004-E Cable can only be cut and re-crimped on the FAKRA connector end.	\$3	5.00	7331021077911	0.22	4.13
AXIS TU6006 Conn Kit FAKRA 10p is a bulk pack of 10x replacement FAKRA connectors for AXIS TU6005 Plenum Cable. It gives all the necessary accessories to re-crimp AXIS TU6005 Plenum Cable with the new FAKRA connector. AXIS TU6005 Plenum Cable can only be cut and re-crimped on the FAKRA connector end.	\$ 3	5.00	7331021077928	0.22	4.13
AXIS TU6009 Conn 6-pin is a male connector for I/O port . Pitch: 2.50 mm. 6pos terminal block. 10pack	\$2	6.00	7331021083882	0.04	2.76
AXIS TU6008 Conn 5-pin is a male connector for RS port . Pitch: 2.50 mm. 5pos terminal block. 10pack	\$2	2.00	7331021083875	0.09	2.76
Adapter bracket that allows Axis P5676-LE to be connected to Q6100. The material is PC+ABS Cycoloy C6600 GY8D352 and comes in Axis White.	\$4	9.00	7331021085374	0.31	5.71
Wireless USB dongle for AXIS M1075-L Box Camera. This allows the camera to communicate with 2.4 GHz and 5 GHz frequency. The wireless adapter supports 802.11ac/b/g/n. Requires PoE injector to power the camera.	\$ 3	9.00	7331021081031	0.02	0.28
AXIS TU6007-E Cable 1m 4P is a bulk pack of 4x 1m (3ft) thin cables used for the 2nd generation F-series. AXIS TU6007-E Cable 1m has rugged connectors. A FAKRA connector on one side (connecting to the F91 main units) and a SMA connector on the other side (connecting to the F21, F72 and F4105-LRE sensors). AXIS TU6007-E Cable 1m is indoor/outdoor rated and complies with the IP66 standard. It has a 3mm (0,1 in) diameter with a 30mm bending radius. This cable is ideal when used in very tight spaces and when the cable needs to be bended.	\$ 4	3.00	7331021083868	0.22	6.30

AXIS TU6007-E Cable 8m is a 8m (26ft) thin cable used for the 2nd generation F-series. AXIS TU6007-E Cable 8m has rugged connectors. A FAKRA connector on one side (connecting to the F91 main units) and a SMA connector on the other side (connecting to the F21, F72 and F4105-LRE sensors). AXIS TU6007-E Cable 8m is indoor/outdoor rated and complies with the IP66 standard. It has a 3mm (0,1 in) diameter with a 30mm bending radius. This cable is ideal when used in very tight spaces and when the cable needs to be bended.	\$ 19.00	7331021083837	0.33	6.30
 AXIS TU6007-E Cable 8m 4P is a bulk pack of 4x 8m (26ft) thin cables used for the 2nd generation F-series. AXIS TU6007-E Cable 8m has rugged connectors. A FAKRA connector on one side (connecting to the F91 main units) and a SMA connector on the other side (connecting to the F21, F72 and F4105-LRE sensors). AXIS TU6007-E Cable 8m is indoor/outdoor rated and complies with the IP66 standard. It has a 3mm (0,1 in) diameter with a 30mm bending radius. This cable is ideal when used in very tight spaces and when the cable needs to be bended. 	\$ 66.00	7331021083844	0.99	6.10
AXIS TS3901 Rail Extensions allow AXIS S3016 Recorder to be mounted in deep server racks with a post to post distance between 499mm (19.6in) and 690mm (27.1in). No rails extensions are needed for a post to post distance between 376mm (14.8in) and 499mm (19.6in). Each rail extension is composed of two parts which replace two segments of the original rails provided with AXIS S3016 Recorder.	\$ 29.00	7331021079052	2.25	2.56
AXIS TU6011 Mains Cable is compatible with AXIS TU8004 90 W Midspan. It comes with a country specific power cord and plug.	\$ 19.00	7331021085688	0.55	4.13
AXIS TU6011 Mains Cable is compatible with AXIS TU8004 90 W Midspan. It comes with a country specific power cord and plug. 10 pcs package.	\$ 179.00	7331021085794	4.63	9.06
Protective camera housing for P13XX, M11XX, Q16XX and Q1755. Die cast aluminum casing and wallbracket, polycarbonate sunshield. The housing is IP66-, Nema 4X rated and IK10 impact-resistant. Sunshield, wallbracket and screwdriver included.	\$ 219.00	7331021031876	8.82	9.45

Outdoor PoE camera housing with window- /camera heaters and fan for P13XX, M11XX, Q16XX and Q1755. Die cast aluminum casing and wallbracket, polycarbonate sunshield. The housing is IP66-, Nema 4X-, Vibration 4M3 rated and IK10 impact-resistant. Sunshield, wallbracket and screwdriver included.	\$ 359.00	7331021034211	10.54	9.45
Metal camera housings with heater and blower for Axis Network Cameras. Weathershields included. Housings can be powered with 24VAC. 6-piece pack. Required accessory: AXIS T94X01A Wall Mount 6PCS (sold separately) Optional accessory: AXIS T94Y01G Pole Mount 6PCS (sold seperately)	\$ 699.00	7331021054240	23.79	8.07
Outdoor PoE+ camera housing with IR illumination, window & camera heaters, and fan. Compatible with AXIS P1375, AXIS P1377, AXIS P1378, AXIS Q1615 Mk III, AXIS Q1615-LE Mk III, AXIS Q1645, AXIS Q1647, AXIS Q1715. Polycarbonate sunshield, aluminum wall mount and torx screwdriver included.	\$ 649.00	7331021075887	17.33	11.42
Outdoor camera housing for Axis cameras with EF lenses (e.g.:Q1656, Q1656-B, P1375, P1377, P1378). Made of IK10 impact resistant thermoplastic with dual-layer UV protection. IP66, NEMA 4X rated and UL listed. Powered by 24 VDC (power supply not included). Heavy duty wall mount included.	\$ 1,399.00	7331021058514	15.53	13.35
Extension kit to allow mounting of longer lenses in AXIS T93C10 Outdoor Housing (e.g.: compatible with AXIS Q1659 55-250 mm). Includes built-in sunshield and front window. The extension kit provides an extra space of 80mm in length within the housing, giving a total length of 380mm for the camera and lens. The part of the lens within the extension kit can have maximum diameter of 75mm.	\$ 109.00	7331021061064	1.30	5.51
Fixed box protective camera housing made of IK10 impact resistant and UV resistant polymer. IP66, NEMA 4X rated and UL listed. Compatible with AXIS P13 Series and AXIS Q16 Series. AXIS T94Q01A Wall mount included.	\$ 169.00	7331021043824	4.51	6.22

	•		 		
Fixed box outdoor camera housing made of IK10 impact resistant and UV resistant polymer. IP66, NEMA 4X rated and UL listed. Powered by 24 V AC or 12-24 V DC. Compatible with AXIS P13 Series, AXIS Q16 Series, and M11 Series. AXIS T94Q01A Wall mount included. AXIS P1353/P1354/P1355/P1357 and AXIS Q1604/Q1614: -40 °C to 50 °C (-40 °F to 122 °F) AXIS P1365 and AXIS Q1615/Q1635: -40 °C to 55 °C (-40 °F to 131 °F). AXIS Q1645/Q1647: -40 °C to 40 °C (-40 °F to 104 °F) AXIS M1124/M1125: - 40 °C to 55 °C (-40 °F to 131 °F)	\$	259.00	7331021048317	4.74	6.22
Fixed box outdoor camera housing made of IK10 impact resistant and UV resistant polymer. IP66, NEMA 4X rated and UL listed. Powered by PoE IEEE802.3af. Compatible with AXIS P13 Series, AXIS Q16 Series and M11 Series. AXIS T94Q01A Wall mount included. Temperature range: AXIS P1353/P1354/P1355/P1357 and AXIS Q1604/Q1614: -40 °C to 50 °C (-40 °F to 122 °F), AXIS P1365 and AXIS Q1615/Q1635: -40 °C to 55 °C (-40 °F to 131 °F), AXIS Q1645/Q1647: - 40 °C to 40 °C (-40 °F to 104 °F), AXIS M1124/M1125: -40 °C to 55 °C (-40 °F to 131 °F).	\$	259.00	7331021043831	5.00	6.22
Tailor-made light weight IP66- and IK10-rated housing for AXIS M1124/M1125. Operating temperature: -20 °C to 50 °C (-4 °F to 122 °F). Material: IK10 impact-resistant polymer. Wallmount included.	\$	119.00	7331021047747	4.67	9.25
Accessory sunshield and weather protection for AXIS T93F Housing Series	\$	49.00	7331021043800	1.28	6.42
IP66, IK10 and NEMA 4X rated outdoor-ready surveillance cabinet. Protects accessory devices such as power supply, media converter, midspan and fuse from tough weather and vandalism. Mounting bracket for wall, DIN-rail, device mounting bracket and Electrical safety cover is included.	\$	329.00	7331021003675	9.70	12.87
IP66, IK10 and NEMA 4X rated outdoor-ready surveillance cabinet. Protects accessory devices such as power supply, media converter, midspan and fuse from tough weather and vandalism. The camera is mounted on the door of the cabinet. Mounting bracket for wall, DIN-rail, device mounting bracket and Electrical safety cover is included. Compatible cameras: AXIS M111X-E, P13XX-E, Q16XX-E, Q1755-E, Q191X-E Q192X-E.	\$	339.00	7331021003682	9.92	12.87

		 -		
IP66, IK10 and NEMA 4X rated outdoor-ready surveillance cabinet. Protects accessory devices such as power supply, media converter, midspan and fuse from tough weather and vandalism. The camera is mounted on the door of the cabinet. Mounting bracket for wall, DIN-rail, device mounting bracket and Electrical safety cover is included. Compatible cameras: AXIS P33-VE/-LVE.	\$ 339.00	7331021003699	9.92	12.87
IP66, IK10 and NEMA 4X rated outdoor-ready surveillance cabinet. Protects accessory devices such as power supply, media converter, midspan and fuse from tough weather and vandalism. The camera is mounted on the door of the cabinet. Mounting bracket for wall, DIN-rail, device mounting bracket and Electrical safety cover is included. Compatible products: AXIS T91B61 Wall bracket for use with AXIS P55, P56, Q60 and Q61-series or fixed dome pendant kits.	\$ 339.00	7331021003705	9.92	12.87
IP66, IK10 and NEMA 4X rated outdoor-ready surveillance cabinet. Protects accessory devices such as power supply, media converter, midspan and fuse from tough weather and vandalism. The camera is mounted on the door of the cabinet. Mounting bracket for wall, DIN-rail, device mounting bracket and Electrical safety cover is included. Compatible products: AXIS P5414-E/15-E.	\$ 339.00	7331021007529	9.92	12.87
Metal sunshield for AXIS T98A-VE Surveillance Cabinet series. Reduces the temperature inside the cabinet, caused by sun radiation, with up to 15°C (27°F).	\$ 149.00	7331021001435	3.53	6.30
Door lock for AXIS T98A surveillance cabinet. Uses a generic key but it is possible to change locking cylinder to a unique key solution (not supplied from Axis)	\$ 69.00	7331021046085	0.43	2.76
The corridor format bracket makes it possible to mount a camera rotated 90 degrees inside the AXIS T93F05 and AXIS T93F20 housings to enable a vertically oriented, "portrait"-shaped video stream from the camera. Includes built-in camera heater (only applicable when mounted in AXIS T93F20).	\$ 49.00	7331021043794	0.38	4.72
The corridor format bracket makes it possible to mount a camera rotated 90 degrees inside the AXIS T93F10 housing to enable a vertically oriented, "portrait"-shaped video stream from the camera. Included with built-in camera heater.	\$ 49.00	7331021047150	0.40	4.72

Camera holder plate for mounting an AXIS Q1614 in a AXIS T92E05 and AXIS T92E20 housing. Or change the camera unit inside an AXIS P135X-E outdoor camera.	\$ 29.00	7331021043909	0.21	4.13
Kit for mounting an AXIS Q1614 in a AXIS T92E05/AXIS T92E20 housing produced before 2014. Or change the camera unit inside an AXIS P134X-E outdoor camera.	\$ 49.00	7331021043916	0.93	8.27
IP66, IK10 and NEMA 4X rated outdoor-ready surveillance cabinet. Protects accessory devices such as power supply, media converter, and midspan from tough weather and vandalism. Mounting bracket for wall, DIN- rail, device mounting bracket and Electrical safety cover is included. Similar to T98A15 but door is deeper by 4" allowing door to be shut with power supply and switch in it.	\$ 389.00	7331021076334	10.54	12.40
AXIS TP3826-E housing is an outdoor housing for selected AXIS M39 and P39 cameras. It enables the cameras to be mounted outside vehicles such as buses, trams, trucks or emergency vehicles.	\$ 109.00	7331021081475	1.06	7.28
Viewing protector that makes it harder to see where the camera is aiming. For use when the camera is used without dome. 5 pcs.	\$ 49.00	7331021053205	0.26	5.51
White cover skins compatible with AXIS M3024/M3025/M3026/M3027 for covering screws or simplify the painting process.	\$ 129.00	7331021052864	1.50	6.02
Black cover skins compatible with AXIS M3024/M3025/M3026/M3027 for covering screws or simplify the painting process.	\$ 129.00	7331021006249	1.37	6.02
4-pack. Outdoor-ready skin covers compatible with AXIS M3057/58-PLVE cameras for changing the appearance of the camera, simplify re-painting and covering screws. Black color.	\$ 89.00	7331021063631	0.71	6.50
Black accessory casing for AXIS M3044-V/45- V/46-V. Replaces the white original casing. 5 pcs.	\$ 89.00	7331021053199	1.12	6.38
Highly discreet white casing with smoke- detector look for AXIS M3047/48-P. 5 pcs.	\$ 79.00	7331021057807	0.44	11.02
4-pack of black accessory cover ring for AXIS M3015-V/16-V. Magnetic attachment. Replaces the original white cover ring. Dome not included.	\$ 69.00	7331021064027	1.08	6.30
Smoked dome with anti-scratch hard coating. Compatible with AXIS M42 series. 4x domes per pack.	\$ 89.00	7331021065802	0.37	2.17
Smoked dome in polycarbonate. IK09 vandal resistant. Compatible with AXISM5525-E. Single pack.	\$ 49.00	7331021065796	0.49	6.69

5-pack. Skin covers compatible with AXIS P32- V cameras for changing the appearance of the camera, simplify re-painting or covering	\$ 79.00		7331021046207	0.91	7.09
screws. Black color.					
A white metal casing for indoor/outdoor use that is compatible with: M3205-LVE, M3206- LVE, P3245-LVE, P3245-VE, P3247-LVE, AXIS	\$ 219.00		7331021075177	3.06	14.96
P3248-LVE. It is IK 10/IP66, has a 3/4 conduit entry and is easy to install. This casing targeted for corrections and other segments that require a tough metal casing.					
Spare part skin covers for the AXIS P56 Series. Both the camera cover and the ring around the dome are included. 5 pcs.	\$ 139.00		7331021048096	3.81	15.55
Skin covers compatible with AXIS P39-R cameras for changing the appearance of the camera, simplify re-painting or covering screws. White color. 10 pcs.	\$ 159.00		7331021045620	0.11	6.02
Skin covers compatible with AXIS P39-R cameras for changing the appearance of the camera, simplify re-painting or covering screws. Black color. 10 pcs.	\$ 159.00		7331021045637	0.11	6.02
Smoked domes for AXIS M3025-VE, M3026-VE. 5 pcs.	\$ 269.00		7331021045873	0.68	5.12
Smoked dome for AXIS M3044-V/45-V/46-V SM DOME. 5 pcs.	\$ 109.00		7331021053182	0.31	3.15
Black accessory casing for AXIS M3104-L/05- L/06-L. Replaces the white original casing. 5 pcs.	\$ 79.00		7331021052475	0.84	6.30
Black accessory casing for AXIS M3104-LV/5- LV/6-LV. Replaces the white original casing. 5 pcs.	\$ 89.00		7331021052482	0.82	6.30
Smoked domes for AXIS P32-V Series, 5 pcs	\$ 169.00		7331021046160	0.93	5.12
Black cover with clear dome for AXIS P3346.	\$ 29.00		7331021003279	0.99	11.02
Black accessory casing for AXIS P33-V/-LV indoor cameras. Replaces the white original casing. Includes anti-loss screws, conduit side covers. Domes sold separately.	\$ 49.00		7331021064782	0.58	6.10
Smoked dome with anti-scratch hard coating for indoor and outdoor AXIS P337X cameras. 4x domes per pack.	\$ 119.00		7331021064799	0.56	5.51
Smoked dome for AXIS P54-series.	\$ 59.00	ŀ	7331021007413	0.66	7.68
Smoked dome for AXIS P56 Series cameras.	\$ 59.00		7331021048119	0.62	8.66
Skin covers in black, compatible with AXIS Q35- LV indoor cameras. Simple to repaint in other colours, and prevents unwanted access to the cameras' screws. Black in color. 5 pieces per pack.	\$ 79.00		7331021061170	1.17	6.89

2-pack of skin covers in black, compatible with AXIS Q35-VE/-LVE outdoor cameras. Simple to repaint in other colors, and prevents unwanted access to the cameras' screws. Black in color. 2 pieces per pack.	\$ 79.00	7331021064584	0.98	8.27
Smoked dome with anti-scratch hard coating. Compatible with AXIS Q3517-LV/-LVE. 5x domes per pack.	\$ 199.00	7331021061743	1.73	6.30
Accessory clear dome in a special nylon blend with anti-scratch hard coating. IK10+ vandal- resistant with superior chemical resistance. Compatible with AXIS Q3517-SLVE but not recommended to use with IR illumination. 2x domes per pack.	\$ 169.00	7331021065598	0.79	6.30
Smoked dome with anti-scratch hard coating. Compatible with AXIS P38 and AXIS Q36 series.	\$ 59.00	7331021053557	0.88	7.09
Smoked dome with anti-scratch hard coating. Compatible with AXIS Q3708-PVE and Q3709- PVE. Single pack.	\$ 59.00	7331021060739	0.68	7.48
Standard clear dome with anti-scratch hard coating. Compatible with AXIS Q6074, 75, 78-E cameras. Weather-resistant and chemical- resistant. Replacement dome only.	\$ 69.00	7331021076860	0.57	4.72
Accessory clear dome with special hydrophilic coating. Helps to prevent water droplets from covering the dome in rainy conditions. The coating also provides a self-cleaning effect that helps carry away dirt and dust by rain-wash. Compatible with Q6315-LE.	\$ 179.00	7331021079595	0.83	7.95
Smoked dome in a special nylon blend with superior stress and chemical resistance. Compatible with AXIS Q604x-S and Q6055-S cameras. Single-pack.	\$ 89.00	7331021045354	0.60	7.48
Standard clear dome for AXIS Q6114-E/Q6115- E.	\$ 69.00	7331021050891	0.55	7.48
Standard clear dome for AXIS Q61 Series, 5 pcs	\$ 269.00	7331021048003	1.54	12.60
Smoked dome for hiding the direction of the camera. Compatible with AXIS Q8414-LVS. 5 pcs.	\$ 99.00	7331021047495	0.49	4.72
4 Pack black casing to change the appearance of the product.	\$ 69.00	7331021068568	0.40	4.13
Cover top black casing for M3067/68 4P.	\$ 69.00	7331021067158	0.46	5.12
SMOKE DETECTOR CASING - COVER TOP ASS SMOKE M3067/68	\$ 69.00	7331021067165	0.47	5.12
Vandal Casing COVER TOP ASS DOME M304X- PV.	\$ 89.00	7331021067172	0.49	5.51
4P Black casing for M3115/6 LVE. Black accessory casing that replaces the white original casing for changing the appearance of the camera.	\$ 89.00	7331021069008	0.74	6.89

4 pack of outdoor-ready skin covers compatible with AXIS M4308-PLE for changing the appearance of the camera, simplify re-painting and covering screws. Black color. 4 pcs per pack.	\$ 69.00	7331021076044	0.66	7.01
4 Pack black casing to change the appearance of the product. Compatible with M3085-V, M3086-V, M3088-V.	\$ 69.00	7331021079649	0.39	4.33
Accessory black casing for selected AXIS P32 indoor cameras. 4pcs bulk pack.	\$ 89.00	7331021066090	1.10	6.30
Accessory black casing for selected AXIS M32 and P32 outdoor cameras. Pre-assembled with anti-loss screws. 4pcs bulk pack.	\$ 109.00	7331021066120	1.32	6.30
Smoked dome with anti-scratch hard coating. Compatible with selected AXIS P32 indoor cameras. 4pcs bulk pack.	\$ 109.00	7331021066106	1.32	7.64
Smoked dome with anti-scratch hard coating. Compatible with selected AXIS M32 and P32 outdoor cameras. 4pcs bulk pack.	\$ 129.00	7331021066137	1.32	7.64
4 pack black dome cover for AXIS P3925-R. Replaces the standard white dome cover.	\$ 219.00	7331021070677	2.51	11.10
4 pack black dome cover for AXIS P3935-LR. Replaces the standard white dome cover.	\$ 219.00	7331021070660	2.51	11.10
A ventless metal casing for P3717/19-PLE and following products. USP 797/800 has very strict cleaning requirements for Hazardous, non- Hazardous and Ante rooms in an infusion or inpatient pharmacy setting. Ventless metal casing allows cleaning agent to wipe down the cameras easily	\$ 139.00	7331021075184	1.32	10.43
It is easy to install in a fast way and is IK9/IP66 rated.				
Accessory black dome casing for AXIS P3727- PLE. The dome and casing are included.	\$ 89.00	7331021075306	0.71	
Smoked dome for AXIS P3717-PLE, AXIS P3719- PLE, AXIS P3727-PLE. The smoked dome can replace the clear dome delivered with the camera.	\$ 69.00	7331021076815	2.02	4.53
Accessory casing compatible with AXIS P3818- PVE. Includes anti loss screws, weather cover, cover lid, and cover top.	\$ 139.00	7331021076303	1.90	8.46
Black accessory casing for AXIS P3807-PVE. Replace the original white casing to change the appearance of the camera. Sold in packs of 4.	\$ 209.00	7331021076280	7.80	19.09
Accessory black casing for AXIS P3265-LV, V. 4pcs bulk pack.	\$ 89.00	7331021078376	0.99	6.30
Accessory black casing for AXIS P3265-LVE 9 mm. Pre-assembled with anti-loss screws. 4pcs bulk pack.	\$ 109.00	7331021078413	1.21	6.30

Accessory clear dome with special hydrophilic coating. Helps to prevent water droplets from covering the dome in rainy conditions. The coating also provides a self-cleaning effect that helps carry away dirt and dust by rain-wash. Compatible with AXIS P3807-PLE, AXIS Q3615- VE and AXIS Q3617-VE. Single pack	\$ 109.00	7331021068247	0.88	7.09
Accessory black casing for AXIS P3265-LVE 22 mm, P3267-LV, P3267-LVE, P3268-LV, P3268- LVE. Pre-assembled with anti-loss screws. 4pcs bulk pack.	\$ 109.00	7331021078437	1.10	6.30
Accessory casing compatible with Q3819-PVE. Includes anti loss screws, weather cover, cover lid, and cover top.	\$ 139.00	7331021076297	1.90	8.46
Smoked dome with anti-scratch hard coating. Compatible with AXIS Q3536-LVE, AXIS Q3538- LVE. 5x domes per pack.	\$ 219.00	7331021078765	1.76	10.63
Accessory clear dome with special hydrophilic coating. Helps to prevent water droplets from covering the dome in rainy conditions. The coating also provides a self-cleaning effect that helps carry away dirt and dust by rain-wash. Compatible with selected cameras from AXIS Q61 series, e.g.: AXIS Q6124-E, AXIS Q6128-E, AXIS Q6155-E. Single pack.	\$ 159.00	7331021068209	0.47	6.50
Accessory clear dome with special hydrophilic coating. Helps to prevent water droplets from covering the dome in rainy conditions. The coating also provides a self-cleaning effect that helps carry away dirt and dust by rain-wash. Compatible with selected cameras from AXIS Q61 series that support IR illumination, e.g.: AXIS Q6125-LE. Single pack.	\$ 159.00	7331021068216	0.47	6.50
Smoked dome cover including dome cover ring. Compatible with legacy AXIS Q60-E/-C cameras. See axis.com for updated compatibility list.	\$ 149.00	7331021069527	1.68	8.98
Standard smoked dome with anti-scratch hard coating. Compatible with AXIS Q60-E cameras. Weather-resistant and chemical-resistant. Rubber gasket, ring compass, ring support included. Single pack.	\$ 169.00	7331021076846	1.54	9.25
Smoked plastic dome for AXIS 231/232D+ dome cameras	\$ 28.00	7331021018464	0.51	7.48
Clear and Smoked plastic dome for AXIS 233D dome cameras	\$ 79.00	7331021021655	3.59	11.02

Outdoor accessory weathershield for AXIS P3265-LVE, P3267-LVE, P3268-LVE. A black accessory weathershield that goes well with black casing and smoked dome. The underside of the cover is specially coated with matte black anti-reflective coating to prevent reflections from external light sources. Anti- loss screws included. Bulk 2 pack.	\$7	9.00	7331021080522	0.55	5.31
Accessory black dome cover for AXIS M5000 & AXIS M5000-G. Includes dome and cover, 4 SCREW TX+ 8 DOME FLANGE, and 2 spring clips.	\$6	9.00	7331021077188	1.43	10.04
Accessory smoked dome with anti-scratch hard coating. Compatible with AXIS P3265-LVE 22 mm, P3267-LV, P3267-LVE, P3268-LV, P3268- LVE. 4pcs bulk pack.	\$ 10	9.00	7331021079304	1.38	11.61
Smoked dome accessory with anti-scratch hard coating. Compatible with:AXIS M3215-LVE, AXIS M3216-LVE. 4pcs bulk pack.	\$ 12	9.00	7331021080157	1.28	11.61
AXIS TP3819-E Dome Smoked, is a smoked dome and is offered as an optional accessory for AXIS P4705-PLVE and P4707-PLVE.	\$2	9.00	7331021078147	0.35	4.72
AXIS TP3825-E Weathershield Black, is a black weathershield and is offered as an optional accessory for AXIS P4705-PLVE and P4707- PLVE.	\$2	9.00	7331021079724	0.40	6.69
AXIS TF1803-RE Lens Protector 4P is a bulk pack of 4x Lens Protectors for AXIS F2135-RE. AXIS TF1803-RE is highly recommended to protect the sensor lens when AXIS F2135-RE is installed in harsh environments such as on the coast line, hot places with direct sun exposure on the sensor or if the sensor is subject to strong detergents. AXIS TF1803-RE is IK10 rated.	\$6	9.00	7331021077263	0.22	3.94
AXIS TF1802-RE Lens Protector 4P is a bulk pack of 4 Lens protectors for AXIS F2105-RE standard sensor. AXIS TF1802-RE Lens Protector is highly recommended to protect the sensor lens when AXIS F2105-RE is installed in harsh environments such as on the coastline, hot places with direct sun exposure on the sensor or if the sensor is subject to strong detergents. AXIS TF1802-RE is IK10 rated.	\$6	9.00	7331021077256	0.22	3.94
AXIS TF1801-R Lens Hood 4P is a bulk pack of 4x Lens Hood for AXIS F2105-RE standard sensor and AXIS F2135-RE fisheye sensor. The Lens Hood avoids reflections on the sensor unit lens when used as front facing camera onboard a vehicle. Lens Hood is made of silicone.	\$ 1	9.00	7331021074767	0.18	1.77

AXIS TP3827 Clear Dome Cover 10p is bulk pack of 10 original top cover with dome for	\$ 299.00	7331021082038	1.81	4.72
AXIS M3905-R and AXIS P3905-R MkIII cameras.				
AXIS TP3830 Top Cover Black 10p is a bulk pack of 10 top covers black without dome compatible with AXIS M3905-R and P3905-R MkIII cameras.	\$ 159.00	7331021082045	0.93	4.72
Smoked dome accessory with anti-scratch hard coating. Compatible with AXIS Q3626/8-VE.	\$ 39.00	7331021083981	0.43	5.71
Accessory casing with ring, and 4 anti-loss screws.	\$ 79.00	7331021084995	1.21	8.07
AXIS TM3814 Skin Cover Black 4-Pack, are outdoor-ready skin covers compatible with AXIS M4317/M4318-PLVE cameras for changing the appearance of the camera, simplify re- painting and covering screws. Black color.	\$ 89.00	7331021079564	0.66	6.10
Black accessory casings for AXIS M42 series. Replaces the original white casings. 4-piece bulk pack.	\$ 59.00	7331021082601	0.44	5.12
Cover top black casing for AXIS M4327-P and AXIS M4328-P. Comes in 4 Pack.	\$ 69.00	7331021084544	0.44	5.91
Vandal case accessory with dome for AXIS M4327-P and M4328-P. Comes in 4 pack.	\$ 89.00	7331021084551	0.53	4.33
Hard coated clear dome for AXIS Q6114- E/Q6115-E. Includes an O-ring.	\$ 79.00	7331021086609	0.53	7.68
Hard coated scratch resistant smoked dome for AXIS Q6124-E, Q6128-E, Q6154-E, Q6155-E. Includes O-Ring.	\$ 119.00	7331021086616	0.61	7.68
Accessory black dome casing for AXIS P3735- PLE, AXIS P3737-PLE, AXIS P3738-PLE. Casing with 4 screws anti loss TR20 included. Dome not included	\$ 79.00	7331021085916		
Accessory Smoked dome for AXIS P3735-PLE, AXIS P3737-PLE, AXIS P3738-PLE. The smoked dome can replace the clear dome delivered with the camera.	\$ 79.00	7331021085923	2.02	
Wall mount in electro-polished 316L stainless steel for AXIS XPQ1785, designed for harsh industrial environments. Max load 150 kg / 331 lb.	\$ 1,099.00	7331021075917	9.48	7.87
Pole mount in electro-polished 316L stainless steel for use together with AXIS TQ1001-E WALL MOUNT, designed for harsh industrial environments. Pole diameters 50-150 mm (2" - 6"). Max load 150 kg / 331 lb.	\$ 1,099.00	7331021076136	12.57	9.45
Corner bracket for AXIS XPQ1785 Explosion- protected PTZ Camera, to be used with AXIS TQ1001-E Wall Mount. Electro-polished stainless steel (316L) for harsh industrial and maritime environments. Max load 150 kg / 331 lb.	\$ 1,099.00	7331021081062	10.69	1.18

Explosion-protection certified "Ex d" M20x1.5 to 3/4" NPT nickel-plated brass thread reduction adapter. Worldwide certifications for use in Class I/II/III Div 1, Class I Zone 1, 21 and Zone 1, 21.	\$ 69.00	7331021083301	0.24	6.10
The power supply is UL certified and made of epoxy powder coated copper free aluminum with stainless steel cover bolts and hinges. It is pre-mounted with fuses, terminals, RJ45 coupler and 115/230 V AC transformer, which provides 24 V AC for Explosion Protected Cameras. The cabinet has 3 open ³ / ₄ "NPT cable entries and a fourth plugged entry and is Class I, Div 1 & 2, Class II, Div 1 & 2, Class 3, cUL to CSA C22.2 No. 30, No. 25 and NEMA 3 & 4 certified for temperatures between -40°C and +55°C. Weight is 67.3 lb (30.5 kg).	\$ 7,999.00	7331021056718	77.16	18.31
The Electro-polished 316L stainless steel pole bracket is specifically designed for top mounting installations of XF40 and suitable for onshore, offshore, marine and heavy industrial applications. It features a swivel movement of pan ±90° and tilt ±45° and its weight is 1.1kg.	\$ 499.00	7331021050440	2.87	4.53
Electro-polished 316L stainless steel wall mount for XF40, designed for onshore, offshore, marine and heavy industrial applications. Can also be used in conjunction with Bracket Pole Clamp Adaptor XF40 EX for pole mounting. It features a swivel movement of pan ±90° and tilt ±45° and its weight is 2.5 kg.	\$ 999.00	7331021050457	6.17	11.42
Pole mounting explosion protected fixed network cameras is made simple using this electo-polished 316L stainless steeel Ex Pole mount XF40, accompanied by the requisite Ex Wall Mount XF40. The Ex Pole Mount XF40 is specifically designed to mount Ex Wall Mount XF40 to poles of a diameter from 90mm to 120mm. Weight 4.2 kg.	\$ 699.00	7331021050471	11.02	7.28
316L Stainless steel wall mount for use with D201-S AXIS Q6055 explosion-protected camera.	\$ 599.00	7331021064546	11.66	12.60
Stainless steel (1.4404 / 316L) wall bracket for fixed explosion-protected cameras in the ExCam range, includes hinge and mounting material.	\$ 1,199.00	7331021065062	16.09	10.63
Replacement wiper blade for ExCam XF Q1785. Natural black rubber, 54mm, 10-pack.	\$ 209.00	7331021069213	0.26	3.94

Plastic protective film for the front glass of the F101-A explosion-protected cameras. For use in highly corrosive atmospheres like hydrogen fluoride (HF) gas. Set of 5.	\$ 159.00		7331021071230	0.14	4.33
Explosion-protected PoE++ switch and for use with up to 8 cameras, certified for use in hazardous areas according to ATEX and IECEx, in an Ex d copper free and sea water resistant aluminum enclosure. Model name: T04.6- D.BOR-8PoE++-1000BaseXX. Ex II 2G Ex d IIC [op pr] T5 Gb, Ex II 2D Ex t IIIC T95°C Db IP66, operating temperature -60°C to +50°C. Input voltage 100 VAC – 240VAC, network uplink 2x 10BASE-T/100BaseTX/1000BASE-T, 2x SFP, network output 8x PoE++ IEEE802.3at/bt, max 60W/port).	\$ 13,499.00		7331021083035	130.07	31.50
Explosion-protection certified "Ex d" M25x1.5 to 3/4" NPT nickel-plated brass thread reduction adapter. Worldwide certifications for use in Class I/II/III Div 1, Class I Zone 1, 21 and Zone 1, 21.	\$ 69.00		7331021083912	0.23	6.10
Explosion-protection certified "Ex d" M20x1.5 to 1/2" NPT nickel-plated brass thread reduction adapter. Worldwide certifications for use in Class I/II/III Div 1, Class I Zone 1, 21 and Zone 1, 21.	\$ 69.00		7331021083905	0.19	6.10
Explosion-protection certified "Ex d" M25x1.5 to M20x1.5 nickel-plated brass thread reduction adapter. Worldwide certifications for use in Class I/II/III Div 1, Class I Zone 1, 21 and Zone 1, 21.	\$ 69.00	•	7331021083929	0.22	6.10
Stainless steel (316L) weather shield for AXIS XPQ1785.	\$ 199.00		7331021076785		
Stainless steel (316L) weather shield for AXIS XFQ1656.	\$ 199.00		7331021083943	2.36	14.96
Swivel joint in stainless steel (316L) for flexible mounting of AXIS XFQ1656 on AXIS TQ1001-E Wall Mount.	\$ 199.00		7331021083950	1.83	9.45
Silicon wiper blade spare part for AXIS XFQ1656, sold in quantity of 5.	\$ 49.00		7331021083967	0.10	6.10
Replacement washer nozzle in stainless steel (316L) for AXIS XFQ1656.	\$ 59.00		7331021083936	0.12	6.10
Replacement 2-pin power connector with 7.62mm pitch, for AXIS XFQ1656.	\$ 19.00		7331021084599	0.02	2.36
Replacement 2-pin AUX connector with 5.08mm pitch, for AXIS XFQ1656.	\$ 19.00		7331021084582	0.01	2.36
Replacement 6-pin I/O connector with 3.81mm pitch, for AXIS XFQ1656.	\$ 19.00		7331021084605	0.01	2.36

 1.5" NPT Male-to-Male coupler used to connect any AXIS Pendant Kit (e.g.: AXIS T94A01D) to a legacy mount with Female NPT or NPS thread (e.g.: 3rd party wall mount). Useful in retrofitting legacy cameras in existing installations. Lock nut included. Material:Aluminum with black anodizing. Note: The National Pipe Taper (NPT) is a U.S. standard for tapered threads used on threaded 	\$ 49.00	7331021066762	0.32	3.31
pipes and fittings. The National Pipe Straight (NPS) threads are straight (parallel). Both NPT and NPS have the same thread angle, shape, and pitch (threads per inch).				
Wall mount bracket for AXIS T8640 Ethernet over Coax adapter base or device unit.	\$ 25.00	7331021001626	0.18	3.74
DIN rail clip for AXIS 8640 Ethernet over Coax adapter.	\$ 22.00	7331021001640	0.22	4.92
Kit for mounting an AXIS T8642 e.g. inside an AXIS Q8414-LVS. Kit contents: cable tie 432mm (17 in) long, BNC male to female angled adapter and network cable 135 mm (5.3 in) long.	\$ 14.00	7331021047518	0.15	4.13
Rack mount bracket for AXIS T8640 Ethernet over Coax adapter (8 units in 1U).	\$ 62.00	7331021001633	0.60	19.69
DIN rail clip for AXIS Q7401, AXIS P8221 and AXIS 7701.	\$ 12.00	7331021035812	0.13	1.46
DIN rail clip for AXIS M7014 and AXIS P7214	\$ 12.00	7331021035829	0.15	1.46
DIN rail clip for AXIS Q7424-R.	\$ 19.00	7331021001343	0.44	4.72
Holding device for pendant mounted cameras. For use with 3/4" pipes with NPS or NPT threading. Compatible with all cameras with standard tripod threading.	\$ 39.00	7331021037588	0.62	4.72
Holding device for pendant mounted cameras. For use with 1,5" pipes with NPS or NPT threading. Compatible with all cameras with standard tripod threading.	\$ 39.00	7331021037595	0.75	4.72
Pipe adapter step up from 3/4" NPT thread to 1.5" NPS thread. Compatible with all pendant kits that are made for the AXIS T91A range of brackets.	\$ 12.00	7331021035706	0.23	5.91
Plastic mounting kit with stand and clamp for flexible moutning of Axis products with tripod thread.	\$ 19.00	7331021051034	0.20	4.13
Plastic camera stand. Original stand for the AXIS M11-series.	\$ 15.00	7331021032668	0.22	3.15

10-pack threaded ceiling mount for quick installation under ceiling tiles. Compatible with cameras with standard 1/4"-20 UNC tripod thread. Total length 80mm (3") with thread length 65mm (2.5"). Threaded rod in nylon, counter nut with friction pad. 10-piece bulk pack.	\$ 49.00	7331021063648	0.36	6.50
4-pack of ceiling mount accessory for mounting Axis cameras and stands on a variety of drop- ceiling tile grid system. Compatible with Axis Safety Wire. Color: Axis white. Bulk pack. Suitable tile grid (T-bar) dimensions: 15mm(0.6in)/24mm(0.9in)/35mm(1.4in). Suitable ceiling tiles type: square-edge, tegular edge.	\$ 89.00	7331021065840	0.99	4.92
4-pack of lighting track mounts. Color: white. Compatible with universal 3-circuit lighting track systems and selected linear trunking systems. Compatible with a wide range of Axis cameras and camera stands.	\$ 89.00	7331021063679	0.89	4.84
4-pack of lighting track mounts. Color: black. Compatible with universal 3-circuit lighting track systems and selected linear trunking systems. Compatible with a wide range of Axis cameras and camera stands.	\$ 89.00	7331021063747	0.89	4.84
Rack mount kit for AXIS T8508 PoE+ Network Switch	\$ 29.00	7331021062399	0.62	3.15
Black aluminum stand for wall or hard ceiling mount. A cable hole in the base of the stand makes it possible to hide the hole in the wall out of which the cable is routed. A snap on cover gives a clean look without visible screws. Compatible with all standard tripod thread cameras e.g. AXIS M11, P13, Q16 series.	\$ 39.00	7331021048935	0.66	7.87
White aluminum stand for wall or hard ceiling mount. A cable hole in the base of the stand makes it possible to hide the hole in the wall out of which the cable is routed. A snap on cover gives a clean look without visible screws. Compatible with all standard tripod thread cameras e.g. AXIS M11, P13, Q16 series.	\$ 39.00	7331021048928	0.68	8.27
Pole mount bracket compatible with all cameras with standard tripod threading (1/4"-20 UNC)	\$ 39.00	7331021005020	0.95	11.22
AXIS T91B47 Pole Mount for indoor and outdoor installations, for poles with diameter between 100-410 mm (4"-16"). Includes 1 pair of AXIS Stainless Steel Straps 1450mm (57") with TX30 screw interface for ease-of-installation. AXIS T91B47 is directly compatible with a wide range of Axis cameras.	\$ 99.00	7331021061248	1.94	8.66

\$ 89.00		7331021061255	1.72	8.66
\$ 129.00		7331021063709	4.63	9.57
\$ 149.00		7331021063440	4.63	9.65
\$ 109.00		7331021063730	3.44	12.68
\$ 59.00		7331021061088	3.75	7.87
\$ 59.00		7331021069565	3.03	5.91
\$ 99.00		7331021040564	4.21	9.84
\$ 49.00		7331021047693	1.28	5.31
\$ \$ \$ \$ \$	\$ 129.00 \$ 149.00 \$ 109.00 \$ 59.00 \$ 59.00 \$ 99.00	\$ 129.00 \$ 149.00 \$ 109.00 \$ 59.00 \$ 59.00 \$ 99.00	\$ 129.00 7331021063709 \$ 149.00 7331021063440 \$ 109.00 7331021063730 \$ 59.00 7331021063730 \$ 59.00 7331021069565 \$ 99.00 7331021040564	\$ 129.00 7331021063709 4.63 \$ 149.00 7331021063440 4.63 \$ 109.00 7331021063730 3.44 \$ 59.00 7331021061088 3.75 \$ 59.00 7331021069565 3.03 \$ 99.00 7331021040564 4.21

Aluminum wall mount with IP66 compartment to safely accommodate power and connectivity accessories (e.g. PoE midspan). IK10 and NEMA 4X rated in Axis white color. Includes a pre-terminated IP66 rated RJ45 connector. Compatible with wide range of Axis cameras, incl. AXIS M55, P56, Q37, Q60, Q61 Series.	\$ 219.00	7331021049932	10.63	10.83
Aluminum wall mount with IP66 compartment to safely accommodate power and connectivity accessories (e.g. PoE midspan). IK10 and NEMA 4X rated in Urban Grey color to match AXIS Q62 series. Includes a pre-terminated IP66 rated RJ45 connector. Compatible with wide range of Axis cameras.	\$ 249.00	7331021063426	10.69	11.22
AXIS TS2901 Appliance Stand is a stand compatible with AXIS S2208 and AXIS S2212 Appliances which allows the unit to be mounted vertically, on a table or shelf. The appliance is secured to the stand with the 4 included screws. Mounted vertically, the appliance will take even less space than it usually does, leaving more space for other activities. The stand itself can be screwed to the table/shelf, which is a simple way to secure the appliance against light thefts and from falling. It can also lie on the table, when using the included rubber feet.	\$ 39.00	7331021071308	2.03	6.30
AXIS T91H61 Wall Mount is designed with a built-in RJ45 cable and connectionto, and spacious compartment for connectivity accessories such as midspans and media converters. The wall mount is impact-resistant (IK10) and weather-resistant (IP66, NEMA 4X) for indoor and outdoor use. The 1.5" NPS thread mount ensures compatibility with all pendant kits for Axis fixed dome cameras.	\$ 199.00	7331021057067	10.45	9.25
Wall mount for AXIS Q3505-SVE, made of stainless steel.	\$ 429.00	7331021051072	3.26	9.06
Wall-and-Pole Mount for Axis PTZ and multi- sensor cameras. Built-in Ethernet cable with an IP66 RJ45 connector for quick installation with protection against dust and water. Connect PoE via either RJ45 or IDC (insulation- displacement contact) connectors. Suitable for both indoor and outdoor environments. Separate stainless steel straps required for pole installation.	\$ 119.00	7331021055568	4.85	7.87

Marine-grade stainless steel wall mount for AXIS Q6055-S PTZ Network Camera. Compatible with stainless steel pole mount (sold separately).	\$ 429.00	7331021060395	3.97	4.72
Aluminum wall mount for Axis positioning cameras and positioning units. Robust and impact-resistant. Compatible with Axis ACI 3/4" conduit adapters, and offers multiple cable entries. Cables can be routed through the back or, by using a conduit connection, from each side or from the bottom. Suitable for indoor and outdoor use.	\$ 219.00	7331021059955	12.02	24.80
Robust and impact-resistant aluminum wall mount for selected Axis PTZ and positioning cameras. Multiple cable entry points for 3/4" (M25) conduit pipes. Suitable for indoor and outdoor use. Color: Urban Grey.	\$ 249.00	7331021063433	12.24	10.24
Made for parapet and wall installations. Telescopic arm with adjustable length between 783 mm (30.1 in) to 1033 mm (40.7 in) for compensating different parapet thicknesses or obstructive elements on the facade of the building. It can Swivel round its own axis 180 degrees, allowing mounting/maintain the camera easily and safely from the rooftop. The mount is intended for outdoor fixed and PTZ dome cameras supporting 1.5" NPS thread. A retrofit mounting bracket (optional accessory) makes it possible to reuse holes drilled for Pelco's PTZ dome parapet mount.	\$ 379.00	7331021052253	16.58	28.54
Retrofit adapter mount bracket for re-using holes drilled from Pelco's PTZ dome parapet mount, or for increasing the attachment area towards the parapet.	\$ 69.00	7331021052512	3.11	11.42
Chromated and powder coated aluminum parapet mount compatible with fixed dome pendant kits and AXIS P55-series and AXIS Q60- series PTZ dome cameras. Cable routing from behind or through 3/4" conduit hole on the side. Includes mounting plate, pipe seal, conduit hole cover and AXIS T94A01D Pendant Kit for PTZ dome cameras. Color: White	\$ 189.00	7331021006560	8.64	18.90

Indoor/outdoor telescopic ceiling mount. Expands between 1 m (39") and 2 m (79"). Features a swivel action to prevent breaking if hit by forklifs or high vehicles. Can be mounted on a sloped ceiling. Accessory extension pipes (Not included) for a maximum lengh of 5 m (197"). Compatible with all Axis pendant kits featuring a 1,5" NPS thread and the AXIS T91A05 Camera holder for fixed cameras.	\$ 219.00	7331021051478	11.57	6.69
The indoor/outdoor ceiling mount is ideal for low ceiling installations such as parking houses, with swivel action to prevent breaking if hit. Can be mounted in a sloped ceilings/soffits to compensate angles up to 45 degrees. Available accessory extension pipes (Not included) of 30 cm (12") or 1 meter (39") to enable correct camera height for the specific environment. Compatible with all Axis pendant kits featuring a 1,5" NPS thread and the AXIS T91A05 Camera holder for fixed cameras.	\$ 129.00	7331021051553	3.09	7.28
Extension pipe for AXIS T91B50 and AXIS T91B51. Length 30 cm (12").	\$ 49.00	7331021052505	1.37	2.56
Extension pipe for AXIS T91B50 and AXIS T91B51. Length 100 cm (39").	\$ 59.00	7331021052499	3.84	2.56
Twin-pack (bulk). Includes 2x indoor telescopic ceiling mounts, extendable between 1m to 1.8m (3.2 to 6ft) at 10cm (4") intervals. Compatible with Axis pendant kits and camera holder with 3/4" conduit interface. Suitable for vertical and horizontal mounting.	\$ 189.00	7331021061798	7.05	7.28
Chromated and powder coated aluminum ceiling mount 75 cm / 29.5 inch compatible with fixed dome pendant kits and AXIS P55-series and AXIS Q60-series PTZ dome cameras. Cable routing from behind or through 3/4" conduit hole on the side. Includes mounting plate, pipe seal, conduit hole cover and AXIS T94A01D Pendant Kit for PTZ dome cameras. Color: White	\$ 129.00	7331021006577	7.17	11.81
Corner Bracket that is compatible with several wall mounts: AXIS T91B61 Wall Mount, AXIS T91D61 Wall Mount 1.5" NPS, AXIS T91G61 Wall Mount, AXIS T91H61 Wall Mount, AXIS T91L61 Wall-and-Pole Mount. These wall mounts in turn are compatible with AXIS P55- series, AXIS Q60/61/63-series, AXIS M32-series, AXIS Q37-series, AXIS M55-series, AXIS P56- series and their associated pendant kits.	\$ 89.00	7331021029798	3.35	7.87

Pole mount bracket for AXIS Q35-SLVE stainless steel cameras. Compatible with AXIS T91F61 Wall mount. Made of marine-grade stainless steel. Includes 1 pair marine-grade (SS316L) stainless steel straps with TX30 screw interface for ease-of-installation. Straps length 1450mm (57"), suitable for pole diameter range 100-410mm (4"-16").	\$ 149.00	7331021051089	2.76	8.66
Pipe seal for AXIS T91A6, to protect from dust, water and bugs.	\$ 11.00	7331021003750	0.09	10.83
Aluminum conduit back box for wall or pole mount. Space for outdoor power supply, and electrical connection boxes. Steel straps for pole mount are sold separately. Recommended to use with POWER SUPPLY PS24 240W (not included).	\$ 219.00	7331021060715	4.52	8.46
For attaching AXIS Q61 PTZ network camera to AXIS Q6000-E MkII PTZ network camera.	\$ 109.00	7331021059702	2.05	10.43
Pendant kit for the AXIS Q60-series and AXIS P55-series PTZ Network Cameras, enables mount on standard '1,5" NPT threaded brackets. White.	\$ 59.00	7331021029354	0.77	6.50
Marine-grade stainless steel pendant kit for AXIS Q60-S with 1.5" NPT male thread.	\$ 139.00	7331021060401	0.88	7.20
Bracket for mounting an AXIS P56 Series camera in a hard ceiling. For indoor and outdoor installations. 3/4" conduit hole, compatible with ACI adapters.	\$ 39.00	7331021048256	0.62	4.72
Aluminum ceiling bracket for Axis PTZ cameras and AXSI Q37 Series for indoor or outdoor use. 3/4" conduit hole on the side.	\$ 59.00	7331021054332	0.66	4.72
Outdoor recessed mount for AXIS Q60-E cameras. Can be mounted in panels, wood or pre-made holes solid concrete. The mount is very sturdy and made of aluminum and stainless steel. It supports the IK10 impact rating of the camera and has two 3/4" conduit holes for a plenum rated and rodent safe installation.	\$ 269.00	7331021045835	5.71	12.60
Outdoor recessed mount for AXIS P56 cameras. Also suitable indoor for recessed camera installations in plenum as the back box is made of metal and has a 3/4" hole for cable protection conduits.	\$ 149.00	7331021047358	3.48	12.60
Indoor and outdoor recessed mount for AXIS Q61 Series. Suitable indoor for recessed camera installations in air handling spaces as the back box is made of metal and has a 3/4" hole for cable protection conduits.	\$ 149.00	7331021054349	3.51	12.40

Pendant kit for wall mount or ceiling mount. Compatible with Axis mounting accessories with 1.5" NPS thread. 3/4" threaded pipes can also be used with a nut for securing. Compatible with the small form factor of AXIS M20, M31-LV/-LVE, M30-V/-WV and Companion dome cameras. 10-pack.	\$ 219.00	7331021061194	2.18	8.27
Pendant kit for wall mount or ceiling mount. Compatible with Axis mounting accessories with 1.5" NPS thread. 3/4" threaded pipes can also be used with a nut for securing. Compatible with the small form factor of AXIS M20, M31-LV/-LVE, M30-V/-WV and Companion dome cameras. Single pack.	\$ 39.00	7331021053144	0.29	1.97
Pendant kit for wall mount or ceiling mount in black. Compatible with Axis mounting accessories with 1.5" NPS thread. 3/4" threaded pipes can also be used with a nut for securing. Compatible with the small form factor of AXIS M20, M31-LV/-LVE, M30-V/-WV and Companion dome cameras. Single pack.	\$ 39.00	7331021061767	0.29	4.84
Indoor recessed mount for drop ceiling installation. The aluminum casing makes it suitable for use in air handling spaces. Compatible with AXIS M3044-V/M3045-V/M3046- V/M3047-V/M3048-V.	\$ 79.00	7331021061101	1.39	6.10
Indoor recessed mount for drop ceiling installations. The aluminum casing makes it suitable for use in air handling spaces. Compatible with AXIS M2025/26 and AXIS Companion Bullet.	\$ 79.00	7331021056190	1.23	6.10
Bracket for mounting a camera on a 4" square, 4" octagon, single or double-gang junction box. Compatible with AXIS M3044-V/M3045-V/M3046- V.	\$ 39.00	7331021052529	0.44	6.89
Conduit back box for 1/2" or M20 pipes. Features the 1/2" ACI interface to enable use of ACI adapters. There is an integrated female tripod thread for use of standard camera stands or holders. Compatible with AXIS M3044-V/M3045-V/M3046- V.	\$ 29.00	7331021053151	0.22	4.33
Indoor recessed mount for drop ceiling installations. Single-screw ceiling attachment for quick and easy installation. Not suitable for air-handling (plenum) spaces. Compatible with AXIS M42 series and AXIS Companion Dome mini LE.	\$ 49.00	7331021062979	0.79	2.95
Bracket for mounting camera on 4" square, 4" octagon, single or double-gang junction box. Compatible with AXIS M42 Series and AXIS Companion Dome mini LE.	\$ 39.00	7331021062986	0.33	7.68

Versatile 4-in-1 mount accessory for use as either a pendant kit with 3/4" (M25) conduit interface, conduit back box with 1/2" (M20) conduit side entry, pole mount, or standard camera thread. Compatible with AXIS M42 series and AXIS Companion Dome mini LE. Pole mounting straps available separately.	\$	39.00	7331021062993	0.31	1.77
White plastic adapter for mounting AXIS P3904- R and AXIS P3905-R on flat surfaces. Does not fit with AXIS P3915-R. Used when the cable must enter from the side. 10 pack.	\$	39.00	7331021043886	1.52	4.72
White plastic adapter for mounting AXIS P3904- R, AXIS P3905-R and AXIS P3915-R on curved surfaces. 10 pack.	\$	39.00	7331021043893	0.50	4.53
Indoor pendant kit for AXIS M3006/7, AXIS M3024-LVE/3025-VE/3026-VE. to enable use of AXIS T91A Brackets or 1.5"(NPT or NPS threaded) pipes. The camera network cable fits into the product and a RJ45 network cable coupler is included.	\$	49.00	7331021004078	0.95	6.30
Mounting stand in plastic for wall and ceiling. Stand height 70 mm (2.7 in). Circular base with diameter 69 mm (2.7 in). White color.	\$	59.00	7331021085299	0.57	6.30
Outdoor pendant kit for M3024-LVE/M3025-VE, P14 Series, to enable use of AXIS T91A Brackets or 1.5"(NPT or NPS threaded) pipes.	\$	39.00	7331021005426	1.34	7.28
Bracket for mounting on 4" square, 4" octagon, single or double-gang junction box. RJ45 network cable coupler included. Compatible with. Compatible with AXIS M3006/7, AXIS M3024-LVE/3025-VE/3026-VE, P14 Series.	\$	39.00	7331021004658	0.42	6.89
Backbox for AXIS M3006-V, AXIS M3007-P/-PV, AXIS M3024-LVE/3025-VE/3026-VE/3027-PVE, P14 Series, which enables safe cabling through 1/2" (M20) conduits.	\$\$	39.00	7331021008083	0.53	6.50
Back box for 3/4" (M25) conduits/cable protection pipes. Compatible with AXIS Q1765- LE and AXIS Q1931-E.	\$	39.00	7331021040687	1.28	6.50
Indoor pendant kit for AXIS P32-V Series- AXIS P33/-V and AXIS Q3505-V, compatible with Axis ceiling-/wall mounts, AXIS T91A67 Pole mount and 1.5" NPS threaded pipes.	\$	49.00	7331021046061	0.82	8.07
Outdoor pendant kit for AXIS P32 & Q35 series. Compatible with several Axis ceiling, wall, and poll mounts, As well 1.5" NPS threaded pipes.	\$	69.00	7331021046078	1.41	8.66

Outdoor recessed mount for mid-size outdoor dome cameras such as: AXIS P32-VE/-LVE, P33- VE/-LVE and Q35-VE/-LVE series. Suitable for outdoor installations in roof overhangs and soffits. Also suitable for indoor installations in plenum spaces.	\$	119.00	7331021061163	3.53	10.43
AXIS T94N01D Pendant Kit comprises a weathershield and a mounting adapter for AXIS P3717-PLE Network Camera. The mounting adapter is compatible with 1.5-inch NPS thread. The kit enables AXIS P3717-PLE to be mounted on walls, poles, parapets and outer corners using AXIS T91 mounting accessories.	\$	99.00	7331021064348	1.12	10.83
AXIS T94N02D Pendant Kit comprises a weathershield and a mounting adapter for AXIS P3715-PLVE Network Camera. The mounting adapter is compatible with 1.5-inch NPS thread. The kit enables AXIS P3715-PLVE to be mounted on walls, poles, parapets and outer corners using AXIS T91 mounting accessories.	\$	69.00	7331021072060	1.11	6.69
Stainless steel pole mount designed for use with heavier Axis products such as positioning cameras and positioning units. IK10. Includes 3pcs stainless steel straps included for pole diameter 60-400mm (2.4-15.7in) and sealing gaskets for multiple cable entries with protection against insect infestation.	\$	219.00	7331021059962	5.22	10.83
Indoor and outdoor recessed mount for discreet installations in drop ceilings, roof overhangs/soffits of AXIS P37 network camera series. Also suitable for installations in plenum space, as the back box is made of metal with a ³ / ₄ " hole for cable protection conduits.	\$ }	129.00	7331021064355	3.15	12.99
Corner mount for AXIS P5414-E/15-E, AXIS Q1765-LE, AXIS Q1931-E and AXIS P33-VE series.	\$	89.00	7331021007987	3.17	10.04
Indoor and outdoor recessed mount for AXIS M55 Series. Suitable for air-handling spaces in indoor installations as the enclosure is made of metal and has a 3/4" (M25) conduit hole for protected cable-routing. UL-approved.	\$	109.00	7331021061347	2.82	11.02
Wall mount compatible with all Axis outdoor fixed box cameras and housings. Corrosion tested according to NEMA 4X, UL listed and IK10 rated.	\$	59.00	7331021042186	1.76	6.50

The powder-coated aluminum AXIS T94Q01F for AXIS fixed box outdoor ready cameras and housings, can be used for both ceiling/soffit and column/parapet installations. This allows Axis' fixed camera housings to be mounted under hard surfaces such as ceilings, beams, soffits and canopies. It can also be mounted on pole or column tops, parapets and other horizontal building structures. Re-direction and maintenance of the camera is easy thanks to the swivel arm feature. The cable is routed through the pipe, and is never exposed to weather or potential vandalism. Cable conduits and Axis' conduit adapters (3/4" dimension) are used for cable protection when routed from the side.	\$ 119.00	7331021054424	3.97	12.01
The powder-coated aluminum AXIS T94R01B Corner Bracket is used for attaching the wall mount of Axis' camera housing to the outer corners of a building. AXIS T94R01B Corner Bracket is compatible with AXIS T91E61 Wall Mount for fixed dome cameras. Small-size fixed dome and bullet-style cameras can also be mounted, thanks to the included and commonly used hole pattern of a single gang junction box.	\$ 69.00	7331021054431	1.32	6.22
Back box to enable external cable entry or use of cable protection equipment. Holes on top and side for 3/4 inch conduits or M25 cable protection pipes. Compatible with AXIS T94Q01A Wall mount, all AXIS M11-E/P13-E/Q16- E/Q1755-E/Q1910-E/21-E/22-E outdoor fixed box camera wall mounts and AXIS T92E Series and AXIS T93E05 Fixed camera housings.	\$ 59.00	7331021076068	1.46	7.09
Indoor recessed mount for drop ceiling installations. Single-screw ceiling attachment for quick and easy installation. Not suitable for air-handling (plenum) spaces. Compatible with AXIS P32-V/-LV series.	\$ 49.00	7331021058163	1.06	7.09
Indoor recessed mount for drop ceiling installations. Single-screw ceiling attachment for quick and easy installation. Not suitable for air-handling (plenum) spaces. Compatible with AXIS P32-V/-LV series. 10-pack.	\$ 429.00	7331021059993	8.58	15.94
Indoor recessed mount for ceiling/wall installations. Compatible with AXIS M3057/58- PLVE cameras. Single-screw ceiling attachment for quick and easy installation. Not suitable for air-handling (plenum) spaces.	\$ 59.00	7331021063624	1.04	3.15

Outdoor-ready, impact resistant (IK10+) back box with sealed compartment (IP66/67) for secure storage of connectivity devices. 3/4" / M25 conduit interface from both side and back. Can be mounted directly behind a wide range of Axis network cameras. Includes a network cable and extra gaskets.	\$ 129.00	7331021061804	2.09	8.07
Outdoor-ready, impact resistant (IK10+) back box with sealed compartment (IP66/67) for secure storage of connectivity devices. 3/4" / M25 conduit interface from both side and back. Can be mounted directly behind a wide range of Axis network cameras. Includes a network cable and extra gaskets. Specifically designed for aesthetically pleasing installations with AXIS Q17/Q19 and P14 Camera Series	\$ 159.00	7331021077034	2.06	8.07
Outdoor pendant kit for AXIS P32-VE Series, compatible with Axis ceiling-/wall mounts, AXIS T91A67 Pole mount and 1.5" NPS threaded pipes.	\$ 59.00	7331021046146	1.10	7.48
Outdoor pendant kit for AXIS M30-PLVE Series. Weathershield made from impact-, UV-, and heat-resistant polymer. Compatible with wide range of Axis mounts with 1.5" NPS threaded interface.	\$ 59.00	7331021063617	0.88	7.48
Pendant kit for AXIS Q3505-SVE, without weather shield, mainly for indoor use made of stainless steel.	\$ 409.00	7331021051058	2.18	9.65
Outdoor pendant kit with weather shield for AXIS Q3505-SVE, made of stainless steel.	\$ 449.00	7331021051065	3.24	10.63
AXIS T94V01C Dual Camera Mount allows back- to-back installation of two Axis cameras for panoramic coverage. Compatible with a wide range of Axis dome cameras, box cameras, and bullet cameras. Compatible with Axis mounting accessories with 1.5" NPS threaded interface, for mounting on walls, poles, and under ceilings. AXIS T94V01C is IK10 rated for impact resistance, which safeguards it against vandalism. Suitable for both indoor and outdoor use. Note: To ensure physical stability, do not use AXIS T94V01C for single camera installations.	\$ 109.00	7331021063570	2.48	8.46
Outdoor pendant kit for AXIS P38-PVE and Q36- VE series. Weathershield made from impact-, UV-, and heat-resistant polymer. Compatible with wide range of Axis mounts with 1.5" NPS threaded interface.	\$ 99.00	7331021064225	2.73	10.04

Pendant kit for indoor and outdoor use for the AXIS Q36-VE Series compatible with Axis ceiling-/wall-/pole mounts with 1.5" NPS thread.	\$ 99.00	7331021052871	2.29	10.24
Wall mount for AXIS T92F10 Outdoor Housing. 6-piece pack. Optional accessory: AXIS T94Y01G Pole Mount 6PCS (sold seperately)	\$ 159.00	7331021054257	12.02	11.81
Pole mount for AXIS T92F10 Outdoor Housing, with 1 pair stainless steel straps included per piece. 6-piece pack. Required accessory: AXIS T94X01A Wall Mount 6PCS (sold separately)	\$ 179.00	7331021054264	4.52	12.20
Corner bracket for AXIS T98A-VE Surveillance Cabinet and AXIS Positioning Cameras. When used with AXIS Positioning Cameras, AXIS T94J01A Wall Mount is required.	\$ 99.00	7331021023604	5.56	8.07
Pole bracket for AXIS T98A-VE Surveillance Cabinet. No straps required.	\$ 139.00	7331021023611	5.69	5.51
Metal box to mount AXIS PS24 to a wall.	\$ 79.00	7331021016187	4.94	8.07
Outdoor pole mount bracket for PS-24 and AXIS T97A10. Requires the Wall Mount AXIS PS-24 (5000-011) and a mounting tool for straps (21776 or similar).	\$ 45.00	667026008047	3.51	9.45
The clip, made of steel, enables mounting on a standard 35mm DIN rail. It includes 2 cable ties. Compatible with AXIS T8120/T8133 midspans and AXIS T8604 / T8605 converters. Weight: 17 g (0.6 oz.). 5-pack.	\$ 19.00	7331021004856	0.49	6.50
Din clip for AXIS midspan T8123, T8124 and T8125	\$ 19.00	7331021046092	0.15	8.07
Mounting bracket for AXIS P33-V/-LV indoor cameras. For mounting cameras on junction boxes (4" square, 4" octagon, single-gang, or double-gang), and other Axis mounting accessories. Also compatible with selected AXIS M30 and P32 cameras.	\$ 39.00	7331021028135	0.55	6.50
Mounting kit for AXIS P1204/E. Kit contents: Flush mount wall bracket. 5 pack.	\$ 29.00	7331021004818	0.31	4.72
Aluminum cable cover with stainless steel adapter used for mounting 3/4" NPS or NPT pipes to AXIS P33XX-VE cameras for cable protection.	\$ 39.00	7331021003354	0.77	4.72
Mounting bracket compatible with AXIS Q1715. It includes bracket, pad, and TX20 screw.	\$ 19.00	7331021077430	0.22	3.54

Aluminum cable cover with stainless steel adapter used for mounting 3/4" NPS or NPT pipes to AXIS P33XX-VE cameras for cable protection. Four complete units.	\$ 144.00	7331021003361	2.20	6.50
Stainless steel adapter used for mounting 3/4" NPS or NPT pipes to AXIS P33XX-VE cameras for cable protection.	\$ 39.00	7331021036659	0.22	2.36
Cover ring and holder for installing selected AXIS P32 cameras with legacy AXIS T94S01L Recessed Mount. Bulk pack with 4 sets of rings and clips to retrofit 4 cameras.	\$ 49.00	7331021070158	0.86	7.68
Retrofit into T94K01L or T94K02L. Mic hole for - LV cameras. Includes 4 sets of lid ring cover, gaskets, screws.	\$ 89.00	7331021070639	1.71	8.35
Pendant kit for selected AXIS P33-VE Fixed Dome Network Cameras, compatible with mounts with 1.5" NPT/NPS threaded interface. Color: Axis white	\$ 59.00	7331021027138	1.90	11.02
Adapter plate for mounting an AXIS M31 using the same foot print as the AXIS 209. 50 PCS	\$ 269.00	7331021038011	4.63	9.65
Aluminum cable cover for AXIS P33XX-VE cameras. 4 pcs.	\$ 59.00	7331021003378	0.84	4.72
Mechanical adapter that provides a U-shaped 30mm wide cable entry for use when a U-shape cable protection is required. The adapter is compatible with AXIS P54-series, AXIS P32-VE Series (requires AXIS ACI Mounting Bracket A), AXIS Q3505-VE, AXIS T91B6X mounts and AXIS AXIS T94R01P Conduit Back Box. 5 pcs.	\$ 39.00	7331021041271	0.35	4.72
Cable protection attachment bracket for AXIS P32-VE Series. Compatible with 3/4" Conduits, M25 pipes and AXIS ACI adapters. 5pcs.	\$ 39.00	7331021046184	0.35	6.89
Step up ACI adapter for attaching 3/4" conduits or M25 pipes to AXIS products with a 1/2" conduit interface such as AXIS P32-V series (requires AXIS ACI conduit bracket B) and AXIS Q3505-V. 2 pcs	\$ 49.00	7331021045996	0.49	4.76
Mechanical adapter that provides a U-shaped 20mm wide cable entry for use when a U-shape cable protection is required. The adapter is compatible with AXIS products with a 1/2" conduit interface such as AXIS P32-V series (requires AXIS ACI conduit bracket B) and AXIS Q3505-V. 5 pcs	\$ 29.00	7331021046245	0.17	4.13
Threaded stainless steel step up ACI adapter for attaching 3/4" NPS conduits to AXIS products with a 1/2" conduit interface such as AXIS Q35-V series. 2 pcs	\$ 79.00	7331021046436	0.40	3.35

Threaded stainless steel ACI adapter for attaching 3/4" NPS conduits to AXIS products with a 3/4" conduit interface such as AXIS Q35- VE series. 2 pcs	\$ 109.00	7331021046443	1.04	3.35
Rack slides for AXIS Q7920 Video Encoder Chassis	\$ 79.00	7331021007314	5.31	5.91
AXIS F7308 comes in packs of four. 8-m (26 ft.) black cable with an RJ12 contact for connection to an AXIS F1004 Sensor Unit. Used as a spare part for the original cable that comes with AXIS F1004 Sensor Unit.	\$ 39.00	7331021049871	1.39	7.48
Lens protection for AXIS F1005-E. The lens protector is screwed onto the threaded front part of the sensor unit to protect the lens. Comes in pack of 5 units.	\$ 89.00	7331021045682	0.31	4.13
Mounting bracket that allows the pinhole sensor unit of AXIS F1025 to be mounted onto a flat surface with the cone being flush with opposite surface. Comes in pack of 5 pcs.	\$ 29.00	7331021045668	0.24	6.50
Metal bracket for stable mounting of AXIS F1005-E, F1015 and F1035-E. Variety of holes for screws for flexible mounting. Comes in pack of 5 units.	\$ 159.00	7331021047778	0.97	6.50
Trim ring for discreet mounting of AXIS F1025 Sensor Unit behind a thin surface. 10 PCS.	\$ 59.00	7331021050181	0.25	4.13
Trim ring for discreet mounting of AXIS F1005- E, F1035-E, P1214-E and P1224-E behind a surface. 10 PCS.	\$ 109.00	7331021050198	1.01	4.72
Bullet-style camera accessory for AXIS F1005- E. AXIS F1005-E provides 113° horizontal FOV. Comes with c-clamp and a stand.	\$ 29.00	7331021047631	0.33	6.50
Discreet accessory for ceiling mount of AXIS F1025 (pinhole). AXIS F1025 provides 92° horizontal FOV. Used to get overview of rooms or of a door. Can easily be repainted to fit ceiling color.	\$ 39.00	7331021048294	0.44	6.50
Discreet accessory to mount a AXIS F1035-E in a ceiling. Perfect for overview in small rooms or in parts of a larger room. Can easily be repainted to fit ceiling color.	\$ 39.00	7331021048300	0.44	6.50
Height strip housing for discrete mounting of a pin hole sensor unit, for capturing eye-level images e.g. of people leaving a store. It is compatible with AXIS F1025, FA1125, F1004 Pin hole, AXIS P1264 and P1265. Comes with both a metric and an imperial height strip. Black aluminium housing.	\$ 109.00	7331021066168	2.82	8.66

·				
Height strip housing for discrete mounting of a pin hole sensor unit, for capturing eye-level images e.g. of people leaving a store. It is compatible with AXIS F1025, FA1125, F1004 Pin hole, AXIS P1264 and P1265. Comes with both a metric and an imperial height strip. Silver aluminium housing.	\$ 99.00	7331021066175	2.82	8.66
Tiltable wall-mount for AXIS D2110-VE Security Radar and AXIS D2050-VE Network Radar Detector. Includes arm, AXIS T94R01P CONDUIT BACK BOX and conduit 260 mm (10 inch) cable kit.	\$ 129.00	7331021064461	4.41	12.80
AXIS TD4601 is an ACI Conduit Bracket for AXIS D4100-E Network Strobe Siren. 5P	\$ 39.00	7331021075689	0.17	3.15
Tilt Mount Plastic, 15deg tilt, 1/2" (M20) conduit. BRACKET MOUNT ASSEMBLY M3067.	\$ 39.00	7331021067196	0.28	5.12
Elegant mount for indoor mounting of Axis mini dome cameras in pendant style. Concealed mounting with no visible screws. Room for microphone and connectivity devices (e.g.: AXIS T6101, AXIS T8643). Compatible with wide range of cameras, incl. AXIS M20/M30/M31/M42, etc. Made from strengthened eco-friendly plastic.	\$ 49.00	7331021067103	0.53	5.31
Elegant mount in black for indoor mounting of Axis mini dome cameras in pendant style. Concealed mounting with no visible screws. Room for microphone and connectivity devices (e.g.: AXIS T6101, AXIS T8643). Compatible with wide range of cameras, incl. AXIS M30, AXIS M31, AXIS M42, etc. Made from strengthened eco-friendly plastic.	\$ 49.00	7331021068995	0.57	5.31
Recessed mount for selected AXIS M30 cameras. Includes covers for fixed mini dome and panoramic cameras.	\$ 49.00	7331021068582	0.82	5.31
Indoor recessed mount for ceiling/wall installations. Compatible with AXIS M4308-PLE. Single-screw ceiling attachment for quick and easy installation. Not suitable for air-handling (plenum) spaces.	\$ 59.00	7331021077157	1.00	7.28
Designed for indoor drop ceiling installations for selected Axis cameras (M3057/8 and M3077). It's robust with an IK10-rating and is easily installed. The enclosure is made of metal alloy, making it suitable for installations in air- handling (plenum) spaces. Casing includes mic holes for M3077 and plugs in mic holes when used with M3057/8.	\$ 129.00	7331021076716	2.29	8.86

Indoor recessed mount for ceiling/wall installations. Compatible with AXIS M3057- PLVE, AXIS M3057-PLVE Mk II, AXIS M3058- PLVE, AXIS M3077-PLVE. Single-screw ceiling attachment for quick and easy installation. Not suitable for air-handling (plenum) spaces.	\$ 69.00	7331021077416	1.00	7.28
Indoor recessed mount for drop ceiling installation. The aluminum casing makes it suitable for use in air handling spaces. Compatible with AXIS M3064-V, AXIS M3065-V, AXIS M3066-V, AXIS M3067-P, AXIS M3068-P, AXIS M3075-V, AXIS M3085-V, AXIS M3086-V, AXIS M3088-V.	\$ 149.00	7331021077676	1.32	6.30
Indoor recessed mount for drop ceiling installation. The aluminum casing makes it suitable for use in air handling spaces. Compatible with selected AXIS M43 Series fisheye panoramic cameras.	\$ 149.00	7331021084520	1.15	6.30
Recessed mount for selected AXIS M43 cameras. Includes cover for fisheye panoramic cameras.	\$ 49.00	7331021084537	1.06	11.42
Adapter plate for mounting on conduit back box TP3603 or T94S01P. Plate is for P14 series and M42 series that allows for the cameras to look aesthetically pleasing when mounted onto a conduit back box.	\$ 39.00	7331021072312	0.28	6.30
Elegant mount for indoor mounting of Axis dome cameras in pendant style. Concealed mounting with no visible screws. Room for microphone and connectivity devices (e.g.: AXIS T6101, T8643) and AXIS I/O Indication LED. Compatible with AXIS M32-LVE and AXIS P32-V/-LV cameras. Made from strengthened eco-friendly plastic.	\$ 59.00	7331021067677	0.60	6.30
Outdoor pendant kit for AXIS P3265-LVE, P3267- LVE, P3268-LVE. Compatible with Axis mounts: ceiling, wall, parapet, poll and 1.5" NPS threaded pipes.	\$ 79.00	7331021079281	1.21	9.61
Indoor recessed mount for drop ceiling installation. Supports the optional use of an internal microphone. Metal enclosure with conduit entries, suitable for installation in air handling / plenum spaces. Compatible with: AXIS M32-LVE, AXIS P32-V/-LV, AXIS P33/-V and AXIS Q35-V/-LV series; and AXIS Device Microphone A and B.	\$ 89.00	7331021067400	2.43	8.86

Outdoor recessed mount for drop ceiling plenum installations. Supports the optional use of an internal microphone. Metal enclosure with conduit entries, suitable for installation in air handling / plenum spaces. Compatible with: AXIS M32-LVE, AXIS P32-VE/-LVE. T94M02L used in the past for outdoor but size was too big not matching form factor.	\$ 149.00	7331021077461	2.38	8.86
Indoor recessed mount for drop ceiling installations. Single-screw ceiling attachment for quick and easy installation. Not suitable for air-handling (plenum) spaces. Compatible with selected AXIS M32 and AXIS P32 cameras.	\$ 49.00	7331021070165	1.09	11.61
Indoor recessed mount for drop ceiling installations. Single-screw ceiling attachment for quick and easy installation. Not suitable for air-handling (plenum) spaces. Compatible with selected AXIS M32 and AXIS P32 cameras.	\$ 59.00	7331021078529	1.07	11.42
Adapters for protected cable routing in 3/4" conduit (M25 pipe). Compatible with selected AXIS M32 and P32 cameras. 4pcs bulk pack.	\$ 39.00	7331021068032	0.20	2.76
TP3603 indoor conduit back box a complement to T94S01P at a lower price point for large indoor installations (eg data centers). Compatible with P32/M32 indoor versions as well as indoor versions of Q17/19/29, P33, Q35, and P14/M42(plate needed TP1601). TP3603 has two seperate conduit entries (1/2" & 3/4") and has space for connectors (e.g. T86 Media Converters & T6101 I/O interface).	\$ 59.00	7331021070967	0.94	6.30
Optional accessory for mounting over junction boxes or on poles. Plastic straps (two) are included. Compatible with AXIS TM3101 and TP3101 Pendant Wall Mount.	\$ 39.00	7331021067110	0.49	5.12
Step down ACI adapter 1" to ¾". IK8 and made of plastic. For attaching 1" conduits or M25 pipes to AXIS products with a 3/4" conduit interface such as P32 or conduit back boxes. Pack of 4.	\$ 219.00	7331021076754	0.31	6.30
An indoor metal pendant kit for mounting AXIS P8815-2 3D People Counter. Compatible AXIS ceiling mounts and 1.5" and 3/4" conduits.	\$ 49.00	7331021070820	0.53	3.94
A plenum rated recessed mount for P8815-2 3D People Counter	\$ 109.00	7331021070837	1.63	4.72
Adapters for protected cable routing in 1/2" conduit (M20 pipe). Compatible with selected AXIS M32 and P32 cameras. 4pcs bulk pack.	\$ 39.00	7331021068049	0.21	2.76

Metal bracket with snap-on features for replacing legacy AXIS P3214/15/24/25/35-VE/- LVE outdoor fixed dome cameras with the new AXIS P324x-VE/-LVE cameras. Bulk pack for retrofitting 4 cameras.	\$ 49.00	7331021068063	0.39	4.53
An outdoor pendant kit for mounting AXIS Q38 Series.	\$ 99.00	7331021072756	3.26	13.39
An indoor pendant kit for mounting AXIS Q38 Series.	\$ 69.00	7331021072763	1.36	7.87
Recessed mount for indoor and outdoor use of AXIS Q36, P38 and Q38 Series.	\$ 149.00	7331021073357	4.30	10.63
Parapet Mount is an outdoor-ready mount. The round base of the mount makes it easy to install as well as suitable for installations on poles. Cables can be routed through the bottom, or from the side by using a conduit connection. Chromated and powder coated aluminum parapet mount compatible with fixed dome pendant kits and AXIS P55-series and AXIS Q60-series PTZ dome cameras. Includes mounting plate, pipe seal, conduit hole cover. Color: White	\$ 219.00	7331021072787	8.38	19.02
CONDUIT TOP BOX for Q9216-SLV.	\$ 109.00	7331021068223	0.97	6.69
AXIS TQ6901-E is a useful adapter for retrofitting AXIS Q6215-LE in camera installations that have 3rd party competitor mounts. AXIS TQ6901-E is made of powder coated aluminum and is sold in packs of four.	\$ 219.00	7331021072794	3.31	6.30
AXIS TS3001 Recorder Mount ensures that the AXIS S3008 Recorder is in a fixed position either if it is mounted on walls, shelves, or under tables. Its design and shape allows the recorder to be mounted in two opposite directions.	\$ 19.00	7331021072268	1.10	7.87
Indoor and outdoor plenum recessed mount for AXIS Q6315-LE PTZ. Suitable for outdoor installations in roof overhangs and soffits. Also suitable for indoor installations in plenum spaces.	\$ 279.00	7331021072596	3.86	12.60
A crane and traffic mount for more stability and less vibrations. Note: Pivot mount for more stability, Robust, IK10, Coating in corrosion resilient material, offers more stability to your camera installations in demanding situations, such as mounting on cranes or traffic lights. NEMA 4X-ratings and can be tilted up to 45 degrees. Compatible with P13-E/LE, T92E, T93F, Q16-LE, T92G20, T91B47.	\$ 79.00	7331021076747	1.76	7.87

Designed for indoor drop ceiling installations for M4308. It's robust with an IK10-rating and is easily installed. The enclosure is made of metal alloy, making it suitable for installations in air- handling (plenum) spaces. Casing includes mic holes.	\$ 129.00		7331021076723	2.29	8.86
Designed for indoor drop ceiling installations for selected Axis cameras (M3067/8, M4216). It's robust with an IK10-rating and is easily installed. The enclosure is made of metal alloy, making it suitable for installations in air- handling (plenum) spaces.	\$ 129.00		7331021076730	1.32	6.30
Bracket to mount and secure a F series main unit onto a surface. It withstands vibrations and secures all cables to/from the main unit.	\$ 39.00		7331021076396	0.62	6.30
DIN clip + angled mounting bracket. Allows an AXIS F Series main unit to be mounted on a DIN rail with the short side against the rail to minimize used space. Main unit can be mounted with cables going in any of three directions (up, down or out from the rail).	\$ 39.00		7331021076402	0.40	6.30
Indoor conduit back box for AXIS M5000 & AXIS M5000-G. Has a conduit side entry with a conduit cover. Has 3 tx20 screws.	\$ 59.00		7331021077171	1.01	10.47
Strain relief accessory for AXIS D3110 Connectivity Hub, preventing cables getting lose over time causing disconnection of the device or sensors. Easy to mount, comes with two screws. 2 pack	\$ 29.00		7331021075726	0.01	4.33
Spare kit of connectors for AXIS D3110	\$ 19.00	ľ	7331021075757	0.03	2.36
Connectivity Hub. A conduit back box that gives more space needed for installation. Deeper back box than what product comes with and existing conduit back boxes. Compatible with P1455-LE, P1467/8-LE. Comes in Axis white and is IP66 and IK10.	\$ 79.00		7331021082205	1.06	6.69
AXIS TF1902-RE Mounting Bracket 4P is a bulk pack of 4x Mounting brackets. The mounting bracket is an accessory for the AXIS F2105-RE and F2135-RE, F7225-RE, FA1105, FA1125 and FA1080-E sensors. Thanks to the different hole pattens as well as the possibility to bend the bracket in numerous directions, AXIS TF1202-RE Mounting bracket gives extra flexibility and resilience of the sensor unit.	\$ 9.00	-	7331021074774	0.35	4.02

 TF1202-RE Recessed Mount 4P is a bulk pack of 4x Recessed Mounts for AXIS F2105-RE Standard sensor. AXIS TF1202-RE Recessed Mount is the perfect accessory when installing AXIS F2105-RE standard sensor in a wall, a glass, plastic or metal panel from 1 to 15mm. Beyond the aesthetics aspect giving a finishing look of the installation, it also guarantees that no water will leak into the wall or the panel. AXIS TF1202-RE Recessed Mount is made of plastic and comes with a built-in lens protection highly recommended when AXIS F2105-RE is used in harsh environment. 	\$ 32.00	7331021074798	0.31	4.13
 AXIS TF1203-RE Recessed Mount 4P is a bulk pack of 4x Recessed Mount for AXIS F2135-RE Fisheye sensor. AXIS TF1203-RE Recessed Mount is the perfect accessory when installing AXIS F2135-RE standard sensor in a wall, a glass, plastic or metal panel from 1 to 15mm. Beyond the esthetics aspect giving a finishing look of the installation, it also guarantees that no water will leak into the wall or the panel. AXIS TF1203-RE Recessed Mount is made of plastic and comes with a built-in lens protection highly recommended when AXIS F2135-RE is used in harsh environments. 	\$ 32.00	7331021074804	0.31	4.13
AXIS TF1901-RE Swivel Mount 4P is a bulk pack of 4x Swivel Mounts for AXIS F21 sensors. It allows the modular sensor unit to be fixed and angled to get the desired viewing direction.	19.00	7331021074750	0.18	4.02
AXIS TF1201-RE Recessed Mount is a bulk pack of 4x Recessed Mount for AXIS F2105-RE standard sensor unit and AXIS F2135-RE fisheye sensor unit. AXIS TF1201-RE Recessed Mount is the perfect accessory when installing the selected sensor units in a wall, a glass, plastic or metal panel from 1mm to 15mm. Beyond the aesthetics aspect giving a finishing look of the installation, it also guarantees that no water will leak into the wall or the panel. AXIS TF1201-RE comes in silver and is made of aluminium.	62.00	7331021077249	0.53	4.13
Wall mount compatible with all Axis outdoor fixed box cameras and housings. Corrosion tested according to NEMA 4X, UL listed and IK10 rated.Highly robust, Rotatable, and Flexible cable routing.	\$ 59.00	7331021079472	2.40	5.91

Pendant kit for indoor and outdoor use for the AXIS Q36-VE Series compatible with Axis ceiling-/wall-/pole mounts with 1.5" NPS thread.	\$ 119.00	7331021085381	1.90	12.20
Recessed mount for indoor and outdoor use of AXIS Q3626/8 VE. It has a metal back box and is suitable for installation in plenum (air- handling) spaces.	\$ 159.00	7331021085398	3.44	10.63
Pendant kit for wall mount or ceiling mount. Compatible with Axis mounting accessories with 1.5" NPS thread. Compatible with the small form factor of AXIS M42 series of cameras.	\$ 39.00	7331021085084	0.35	5.08
A recessed mount compatible with M42 series of cameras. Designed for soft ceilings that have thickness of 15+/-1 mm. Includes adapter mount top and mount bottom. Comes in 4p.	\$ 59.00	7331021085077	0.86	11.18
Outdoor recessed mount for AXIS P56 cameras. Also suitable indoor for recessed camera installations in plenum as the back box is made of metal and has a hole for cable protection conduits.	\$ 199.00	7331021085015	3.51	12.60
Outdoor-ready, impact resistant (IK10) back box with sealed compartment (IP66/67) for secure storage of connectivity devices (T6101 MKII, T8645,8). 3/4" / M25 conduit interface from both side and back. Can be mounted directly behind AXIS P4705-PLVE, and AXIS P4707-PLVE.	\$ 159.00	7331021083059	3.00	7.87
Outdoor-ready, impact resistant (IK11) back box with sealed compartment (IP66/67) for secure storage of connectivity devices. 3/4" / M25 conduit interface from both side and back. Can be mounted directly behind AXIS P3807-PVE, AXIS P3818-PVE, AXIS P3827-PVE, AXIS Q3536- LVE, AXIS Q3538-LVE, AXIS Q3626-VE, AXIS Q3628-VE, AXIS Q3819-PVE, AXIS Q3839-PVE. Includes a network cable and extra gaskets.	\$ 179.00	7331021086241	3.24	9.06
A black version of T91D61 which is chromated and powder coated aluminum wall mount with 1.5" NPS thread for fixed dome pendant kits. Cable routing from behind or through 3/4" conduit hole on the side. Includes mounting plate, pipe seal and conduit hole cover. Color: Black	\$ 149.00	7331021086463	4321.06	

TP3105-E is a black version of T94N01D which is white. It has a weathershield and a mounting adapter for AXIS P37x-PLE Network Cameras. The mounting adapter is compatible with 1.5- inch NPS thread. The kit enables AXIS P37x- PLE to be mounted on walls, poles, parapets and outer corners using AXIS T91 mounting accessories. Black Indoor pendant kit similar to T94K01D	\$ 99.00	7331021086470	0.88	10.91 7.40
white for AXIS P32-V Series- AXIS M43/-V, AXIS M32-V, AXIS M30-V compatible with Axis ceiling /wall mounts, AXIS pole mount and 1.5" NPS threaded pipes.				
A black version of T91B67 white which is Outdoor-ready, powder-coated aluminum pole mount with 1.5" NPS thread for fixed dome pendant kits. Includes insect-proof cable gasket and 1 pair of stainless steel straps (with TX30 screw) for pole diameter between 65- 165mm (2.5"-6.5"). White in color.	\$ 159.00	7331021086845	3880.14	
Outdoor recessed mount for discreet installations in drop ceilings, roof overhangs/soffits of AXIS P3735-PLE, AXIS P3737-PLE, AXIS P3738- PLE. Suitable for installations in plenum space, as the back box is made of metal with a ¾" hole for cable protection conduits.	\$ 129.00	7331021085930		
Wall-and-Pole Mount for Axis PTZ and multi- sensor cameras. Built-in Ethernet cable with an IP66 RJ45 connector for quick installation with protection against dust and water. Connect PoE via either RJ45 or IDC (insulation- displacement contact) connectors. Suitable for both indoor and outdoor environments. Separate stainless steel straps required for pole installation.	\$ 159.00	7331021076914	5.20	6.50
Wall-and-Pole Mount for Axis PTZ and multi- sensor cameras. Built-in Ethernet cable with an IP66 RJ45 connector for quick installation with protection against dust and water. Connect PoE via either RJ45 or IDC (insulation- displacement contact) connectors. Suitable for both indoor and outdoor environments. Separate stainless steel straps required for pole installation. The 1.5" NPS thread mount ensures compatibility with all pendant kits for Axis fixed dome cameras.	\$ 189.00	7331021085268	5.69	6.50

High accuracy outdoor positioning unit with AXIS T93F10 camera housing. Responsive absolute positioning with high-speed and ultra- smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IK10, IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC. Recommended for AXIS P13 and Q16 network camera series. Optional wall mount and pole mount accessories available separately.	\$ 1,949.00	_	7331021062320	33.29	11.61
High accuracy outdoor positioning unit to be used with PT Mount models in AXIS Q19 and Q29 series. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long- distance fiber connection. IK10, IP66, NEMA 4X rated and UL listed. Ready for column-mount. Optional wall mount and pole mount accessories available separately. Powered by 24 V AC/DC.	\$ 1,949.00		7331021062337	29.37	14.76
High accuracy outdoor positioning unit to be used with the outdoor models of AXIS P13 Series and AXIS Q1656-LE. Responsive absolute positioning with high-speed and ultra- smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IK10, IP66, NEMA 4X rated and UL listed. Ready for column-mount. Optional wall mount and pole mount accessories available separately. Powered by 24 V AC/DC. T99A12 expand the possibilities for IR light, upcoming White light as well as wiper which is included in upcoming AXIS Q1656-LE.	\$ 1,949.00		7331021079588	25.57	11.02
Versatile accessory to be used with AXIS C1410 Network Mini Speaker. It can be used as either a pendant kit with 3/4" (M25) conduit interface, conduit back box with 1/2" (M20) conduit side entry, or with standard stands or holders using the integrated female (M6) tripod thread.	\$ 49.00		7331021075023	0.74	8.27
AXIS TC1701 Front Cover is sold as spare parts to the AXIS C1410 Network Mini Speaker. It enables easy on-site replacement in case the original front cover has been damaged. The cover is re-paintable. Solid in packs of five units.	\$ 109.00		7331021075030	1.32	8.27
AXIS TC1702 Back Cover is an extra plenum cover to meet special plenum requirements in Chicago and Las Vegas installation. This back cover needs to be installed together with the AXIS TC1603 Tile Bridge. Sold in 4pcs per pack.	\$ 379.00		7331021079366	14.77	29.53

	•		 		
AXIS TC1603 Tile Bridge is a mount plate used with AXIS C1210-E Network Ceiling Speaker and AXIS C1211-E Network Ceiling Speaker. The tile bridge is to used in soft ceiling installations, as it prevents the ceiling tile to sink downward by distributing the speaker weight. Sold in 2pcs per pack.	\$	49.00	7331021079359	8.02	15.16
AXIS TC1602 Conduit Adapter is used for protected cable routing in 3/4" conduits and M20 pipes. Compatable with AXIS C12-series of network ceiling speakers. Sold in 5pcs per pack.		59.00	7331021079373	1.21	5.51
AXIS TC1901 is a kit for installing AXIS C15 pendant speakers hanging from the ceiling. It contains a 10m/32.8ft wire and a hook for easy adjustment of the mounting height. Sold in 5pcs per pack.	\$	99.00	7331021079380	1.29	5.51
AXIS TC1902 is a gasket to use with AXIS C1210-E ceiling speakers to allow IP54 rating.	\$	99.00	7331021082304	0.62	12.20
AXIS TC1903 is a gasket to use with AXIS C1211-E ceiling speakers to allow IP54 rating.	\$	79.00	7331021082311	0.57	12.20
 AXIS Audio Manager Center is a subscription- based hybrid cloud service for remote management and monitoring of multisite audio systems. Cloud-based and on-premises components combine to provide a stable solution, even if internet access is temporarily down. The software significantly reduces user workloads, with a single sign-on to schedule announcements, background music, ads, and more for all selected sites using AXIS Audio Manager Edge. It's simple to set up and to adjust zones, content, and schedules, without downtime. Furthermore, health monitoring provides immediate notifications if any part of the system isn't working. AXIS Audio Manager is licensed annually by the number of speaker devices (or equivalent) in the system. A no-cost version with a limited feature set is also available. One license key per order line 	\$	7.00			

 AXIS Audio Manager Pro provides easy, remote management of large IP audio installations. The AXIS AUDIO MANAGER PRO - E-LICENSE is used to when installing AXIS Audio Manager Pro on your own custom hardware or virtual machine (VMWare, Microsoft Hyper-V, Microsoft Windows Datacenter) One license key per sales unit 	\$ 2,699.00		0.00	0.00
AXIS Audio Manager Pro provides easy, remote management of large IP audio installations. Take control of your complete audio system from one single user interface which handles, for example, system setup of audio devices, zone management, audio content management, and audio scheduling. Especially useful in retail or in schools, AXIS Audio Manager Pro helps you broadcast music, live or scheduled announcements, emergency messages, and more, either individually in separate zones or centrally to all devices. With quick installation, intuitive operation, and online device status monitoring, AXIS Audio Manager realizes the benefits of network audio.	\$ 3,299.00	7331021082496	6.17	10.24
AXIS Audio Manager Pro provides easy, remote management of large IP audio installations. Take control of your complete audio system from one single user interface which handles, for example, system setup of audio devices, zone management, audio content management, and audio scheduling. Especially useful in retail or in schools, AXIS Audio Manager Pro helps you broadcast music, live or scheduled announcements, emergency messages, and more, either individually in separate zones or centrally to all devices. With quick installation, intuitive operation, and online device status monitoring, AXIS Audio Manager realizes the benefits of network audio.	\$ 3,299.00	7331021071988	5.51	7.36

AXIS Audio Manager provides easy, remote management of large IP audio installations. Take control of your complete audio system from one single user interface which handles, for example, system setup of audio devices, zone management, audio content management, and audio scheduling. Especially useful in retail or in schools, AXIS Audio Manager helps you broadcast music, live or scheduled announcements, emergency messages, and more, either individually in separate zones or centrally to all devices. With quick installation, intuitive operation, and online device status monitoring, AXIS Audio Manager realizes the benefits of network audio.	\$ 2,995.00	7331021064843	6.88	9.17
AXIS C1310-E Network Horn Speaker is perfect for outdoor environments in most climates. The speaker is a complete audio system in a single unit. It connects to the standard existing network so there is no need for a separate audio network. Further it is simple to install with PoE for both power and connectivity. AXIS C1310-E allows users to remotely It allows users to remotely warn off intruders before they commit a crime, to deliver instructions during an emergency or to make general voice messages. Built-in memory supports pre- recorded messages, or security personal can respond to notifications with live speak. Digital signal processing (DSP) ensures clear sound. Open standards support easy integration with network video, access control, analytics, and VoIP (supporting SIP). AXIS C1310-E is a standalone unit that can be placed anywhere, which supports a flexible, scalable and cost- effective approach to system design.	\$ 599.00	7331021067783	4.12	7.87
AXIS C1004-E Network Cabinet Speaker (black) is an all-in-one speaker system connected with a single network cable. It delivers out-of-the- box-ready high-quality sound without any need for fine-tuning. Background music can be played via the preinstalled AXIS Audio Player application. You can create and schedule your own playlists from an onboard SD card or from audio streaming services. AXIS C1004-E is also perfect for voice announcements (scheduled or live calls). The speakers can be zoned together thanks to built-in audio synchronization technology.	\$ 649.00	7331021052468	7.28	11.61

AXIS C1004-E Network Cabinet Speaker (white) is an all-in-one speaker system connected with a single network cable. It delivers out-of-the- box-ready high-quality sound without any need for fine-tuning. Background music can be played via the preinstalled AXIS Audio Player application. You can create and schedule your own playlists from an onboard SD card or from audio streaming services. AXIS C1004-E is also perfect for voice announcements (scheduled or live calls). The speakers can be zoned together thanks to built-in audio synchronization technology.	\$ 649.0	0 7331021052444	7.28	11.61
AXIS C1410 Network Mini Speaker is a discrete and affordable speaker that fits into smaller spaces and provides wide-area audio coverage. The speaker is a complete audio system in a single unit. It connects to the standard existing network so there is no need for a separate audio network. Further it is simple to install with PoE for both power and connectivity. AXIS C1410 allows users to remotely warn off intruders before they commit a crime, to deliver instructions during an emergency or to make general announcements. Built-in memory supports pre-recorded messages, or personnel can respond to notifications with live speak. Digital signal processing (DSP) ensures clear sound and with remote health testing you know that it is working. Open standards support easy integration with network video, access control, analytics, and VoIP. AXIS C1410 is a standalone unit that can be placed anywhere, which supports a flexible, scalable and cost- effective approach to system design. It also has a built-in PIR sensor for motion detection.	\$ 329.0	0 7331021068988	1.58	7.68

 AXIS C1210-E Network Ceiling Speaker is an all- in-one speaker system that makes voice announcements and background music smart and easy. It connects to standard network using one cable for both power (PoE) and connectivity. AXIS C1210-E offers flexible, discrete recessed ceiling installation, ideal for indoor environments but can also be used for protected outdoor areas like under the eaves. Additionally, it features a backbox that meets plenum requirements. It offers easy integration with your video management software (VMS), VoIP telephony, analytics, and more. Including a preconfigured digital signal processer (DSP) it produces clear voice every time. It also features a built-in microphone enabling remote health testing and 2-way audio talk-back. Furthermore, the embedded audio management software supports user, content, zone, and scheduling management. The outer diameter is 283 mm (11,1 in) and the dimension for fixing hole is 261 mm (10,3 in). 	\$ 499.00	7331021075900	9.48	14.37
AXIS C1211-E Network Ceiling Speaker is an all- in-one speaker system that makes voice announcements smart and easy. It connects to standard network using one cable for both power (PoE) and connectivity. AXIS C1211-E offers flexible, discrete recessed ceiling installation, ideal for indoor environments but can also be used for protected outdoor areas like under the eaves. Additionally, it features a backbox that meets plenum requirements. It offers easy integration with your video management software (VMS), VoIP telephony, analytics, and more. Including a preconfigured digital signal processer (DSP) it produces clear voice every time. It also features a built-in microphone enabling remote health testing and 2-way audio talk-back. Furthermore, the embedded audio management software supports user, content, zone, and scheduling management. The outer diameter is 216 mm (8,5 in) and the dimension for fixing hole is 194 mm (7,6 in).	\$ 429.00	7331021075894	5.18	9.25

	*	F00 00	 7004004050505	10.10	10.00
AXIS C1510 Network Pendant Speaker is an all- in-one speaker system that makes voice announcements smart and easy. It connects to standard network using one cable for both power (PoE) and connectivity. AXIS C1510 is ideal for high ceiling installations of any height, thanks to easy adjustable wire length [wire not included]. It offers easy integration with your video management software (VMS), VoIP telephony, analytics, and more. Including a preconfigured digital signal processer (DSP) it produces clear voice every time. It also features a built-in microphone enabling remote health testing and 2-way audio talk-back. Furthermore, the embedded audio management software supports user, content, zone, and scheduling management. Axis pendant speakers comes in two sizes, whereas AXIS C1510 is the larger more powerful model.	\$	599.00	7331021076792	12.46	16.22
AXIS C1511 Network Pendant Speaker is an all- in-one speaker system that makes voice announcements smart and easy. It connects to standard network using one cable for both power (PoE) and connectivity. AXIS C1511 is ideal for high ceiling installations of any height, thanks to easy adjustable wire length [wire not included]. It offers easy integration with your video management software (VMS), VoIP telephony, analytics, and more. Including a preconfigured digital signal processer (DSP) it produces clear voice every time. It also features a built-in microphone enabling remote health testing and 2-way audio talk-back. Furthermore, the embedded audio management software supports user, content, zone, and scheduling management. Axis pendant speakers comes in two sizes, whereas AXIS C1511 is the smaller model.	\$	529.00	7331021076808	7.28	11.42
This timesaving, pre-assembled Audio Ceiling Tile Kit includes Quam SYSTEM 17/8 – a 2x2 drop-in, perforated steel ceiling tile speaker - integrated with AXIS C8210 Network Audio Amplifier. Utilizing AXIS C8210, the kit provides network audio via PoE connection as well as flexibility for live or scheduled announcements, alerts, background music and more.	\$	549.00	7331021076679	8.76	24.49

Audio Ceiling Tile Kit - Camera Ready includes Kit includes Quam SYSTEM 17/8 – a 2x2 drop- in, perforated steel ceiling tile speaker - integrated with AXIS C8210 Network Audio Amplifier. Utilizing AXIS C8210, the kit provides network audio via PoE connection as well as flexibility for live or scheduled announcements, alerts, background music and more. This camera-ready version provides mounting for a fixed-dome or panoramic camera, or another device that fits a 1-gang and 4-square mounting hole pattern. Camera sold separately.	\$ 599.00	7331021076686	8.76	24.49
AXIS C1610-VE Network Sound Projector is perfect for outdoor environments in most climates. It has a nice design and is very robust (IK10 rating) making it the perfect choice for environments in need for a less intrusive design and when the placement means a risk for vandalism from people. AXIS C1610-VE allows users to remotely warn off intruders before they commit a crime, to deliver instructions during an emergency or to make general voice messages. The speaker is a complete audio system in a single unit including audio management software. It connects to the standard existing network so there is no need for a separate audio network. Further it is simple to install with PoE for both power and connectivity. Built-in memory supports pre-recorded messages, or security personal can respond to notifications with live speak. Digital signal processing (DSP) ensures clear sound and the speakers sound quality enables high quality speech. Open standards support easy integration with network video, access control, analytics, and VoIP (supporting SIP). AXIS C1610-VE is a standalone unit that can be placed anywhere, which supports a flexible, scalable and cost-effective approach to system design.	\$ 799.00	7331021076709	10.63	10.16
AXIS TC1703 Front mesh cover is sold as spare parts to the AXIS C1210-E Ceiling Speaker and AXIS C1510 Pendant Speaker. It enables easy on-site replacement in case the original front mesh cover has been damaged. The cover is re- paintable. Solid in packs of five units.	\$ 99.00	7331021079397	2.38	12.20

AXIS TC1704 Front mesh cover is sold as spare parts to the AXIS C1211-E Ceiling Speaker and AXIS C1511 Pendant Speaker. It enables easy on-site replacement in case the original front mesh cover has been damaged. The cover is re- paintable. Solid in packs of five units.	\$ 79.00	7331021079403	1.65	10.24
AXIS C8033 Network Audio Bridge is a smart solution for connecting and combining analog and digital audio systems. With this scalable and cost-efficient product, you can connect analog audio sources to Axis network speaker system, connect digital audio sources to an analog speaker system, or combine analog and digital speaker systems to act as one. Based on open standards, the audio bridge is easily integrated with other systems. It is small, easy to place, and easy to connect using Power over Ethernet.	\$ 199.00	7331021058255	0.40	4.53
AXIS C8310 is a control panel for adjusting music volume in a zone and selecting between multiple scheduled audio sources. The panel has six buttons with volume up, volume down, mute and three numbered program selectors. It connects as an accessory to the I/O port of a host network audio device. It supports recessed wall mount (US single gang box and EU connection box). The product is easy to install and a frame for optional wall mount is included. The product is available in white.	\$ 169.00	7331021082755	0.31	3.94
AXIS C8110 Network Audio Bridge is a smart solution based on open standards for connecting and combining analog and digital audio systems. Thanks to the built-in AXIS Audio Manager Edge application you can get functionalities like zone management and content scheduling in existing analog systems. With SIP support it is possible to connect an IP telephony system for callouts in analog speakers. With analog audio input you can easily integrate your intercom system or music streaming box with network speakers from Axis.	\$ 269.00	7331021076518	0.49	4.57

AXIS C8210 Network Audio Amplifier is a smart migration tool for transforming any passive speaker, independent of brand or formfactor, into a network speaker. This gives you all the benefits of network audio including less components. AXIS C8210 enables scalable and cost-effective solutions and can power up to eight speakers with a total power output of 15 W. Based on open standards, the amplifier is easily integrated with other systems. It is small, easy to place, and easy to connect using Power over Ethernet.	429.00	7331021064935	0.71	4.61
 Explosion-protected stainless steel (316L) PTZ network camera certified for use in hazardous areas according to ATEX, IECEx, cMETus. Ex db IIC T5 Gb, Ex tb IIIC T100°C Db, Class I/I/III Div 1 Groups B, C, D, E, F, G, Class I Zone 1 AEx db IIC T5 Gb, Zone 21 AEx tb IIIC T100°C Db. IP 66/67/68, Type 4X. Certificate: 20ATEX0651X (ATEX), EXV 20.0017X (IECEx), E115198 (cMETus), part code: P21. AXIS Q1785 1080p HDTV camera inside with 32x optical zoom, auto focus and day/night mode. Continuous 360° pan and tilt and 256 preset positions. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR, EIS and built-in smoke and fire detection. Operating temp -60°C to +60°C. 110-230VAC, RJ45 and SFP for fiber or coax connection. Integrated wiper, sunshield and AXIS Surveillance microSDXC card 128Gb included. 	18,899.00	7331021075658	72.75	15.75

Explosion-protected (ATEX: II 3 G Ex ec IIC T4	\$	2,999.00	7331021079106	3.62	5.51
Gc, II 2 D Ex tb IIIC 135C Db; IECEx: Ex ec IIC	Ð	2,999.00	/3310210/9106	3.62	5.51
T4 Gc, Ex tb IIIC T135C Db; cULus: Class I Div 2					
Group ABCD T4, Class II Div 2 Group FG T135C: Class III Div 2, Class I Zone 2 AEx ec IIC					
T4 Gc, Zone 21 AEx IIIC T135C Db) fixed bullet					
camera with Deep Learning Processing Unit (DLPU). Support for Forensic WDR and					
Lightfinder 2.0 and OptimizedIR. Varifocal 6-13					
mm P-iris lens with remote zoom and focus.					
Multiple, individually configurable H.264/H.265					
with Zipstream and Motion JPEG. 8MP stream					
up to 60 fps, 30fps with WDR. Axis Zipstream					
technology for reduced bandwidth and storage					
needs. AXIS Object Analytics, Smoke alert					
analytic. Video motion detection, shock					
detection and active tampering alarm.					
Barrel distortion correction, defogging and					
scene profiles. Audio in and supervised I/O					
port, microSD memory card slot for local					
storage. MQTT Support. AXIS Edge Vault for					
added cyber security. OptimizedIR, a power-					
efficient IR LED technology. Integrated bracket					
for easy mounting on wall and ceiling.					
Powered by IEEE 802.3af/802.3at Type 1 Class 3					
and 10-28V DC power with redundancy.					
Operating conditions -40 °C to 60 °C (-40 °F to					
140 °F). Includes removable sunshield.					

 1/1.8" sensor, 4 MP, Day/night, explosion-protected fixed camera with Deep Learning Processing Unit (DLPU). Support for Forensic WDR and Lightfinder 2.0. Includes an IR corrected varifocal 3.9-10 mm F1.5 i-CS lens with remote zoom and focus. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. 4MP stream up to 60 fps, 30 fps with WDR. AXIS Object Analytics with PPE monitoring (missing hard hat detection), Video motion detection, shock detection and active tampering alarm. Smoke alert smoke and fire detection analytic. AXIS Edge Vault with FIPS certified TPM for added cyber security. Barrel distortion correction, defogging, electronic image stabilization and scene profiles. MQTT Support. Optional analog or digital microphone, two-way audio. Supervised I/O for alarm/event handling, 128GB SD card included. Serial port for RS485 communication. PoE or 110-230VAC power input, SFP + RJ45 for network connectivity. Electropolished stainless steel (316L) enclosure, certified for use in hazardous areas according to ATEX, IECEx, cMETus. Ex db IIC T5 Gb, Ex tb IIIC T100°C Db, Class I/II/III Div 1 Groups B, C, D, E, F, G, Class I Zone 1 AEx db IIC T5 Gb, Zone 21 AEx tb IIIC T100°C Db. IP 66/67/68, Type 4X. Certificate: 20ATEX0651X (ATEX), EXV 20.0017X (IECEx), E115198 (cMETus), part code: F31. Swivel joint included. 	\$ 9,999.00	7331021077775	23.04	11.22
Explosion-protected, top performance, PoE powered HDTV 1080p PTZ dome network camera with 40x zoom, FM listed for hazardous locations Class I Division 1, Groups B, C, D, T6; Class 1 Zone 1 IIB + H2 T6, -20°C <= Ta <= +55°C (FM17US0156). Stainless Steel 316L housing. Auto day/night functionality, Zipstream, wide dynamic range, electronic image stabilization, highlight compensation. Continuous 360° rotation and 220° tilt with E- flip. HDTV 1080p@30 fps, 720@60 fps. High PoE midspan with fiber slot is included (for installation in safe area or Ex d enclosure), AXIS Surveillance SD Card 64GB. Optional accessories: Wall and pole mount.	\$ 16,499.00	7331021069138	63.00	12.60

Explosion-protected 316L stainless steel fixed network camera certified for hazardous areas according to UL. Certification part code Oxalis- UL1410-15. Oxalis explosion-protected housing with three 3/4" NPT cable entries, AXIS Q1785 1080p HDTV camera inside with 32x optical zoom, auto focus and day/night mode. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR- dynamic contrast, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -58°F to +158°F (-50°C to +70°C). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	\$ 8,599.00	7331021074453	33.07	10.24
Small, wireless indoor cube camera for day & night surveillance. 2.8mm fixed lens with 110° HFOV. Automatic IR cut filter. IR illumination up to 10 meters (33 feet) . Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p at 30 fps with WDR. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Connects over wireless LAN (IEEE 802.11a/b/g/n) or wired Ethernet. Supports Wi-Fi Protected Setup™ PBC compatible. Includes wall, corner bracket and table top bracket for easy mounting. Power supply included.	\$ 229.00	7331021051669	0.84	6.10
Day/night, small indoor box style 2 MP / HDTV camera with a Deep Learning Processing Unit (DPLU). Built-in IR illumination and WDR. Fixed lens with 103° HFOV. Automatic IR cut filter. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max HDTV 1080p resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Built in I/O. MQTT support. Axis Object Analytics, video motion detection and active tampering alarm. MicroSD memory card slot for local storage. AXIS Edge Vault for increased Cyber Security. Tally LED to indicate video streaming or recording. Powered by IEEE 802.3af/802.3at Type 1 Class 3. Includes bracket for easy mounting on wall and corner. Midspan not included.	289.00	7331021076228	0.62	4.13

 Small, full-featured indoor cube camera for day & night surveillance. 2.8mm fixed lens with 110° HFOV. Automatic IR cut filter. IR illumination up to 10 meters (33 feet) . Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p at 30 fps with WDR. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Built-in microphone and mini-speaker, integrated PIR motion sensor. Powered over Ethernet (PoE) or by accessory power supply. Includes wall, corner bracket and table top bracket for easy mounting. Power supply not included. 	\$ 279.00	7331021053946	0.66	6.10
Small, full-featured wireless indoor cube camera for day & night surveillance. 2.8mm fixed lens with 110° HFOV. Automatic IR cut filter. IR illumination up to 10 meters (33 feet) . Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p at 30 fps with WDR. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Built-in microphone and mini-speaker, integrated PIR motion sensor. Connects over wireless LAN (IEEE 802.11a/b/g/n) or wired Ethernet. Supports Wi-Fi Protected Setup™ PBC compatible. Includes wall, corner bracket and table top bracket for easy mounting. Power supply included.	\$ 319.00	7331021051652	0.84	6.10
 Day/night, small fully featured indoor box style 2 MP / HDTV camera with a Deep Learning Processing Unit (DPLU). Built-in IR illumination and WDR. Fixed lens with 103° HFOV. Automatic IR cut filter. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max HDTV 1080p resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Built-in microphones and speaker for two-way audio, I/O and integrated PIR motion sensor. Micro-HDMI output. MQTT support. Axis Object Analytics, video motion detection and active tampering alarm. MicroSD memory card slot for local storage. AXIS Edge Vault for increased Cyber Security. Tally LED to indicate video streaming or recording. Powered by IEEE 802.3af/802.3at Type 1 Class 3. Optional wireless kit available. Includes bracket for easy mounting on wall and corner. Midspan not included. 	\$ 339.00	7331021076235	0.62	4.13

HDTV 720p resolution, day/night, compact fixed box camera with CS-mount providing Forensic WDR and Lightfinder technology. Includes an IR corrected varifocal 3-10.5 mm F1.4 DC-iris lens. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; HDTV 720p at 25/30 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Audio in and audio detection with either built-in microphone or optional analog microphone. I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. PoE class 2 or 8-28VDC input. Includes stand for wall and ceiling mount. Midspan or power supply not included.	\$	349.00	7331021070127	1.15	6.30
AXIS M1134 Barebone in single pack. No lens.	\$	329.00	7331021071292	0.97	6.30
No power supply					
HDTV 1080p resolution, day/night, compact fixed box camera with CS-mount providing Forensic WDR and Lightfinder technology. Includes an IR corrected varifocal 3-10.5 mm F1.4 DC-iris lens. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; full HDTV 1080p at 25/30 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Audio in and audio detection with either built-in microphone or optional analog microphone. I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. PoE class 2 or 8-28VDC input. Includes stand for wall and ceiling mount. Midspan or power supply not included.	6	419.00	7331021067516	1.16	6.30

HDTV 1080p resolution, day/night, compact fixed box camera with CS-mount providing Forensic WDR and Lightfinder technology. Includes an IR corrected varifocal 3-10.5 mm F1.4 DC-iris lens. Camera also supports i-CS lenses for remote installation zoom and focus. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; full HDTV 1080p at 25/30 fps. Axis Zipstream technology for reduced bandwidth and storage needs. AXIS Object Analytics and active tampering alarm. Audio in and audio detection with either built-in microphone or optional microphone. I/O for alarm/event handling. MQTT support. Axis Edge Vault for added cyber security. MicroSD card slot for local storage. Powered by IEEE 802.3af/802.3at Type 1 Class 3 or 8-28VDC input. Includes stand for wall and ceiling mount. Midspan or power supply not included.	\$ 449.00	7331021078178	1.06	5.91
HDTV 1080p resolution, day/night, compact fixed box camera with CS-mount providing Forensic WDR and Lightfinder technology. Includes an IR corrected varifocal i-CS lens 3.5- 10 mm F1.8 with remote installation zoom and focus. Camera also supports DC-iris lenses. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; full HDTV 1080p at 25/30 fps. Axis Zipstream technology for reduced bandwidth and storage needs. AXIS Object Analytics and active tampering alarm. Audio in and audio detection with either built-in microphone or optional microphone. I/O for alarm/event handling. MQTT support. Axis Edge Vault for added cyber security. MicroSD card slot for local storage. Powered by IEEE 802.3af/802.3at Type 1 Class 3 or 8-28VDC input. Includes stand for wall and ceiling mount. Midspan or power supply not included.	\$ 549.00	7331021079663	1.15	5.91
AXIS M1135 Barebone in single pack. No lens. No power supply.	\$ 399.00	7331021067530	0.97	6.30

Outdoor, NEMA 4X, IP66 and IK10-rated, light weight HDTV 1080p resolution, day/night, compact fixed box camera with CS-mount providing Forensic WDR and Lightfinder technology. Includes an IR corrected varifocal 3- 10.5 mm F1.4 DC-iris Iens. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; full HDTV 1080p at 25/30 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Audio in and audio detection with optional analog microphone. I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Operation in -25°C to +50°C. PoE class 2 or 8-28VDC input. Includes removable sunshield, wall bracket, Torx T20 screw driver and IP66- rated cable glands. Midspan or power supply not included.	\$ 519.00	7331021067554	5.20	10.24
Outdoor, NEMA 4X, IP66 and IK10-rated, light weight HDTV 1080p resolution, day/night, compact fixed box camera with CS-mount providing Forensic WDR and Lightfinder technology. Includes an IR corrected varifocal 3 10.5 mm F1.4 DC-iris lens. Camera also supports i-CS lenses for remote installation zoom and focus. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; full HDTV 1080p at 25/30 fps. Axis Zipstream technology for reduced bandwidth and storage needs. AXIS Object Analytics and active tampering alarm. Audio in and audio detection with optional microphone. I/O for alarm/event handling, MQTT support. Axis Edge Vault for added cyber security. MicroSD card slot for local storage. Operation in -25°C to +50°C. Powered by IEEE 802.3af/802.3at Type 1 Class 3 or 8-28VDC input. Includes removable sunshield, wall bracket, Torx T20 screw driver and IP66- rated cable glands. Midspan or power supply not included.	\$ 549.00	7331021078253	5.29	10.04

	<u> </u>	0 40 00	 		40.04
Outdoor, NEMA 4X, IP66 and IK10-rated, light weight HDTV 1080p resolution, day/night, compact fixed box camera with CS-mount providing Forensic WDR and Lightfinder technology. Includes an IR corrected varifocal i- CS lens 3.5-10 mm F1.8 with remote installation zoom and focus. Camera also supports DC-iris lenses. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; full HDTV 1080p at 25/30 fps. Axis Zipstream technology for reduced bandwidth and storage needs. AXIS Object Analytics and active tampering alarm. Audio in and audio detection with optional microphone. I/O for alarm/event handling, MQTT support. Axis Edge Vault for added cyber security. MicroSD card slot for local storage. Operation in -25°C to +50°C. Powered by IEEE 802.3af/802.3at Type 1 Class 3 or 8-28VDC input. Includes removable sunshield, wall bracket, Torx T20 screw driver and IP66- rated cable glands. Midspan or power supply not included.	\$	649.00	7331021080249	5.69	10.04
5MP resolution, day/night, compact fixed box camera with CS-mount providing Forensic WDR and Lightfinder technology. Includes an IR corrected varifocal 2.8-13 mm F1.4 DC-iris lens. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 5MP at 25/30 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Audio in and audio detection with either built-in microphone or optional analog microphone. I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. PoE class 3 or 8-28VDC input. Includes stand for wall and ceiling mount. Midspan or power supply not included.	\$	499.00	7331021067523	1.23	6.30

		-		
5MP resolution, day/night, compact fixed box camera with CS-mount providing Forensic WDR and Lightfinder technology. Includes an IR corrected varifocal 2.8-13 mm F1.4 DC-iris lens. Camera also supports i-CS lenses for remote installation zoom and focus. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 5MP at 25/30 fps. Axis Zipstream technology for reduced bandwidth and storage needs. AXIS Object Analytics and active tampering alarm. Audio in and audio detection with either built-in microphone or optional microphone. I/O for alarm/event handling. MQTT support. Axis Edge Vault for added cyber security. MicroSD card slot for local storage. Powered by IEEE 802.3af/802.3at Type 1 Class 3 or 8-28VDC input. Includes stand for wall and ceiling mount. Midspan or power supply not included.	\$ 539.00	7331021078215	1.06	5.91
5MP resolution, day/night, compact fixed box camera with CS-mount providing Forensic WDR and Lightfinder technology. Includes an IR corrected varifocal i-CS lens 3.5-10 mm F1.8 with remote installation zoom and focus. Camera also supports DC-iris lenses. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 5MP at 25/30 fps. Axis Zipstream technology for reduced bandwidth and storage needs. AXIS Object Analytics and active tampering alarm. Audio in and audio detection with either built-in microphone or optional microphone. I/O for alarm/event handling. MQTT support. Axis Edge Vault for added cyber security. MicroSD card slot for local storage. Powered by IEEE 802.3af/802.3at Type 1 Class 3 or 8-28VDC input. Includes stand for wall and ceiling mount. Midspan or power supply not included.	\$ 639.00	7331021079687	1.28	5.91
AXIS M1135 in 10-pack. Cannot be sold separately as single packs.	\$ 4,149.00	7331021071551	10.63	14.17
AXIS M1137 Barebone in single pack. No lens. No power supply	\$ 479.00	7331021067547	0.97	6.30

Outdoor, NEMA 4X, IP66 and IK10-rated, light weight 5MP resolution, day/night, compact fixed box camera with CS-mount providing Forensic WDR and Lightfinder technology. Includes an IR corrected varifocal 2.8-13 mm F1.4 DC-iris lens. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 5MP at 25/30 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Audio in and audio detection with optional analog microphone. I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Operation in -25°C to +50°C. PoE class 3 or 8-28VDC input. Includes removable sunshield, wall bracket, Torx T20 screw driver	\$ 599.00	7331021067561	5.27	10.24
 and IP66- rated cable glands. Midspan or power supply not included. Outdoor, NEMA 4X, IP66 and IK10-rated, light weight 5MP resolution, day/night, compact fixed box camera with CS-mount providing Forensic WDR and Lightfinder technology. Includes an IR corrected varifocal 2.8-13 mm F1.4 DC-iris lens. Camera also supports i-CS lenses for remote installation zoom and focus. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; full HDTV 5MP at 25/30 fps. Axis Zipstream technology for reduced bandwidth and storage needs. AXIS Object Analytics and active tampering alarm. Audio in and audio detection with optional microphone. I/O for alarm/event handling, MQTT support. Axis Edge Vault for added cyber security. MicroSD card slot for local storage. Operation in -25°C to +50°C. Powered by IEEE 802.3af/802.3at Type 1 Class 3 or 8-28VDC input. Includes removable sunshield, wall bracket, Torx T20 screw driver and IP66- rated cable glands. Midspan or power supply not included. 	\$ 639.00	7331021078277	5.29	10.04

Outdoor, NEMA 4X, IP66 and IK10-rated, light weight 5MP resolution, day/night, compact fixed box camera with CS-mount providing Forensic WDR and Lightfinder technology. Includes an IR corrected varifocal i-CS lens 3.5- 10 mm F1.8 with remote installation zoom and focus. Camera also supports DC-iris lenses.	\$ 739.00	7331021080263	5.29	10.04
 Multiple, individually configurable H.264, H.265 and Motion JPEG streams; full HDTV 5MP at 25/30 fps. Axis Zipstream technology for reduced bandwidth and storage needs. AXIS Object Analytics and active tampering alarm. Audio in and audio detection with optional microphone. I/O for alarm/event handling, MQTT support. Axis Edge Vault for added cyber security. MicroSD card slot for local storage. Operation in -25°C to +50°C. Powered by IEEE 802.3af/802.3at Type 1 Class 3 or 8-28VDC input. Includes removable sunshield, wall bracket, Torx T20 screw driver and IP66- rated cable glands. Midspan or power supply not included. 				
Day/night, compact and outdoor-ready bullet style HDTV camera, IP66- and IK08-rated. Built- in IR illumination and WDR – Forensic Capture. Fixed lens with 115° HFOV. Automatic IR cut filter. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection, active tampering alarm and corridor format. Integrated bracket for easy mounting on wall and ceiling. Power over Ethernet. Operating conditions -30 °C to 50 °C (-22 °F to 122 °F). Midspan not included.	\$ 329.00	7331021052260	1.37	4.53

				-
Day/night, compact and outdoor-ready bullet style HDTV camera in black color, IP66- and IK08-rated Built-in IR illumination and WDR – Forensic Capture. Fixed lens with 115° HFOV. Automatic IR cut filter. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection, active tampering alarm and corridor format. Integrated bracket for easy mounting on wall and ceiling. Power over Ethernet. Operating conditions -30 °C to 50 °C (-22 °F to 122 °F). Midspan not included.	\$ 329.00	7331021056503	1.37	4.53
AXIS M2025-LE in 10-pack/bulk. Cannot be sold	\$ 3,249.00	7331021052277	14.15	14.76
separately as single packs. Day/night, compact and outdoor-ready bullet style HDTV camera, IP66- and IK08-rated. Built- in IR illumination and WDR. Fixed lens with 130° HFOV. Automatic IR cut filter. Multiple, individually configurable H.264/H.265 and Motion JPEG streams; max 4 MP / QuadHD resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection, active tampering alarm and corridor format. Integrated bracket for easy mounting on wall and ceiling. Power over Ethernet. Operating conditions -30 °C to 50 °C (-22 °F to 122 °F). Midspan not included.	\$ 399.00	7331021058491	1.37	4.92
Day/night, compact and outdoor-ready bullet style HDTV camera in black color, IP66- and IK08-rated. Built-in IR illumination and WDR. Fixed lens with 130° HFOV. Automatic IR cut filter. Multiple, individually configurable H.264/H.265 and Motion JPEG streams; max 4 MP / QuadHD resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection, active tampering alarm and corridor format. Integrated bracket for easy mounting on wall and ceiling. Power over Ethernet. Operating conditions -30 °C to 50 °C (-22 °F to 122 °F). Midspan not included.	\$ 399.00	7331021058507	1.37	4.92
AXIS M2026-LE Mk II in 10-pack/bulk. Cannot be	\$ 3,949.00	7331021061439	13.58	14.76
sold separately as single packs.				
AXIS M2026-LE Mk II Black in 10-pack/bulk. Cannot be sold separately as single packs.	\$ 3,949.00	7331021061446	13.58	14.76

Day/night, compact and outdoor-ready bullet style HDTV camera, IP66, IP67, NEMA 4X and IK08-rated. Built-in IR illumination and WDR. Fixed lens with 101° HFOV, corridor format, automatic IR cut filter. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max HDTV 1080p resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Includes a Deep Learning Processing Unit (DPLU) for advanced analytics. Axis Object Analytics, video motion detection and active tampering alarm. Memory card slot for optional local video storage. AXIS Edge Vault for increased Cyber Security. Integrated bracket for easy mounting on wall and ceiling. Power over Ethernet. Operating conditions -30 °C to 50 °C (-22 °F to 122 °F). Midspan not included.	\$ 379.00	7331021072961	1.54	4.41
Day/night, compact and outdoor-ready bullet style HDTV camera in black color, IP66, IP67, NEMA 4X and IK08-rated. Built-in IR illumination and WDR. Fixed lens with 101° HFOV, corridor format, automatic IR cut filter. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max HDTV 1080p resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Includes a Deep Learning Processing Unit (DPLU) for advanced analytics. Axis Object Analytics, video motion detection and active tampering alarm. Memory card slot for optional local video storage. AXIS Edge Vault for increased Cyber Security. Integrated bracket for easy mounting on wall and ceiling. Power over Ethernet. Operating conditions -30 °C to 50 °C (- 22 °F to 122 °F). Midspan not included.	\$ 379.00	7331021073043	1.54	4.41

Day/night, compact and outdoor-ready bullet style HDTV camera, IP66, IP67, NEMA 4X and IK08-rated. Built-in IR illumination and WDR. Fixed tele lens with 39° HFOV, corridor format, automatic IR cut filter. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max HDTV 1080p resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Includes a Deep Learning Processing Unit (DPLU) for advanced analytics. Axis Object Analytics, video motion detection and active tampering alarm. Memory card slot for optional local video storage. AXIS Edge Vault for increased Cyber Security. Integrated bracket for easy mounting on wall and ceiling. Power over Ethernet. Operating conditions -30 °C to 50 °C (-22 °F to 122 °F). Midspan not included.	\$ 379.00	7331021073050	1.54	4.41
Day/night, compact and outdoor-ready bullet style HDTV camera in black color, IP66, IP67, NEMA 4X and IK08-rated. Built-in IR illumination and WDR. Fixed tele lens with 39° HFOV, corridor format, automatic IR cut filter. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max HDTV 1080p resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Includes a Deep Learning Processing Unit (DPLU) for advanced analytics. Axis Object Analytics, video motion detection and active tampering alarm. Memory card slot for optional local video storage. AXIS Edge Vault for increased Cyber Security. Integrated bracket for easy mounting on wall and ceiling. Power over Ethernet. Operating conditions -30 °C to 50 °C (- 22 °F to 122 °F). Midspan not included.	\$ 379.00	7331021073067	1.54	4.41

Day/night, compact and outdoor-ready bullet style 4 MP camera, IP66, IP67, NEMA 4X and IK08-rated. Built-in IR illumination and WDR. Fixed lens with 130° HFOV, corridor format, automatic IR cut filter. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max 4 MP / QuadHD resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Includes a Deep Learning Processing Unit (DPLU) for advanced analytics. Axis Object Analytics, video motion detection and active tampering alarm. Memory card slot for optional local video storage. AXIS Edge Vault for increased Cyber Security. Integrated bracket for easy mounting on wall and ceiling. Power over Ethernet. Operating conditions -30 °C to 50 °C (-22 °F to 122 °F). Midspan not included.	\$ 429.00	7331021072978	1.54	4.41
Day/night, compact and outdoor-ready bullet style 4 MP camera in black color, IP66, IP67, NEMA 4X and IK08-rated. Built-in IR illumination and WDR. Fixed lens with 130° HFOV, corridor format, automatic IR cut filter. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max 4 MP / QuadHD resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Includes a Deep Learning Processing Unit (DPLU) for advanced analytics. Axis Object Analytics, video motion detection and active tampering alarm. Memory card slot for optional local video storage. AXIS Edge Vault for increased Cyber Security. Integrated bracket for easy mounting on wall and ceiling. Power over Ethernet. Operating conditions -30 °C to 50 °C (- 22 °F to 122 °F). Midspan not included.	\$ 429.00	7331021073074	1.54	4.41

AXIS P1245 Network Camera is a modular camera based on a small-sized main unit (AXIS P12 Mk II) and AXIS FA1105 Sensor Unit. The camera provides HDTV 1080p resolution, 111° horizontal FoV and WDR - Forensic Capture. Supports multiple streams in H.264 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, and edge storage using microSD card. The main unit is powered with PoE. The sensor unit has a built in connector and a detachable cable (8 m/26 ft.) for easy installation and maintenance. Comes with a kit for flush mount installation in ceiling/wall.	\$ 369.00	7331021052826	0.78	5.91
AXIS P1265 Network Camera is a modular camera based on a small-sized main unit (AXIS P12 Mk II) and an AXIS FA1125 Pinhole Sensor Unit that is designed for extremely discreet indoor installations. The camera provides HDTV 1080p resolution, 91° horizontal FoV and WDR - Forensic Capture. Supports multiple streams in H.264 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, and edge storage using microSD card. The main unit is powered with PoE. The sensor unit has a built in connector with a detachable cable (8 m/26 ft.) for easy installation and maintenance. Bracket included for mounting behind a thin metal, plastic or glass panel.	\$ 379.00	7331021052833	0.77	6.50
AXIS P1275 Network Camera is a modular camera based on a small-sized main unit (AXIS P12 Mk II) and an AXIS FA4115 Dome Sensor Unit with a varifocal lens that enables easy mounting on walls or ceilings. It can be manually directed with pan, tilt and rotate movements. The camera provides HDTV 1080p resolution, 53-99° horizontal FoV and WDR - Forensic Capture. Supports multiple streams in H.264 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, and edge storage using microSD card. The main unit is powered with PoE. The sensor unit has a built in connector and a detachable cable (8 m/26 ft.) for easy installation and maintenance.	\$ 409.00	7331021052840	0.93	6.50

LIDTV 4000m recelution dow/night fixed how	¢	<u> </u>	 7004004004004	2.00	7.05
HDTV 1080p resolution, day/night, fixed box	\$	699.00	7331021064621	2.90	7.95
camera providing Forensic WDR and					
Lightfinder 2.0 technology. Includes an IR					
corrected varifocal 2.8-8 mm F1.2 P-Iris lens					
and remote back focus. Camera also supports					
CS-mount DC-iris lenses and i-CS lenses for					
remote installation zoom and focus. Multiple,					
individually configurable H.264, H.265 and					
Motion JPEG streams; full HDTV 1080p at 50/60					
fps. Axis Zipstream technology for reduced					
bandwidth and storage needs. Video motion					
detection, shock detection, active tampering					
alarm and security lock slot. Corridor format,					
barrel distortion correction, defogging and					
electronic image stabilization. Scene profiles.					
Two-way audio, audio detection with either					
built-in microphone or optional analog or					
digital microphone. Supervised I/O for					
alarm/event handling, MicroSD/MicroSDHC					
memory card slot for optional local video					
storage. Serial port for RS422/485					
communication. Power over Ethernet or 12-					
28VDC input. Includes black stand for wall and					
ceiling mount with hole for easy cable					
management. Midspan or power supply not					
included.					
AXIS P1375 Barebone in single pack. No lens.	\$	649.00	7331021064652	2.73	7.95
No power supply.					

\$	949.00			
Ŧ	343.00	7331021064638	8.93	9.57
\$	899.00	7331021064669	8.60	7.87
- T				

Outdoor with extra heater, NEMA 4X, IP66/67 and IK10-rated, light weight HDTV 1080p	\$ 949.00	7331021085305	8.93	9.57
resolution, day/night, fixed box camera				
providing Forensic WDR and Lightfinder 2.0				
technology. Includes an IR corrected varifocal				
2.8-8 mm F1.2 P-Iris lens and remote back				
focus. Camera also supports CS-mount DC-iris				
lenses and i-CS lenses for remote installation				
zoom and focus. Multiple, individually				
configurable H.264, H.265 and Motion JPEG				
streams; full HDTV 1080p at 50/60 fps. Axis				
Zipstream technology for reduced bandwidth				
and storage needs. Video motion detection,				
shock detection, active tampering alarm and				
open casing intrusion switch. Corridor format,				
barrel distortion correction, defogging and				
electronic image stabilization. Scene profiles.				
Two-way audio, audio detection with optional				
analog or digital microphone. Supervised I/O				
for alarm/event handling, MicroSD/MicroSDHC				
memory card slot for optional local video				
storage. Support for optional AXIS Fixed Box IR				
Illuminator Kit A and AXIS P13 Weathershield				
Extension A. Serial port for RS422/485				
communication. Operation in -40°C to +60°C.				
PoE+ class4 or 12-28VDC input. Includes				
removable sunshield, wall bracket, Torx T20				
screw driver and IP66/67- rated cable glands.				
Midspan or power supply not included.				
AXIS P1375-E Barebone with extra heater. No	\$ 899.00	7331021085336	8.60	7.87
lens. Midspan not included				

5MP resolution, day/night, fixed box camera	\$	799.00	7331021068087	2.98	7.87
providing Forensic WDR and Lightfinder	1				
technology. Includes an IR corrected varifocal	1				
2.8-8 mm F1.2 P-Iris lens and remote back	1				
focus. Camera also supports CS-mount DC-iris					
lenses and i-CS lenses for remote installation					
zoom and focus. Multiple, individually					
configurable H.264, H.265 and Motion JPEG	1				
streams; 5MP at 25/30 fps. Axis Zipstream	1				
technology for reduced bandwidth and storage	1				
needs. Video motion detection, shock	1				
detection, active tampering alarm and security	1				
lock slot. Corridor format, barrel distortion	1				
correction, defogging and electronic image	1				
stabilization. Scene profiles. Two-way audio,					
audio detection with either built-in microphone					
or optional analog or digital microphone.	1				
Supervised I/O for alarm/event handling,	1				
MicroSD/MicroSDHC memory card slot for	1				
optional local video storage. Serial port for	1				
RS422/485 communication. PoE class 3 or 12-	1				
28VDC input. Includes black stand for wall and					
ceiling mount with hole for easy cable	1				
management. Midspan or power supply not	1				
included	1				
	1				
AXIS P1377 Barebone in single pack. No lens.	\$	749.00	7331021068100	2.82	7.87
No power supply.					

Outdoor, NEMA 4X, IP66/67 and IK10-rated,	\$	1,079.00	7331021068094	9.48	7.87
5MP resolution, day/night, fixed box camera	l				
providing providing Forensic WDR and					
Lightfinder technology. OptimizedIR, a power-					
efficient 850nm IR LED technology covering 50					
meters (130 feet).Includes an IR corrected					
varifocal 2.8-8 mm F1.2 P-Iris lens and remote					
back focus. Camera also supports CS-mount					
DC-iris lenses and i-CS lenses for remote					
installation zoom and focus. Multiple,					
individually configurable H.264, H.265 and					
Motion JPEG streams; 5MP at 50/60 fps. Axis					
Zipstream technology for reduced bandwidth	1				
and storage needs. Video motion detection,	1				
shock detection, active tampering alarm and	l				
open casing intrusion switch. Corridor format,	1				
barrel distortion correction, defogging and					
electronic image stabilization. Scene profiles.					
Two-way audio, audio detection with optional					
analog or digital microphone. Supervised I/O					
for alarm/event handling, MicroSD/MicroSDHC					
memory card slot for optional local video					
storage. Serial port for RS422/485					
communication. Operation in -40°C to +60°C.					
PoE+ class4 or 12-28VDC input. Support for					
optional AXIS P13 Weathershield Extension A.					
Includes pre-mounted AXIS Fixed Box IR					
illuminator Kit A, removable sunshield, wall					
bracket, Torx T20 screw driver and IP66/67-					
rated cable glands. Midspan or power supply					
not included.	1				
	1				
	1				
	1				
	l				
	1				
	Ļ				
AXIS P1377-LE Barebone. No lens. Midspan not	\$	1,029.00	7331021069664	9.04	7.87
included					

and IK10-rated, 5MP resolution, day/night, fixed box camera providing providing Forensic WDR and Lightfinder technology. OptimizedIR, a power-efficient 850nm IR LED technology covering 50 meters (130 feet).Includes an IR corrected varifcoal 2.84 mm F1.2 P1/si lens and remote back focus. Camera also supports CS-mount DC-iris lenses and 1-CS lenses for remote installation zoom and focus. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; SMP at 50/60 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, shock detection, active tampering alarm and open casing intrusion switch. Corridor format, barrel distortion correction, defogging and electronic image stabilization. Scene profiles. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSD/HC memory card slot for optional local Video storage. Serial port for RS422/485 communication. Operation in -40°C to +60°C. POF+ class of 12-28/DC input. Support for optional AXIS P137 weathershield Extension A. Includes pre-mounted AXIS Fixed Box IR illuminator Kit A, removable sunshield, wall bracket, Torx T20 screw driver and IP66/67- rated cable glands. Midspan or power supply not included.73310210853439.047.87			 		
box camera providing providing Forensic WDR and Lightfinder technology. OptimizedIR, a power-efficient 850m IR LED technology covering 50 meters (130 feet).Includes an IR 	Outdoor with extra heater, NEMA 4X, IP66/67	\$ 1,079.00	7331021085312	9.48	7.87
and Lightlinder technology. OptimizedIR, a power-efficient 850nm IR LED technology covering 50 meters (130 feet).Includes an IR corrected varifocal 2.8-8 mm F1.2 P-Iris lens 					
power-efficient 850nm IR LED technology covering 50 meters (130 feet).Includes an IR corrected varifocal 2.8-8 mm F1.2 P-Iris lens and remote back focus. Camera also supports CS-mount DC-iris lenses and i-CS lenses for remote installation zoom and focus. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 5MP at 50/60 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, shock detection, active tampering alarm and open casing intrusion switch. Corridor format, barrel distortion correction, defogging and electronic image stabilization. Scene profiles. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSD/HC memory card slot for optional local video storage. Serial port for R5422/485 communication. Operation in .40°C to +60°C. PoE+ class4 or 12-28VDC input. Support for optional AXIS P13 Weathershield Extension A. Includes Box moves and IP66/67- rated cable glands. Midspan or power supply not included.\$ 1,029.0073310210853439.047.87					
covering 50 meters (130 feet).Includes an IR corrected varifocal 2.8-8 mm F1.2 P-Iris lens and remote back focus. Camera also supports CS-mount DC-iris lenses and i-CS lenses for remote installation zoom and focus. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 5MP at 50/60 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, shock detection, active tampering alarm and open casing intrusion switch. Corridor format, barrel distortion correction, defogging and electronic image stabilization. Scene profiles. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Operation in 4.40° C to +60°C. PoE+ class4 or 12-28VDC input. Support for optional AXIS P13 Weathershield Extension A. Includes pre-mounted AXIS Fixed Box IR Illuminator Kit A, removable sunshield, wall bracket, Torx T20 screw driver and IP66/67- rated cable glands. Midspan or power supply not included. \$ 1,029.00 7331021085343 9.04 7.87					
corrected varifocal 2.8-8 mm F1.2 P-Iris lens and remote back focus. Camera also supports CS-mount DC-iris lenses and I-CS lenses for remote installation zoom and focus. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 5MP at 50/60 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, shock detection, active tampering alarn and open casing intrusion switch. Corridor format, barrel distortion correction, defogging and electronic image stabilization. Scene profiles. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS42/485 communication. Operation in -40°C to +60°C. PoE+ class4 or 12-28VDC input. Support for optional AXIS P13 Weathershield Extension A. Includes pre-mounted AXIS Fixed Box IR illuminator Kit A, removable sunshield, wall bracket, Torx T20 screw driver and IP66/67- rated cable glands. Midspan or power supply not included. 7331021085343 9.04 7.87					
and remote back focus. Camera also supports CS-mount DC-iris lenses and i-CS lenses for remote installation zoom and focus. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 5MP at 50/60 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, shock detection, active tampering alarm and open casing intrusion switch. Corridor format, barrel distortion correction, defogging and electronic image stabilization. Scene profiles. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Operation in -40°C to +60°C. PoE+ class4 or 12-28VDC input. Support for optional AXIS P13Weathershield Extension A. Includes pre-mounted AXIS Fixed Box IR illuminator Kit A, removable sunshield, wall bracket, Torx T20 screw driver and IP66/67- rated cable glands. Midspan or power supply not included.73310210853439.047.87	•				
CS-mount DC-iris lenses and i-CS lenses for remote installation zoom and focus. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 5MP at 50/60 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, shock detection, active tampering alarm and open casing intrusion switch. Corridor format, barrel distortion correction, defogging and electronic image stabilization. Scene profiles. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for R5422/485 communication. Operation in -40°C to +60°C. PoE+ class4 or 12-28VDC input. Support for optional AXIS P13 Weathershield Extension A. Includes pre-mounted AXIS Fixed Box IR illuminator Kit A, removable sunshield, wall bracket, Torx T20 screw driver and IP66/67- rated cable glands. Midspan or power supply not included. 7331021085343 9.04 7.87					
remote installation zoom and focus. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 5MP at 50/60 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, shock detection, active tampering alarm and open casing intrusion switch. Corridor format, barrel distortion correction, defogging and electronic image stabilization. Scene profiles. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for R5422/485 communication. Operation in -40°C to +60°C. PoE+ class4 or 12-28VDC input. Support for optional AXIS P13 Weathershield Extension A. Includes pre-mounted AXIS Fixed Box IR illuminator Kit A, removable sunshield, wall bracket, Torx T20 screw driver and IP66/67- rated cable glands. Midspan or power supply not included.\$ 1,029.0073310210853439.047.87					
individually configurable H.264, H.265 and Motion JPEG streams; 5MP at 50/60 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, shock detection, active tampering alarm and open casing intrusion switch. Corridor format, barrel distortion correction, defogging and electronic image stabilization. Scene profiles. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSDMicroSDHC memory card slot for optional local video storage. Serial port for R\$422/485 communication. Operation in 40°C to +60°C. PoE+ class4 or 12-28VDC input. Support for optional AXIS P13Weathershield Extension A. Includes pre-mounted AXIS Fixed Box IR illuminator Kit A, removable sunshield, wall bracket, Torx T20 screw driver and IP66/67- rated cable glands. Midspan or power supply not included.\$ 1,029.0073310210853439.047.87					
Motion JPEG streams; 5MP at 50/60 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, shock detection, active tampering alarm and open casing intrusion switch. Corridor format, barrel distortion correction, defogging and electronic image stabilization. Scene profiles. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Operation in -40°C to +60°C. PoE+ class4 or 12-28VDC input. Support for optional AXIS P13Weathershield Extension A. Includes pre-mounted AXIS Fixed Box IR illuminator Kit A, removable sunshied, wall bracket, Torx T20 screw driver and IP66/67- rated cable glands. Midspan or power supply not included. AXIS P1377-LE Barebone with extra heater. No \$ 1,029.00 7331021085343 9.04 7.87					
Zipstream technology for reduced bandwidth and storage needs. Video motion detection, shock detection, active tampering alarm and open casing intrusion switch. Corridor format, barrel distortion correction, defogging and electronic image stabilization. Scene profiles. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Operation in .40°C to +60°C. PoE+ class4 or 12-28VDC input. Support for optional AXIS P13 Weathershield Extension A. Includes pre-mounted AXIS Fixed Box IR illuminator Kit A, removable sunshield, wall bracket, Torx T20 screw driver and IP66/67- rated cable glands. Midspan or power supply not included.73310210853439.047.87					
and storage needs. Video motion detection, shock detection, active tampering alarm and open casing intrusion switch. Corridor format, barrel distortion correction, defogging and electronic image stabilization. Scene profiles. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Operation in -40°C to +60°C. PoE+ class4 or 12-28VDC input. Support for optional AXIS P13 Weathershield Extension A. Includes pre-mounted AXIS Fixed Box IR illuminator Kit A, removable sunshield, wall bracket, Torx T20 screw driver and IP66/67- rated cable glands. Midspan or power supply not included.73310210853439.047.87	· · ·				
shock detection, active tampering alarm and open casing intrusion switch. Corridor format, barrel distortion correction, defogging and electronic image stabilization. Scene profiles. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Operation in -40°C to +60°C. PoE+ class4 or 12-28VDC input. Support for optional AXIS P13 Weathershield Extension A. Includes pre-mounted AXIS Fixed Box IR illuminator Kit A, removable sunshield, wall bracket, Torx T20 screw driver and IP66/67- rated cable glands. Midspan or power supply not included.73310210853439.047.87					
open casing intrusion switch. Corridor format, barrel distortion correction, defogging and electronic image stabilization. Scene profiles. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Operation in -40°C to +60°C. PoE+ class4 or 12-28VDC input. Support for optional AXIS P13 Weathershield Extension A. Includes pre-mounted AXIS Fixed Box IR illuminator Kit A, removable sunshield, wall bracket, Torx T20 screw driver and IP66/67- rated cable glands. Midspan or power supply not included.73310210853439.047.87					
barrel distortion correction, defogging and electronic image stabilization. Scene profiles. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Operation in -40°C to +60°C. PoE+ class4 or 12-28VDC input. Support for optional AXIS P13 Weathershield Extension A. Includes pre-mounted AXIS Fixed Box IR illuminator Kit A, removable sunshield, wall bracket, Torx T20 screw driver and IP66/67- rated cable glands. Midspan or power supply not included.73310210853439.047.87	· · · ·				
electronic image stabilization. Scene profiles. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Operation in -40°C to +60°C. PoE+ class4 or 12-28VDC input. Support for optional AXIS P13 Weathershield Extension A. Includes pre-mounted AXIS Fixed Box IR illuminator Kit A, removable sunshield, wall bracket, Torx T20 screw driver and IP66/67- rated cable glands. Midspan or power supply not included. 7331021085343 9.04 7.87					
Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for R\$422/485 communication. Operation in -40°C to +60°C. PoE+ class4 or 12-28VDC input. Support for optional AXIS P13 Weathershield Extension A. Includes pre-mounted AXIS Fixed Box IR illuminator Kit A, removable sunshield, wall bracket, Torx T20 screw driver and IP66/67- rated cable glands. Midspan or power supply not included. AXIS P1377-LE Barebone with extra heater. No \$ 1,029.00 7331021085343 9.04 7.87					
analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Operation in -40°C to +60°C. POE+ class4 or 12-28VDC input. Support for optional AXIS P13 Weathershield Extension A. Includes pre-mounted AXIS Fixed Box IR illuminator Kit A, removable sunshield, wall bracket, Torx T20 screw driver and IP66/67- rated cable glands. Midspan or power supply not included.73310210853439.047.87					
for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Operation in -40°C to +60°C. PoE+ class4 or 12-28VDC input. Support for optional AXIS P13 Weathershield Extension A. Includes pre-mounted AXIS Fixed Box IR illuminator Kit A, removable sunshield, wall bracket, Torx T20 screw driver and IP66/67- rated cable glands. Midspan or power supply not included. AXIS P1377-LE Barebone with extra heater. No 1,029.00 7331021085343 9.04 7.87 					
memory card slot for optional local video storage. Serial port for RS422/485 communication. Operation in -40°C to +60°C. PoE+ class4 or 12-28VDC input. Support for optional AXIS P13 Weathershield Extension A. Includes pre-mounted AXIS Fixed Box IR illuminator Kit A, removable sunshield, wall bracket, Torx T20 screw driver and IP66/67- rated cable glands. Midspan or power supply not included.Fixed Box IRIncludes pre-mounted AXIS P13 Weathershield Extension A. Includes pre-mounted AXIS Fixed Box IR illuminator Kit A, removable sunshield, wall bracket, Torx T20 screw driver and IP66/67- rated cable glands. Midspan or power supply not included.Fixed Box IR POE+ Classe P1377-LE Barebone with extra heater. No\$ 1,029.0073310210853439.047.87					
storage. Serial port for RS422/485 communication. Operation in -40°C to +60°C. PoE+ class4 or 12-28VDC input. Support for optional AXIS P13 Weathershield Extension A. Includes pre-mounted AXIS Fixed Box IR illuminator Kit A, removable sunshield, wall bracket, Torx T20 screw driver and IP66/67- rated cable glands. Midspan or power supply not included.Image: Comparison of the stress of the st	•				
communication. Operation in -40°C to +60°C. PoE+ class4 or 12-28VDC input. Support for optional AXIS P13 Weathershield Extension A. Includes pre-mounted AXIS Fixed Box IR illuminator Kit A, removable sunshield, wall bracket, Torx T20 screw driver and IP66/67- rated cable glands. Midspan or power supply not included.and the form of the					
PoE+ class4 or 12-28VDC input. Support for optional AXIS P13 Weathershield Extension A. Includes pre-mounted AXIS Fixed Box IR illuminator Kit A, removable sunshield, wall bracket, Torx T20 screw driver and IP66/67- rated cable glands. Midspan or power supply not included.Image: Comparison of the streshield included in the streshield included included in the streshield extension of the streshield e					
optional AXIS P13 Weathershield Extension A. Includes pre-mounted AXIS Fixed Box IR illuminator Kit A, removable sunshield, wall bracket, Torx T20 screw driver and IP66/67- rated cable glands. Midspan or power supply not included.Image: Comparison of the stress of	•				
Includes pre-mounted AXIS Fixed Box IR illuminator Kit A, removable sunshield, wall bracket, Torx T20 screw driver and IP66/67- rated cable glands. Midspan or power supply not included.Image: Comparison of the stress of the str					
illuminator Kit A, removable sunshield, wall bracket, Torx T20 screw driver and IP66/67- rated cable glands. Midspan or power supply not included.included.included.AXIS P1377-LE Barebone with extra heater. No\$ 1,029.0073310210853439.047.87					
bracket, Torx T20 screw driver and IP66/67-rated cable glands. Midspan or power supply not included. Image: Comparison of the street of th					
rated cable glands. Midspan or power supply not included. Image: Comparison of the system of the					
not included. AXIS P1377-LE Barebone with extra heater. No \$ 1,029.00 7331021085343 9.04 7.87	,				
AXIS P1377-LE Barebone with extra heater. No \$ 1,029.00 7331021085343 9.04 7.87	• • • • • • • • • • • • • • • • • • • •				
	not included.				
	AXIS P1377-LE Barebone with extra heater. No	\$ 1,029.00	7331021085343	9.04	7.87
lens. Midspan not included	lens. Midspan not included				

Outdoor, 4K Ultra HD (8MP) camera, day/night, fixed box camera providing Forensic WDR and Lightfinder for demanding light conditions. Includes an IR corrected varifocal 2.8-8.5 mm F1.2 i-CS lens with P-Iris, remote zoom and focus for installation (camera also supports P- Iris and DC-iris lenses with CS Mount). Multiple, individually configurable H.264 and Motion JPEG streams; max 4K Ultra HD/8MP at 25/30 fps in 16:9 format. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Two-way audio. I/O for alarm/event handling, Memory card slot for optional local video storage. Serial port for RS422/485 communication NEMA 4X, IP66/67 and IK10-rated for operation in -40°C to +55°. Powered by IEEE 802.3af Type 1 Class 3 midspan. Includes a removable sunshield, wall bracket, Torx T20 screw driver and IP66/67- rated cable glands. Midspan not included.	\$	1,099.00	7331021060418	9.04	9.45
AXIS P1368-E Barebone. No lens. Midspan not	\$	999.00	7331021062894	7.50	9.45
included	^			• • •	
4K resolution, day/night, fixed box camera providing Forensic WDR and Lightfinder technology. Features a 1/1.8" image sensor. Includes an IR corrected varifocal 3.9-10 mm F1.5 P-Iris lens and remote back focus. Camera also supports CS-mount DC-iris lenses and i- CS lenses for remote installation zoom and focus. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 4K at 25/30 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, shock detection, active tampering alarm and security lock slot. Corridor format, barrel distortion correction, defogging and electronic image stabilization. Scene profiles. Two-way audio, audio detection with either built-in microphone or optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. PoE class 3 or 12-28VDC input. Includes black stand for wall and ceiling mount with hole for easy cable management. Midspan or power supply not included.	\$	899.00	7331021068117	2.98	7.87
AXIS P1378 Barebone in single pack. No lens.	\$	849.00	7331021068131	2.73	7.87
No power supply.					

Outdoor, NEMA 4X, IP66/67 and IK10-rated, 4K	\$ 1,179.00	7331021068124	9.48	7.87
resolution, day/night, fixed box camera				
providing providing Forensic WDR and				
Lightfinder technology. Features a 1/1.8" image				
sensor. OptimizedIR, a power-efficient 850nm				
IR LED technology covering 50 meters (164				
feet).Includes an IR corrected varifocal 3.9-10				
mm F1.5 P-Iris lens and remote back focus.				
Camera also supports CS-mount DC-iris lenses				
and i-CS lenses for remote installation zoom				
and focus. Multiple, individually configurable				
H.264, H.265 and Motion JPEG streams; 4K at				
25/30 fps. Axis Zipstream technology for				
reduced bandwidth and storage needs. Video				
motion detection, shock detection, active				
tampering alarm and open casing intrusion				
switch. Corridor format, barrel distortion				
correction, defogging and electronic image				
stabilization. Scene profiles. Two-way audio,				
audio detection with optional analog or digital				
microphone. Supervised I/O for alarm/event				
handling, MicroSD/MicroSDHC memory card				
slot for optional local video storage. Serial port				
for RS422/485 communication. Operation in -				
40°C to +60°C. PoE+ class4 or 12-28VDC input.				
Support for optional AXIS P13 Weathershield				
Extension A. Includes pre-mounted AXIS Fixed				
Box IR illuminator Kit A, removable sunshield,				
wall bracket, Torx T20 screw driver and IP66/67-				
rated cable glands. Midspan or power supply				
not included.				
AXIS P1378-LE Barebone. No lens. Midspan not	\$ 1,129.00	7331021069657	9.26	7.87
included				
J				

Outdoor with extra heater, NEMA 4X, IP66/67	\$ 1,179.00	7331021085329	9.48	7.87
and IK10-rated, 4K resolution, day/night, fixed				
box camera providing providing Forensic WDR				
and Lightfinder technology. Features a 1/1.8"				
image sensor. OptimizedIR, a power-efficient				
850nm IR LED technology covering 40 meters				
(130 feet).Includes an IR corrected varifocal 3.9-				
10 mm F1.5 P-Iris lens and remote back focus.				
Camera also supports CS-mount DC-iris lenses				
and i-CS lenses for remote installation zoom				
and focus. Multiple, individually configurable				
H.264, H.265 and Motion JPEG streams; 4K at				
25/30 fps. Axis Zipstream technology for				
reduced bandwidth and storage needs. Video				
motion detection, shock detection, active				
tampering alarm and open casing intrusion				
switch. Corridor format, barrel distortion				
correction, defogging and electronic image				
stabilization. Scene profiles. Two-way audio,				
audio detection with optional analog or digital				
microphone. Supervised I/O for alarm/event				
handling, MicroSD/MicroSDHC memory card				
slot for optional local video storage. Serial port				
for RS422/485 communication. Operation in -				
40°C to +60°C. PoE+ class4 or 12-28VDC input.				
Support for optional AXIS P13 Weathershield				
Extension A. Includes pre-mounted AXIS Fixed				
Box IR illuminator Kit A, removable sunshield,				
wall bracket, Torx T20 screw driver and IP66/67-				
rated cable glands. Midspan or power supply				
not included.				
AXIS P1378-LE Barebone with extra heater. No	\$ 1,129.00	7331021085350	9.26	7.87
lens. Midspan not included				

	•		 		
Compact outdoor, HDTV, day/night, fixed bullet camera providing Forensic WDR and Lightfinder for demanding light conditions. IR corrected varifocal 2.8-8.5 mm F1.2 P-iris lens with remote 3x optical zoom and focus. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p /2MP resolution at 50/60 fps Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, active tampering alarm, shock detection and corridor format. Audio mic/line in, I/O for alarm/event handling and memory card slot for optional local video storage. OptimizedIR, a power- efficient IR LED technology covering 40 meters (131 feet). Integrated bracket for easy mounting on wall and ceiling. NEMA 4X, IP66/67 and IK10-rated for operation in -40°C to +60°C(-40 °F to 140 °F). Powered by IEEE 802.3af Type 1 Class 3 midspan (PoE). Midspan not included.	\$	699.00	7331021064270	2.89	5.51
Please check the supported countries Visit www.axis.com for supported products and application download. Compact outdoor, HDTV / 1080p, day/night, fixed bullet camera with built-in AXIS License Plate Verifier application. Detect and verify vehicles in single lanes with speed up to 70 km/h (45 mph) in 7 to 20 meter distance (23-65 feet). License plate reading time less than 1 second. OptimizedIR, Forensic WDR, Lightfinder, shock detection, IK10, IP66/67, NEMA TS-2-2003 v02.06. Operation temperature -40°C to +60°C (- 40°F to 140°F). Integrated bracket for easy mounting on wall and ceiling. License plate verification day and night. Powered by IEEE 802.3af Type 1 Class 3 midspan (PoE) or or 12- 28 VDC input. Midspan not included.	\$	1,289.00	7331021075160	3.44	5.71

 Please check the supported countries Visit www.axis.com for supported products and application download. Compact outdoor, HDTV / 1080p, day/night, fixed bullet camera with built-in AXIS License Plate Verifier application. Detect and verify vehicles in single lanes with speed up to 70 km/h (45 mph) in 7 to 20 meter distance (23-65 feet). License plate reading time less than 1 second. OptimizedIR, Forensic WDR, Lightfinder, shock detection, IK10, IP66/67, NEMA TS-2-2003 v02.06. Operation temperature -40°C to +60°C (-40°F to 140°F). Integrated bracket for easy mounting on wall and ceiling. License plate verification day and night. Powered by IEEE 802.3af Type 1 Class 3 midspan (PoE) or or 12-28 VDC input. Midspan not included. 	\$ 1,339.00	7331021084377	3.40	5.51
Compact and outdoor-ready HDTV camera for day and night surveillance. NEMA 4X, IP66/67 and IK10-rated, light weight HDTV 1080p resolution fixed bullet camera providing Forensic WDR and Lightfinder 2.0. Varifocal 3-9 mm F1.6 lens with remote 3 x optical zoom and focus with automatic IR cut filter. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; full HDTV 1080p at 50/60 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, shock detection and active tampering alarm, defogging and corridor format. Audio in and I/O port, microSD/SDHC memory card slot for edge storage. OptimizedIR, a power-efficient LED technology with adaptable angle of IR illumination up to 40 meters (131 feet). Integrated bracket for easy mounting on wall and ceiling. Power over Ethernet. Operating conditions -40 °C to 60 °C (- 40 °F to 140 °F). Includes removable sunshield, mounting bracket, Torx L-key, and IP66/67- rated cable glands. Midspan not included.	\$ 649.00	7331021070608	2.91	5.75

Compact and outdoor-ready 1080p HDTV fixed bullet camera for day and night surveillance. NEMA 4X, IP66/67 and IK10-rated, light weight network camera providing Forensic WDR and Lightfinder 2.0. Varifocal 10.9-29 mm F1.7 lens with remote 3 x optical zoom and focus with automatic IR cut filter. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; full HDTV 1080p at 50/60 fps. Axis Zipstream technology for reduced bandwidth and storage needs. AXIS Object Analytics, shock detection and active tampering alarm, defogging and corridor format. Electronic Image Stabilization, Audio in and supervised I/O port, microSD/SDHC memory card slot for edge storage. OptimizedIR, a power-efficient LED technology with adaptable angle of IR illumination up to 80 meters (262 feet). Integrated bracket for easy mounting on wall and ceiling. Power over Ethernet and DC input. Operating conditions -40 °C to 60 °C (-40 °F to 140 °F). Includes removable sunshield, mounting bracket, Torx L-keys, and IP66/67- rated cable glands. Midspan not included.	\$ 749.00	7331021072480	3.35	5.59
Compact outdoor, NEMA 4X, IP66, IP67 and IK10-rated 2MP /1080p resolution, day/night, fixed bullet camera with Deep Learning Processing Unit (DLPU). Support for Forensic WDR and Lightfinder 2.0 and OptimizedIR. Varifocal 3-9 mm P-iris lens with remote zoom and focus. Multiple, individually configurable H.264/H.265 with Zipstream and Motion JPEG. 2MP at 50/60 fps. Axis Zipstream technology for reduced bandwidth and storage needs. AXIS Object Analytics, Video motion detection, shock detection and active tampering alarm. Barrel distortion correction, defogging and scene profiles. Audio in and supervised I/O port, microSD memory card slot for local storage. MQTT Support. AXIS Edge Vault for added cyber security. OptimizedIR, a power- efficient IR LED technology. Integrated bracket for easy mounting on wall and ceiling. Powered by IEEE 802.3af/802.3at Type 1 Class 3 and 10-28V DC power with redundancy. Operating conditions -40 °C to 60 °C (-40 °F to 140 °F). Includes removable weather shield, mounting bracket, Torx L-keys, and IP66/67- rated cable glands. Midspan not included.	749.00	7331021076099	3.35	10.24

	•		 		
Compact outdoor, NEMA 4X, IP66, IP67 and	\$	799.00	7331021076105	3.35	10.24
IK10-rated 2MP /1080p resolution, day/night,					
fixed bullet camera with Deep Learning					
Processing Unit (DLPU). Support for Forensic					
WDR and Lightfinder 2.0 and OptimizedIR.					
Varifocal 10.9-29 mm P-iris tele lens with					
remote zoom and focus. Multiple, individually					
configurable H.264/H.265 with Zipstream and					
Motion JPEG. 2MP at 50/60 fps. Axis Zipstream					
technology for reduced bandwidth and storage					
needs. AXIS Object Analytics, Video motion					
detection, shock detection and active					
tampering alarm.					
Electronic image stabilization, Barrel distortion					
correction, defogging and scene profiles. Audio					
in and supervised I/O port, microSD memory					
card slot for local storage. MQTT Support. AXIS					
Edge Vault for added cyber security.					
OptimizedIR, a power-efficient IR LED					
technology. Integrated bracket for easy					
mounting on wall and ceiling.					
Powered by IEEE 802.3af/802.3at Type 1 Class 3					
and 10-28V DC power with redundancy.					
Operating conditions -40 °C to 60 °C (-40 °F to					
140 °F). Includes removable weather shield,					
mounting bracket, Torx L-keys, and IP66/67-					
rated cable glands. Midspan not included.					
·					
Compact outdoor, 5MP resolution, day/night,	\$	749.00	7331021059153	2.89	5.71
fixed bullet camera providing Forensic WDR	Ŧ			2.00	•
and Lightfinder for demanding light conditions.					
IR corrected varifocal 2.8-8.5 mm F1.2 P-iris					
lens with remote 3x optical zoom and focus.					
Multiple, individually configurable H.264 and					
Motion JPEG streams; max 5MP at 25/30 fps in					
16:9 format. Axis Zipstream technology for					
I required pandwigth and storado hoods. Vidoo					
reduced bandwidth and storage needs. Video					
motion detection, active tampering alarm,					
motion detection, active tampering alarm, shock detection and corridor format. Audio					
motion detection, active tampering alarm, shock detection and corridor format. Audio mic/line in, I/O for alarm/event handling and					
motion detection, active tampering alarm, shock detection and corridor format. Audio mic/line in, I/O for alarm/event handling and memory card slot for optional local video					
motion detection, active tampering alarm, shock detection and corridor format. Audio mic/line in, I/O for alarm/event handling and memory card slot for optional local video storage. OptimizedIR, a power-efficient IR LED					
motion detection, active tampering alarm, shock detection and corridor format. Audio mic/line in, I/O for alarm/event handling and memory card slot for optional local video storage. OptimizedIR, a power-efficient IR LED technology covering 30 meters (98 feet).					
motion detection, active tampering alarm, shock detection and corridor format. Audio mic/line in, I/O for alarm/event handling and memory card slot for optional local video storage. OptimizedIR, a power-efficient IR LED technology covering 30 meters (98 feet). Integrated bracket for easy mounting on wall					
motion detection, active tampering alarm, shock detection and corridor format. Audio mic/line in, I/O for alarm/event handling and memory card slot for optional local video storage. OptimizedIR, a power-efficient IR LED technology covering 30 meters (98 feet). Integrated bracket for easy mounting on wall and ceiling.					
motion detection, active tampering alarm, shock detection and corridor format. Audio mic/line in, I/O for alarm/event handling and memory card slot for optional local video storage. OptimizedIR, a power-efficient IR LED technology covering 30 meters (98 feet). Integrated bracket for easy mounting on wall and ceiling. NEMA 4X, IP66/67 and IK10-rated for operation					
motion detection, active tampering alarm, shock detection and corridor format. Audio mic/line in, I/O for alarm/event handling and memory card slot for optional local video storage. OptimizedIR, a power-efficient IR LED technology covering 30 meters (98 feet). Integrated bracket for easy mounting on wall and ceiling. NEMA 4X, IP66/67 and IK10-rated for operation in -40°C to +60°C(-40 °F to 140 °F).					
motion detection, active tampering alarm, shock detection and corridor format. Audio mic/line in, I/O for alarm/event handling and memory card slot for optional local video storage. OptimizedIR, a power-efficient IR LED technology covering 30 meters (98 feet). Integrated bracket for easy mounting on wall and ceiling. NEMA 4X, IP66/67 and IK10-rated for operation in -40°C to +60°C(-40 °F to 140 °F). Powered by IEEE 802.3af Type 1 Class 3					
motion detection, active tampering alarm, shock detection and corridor format. Audio mic/line in, I/O for alarm/event handling and memory card slot for optional local video storage. OptimizedIR, a power-efficient IR LED technology covering 30 meters (98 feet). Integrated bracket for easy mounting on wall and ceiling. NEMA 4X, IP66/67 and IK10-rated for operation in -40°C to +60°C(-40 °F to 140 °F).					
motion detection, active tampering alarm, shock detection and corridor format. Audio mic/line in, I/O for alarm/event handling and memory card slot for optional local video storage. OptimizedIR, a power-efficient IR LED technology covering 30 meters (98 feet). Integrated bracket for easy mounting on wall and ceiling. NEMA 4X, IP66/67 and IK10-rated for operation in -40°C to +60°C(-40 °F to 140 °F). Powered by IEEE 802.3af Type 1 Class 3					
motion detection, active tampering alarm, shock detection and corridor format. Audio mic/line in, I/O for alarm/event handling and memory card slot for optional local video storage. OptimizedIR, a power-efficient IR LED technology covering 30 meters (98 feet). Integrated bracket for easy mounting on wall and ceiling. NEMA 4X, IP66/67 and IK10-rated for operation in -40°C to +60°C(-40 °F to 140 °F). Powered by IEEE 802.3af Type 1 Class 3					
motion detection, active tampering alarm, shock detection and corridor format. Audio mic/line in, I/O for alarm/event handling and memory card slot for optional local video storage. OptimizedIR, a power-efficient IR LED technology covering 30 meters (98 feet). Integrated bracket for easy mounting on wall and ceiling. NEMA 4X, IP66/67 and IK10-rated for operation in -40°C to +60°C(-40 °F to 140 °F). Powered by IEEE 802.3af Type 1 Class 3					

Compact outdoor, NEMA 4X, IP66, IP67 and	\$ 849.00	 7331021076112	3.35	10.24
IK10-rated 5MP resolution, day/night, fixed bullet camera with Deep Learning Processing Unit (DLPU). Support for Forensic WDR and Lightfinder 2.0 and OptimizedIR. Varifocal 2.8-8				
mm P-iris lens with remote zoom and focus. Multiple, individually configurable H.264/H.265 with Zipstream and Motion JPEG. 5MP at 25/30.				
Axis Zipstream technology for reduced bandwidth and storage needs. AXIS Object Analytics, Video motion detection, shock detection and active tampering alarm. Barrell distortion correction, defogging and scene profiles. Audio in and supervised I/O port, microSD memory card slot for local storage. MQTT Support. AXIS Edge Vault for added cyber security. OptimizedIR, a power- efficient IR LED technology. Integrated bracket for easy mounting on wall and ceiling. Powered by IEEE 802.3af/802.3at Type 1 Class 3 and 10-28V DC power with redundancy.				
Operating conditions -40 °C to 60 °C (-40 °F to 140 °F). Includes removable sunshield, mounting bracket, Torx L-keys, and IP66/67- rated cable glands. Midspan not included.				
Compact outdoor, 4K Ultra HD (8MP) resolution, day/night, fixed bullet camera providing Forensic WDR and Lightfinder for demanding light conditions. IR corrected varifocal 2.8-9.8 mm F1.6 P-iris lens with remote 3.5x optical zoom and focus. Multiple, individually configurable H.264 and Motion JPEG streams; max 4K Ultra HD/8MP at 25/30 fps in 16:9 format. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, active tampering alarm, shock detection and corridor format. Audio mic/line in, I/O for alarm/event handling and memory card slot for optional local video storage. OptimizedIR, a power-efficient IR LED technology covering 25 meters (82 feet). Integrated bracket for easy mounting on wall and ceiling. NEMA 4X, IP66/67 and IK10-rated for operation in -40°C to +60°C(-40 °F to 140 °F). Powered by IEEE 802.3af Type 1 Class 3 midspan (PoE). Midspan not included.	\$ 949.00	7331021059160	2.89	5.71

Compact outdoor, NEMA 4X, IP66, IP67 and IK10-rated 8MP resolution, day/night, fixed bullet camera with Deep Learning Processing Unit (DLPU). Support for Forensic WDR and Lightfinder 2.0 and OptimizedIR. Varifocal 6-13 mm P-iris lens with remote zoom and focus. Multiple, individually configurable H.264/H.265 with Zipstream and Motion JPEG. 8MP stream up to 60 fps, 30fps with WDR. Axis Zipstream technology for reduced bandwidth and storage needs. AXIS Object Analytics, Video motion detection, shock detection and active tampering alarm. Barrell distortion correction, defogging and scene profiles. Audio in and supervised I/O port, microSD memory card slot for local storage. MQTT Support. AXIS Edge Vault for added cyber security. OptimizedIR, a power- efficient IR LED technology. Integrated bracket for easy mounting on wall and ceiling. Powered by IEEE 802.3af/802.3at Type 1 Class 3 and 10-28V DC power with redundancy. Operating conditions -40 °C to 60 °C (-40 °F to 140 °F). Includes removable sunshield, mounting bracket, Torx L-keys, and IP66/67- rated cable glands. Midspan not included.	\$ 1,049.00	7331021076129	3.35	10.24
HDTV 1080p resolution, day/night, fixed box camera providing Forensic WDR and Lightfinder 2.0. Includes an IR corrected varifocal 2.8-8.5 mm F1.2 i-CS lens with remote zoom and focus. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; full HDTV 1080p/2MP resolution up to 60 fps with Forensic WDR and up to 120 fps without. Axis Zipstream technology for reduced bandwidth and storage needs. Deep learning processing unit, shock detection, barrel distortion correction, defogging and electronic image stabilization. Scene profiles. Two-way audio, audio detection with either built-in microphone or optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Power over Ethernet or 12-28VDC input. Includes black stand for wall and ceiling mount with hole for easy cable management. Midspan or power supply not included.	\$ 1,099.00	7331021071544	3.00	9.84

Outdoor, NEMA 4X, IP66/67 and IK10-rated, light weight HDTV 1080p resolution, day/night, fixed box camera providing OptimizedIR, Forensic WDR and Lightfinder 2.0. Includes an IR corrected varifocal 2.8-8.5 mm F1.2 i-CS lens with remote zoom and focus. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; full HDTV 1080p/2MP resolution up to 60 fps with Forensic WDR and up to 120 fps without. Axis Zipstream technology for reduced bandwidth and storage needs. Deep learning processing unit, shock detection, intrusion alarm. Barrel distortion correction, defogging and electronic image stabilization. Scene profiles. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Powered by IEEE 802.3at Type 2 Class 4 (PoE+). Built-in heaters and fan, Arctic Temperature Control for start-up in -40°C to 60°C (-40 °F to 140 °F).I ncludes removable sunshield, wall bracket, Torx T20 screw driver and IP66/67- rated cable glands. Midspan or power supply not included.	\$ 1,399.00	7331021071797	19.62	11.81
AXIS Q1615 MK III Barebone in single pack. No	\$ 999.00	7331021071803	2.76	9.84
lens. No power supply. 1/2" image sensor, HDTV, Day/night fixed camera providing Forensic WDR and Lightfinder for demanding light conditions. Varifocal 3.9-10 mm i-CS lens with remote zoom and focus for installation. Support for P- Iris and DC-iris lenses, multiple, individually configurable H.264 and Motion JPEG streams; full HDTV 1080p/2MP resolution up to 60 fps with Forensic WDR and up to 120 fps without. Zipstream for reduced bandwidth and storage. Fence Guard, Motion Guard, Video motion detection, shock detection and active tampering alarm. Barrel distortion correction, Defog and Electronic image stabilization. Scene profiles.Two-way audio with built-in microphone and audio detection. I/O for alarm/event handling. Memory card slot for optional local video storage. Serial port for RS485/RS422 communication. Power over Ethernet or 8-28 V DC input. Includes stand for wall and ceiling mount. Midspan or power supply not included	\$ 1,199.00	7331021062283	3.59	8.07

AVIS 04645 Barahana in single pack No long	¢	000.00		7224024062024	2.22	9.07
AXIS Q1645 Barebone in single pack. No lens. No power supply.	\$	999.00		7331021062931	3.33	8.07
1/2" image sensor, outdoor, NEMA 4X, IP66 and	\$	1,499.00		7331021062290	20.50	11.81
IK10-rated HDTV, day/night fixed camera	Ŷ	1,400.00		1001021002200	20.00	1
providing OptimizedIR, Forensic WDR and						
Lightfinder. Varifocal 3.9-10 mm i-CS lens with						
remote zoom and focus. Support for CS-mount						
P-Iris and DC-iris lenses, multiple, individually						
configurable H.264 and Motion JPEG streams;						
full HDTV 1080p/2MP resolution up to 60 fps						
with Forensic WDR and up to 120 fps without.						
Zipstream for reduced bandwidth and storage.						
Includes analytics AXIS Guard Suite, shock						
detection and active tampering alarm. Barrel						
distortion correction, Defog and Electronic						
image stabilization. Scene profiles. Two-way						
audio and I/O for alarm/event handling. Memory						
card slot for optional local video storage. Serial						
port for RS485/RS422 communication.						
Powered by IEEE 802.3at Type 2 Class 4 (PoE+).						
Built-in heaters and fan, Arctic Temperature						
Control for start up in -40°C to 60°C (-40 °F to						
140 °F). Includes a removable sunshield and						
wall bracket. Midspan not included.						
1/2" sensor, 5 MP, Day/night fixed camera	\$	1,399.00		7331021058545	3.62	8.07
providing Forensic WDR and Lightfinder for	Ť	.,			0.02	0.01
demanding light conditions. Varifocal 3.9-10						
mm i-CS lens with remote zoom and focus for						
installation. Support for P-Iris and DC-iris						
lenses, multiple, individually configurable						
H.264 and Motion JPEG streams; 5 MP at 30 fps						
with Forensic WDR, and 4 MP at up to 60 fps						
without Forensic WDR. Zipstream for reduced						
bandwidth and storage. Fence Guard, Motion						
Guard, Video motion detection, shock detection						
and active tampering alarm. Barrel distortion						
correction, Defog and Electronic image						
stabilization. Scene profiles. Two-way audio						
with built-in microphone and audio detection.						
I/O for alarm/event handling. Memory card slot						
for optional local video storage. Serial port for						
RS485/RS422 communication. Power over						
Ethernet or 8-28 V DC input. Includes stand for						
wall and ceiling mount. Midspan or power						
supply not included			1	1		1

 1/2" sensor, outdoor, NEMA 4X, IP66 and IK10-rated, 5 MP, Day/night fixed camera providing OptimizedIR, Forensic WDR and Lightfinder. Varifocal 3.9-10 mm i-CS lens with remote zoom and focus. Support for CS-mount P-Iris and DC-iris lenses, multiple, individually configurable H.264 and Motion JPEG streams; 5 MP at 30 fps with Forensic WDR, and 4 MP at up to 60 fps without Forensic WDR. Zipstream for reduced bandwidth and storage. InIcudes analytics AXIS Guard Suite, shock detection and active tampering alarm and shock detection. Barrel distortion correction, Defog and Electronic image stabilization. Scene profiles. Two-way audio and I/O for alarm/event handling. Memory card slot for optional local video storage. Serial port for RS485/RS422 communication. Powered by IEEE 802.3at Type 2 Class 4 (PoE+). Built-in heaters and fan, Arctic Temperature Control for start up in -40°C to 60°C (-40 °F to 140 °F). Includes a removable sunshield and wall bracket. Midspan not included. 	\$ 1,699.00	7331021058552	20.50	11.81
 1/1.8" sensor, 4 MP, Day/night fixed box camera with Deep Learning Processing Unit (DLPU). Support for Forensic WDR and Lightfinder 2.0. Includes an IR corrected varifocal 3.9-10 mm F1.5 i-CS lens with remote zoom and focus. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. 4MP stream up to 60 fps, 30 fps with WDR. AXIS Object Analytics, Video motion detection, shock detection and active tampering alarm. AXIS Edge Vault with FIPS certified TPM for added cyber security. Barrel distortion correction, defogging, electronic image stabilization and scene profiles. MQTT Support. Two-way audio, audio detection with either built-in microphone or optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Powered by IEEE 802.3af Type1 Class 3 (PoE) or 10-28 V DC power with redundancy. Includes black stand for wall and ceiling. Midspan or power supply not included. 	\$ 1,299.00	7331021073944	2.43	8.27

1/1.8" sensor, 4 MP, Day/night fixed box camera	\$ 1,099.00	7331021074668	1.63	8.27
with Deep Learning Processing Unit (DLPU).				
Support for Forensic WDR and Lightfinder 2.0.				
Multiple, individually configurable streams,				
H.264/H.265 with Zipstream and Motion JPEG.				
4MP stream up to 60 fps, 30 fps with WDR.				
AXIS Object Analytics, Video motion detection,				
shock detection and active tampering alarm.				
AXIS Edge Vault with FIPS certified TPM for				
added cyber security. Barrel distortion				
correction, defogging, electronic image				
stabilization and scene profiles. MQTT Support.				
Two-way audio, audio detection with either				
built-in microphone or optional analog or				
digital microphone. Supervised I/O for				
alarm/event handling, MicroSD/MicroSDHC				
memory card slot for optional local video				
storage. Serial port for RS422/485				
communication. Powered by IEEE 802.3af				
Type1 Class 3 (PoE) or 10-28 V DC power with				
redundancy. Lens and stand are not included				
but available as optional accessories. Midspan				
and power supply not included.				

1/1.8" image sensor, outdoor, NEMA 4X, IP66,	\$	1,799.00	7331021073982	12.13	7.87
IP67 and impact resistant, 4 MP, Day/night fixed	•	.,			
box camera with Deep Learning Processing					
Unit (DLPU). Built in wiper. Support for					
Forensic WDR and Lightfinder 2.0.					
OptimizedIR, a power-efficient 850nm IR and					
White IR LED technology. Includes an IR					
corrected varifocal 3.9-10 mm F1.5 i-CS lens					
with remote zoom and focus. Multiple,					
individually configurable streams, H.264/H.265					
with Zipstream and Motion JPEG. 4MP stream					
up to 60 fps, 30 fps with WDR. AXIS Object					
Analytics, Video motion detection, shock					
detection and active tampering alarm. AXIS					
Edge Vault with FIPS certified TPM for added					
cyber security. Barrel distortion correction,					
defogging, electronic image stabilization and					
scene profiles. MQTT Support. Two-way audio,					
audio detection with optional analog or digital					
microphone. Supervised I/O for alarm/event					
handling, MicroSD/MicroSDHC memory card					
slot for optional local video storage. Serial port					
for RS422/485 communication. Powered by					
IEEE 802.3at Type2 Class 4 (PoE+) or 10-28 V					
DC power with redundancy. Built-in heater,					
Arctic Temperature Control for start-up in -40°C					
to +60°C (-40 °F to 140 °F). Includes removable					
sunshield, wall bracket, Torx T20 screwdriver and cable glands. Midspan or power supply not					
included.					
					ļļ

IP67 and impact resistant, 4 MP, Day/night fixed box camera with Deep Learning Processing Unit (DLPU). Built in wiper. Support for Forensic WDR and Lightfinder 2.0. OptimizedIR, a power-efficient 850nm IR and White LED technology. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. 4MP stream up to 60 fps, 30 fps with WDR. AXIS Object Analytics, Video motion detection, shock detection and active tampering alarm. AXIS Edge Vault with FIPS certified TPM for added cyber security. Barrel distortion correction, defogging, electronic image stabilization and scene profiles. MQTT Support. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Powered by	1/1.8" image sensor, outdoor, NEMA 4X, IP66,	\$	1,549.00	7331021077362	9.88	7.87
box camera with Deep Learning Processing Unit (DLPU). Built in wiper. Support for Forensic WDR and Lightfinder 2.0. OptimizedIR, a power-efficient 850nm IR and White LED technology. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. 4MP stream up to 60 fps, 30 fps with WDR. AXIS Object Analytics, Video motion detection, shock detection and active tampering alarm. AXIS Edge Vault with FIPS certified TPM for added cyber security. Barrel distortion correction, defogging, electronic image stabilization and scene profiles. MQTT Support. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Powered by	S 1 1 1 1	Ŧ	,			
Unit (DLPU). Built in wiper. Support for Forensic WDR and Lightfinder 2.0. OptimizedIR, a power-efficient 850nm IR and White LED technology. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. 4MP stream up to 60 fps, 30 fps with WDR. AXIS Object Analytics, Video motion detection, shock detection and active tampering alarm. AXIS Edge Vault with FIPS certified TPM for added cyber security. Barrel distortion correction, defogging, electronic image stabilization and scene profiles. MQTT Support. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Powered by						
Forensic WDR and Lightfinder 2.0. OptimizedIR, a power-efficient 850nm IR and White LED technology. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. 4MP stream up to 60 fps, 30 fps with WDR. AXIS Object Analytics, Video motion detection, shock detection and active tampering alarm. AXIS Edge Vault with FIPS certified TPM for added cyber security. Barrel distortion correction, defogging, electronic image stabilization and scene profiles. MQTT Support. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Powered by						
OptimizedIR, a power-efficient 850nm IR and White LED technology. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. 4MP stream up to 60 fps, 30 fps with WDR. AXIS Object Analytics, Video motion detection, shock detection and active tampering alarm. AXIS Edge Vault with FIPS certified TPM for added cyber security. Barrel distortion correction, defogging, electronic image stabilization and scene profiles. MQTT Support. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Powered by	· · · · ·	1				
White LED technology. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. 4MP stream up to 60 fps, 30 fps with WDR. AXIS Object Analytics, Video motion detection, shock detection and active tampering alarm. AXIS Edge Vault with FIPS certified TPM for added cyber security. Barrel distortion correction, defogging, electronic image stabilization and scene profiles. MQTT Support. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Powered by	•					
configurable streams, H.264/H.265 with Zipstream and Motion JPEG. 4MP stream up to 60 fps, 30 fps with WDR. AXIS Object Analytics, Video motion detection, shock detection and active tampering alarm. AXIS Edge Vault with FIPS certified TPM for added cyber security. Barrel distortion correction, defogging, electronic image stabilization and scene profiles. MQTT Support. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Powered by						
Zipstream and Motion JPEG. 4MP stream up to 60 fps, 30 fps with WDR. AXIS Object Analytics, Video motion detection, shock detection and active tampering alarm. AXIS Edge Vault with FIPS certified TPM for added cyber security. Barrel distortion correction, defogging, electronic image stabilization and scene profiles. MQTT Support. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Powered by						
60 fps, 30 fps with WDR. AXIS Object Analytics, Video motion detection, shock detection and active tampering alarm. AXIS Edge Vault with FIPS certified TPM for added cyber security. Barrel distortion correction, defogging, electronic image stabilization and scene profiles. MQTT Support. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Powered by	. .					
Video motion detection, shock detection and active tampering alarm. AXIS Edge Vault with FIPS certified TPM for added cyber security. Barrel distortion correction, defogging, electronic image stabilization and scene profiles. MQTT Support. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Powered by						
active tampering alarm. AXIS Edge Vault with FIPS certified TPM for added cyber security. Barrel distortion correction, defogging, electronic image stabilization and scene profiles. MQTT Support. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Powered by						
FIPS certified TPM for added cyber security. Barrel distortion correction, defogging, electronic image stabilization and scene profiles. MQTT Support. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Powered by	,					
Barrel distortion correction, defogging, electronic image stabilization and scene profiles. MQTT Support. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Powered by						
electronic image stabilization and scene profiles. MQTT Support. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Powered by						
profiles. MQTT Support. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Powered by		1				
detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Powered by	ů.					
microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Powered by		1				
handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Powered by						
slot for optional local video storage. Serial port for RS422/485 communication. Powered by						
for RS422/485 communication. Powered by						
I IEEE 802.3at Type2 Class 4 (PoE+) or 10-28 V	IEEE 802.3at Type2 Class 4 (PoE+) or 10-28 V					
DC power with redundancy. Built-in heater,						
Arctic Temperature Control for start-up in -40°C						
to +60°C (-40 °F to 140 °F). Includes removable						
sunshield and cable glands. Lens and mounts	, ,	1				
are not included but available as optional	-	1				
accessories. Midspan or power supply not						
included.		ı.				
		ı.				
		1				

1/1.8" image sensor, outdoor, NEMA 4X, IP66,	\$ 1,249.00	7331021074682	9.70	7.87
IP67 and IK10 impact resistant, 4 MP, Day/night	·			
fixed box camera with Deep Learning				
Processing Unit (DLPU). Support for Forensic				
WDR and Lightfinder 2.0. Multiple, individually				
configurable streams, H.264/H.265 with				
Zipstream and Motion JPEG. 4MP stream up to				
60 fps, 30 fps with WDR. AXIS Object Analytics,				
Video motion detection, shock detection and				
active tampering alarm. AXIS Edge Vault with				
FIPS certified TPM for added cyber security.				
Barrel distortion correction, defogging,				
electronic image stabilization and scene				
profiles. MQTT Support. Two-way audio, audio				
detection with optional analog or digital				
microphone. Supervised I/O for alarm/event				
handling, MicroSD/MicroSDHC memory card				
slot for optional local video storage. Serial port				
for RS422/485 communication. Powered by				
IEEE 802.3at Type2 Class 4 (PoE+) or 10-28 V				
DC power with redundancy. Built-in heater,				
Arctic Temperature Control for start-up in -40°C				
to +60°C (-40 °F to 140 °F). Includes removable				
sunshield and cable glands. Lens, mounts,				
wiper, illuminator are not included but available				
as optional accessories. Midspan or power				
supply not included.				

AXIS Q1656-DLE Radar-Video Fusion Camera.	\$ 2,499.00	7331021077027	13.67	22.24
Enhanced situational awareness based on the	,			
fusion of visual- and radar sensor information				
in one device.				
1/1.8" image sensor, outdoor, NEMA 4X, IP66,				
IP67 and impact-resistant, 4 MP, Day/night				
radar-video fusion camera with Deep Learning				
Processing Unit (DLPU). Support for Forensic				
WDR and Lightfinder 2.0. OptimizedIR, a power-				
efficient 850nm IR and White IR LED				
technology. Includes an IR corrected varifocal				
3.9-10 mm F1.5 i-CS lens with remote zoom and				
focus. Integrated radar unit, 60.0 GHz-61.5 GHz				
and 95 degree horizontal field of detection. In				
addition to radar-video fusion, radar				
functionality such as built-in analytics				
including classification of humans and				
vehicles, is available and enables filtering on				
distance, customized detection zones, and				
autotracking for PTZ cameras.				
Multiple, individually configurable streams,				
H.264/H.265 with Zipstream and Motion JPEG.				
4MP stream up to 60 fps, 30 fps with WDR.				
AXIS Object Analytics, Video motion detection,				
Radar motion detection, AXIS Speed Monitor,				
shock detection and active tampering alarm.				
Axis Edge Vault with FIPS certified TPM for				
added cyber security. Barrel distortion				
correction, defogging, electronic image				
stabilization and scene profiles. MQTT Support.				
Two-way audio, audio detection with optional				
analog or digital microphone. Supervised I/O				
for alarm/event handling, MicroSD/MicroSDHC				
memory card slot for optional local video				
storage. Serial port for RS422/485				
communication. Powered by IEEE 802.3at				
Type2 Class 4 (PoE+) or 10-28 V DC power with				
rodundancy Ruilt in heater Arctic Tomporature				

Professional photography meets video	\$ 6,369.00	7331021056374	4.41	10.63
surveillance				
AXIS Q1659 Network Camera offers ultra-high				
image resolution for surveillance in superb				
detail at 8 frames per second, achieving				
unprecedented levels of detail for observing				
open spaces and across long distances.				
It features digital single-lens reflex (DSLR)				
imaging technology and offers a choice of				
Canon EF/EF-S lenses, depending on individual				
user needs. Equipped with an EF lens mount,				
the camera enables easy lens changes.				
AXIS Q1659 is compatible with a broad number				
of video management systems, and it supports				
Zipstream that significantly reduces bandwidth				
and storage requirements.				
> 20 MP resolution				
> Canon EF mount and EF/EF-S lenses				
 Axis' Zipstream technology PoE and SFP slot for optional fiber 				
> PoE and SFP slot for optional fiber connectivity				
> Optional accessory housing				
HDTV 1080p camera with 21x motorized zoom,	\$ 1,099.00	7331021075009	2.82	9.25
day/night, fixed block camera with Deep				
Learning Processing Unit (DLPU). Support for Forensic WDR and Lightfinder 2.0. Built-in				
varifocal lens, 4-84.6 mm F1.6 with fixed focus				
and auto focus. Multiple, individually				
configurable streams, H.264/H.265 with				
Zipstream and Motion JPEG. HDTV 1080p/2MP				
resolution up to 60 fps with Forensic WDR. AXIS Object Analytics, Video motion detection,				
shock detection and active tampering alarm.				
Micro-HDMI and HD-SDI output. AXIS Edge				
Vault with FIPS certified TPM for added cyber				
security. Defogging, electronic image				
stabilization and scene profiles. MQTT Support. Two-way audio, audio detection with optional				
analog or digital microphone. Supervised I/O				
for alarm/event handling, MicroSD memory				
card slot for optional local video storage. Serial				
port for RS422/485 communication. Powered by				
IEEE 802.3af Type1 Class 3 or IEEE 802.3at Type2 Class 4 (PoE) or 10-28 V DC power with				
redundancy. Includes black stand for wall and				
ceiling mount. Midspan or power supply not				
included.				

		1	i		
Robust outdoor, color 2 MP/1080p HDTV license plate camera for sharp license plate	\$ 1,399.00		7331021067660	7.23	6.50
images day and night. Multiple, individually					
configurable H.264 and Motion JPEG streams;					
max HDTV 1080p / 2MP resolution at up to					
50/60 fps.					
Varifocal 18-137 mm, 8x optical zoom lens, 16°-					
2.3° HFOV, F2.9 with remote zoom and					
installation focus. License plate capture range					
20-50 meter at night with built-in OptimizedIR at					
speeds up to 130 km/h (81 mph)					
Includes license plate capture assistant for					
easy setup, pixel counter, shock detection,					
active tampering alarm, defogging and electronic image stabilization.					
Audio mic/line in, I/O for alarm/event handling					
and memory card slot for optional local video					
storage.					
Integrated bracket for easy mounting on wall					
and ceiling. Dark grey (NCS S5502-B) casing,					
black fixed metal weather shield with anti-glare		1			
coating.					
NEMA 4X, IP66/67 and impact resistant in -40°C		1			
to +60°C(-40 °F to 140 °F).		1			
Powered by PoE (IEEE 802-3af), RJ45 or IDC					
punchdown connector, 20-28 V DC or 20-24 V					
AC. License plate recognition software, power supply or midspan not included.					
supply of muspan not included.					
		1			
Robust outdoor, 2 MP/HDTV, day/night fixed	\$ 1,299.00		7331021061217	5.73	7.48
bullet camera with 32x optical zoom. Multiple,	\$ 1,299.00	-	7331021061217	5.73	7.48
bullet camera with 32x optical zoom. Multiple, individually configurable H.264 and Motion	\$ 1,299.00		7331021061217	5.73	7.48
bullet camera with 32x optical zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p /2MP	\$ 1,299.00	-	7331021061217	5.73	7.48
bullet camera with 32x optical zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p /2MP resolution at 50/60 fps. Forensic WDR and	\$ 1,299.00		7331021061217	5.73	7.48
bullet camera with 32x optical zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p /2MP resolution at 50/60 fps. Forensic WDR and Lightfinder for demanding light conditions and	\$ 1,299.00	-	7331021061217	5.73	7.48
bullet camera with 32x optical zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p /2MP resolution at 50/60 fps. Forensic WDR and	\$ 1,299.00	-	7331021061217	5.73	7.48
bullet camera with 32x optical zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p /2MP resolution at 50/60 fps. Forensic WDR and Lightfinder for demanding light conditions and Axis Zipstream technology for reduced	\$ 1,299.00	-	7331021061217	5.73	7.48
bullet camera with 32x optical zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p /2MP resolution at 50/60 fps. Forensic WDR and Lightfinder for demanding light conditions and Axis Zipstream technology for reduced bandwidth and storage needs.	\$ 1,299.00	-	7331021061217	5.73	7.48
 bullet camera with 32x optical zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p /2MP resolution at 50/60 fps. Forensic WDR and Lightfinder for demanding light conditions and Axis Zipstream technology for reduced bandwidth and storage needs. Varifocal 4.3–137 mm, F1.4 with remote zoom and autofocus. Includes analytics AXIS Guard Suite, shock 	\$ 1,299.00		7331021061217	5.73	7.48
 bullet camera with 32x optical zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p /2MP resolution at 50/60 fps. Forensic WDR and Lightfinder for demanding light conditions and Axis Zipstream technology for reduced bandwidth and storage needs. Varifocal 4.3–137 mm, F1.4 with remote zoom and autofocus. Includes analytics AXIS Guard Suite, shock detection and active tampering alarm. Corridor 	\$ 1,299.00		7331021061217	5.73	7.48
 bullet camera with 32x optical zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p /2MP resolution at 50/60 fps. Forensic WDR and Lightfinder for demanding light conditions and Axis Zipstream technology for reduced bandwidth and storage needs. Varifocal 4.3–137 mm, F1.4 with remote zoom and autofocus. Includes analytics AXIS Guard Suite, shock detection and active tampering alarm. Corridor format, Barrel distortion correction, Defog, 	\$ 1,299.00	-	7331021061217	5.73	7.48
 bullet camera with 32x optical zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p /2MP resolution at 50/60 fps. Forensic WDR and Lightfinder for demanding light conditions and Axis Zipstream technology for reduced bandwidth and storage needs. Varifocal 4.3–137 mm, F1.4 with remote zoom and autofocus. Includes analytics AXIS Guard Suite, shock detection and active tampering alarm. Corridor format, Barrel distortion correction, Defog, Electronic image stabilization and Scene 	\$ 1,299.00	-	7331021061217	5.73	7.48
 bullet camera with 32x optical zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p /2MP resolution at 50/60 fps. Forensic WDR and Lightfinder for demanding light conditions and Axis Zipstream technology for reduced bandwidth and storage needs. Varifocal 4.3–137 mm, F1.4 with remote zoom and autofocus. Includes analytics AXIS Guard Suite, shock detection and active tampering alarm. Corridor format, Barrel distortion correction, Defog, Electronic image stabilization and Scene profiles 	\$ 1,299.00	-	7331021061217	5.73	7.48
 bullet camera with 32x optical zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p /2MP resolution at 50/60 fps. Forensic WDR and Lightfinder for demanding light conditions and Axis Zipstream technology for reduced bandwidth and storage needs. Varifocal 4.3–137 mm, F1.4 with remote zoom and autofocus. Includes analytics AXIS Guard Suite, shock detection and active tampering alarm. Corridor format, Barrel distortion correction, Defog, Electronic image stabilization and Scene profiles Audio mic/line in, I/O for alarm/event handling 	\$ 1,299.00		7331021061217	5.73	7.48
 bullet camera with 32x optical zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p /2MP resolution at 50/60 fps. Forensic WDR and Lightfinder for demanding light conditions and Axis Zipstream technology for reduced bandwidth and storage needs. Varifocal 4.3–137 mm, F1.4 with remote zoom and autofocus. Includes analytics AXIS Guard Suite, shock detection and active tampering alarm. Corridor format, Barrel distortion correction, Defog, Electronic image stabilization and Scene profiles Audio mic/line in, I/O for alarm/event handling and memory card slot for optional local video 	\$ 1,299.00		7331021061217	5.73	7.48
 bullet camera with 32x optical zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p /2MP resolution at 50/60 fps. Forensic WDR and Lightfinder for demanding light conditions and Axis Zipstream technology for reduced bandwidth and storage needs. Varifocal 4.3–137 mm, F1.4 with remote zoom and autofocus. Includes analytics AXIS Guard Suite, shock detection and active tampering alarm. Corridor format, Barrel distortion correction, Defog, Electronic image stabilization and Scene profiles Audio mic/line in, I/O for alarm/event handling and memory card slot for optional local video storage. 	\$ 1,299.00		7331021061217	5.73	7.48
 bullet camera with 32x optical zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p /2MP resolution at 50/60 fps. Forensic WDR and Lightfinder for demanding light conditions and Axis Zipstream technology for reduced bandwidth and storage needs. Varifocal 4.3–137 mm, F1.4 with remote zoom and autofocus. Includes analytics AXIS Guard Suite, shock detection and active tampering alarm. Corridor format, Barrel distortion correction, Defog, Electronic image stabilization and Scene profiles Audio mic/line in, I/O for alarm/event handling and memory card slot for optional local video 	\$ 1,299.00		7331021061217	5.73	7.48
 bullet camera with 32x optical zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p /2MP resolution at 50/60 fps. Forensic WDR and Lightfinder for demanding light conditions and Axis Zipstream technology for reduced bandwidth and storage needs. Varifocal 4.3–137 mm, F1.4 with remote zoom and autofocus. Includes analytics AXIS Guard Suite, shock detection and active tampering alarm. Corridor format, Barrel distortion correction, Defog, Electronic image stabilization and Scene profiles Audio mic/line in, I/O for alarm/event handling and memory card slot for optional local video storage. OptimizedIR, a power-efficient IR LED 	\$ 1,299.00		7331021061217	5.73	7.48
 bullet camera with 32x optical zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p /2MP resolution at 50/60 fps. Forensic WDR and Lightfinder for demanding light conditions and Axis Zipstream technology for reduced bandwidth and storage needs. Varifocal 4.3–137 mm, F1.4 with remote zoom and autofocus. Includes analytics AXIS Guard Suite, shock detection and active tampering alarm. Corridor format, Barrel distortion correction, Defog, Electronic image stabilization and Scene profiles Audio mic/line in, I/O for alarm/event handling and memory card slot for optional local video storage. OptimizedIR, a power-efficient IR LED technology. 	\$ 1,299.00		7331021061217	5.73	7.48
 bullet camera with 32x optical zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p /2MP resolution at 50/60 fps. Forensic WDR and Lightfinder for demanding light conditions and Axis Zipstream technology for reduced bandwidth and storage needs. Varifocal 4.3–137 mm, F1.4 with remote zoom and autofocus. Includes analytics AXIS Guard Suite, shock detection and active tampering alarm. Corridor format, Barrel distortion correction, Defog, Electronic image stabilization and Scene profiles Audio mic/line in, I/O for alarm/event handling and memory card slot for optional local video storage. OptimizedIR, a power-efficient IR LED technology. Integrated bracket for easy mounting on wall and ceiling. NEMA 4X, IP66/67 and impact resistant in -40°C 	\$ 1,299.00		7331021061217	5.73	7.48
 bullet camera with 32x optical zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p /2MP resolution at 50/60 fps. Forensic WDR and Lightfinder for demanding light conditions and Axis Zipstream technology for reduced bandwidth and storage needs. Varifocal 4.3–137 mm, F1.4 with remote zoom and autofocus. Includes analytics AXIS Guard Suite, shock detection and active tampering alarm. Corridor format, Barrel distortion correction, Defog, Electronic image stabilization and Scene profiles Audio mic/line in, I/O for alarm/event handling and memory card slot for optional local video storage. OptimizedIR, a power-efficient IR LED technology. Integrated bracket for easy mounting on wall and ceiling. NEMA 4X, IP66/67 and impact resistant in -40°C to +60°C(-40 °F to 140 °F). Powered by PoE 	\$ 1,299.00		7331021061217	5.73	7.48
 bullet camera with 32x optical zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p /2MP resolution at 50/60 fps. Forensic WDR and Lightfinder for demanding light conditions and Axis Zipstream technology for reduced bandwidth and storage needs. Varifocal 4.3–137 mm, F1.4 with remote zoom and autofocus. Includes analytics AXIS Guard Suite, shock detection and active tampering alarm. Corridor format, Barrel distortion correction, Defog, Electronic image stabilization and Scene profiles Audio mic/line in, I/O for alarm/event handling and memory card slot for optional local video storage. OptimizedIR, a power-efficient IR LED technology. Integrated bracket for easy mounting on wall and ceiling. NEMA 4X, IP66/67 and impact resistant in -40°C to +60°C(-40 °F to 140 °F). Powered by PoE (IEEE 802-3af), 20-28 V DC or 20-24 V AC. 	\$ 1,299.00		7331021061217	5.73	7.48
 bullet camera with 32x optical zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p /2MP resolution at 50/60 fps. Forensic WDR and Lightfinder for demanding light conditions and Axis Zipstream technology for reduced bandwidth and storage needs. Varifocal 4.3–137 mm, F1.4 with remote zoom and autofocus. Includes analytics AXIS Guard Suite, shock detection and active tampering alarm. Corridor format, Barrel distortion correction, Defog, Electronic image stabilization and Scene profiles Audio mic/line in, I/O for alarm/event handling and memory card slot for optional local video storage. OptimizedIR, a power-efficient IR LED technology. Integrated bracket for easy mounting on wall and ceiling. NEMA 4X, IP66/67 and impact resistant in -40°C to +60°C(-40 °F to 140 °F). Powered by PoE (IEEE 802-3af), 20-28 V DC or 20-24 V AC. Includes a removable sunshield. 	\$ 1,299.00		7331021061217	5.73	7.48
 bullet camera with 32x optical zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p /2MP resolution at 50/60 fps. Forensic WDR and Lightfinder for demanding light conditions and Axis Zipstream technology for reduced bandwidth and storage needs. Varifocal 4.3–137 mm, F1.4 with remote zoom and autofocus. Includes analytics AXIS Guard Suite, shock detection and active tampering alarm. Corridor format, Barrel distortion correction, Defog, Electronic image stabilization and Scene profiles Audio mic/line in, I/O for alarm/event handling and memory card slot for optional local video storage. OptimizedIR, a power-efficient IR LED technology. Integrated bracket for easy mounting on wall and ceiling. NEMA 4X, IP66/67 and impact resistant in -40°C to +60°C(-40 °F to 140 °F). Powered by PoE (IEEE 802-3af), 20-28 V DC or 20-24 V AC. 	\$ 1,299.00		7331021061217	5.73	7.48
 bullet camera with 32x optical zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p /2MP resolution at 50/60 fps. Forensic WDR and Lightfinder for demanding light conditions and Axis Zipstream technology for reduced bandwidth and storage needs. Varifocal 4.3–137 mm, F1.4 with remote zoom and autofocus. Includes analytics AXIS Guard Suite, shock detection and active tampering alarm. Corridor format, Barrel distortion correction, Defog, Electronic image stabilization and Scene profiles Audio mic/line in, I/O for alarm/event handling and memory card slot for optional local video storage. OptimizedIR, a power-efficient IR LED technology. Integrated bracket for easy mounting on wall and ceiling. NEMA 4X, IP66/67 and impact resistant in -40°C to +60°C(-40 °F to 140 °F). Powered by PoE (IEEE 802-3af), 20-28 V DC or 20-24 V AC. Includes a removable sunshield. 	\$ 1,299.00		7331021061217	5.73	7.48

Robust outdoor, 4 MP/Quad HD1440p, day/night	\$ 1,499.00	7331021061224	6.66	7.48
fixed bullet camera with 32x optical zoom.				
Multiple, individually configurable H.264 and				
Motion JPEG streams; max HDTV 1440p /4MP				
resolution at 50/60 fps. Forensic WDR and				
Lightfinder for demanding light conditions and				
Axis Zipstream technology for reduced				
bandwidth and storage needs.				
Varifocal 4.3–137 mm, F1.4 with remote zoom				
and autofocus.				
Includes analytics AXIS Guard Suite, shock				
detection and active tampering alarm. Corridor				
format, Barrel distortion correction, Defog,				
Electronic image stabilization and Scene				
profiles				
Audio mic/line in, I/O for alarm/event handling				
and memory card slot for optional local video				
storage.				
OptimizedIR, a power-efficient IR LED				
technology.				
Integrated bracket for easy mounting on wall				
and ceiling.				
NEMA 4X, IP66/67 and impact resistant in -40°C				
to +60°C(-40 °F to 140 °F). Powered by PoE				
(IEEE 802-3af), 20-28 V DC or 20-24 V AC.				
Includes a removable sunshield.				
Power supply or midspan not included.				
<u> </u>				

and ceiling. Operation in -40°C to +60°C (-40 °F to 140 °F). Powered by PoE class 4 (IEEE 802-3at), 20-28 V DC or 20-24 V AC. Includes a removable sunshield, Torx T20 allen key, IP66/67- rated	Robust outdoor, NEMA 4X, IP66/67 and IK10- rated 10 MP/ 4K, day/night, fixed bullet camera providing Forensic WDR and Lightfinder 2.0 technology. Features a 4/3" type image sensor, built-in varifocal 12–48 mm, 4 x optical Canon zoom lens, 90°-21° HFOV, F1.7 with remote zoom and autofocus. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max 4K at 30 fps /10MP resolution at 20 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Includes analytics AXIS Guard Suite, Video motion detection, shock detection and active tampering alarm. Corridor format, barrel distortion correction, defogging and electronic image stabilization. Scene profiles. Audio mic/line in, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling. MicroSD/MicroSDHC memory card slot for optional local video storage. OptimizedIR, a power-efficient IR LED technology. Integrated bracket for easy mounting on wall	\$ 1,899.00	7331021066670	6.75	6.89
distortion correction, defogging and electronic image stabilization. Scene profiles. Audio mic/line in, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling. MicroSD/MicroSDHC memory card slot for optional local video storage. OptimizedIR, a power-efficient IR LED technology. Integrated bracket for easy mounting on wall and ceiling. Operation in -40°C to +60°C (-40 °F to 140 °F). Powered by PoE class 4 (IEEE 802-3at), 20-28 V DC or 20-24 V AC. Includes a removable	motion detection, shock detection and active				
image stabilization. Scene profiles. Audio mic/line in, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling. MicroSD/MicroSDHC memory card slot for optional local video storage. OptimizedIR, a power-efficient IR LED technology. Integrated bracket for easy mounting on wall and ceiling. Operation in -40°C to +60°C (-40 °F to 140 °F). Powered by PoE class 4 (IEEE 802-3at), 20-28 V DC or 20-24 V AC. Includes a removable	tampering alarm. Corridor format, barrel				
mic/line in, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling. MicroSD/MicroSDHC memory card slot for optional local video storage. OptimizedIR, a power-efficient IR LED technology. Integrated bracket for easy mounting on wall and ceiling. Operation in -40°C to +60°C (-40 °F to 140 °F). Powered by PoE class 4 (IEEE 802-3at), 20-28 V DC or 20-24 V AC. Includes a removable	,				
analog or digital microphone. Supervised I/O for alarm/event handling. MicroSD/MicroSDHC memory card slot for optional local video storage. OptimizedIR, a power-efficient IR LED technology. Integrated bracket for easy mounting on wall and ceiling. Operation in -40°C to +60°C (-40 °F to 140 °F). Powered by POE class 4 (IEEE 802-3at), 20-28 V DC or 20-24 V AC. Includes a removable					
for alarm/event handling. MicroSD/MicroSDHC memory card slot for optional local video storage. OptimizedIR, a power-efficient IR LED technology. Integrated bracket for easy mounting on wall and ceiling. Operation in -40°C to +60°C (-40 °F to 140 °F). Powered by POE class 4 (IEEE 802-3at), 20-28 V DC or 20-24 V AC. Includes a removable	· · ·				
memory card slot for optional local video storage. OptimizedIR, a power-efficient IR LED technology. Integrated bracket for easy mounting on wall and ceiling. Operation in -40°C to +60°C (-40 °F to 140 °F). Powered by PoE class 4 (IEEE 802-3at), 20-28 V DC or 20-24 V AC. Includes a removable					
storage. OptimizedIR, a power-efficient IR LED technology. Integrated bracket for easy mounting on wall and ceiling. Operation in -40°C to +60°C (-40 °F to 140 °F). Powered by PoE class 4 (IEEE 802-3at), 20-28 V DC or 20-24 V AC. Includes a removable	5				
OptimizedIR, a power-efficient IR LED technology. Integrated bracket for easy mounting on wall and ceiling. Operation in -40°C to +60°C (-40 °F to 140 °F). Powered by PoE class 4 (IEEE 802-3at), 20-28 V DC or 20-24 V AC. Includes a removable					
technology. Integrated bracket for easy mounting on wall and ceiling. Operation in -40°C to +60°C (-40 °F to 140 °F). Powered by PoE class 4 (IEEE 802-3at), 20-28 V DC or 20-24 V AC. Includes a removable	5				
Integrated bracket for easy mounting on wall and ceiling. Operation in -40°C to +60°C (-40 °F to 140 °F). Powered by PoE class 4 (IEEE 802-3at), 20-28 V DC or 20-24 V AC. Includes a removable					
and ceiling. Operation in -40°C to +60°C (-40 °F to 140 °F). Powered by PoE class 4 (IEEE 802-3at), 20-28 V DC or 20-24 V AC. Includes a removable					
Operation in -40°C to +60°C (-40 °F to 140 °F). Powered by PoE class 4 (IEEE 802-3at), 20-28 V DC or 20-24 V AC. Includes a removable					
Powered by PoE class 4 (IEEE 802-3at), 20-28 V DC or 20-24 V AC. Includes a removable	5				
DC or 20-24 V AC. Includes a removable	,				
Sunsmold, FOX 120 and Rey, IF 00/07-14/60					
cable glands and optional IDC punch					
connector.					
Power supply or midspan not included.					
	i ower suppry of muspan not meluded.				

Robust, outdoor, NEMA 4X, IP66, IP67 and IK10-	\$	1,449.00	7331021078482	8.58	7.87
rated, 2 MP/1080p resolution, day/night, fixed	Ψ	1,443.00	10010210/0402	0.00	1.07
bullet camera with Deep Learning Processing					
Unit (DLPU). Support for Forensic WDR and					
Lightfinder 2.0 and OptimizedIR, a power-					
efficient 850 nm IR LED technology. Varifocal					
4.3-137 mm, 32x optical zoom lens, 60°–2.3°					
HFOV with remote zoom and autofocus.					
Multiple, individually configurable H.264/H.265					
with Zipstream and Motion JPEG. 2MP up to 90					
fps, 25/30 fps with WDR. AXIS Object Analytics,					
Video motion detection, shock detection and					
active tampering alarm. AXIS Edge Vault with					
FIPS certified TPM for added cyber security.					
Corridor format, barrel distortion correction,					
defogging, electronic imaging stabilization and					
scene profiles. Audio in and supervised I/O					
port, microSD memory card slot for local					
storage. MQTT Support. Integrated bracket for					
easy mounting on wall and ceiling.					
Operation in -40°C to +60°C (-40 °F to 140 °F).					
Powered by PoE class 4 (IEEE 802-3at), 10-28 V					
DC or 20-24 V AC. Includes a removable					
sunshield, IP66/67- rated cable glands and					
optional IDC punch connectors. 30W PoE out					
to power an additional device, requires Axis					
Midspan 60 W, IEEE 802.3bt Type 3 Class 6					
Power supply or midspan not included.					

 1/1.8" image sensor, robust, outdoor, NEMA 4X, IP66, IP67 and IK10-rated, 4 MP resolution, day/night, fixed bullet camera with Deep Learning Processing Unit (DLPU). Support for Forensic WDR and Lightfinder 2.0 and OptimizedIR, a power-efficient 850 nm IR LED technology. Varifocal 4.3-137 mm, 32x optical zoom lens, 60°–2.3° HFOV with remote zoom 	\$ 1,649.00	7331021078499	8.62	7.87
and autofocus. Multiple, individually configurable H.264/H.265 with Zipstream and Motion JPEG. 4MP up to 90 fps, 25/30 fps with WDR. AXIS Object Analytics, Video motion detection, shock detection and active tampering alarm. AXIS Edge Vault with FIPS certified TPM for added cyber security. Corridor format, barrel distortion correction, defogging,				
optical imaging stabilization and scene profiles. Audio in and supervised I/O port, microSD memory card slot for local storage. MQTT Support. Integrated bracket for easy mounting on wall and ceiling. Operation in -40°C to +60°C (-40 °F to 140 °F). Powered by PoE class 4 (IEEE 802-3at), 10-28 V DC or 20-24 V AC. Includes a removable				
sunshield, IP66/67- rated cable glands and optional IDC punch connectors. 30W PoE out to power an additional device, requires Axis Midspan 60 W, IEEE 802.3bt Type 3 Class 6 Power supply or midspan not included.				
AXIS FA1105 is a discreet indoor sensor unit with 111° horizontal field of view, for use with an AXIS FA Main Unit. It can be installed in tight places and flush-mounted in a wall, ceiling or metal panel with only a small hole visible for the lens. AXIS FA1105 provides a 1080p resolution and Forensic WDR (wide dynamic range) that is optimized for low light and motion. The unit comes with a mounting bracket and an 8 m (26 ft.) cable for connection to a main unit.	\$ 149.00	7331021052307	0.60	6.50

AXIS FA1125 is an extremely discreet indoor, pin hole lens, Sensor Unit with a 91° horizontal field of view, for use with an AXIS FA Main Unit. It can be installed in tight places and flush- mounted in a wall, ceiling or metal panel with only a pinhole visible for the lens. AXIS FA1125 provides a 1080p resolution and Forensic WDR (wide dynamic range) that is optimized for low light and motion. The unit comes with a mounting bracket and an 8 m (26 ft.) cable for connection to a main unit.	\$ 159.00	7331021052314	0.44	6.50
AXIS FA3105-L is a compact eyeball sensor unit with built in IR illumination (15 m / 49 ft range of reach) for use with AXIS FA Main Unit. It has 103° horizontal field of view and 1080p HDTV resolution with Forensic WDR (wide dynamic range) that is optimized for low light and motion. The unit comes with a mounting bracket and an 8 m (26 ft.) cable for connection to the main unit.	\$ 159.00	7331021058279	0.77	6.50
AXIS FA4115 is a compact varifocal dome sensor unit with 53° to 99° horizontal field of view for use with an AXIS FA Main Unit. AXIS FA4115 provides a 1080p resolution a Forensic WDR (wide dynamic range) that is optimized for low light and motion. The unit comes with a mounting bracket and an 8-m (26 ft.) cable for connection to a main unit.	\$ 189.00	7331021054318	0.75	6.50
AXIS FA51 is a single-channel modular camera Main Unit. It is equipped with HDMI out for connection to a public view monitor or a surveillance monitor, I/O ports and a SD card slot. It features Axis Forensic WDR (wide dynamic range) for clarity when there are both dark and light areas in the scene and Axis Zipstream for lowered bandwidth and storage requirements, without compromising image quality. It is compatible with all Sensor Units in the FA Series including IR and thermal units. The AXIS Face Detector application for loss prevention comes pre-loaded.	\$ 319.00	7331021074545	0.55	3.35

AXIS FA51 is a single-channel modular camera Main Unit in bulk 10-pack. It is equipped with HDMI out for connection to a public view monitor or a surveillance monitor, I/O ports and a SD card slot. It features Axis Forensic WDR (wide dynamic range) for clarity when there are both dark and light areas in the scene and Axis Zipstream for lowered bandwidth and storage requirements, without compromising image quality. It is compatible with all Sensor Units in the FA Series including IR and thermal units. The AXIS Face Detector application for loss prevention comes pre-loaded.	\$ 3,109.00	7331021074552	4.74	6.89
AXIS FA51-B is a single-channel barebone modular camera Main Unit in bulk 10-pack. The PCBAs are individually packed in ESD bags inside the bulk box. They are UR-certified and designed for integration into machines, devices and enclosures. The product is equipped with HDMI out for connection to a public view monitor or a surveillance monitor, I/O ports and a SD card slot. It features Axis Forensic WDR (wide dynamic range) for clarity when there are both dark and light areas in the scene and Axis Zipstream for lowered bandwidth and storage requirements, without compromising image quality. It is compatible with all Sensor Units in the FA Series including IR and thermal units. The AXIS Face Detector application for loss prevention comes pre-loaded. Important notice: This product must be integrated into a final product or solution and is not intended for stand-alone use. Consequently, this product must be properly integrated into a suitable casing before it is made available to the end user. The entity or person who integrates this product into a final product or solution is also responsible for ensuring that the final product fulfills safety, EMC and other regulatory standards required by law and that the final product is certified accordingly.	\$ 2,779.00	7331021074576	2.09	7.76

		 	-	
AXIS FA54 is a modular camera Main Unit and can stream full frame rate HDTV 1080p videos from four sensor units simultaneously using one IP address. It has an HDMI port for connection to a surveillance or public view monitor, Forensic WDR (wide dynamic range) that is optimized for low light and motion, Axis Zipstream, two microphone inputs and one audio out, I/O port and two micro SD card slots for local storage.	\$ 479.00	7331021058880	2.18	4.92
AXIS P8815-2 3D People Counter is a custom- designed stereo camera designed for people counting. The people counter functionality is included; no need to purchase and install a separately licensed product. Main features include: Accurate and reliable 3D people counting. All-in-one solution with reliable hardware. Optimized for challenging conditions. Flexible counting zones. Easy integration in AXIS Store Reporter or 3rd party reporting system. This version comes with a black casing.	\$ 859.00	7331021067714	1.06	7.40
AXIS P8815-2 3D People Counter is a custom- designed stereo camera designed for people counting. The people counter functionality is included; no need to purchase and install a separately licensed product. Main features include: Accurate and reliable 3D people counting. All-in-one solution with reliable hardware. Optimized for challenging conditions. Flexible counting zones. Easy integration in AXIS Store Reporter or 3rd party reporting system. This version comes with a white casing.	\$ 859.00	7331021067707	1.10	7.40
 AXIS F9114 is a 4-channel main unit part of the 2nd generation F-series. Up to 4x F21, F7225- RE or F4105-LRE video sensors can be connected to it. It also has 2 Audio IN, 1 Audio Out, 4x configuration I/O, 1 RS 232/485, 1x 10- 48V DC. It has an Ethernet port and PoE Class 4. Max 25,5W AXIS TU6009 Connector 6-pin (for the I/O port), AXIS TU6009 Connector 5-pin (for RS port) and AXIS TU6001 Connector 3-in (for DC power) have to be purchased separately. AXIS F9114 main unit is NOT compatible with the 1st generation of F-series sensors (F1005-E, F1015-E, F1025-E, F1025 F4005, F4005-E) 	\$ 649.00	7331021070516	1.87	6.50

AXIS F9114-B is a 4-channel Barebone main	\$6	629.00	7331021070523	0.66	5.67
unit part of the 2nd generation F-series. AXIS					
F9114-B has no casing. It is UL recognised and					
meant to be integrated into a something else					
(ex: machine). The final product has to be UL					
certified.					
Up to 4x F21, F7225-RE or F4105-LRE video					
sensors can be connected to it. It also has 2					
Audio IN, 1 Audio Out, 4x configuration I/O, 1					
RS 232/485, 1x 10-48V DC. It has an Ethernet					
port and PoE Class 4. Max 25,5W.					
AXIS TU6009 Connector 6-pin (for the I/O port),					
AXIS TU6008 Connector 5-pin (for RS port) and					
AXIS TU6001 Connector 3-pin (for ICS port) and AXIS TU6001 Connector 3-in (for DC power)					
· · · /					
have to be purchased separately.					
AXIS F9114-B main unit is NOT compatible with					
the 1st generation of F-series sensors (F1005-E,					
F1015-E, F1025-E, F1025 F4005, F4005-E).					
AXIS F9104-B is a 4-channel Barebone main	\$ 4	499.00	7331021074613	0.44	4.33
unit part of the 2nd generation F-series. AXIS	•				
F9104-B has no casing. It is UL recognised and					
is meant to be integrated into a something else					
(ex: machine). The final product has to be UL					
certified.					
Certified.					
Up to 4x F21, F7225-RE or F4105-LRE video					
sensors can be connected to it. it has a 10-48V					
DC and an Ethernet port. AXIS F9104-B is PoE					
•					
Class 4. Max 25,5W.					
AXIS TU6001 Connector 3-in (for DC power) has					
· · · ·					
to be purchased separately.					
AXIS F9104-B main unit is NOT compatible with					
AXIS F9104-B main unit is NOT compatible with					
the 1st generation of F-series sensors (F1005-E,					
the 1st generation of F-series sensors (F1005-E,					
the 1st generation of F-series sensors (F1005-E,					

 AXIS F9111 is a one channel main unit part of the 2nd generation F-series. One F21, F7225-RE or F4105-LRE video sensor can be connected to it. It also has 2 Audio IN, 1 Audio Out, 4x configuration I/O, 1 RS 232/485, 1x 10-48V DC. It has an Ethernet port and PoE Class 4. Max 25,5W. AXIS TU6009 Connector 6-pin (for the I/O port), AXIS TU6008 Connector 5-pin (for RS port) and AXIS TU6001 Connector 3-in (for DC power) have to be purchased separately. AXIS F9111 main unit is NOT compatible with the 1st generation of F-series sensors (F1005-E, F1015-E, F1025-E, F1025 F4005, F4005-E) 	\$ 549.00	7331021070493	1.85	6.50
 AXIS F2115-R is a 1080p Varifocal sensor part for the 2nd generation F-series. The focus as well as the focal length has to be manually adjusted on the lens. The Horizontal Field of View varies from 107° to 56°. The focal length varies from 3.2mm to 5.7mm. AXIS F2115-R is a rugged indoor sensor. It can deliver up a 1080p resolution at 60fps (all AXIS F91 main units) or 720p at 180fps (AXIS F9111 main unit only). There is no cable included with AXIS F2115-R Varifocal sensor. An AXIS TU600X cable has to be purchased separately. There is no mounting accessory included with AXIS F2115-R Varifocal sensor. Mounting accessories can be purchased separately. AXIS F2115-R Varifocal sensor is NOT compatible with the 1st generation F-series main unit (F34, F41 or F44) 	\$ 309.00	7331021080690	0.22	3.15

 AXIS F2135-RE is a 1080p Fisheye sensor part of the 2nd generation F-series. It has 185° Horizontal Field of View and 1.98mm focal length. AXIS F2135-RE is a rugged outdoor sensor. It is both IP66 and IP6K9K certified. It can deliver up a 1080p resolution at 60fps (all AXIS F91 main units) or 720p at 180fps (AXIS F9111 main unit only). There is no cable included with AXIS F2135-RE fisheye sensor. An AXIS TU600X cable has to be purchased separately. There is no mounting accessory included with 	\$ 259	00 733102'	1080737 0.22	
AXIS F2135-RE fisheye sensor. Mounting accessories can be purchased separately. AXIS F2135-RE fisheye sensor is NOT compatible with the 1st generation F-series main unit (F34, F41 or F44)				
 AXIS F2105-RE is a 1080p Standard sensor part for the F-series. It has 108° Horizontal Field of View and 3.1mm focal length. AXIS F2105-RE is a rugged outdoor sensor. It is both IP66 and IP6K9K certified. It can deliver up a 1080p resolution at 60fps (all AXIS F91 main units) or 720p at 180fps (AXIS F9111 main unit only). There is no cable included with AXIS F2105-RE standard sensor. An AXIS TU600X cable has to be purchased separately. There is no mounting accessory included in AXIS F2105-RE standard sensor. Mounting accessories can be purchased separately. AXIS F2105-RE is NOT compatible with the 1st generation F-series main unit (F34, F41 or F44) 	\$ 259	00 733102	1080713 0.22	3.15

of 8x 1080p Standard sensor part for the F-series. It has 180° Horizontal Field of View and 3.1mm focal length. AXIS F2105-RE is a rugged outdoor sensor. It is both IP66 and IP6K9K certified. It can deliver up a 1080p resolution at 60fps (all AXIS F91 main units) or 720p at 180fps (AXIS F9111 main unit only). There is no cable included with AXIS F2105-RE standard bulk 8p. AXIS TU600X cables have to be purchased separately. There is no mounting bracket included with AXIS F2105-RE standard bulk 8p. AXIS TU600X cables have to be purchased separately. AXIS F2105-RE bulk 8 p. Mounting accessories can be purchased separately. AXIS F2105-RE standard sensor is NOT compatible with the 1st generation F-series main unit (F34, F41 or F44) AXIS F2115-R Varifocal Bulk 8P is bulk pack of 8x 1080p Varifocal sensor part for the F-series. The focus as well as the focal length has to be manually adjusted on the lens. The Horizontal Field of View varies from 107° to 56°. The focal length varies from 3.2mm to 5.7mm.	AVIO F0405 DE Otendent Dulle op te e hull	<i>*</i>	4 050 00	 7004004000700	0.00	F 54
8x 1080p Varifocal sensor part for the F-series. The focus as well as the focal length has to be manually adjusted on the lens. The Horizontal Field of View varies from 107° to 56°. The focal length varies from 3.2mm to 5.7mm.	 series. It has 180° Horizontal Field of View and 3.1mm focal length. AXIS F2105-RE is a rugged outdoor sensor. It is both IP66 and IP6K9K certified. It can deliver up a 1080p resolution at 60fps (all AXIS F91 main units) or 720p at 180fps (AXIS F9111 main unit only). There is no cable included with AXIS F2105-RE standard bulk 8p. AXIS TU600X cables have to be purchased separately. There is no mounting bracket included with AXIS F2105-RE bulk 8 p. Mounting accessories can be purchased separately. AXIS F2105-RE standard sensor is NOT compatible with the 1st generation F-series 	\$	1,859.00	7331021080720	0.99	5.51
manually adjusted on the lens. The Horizontal Field of View varies from 107° to 56°. The focal length varies from 3.2mm to 5.7mm.	-	\$	2,199.00	7331021080706	0.99	5.51
length varies from 3.2mm to 5.7mm.	manually adjusted on the lens. The Horizontal					
deliver up a 1080p resolution at 60fps (all AXIS F91 main units) or 720p at 180fps (AXIS F9111 main unit only).	deliver up a 1080p resolution at 60fps (all AXIS F91 main units) or 720p at 180fps (AXIS F9111					
There is no cable included with AXIS F2115-R standard Bulk 8p. AXIS TU600X cables have to be purchased separately.	standard Bulk 8p. AXIS TU600X cables have to					
There is no cable included with AXIS F2115-R standard Bulk 8P. Mounting accessories can be purchased separately.	standard Bulk 8P. Mounting accessories can be					
AXIS F2115-R is NOT compatible with the 1st generation F-series main unit (F34, F41 or F44)						

AXIS F2135-RE Fisheye Bulk 8P is a bulk pack of 8x 1080p Fisheye sensor part for the F- series. It has 185° Horizontal Field of View and 1.98mm focal length. AXIS F2135-RE is a rugged outdoor sensor. It is both IP66 and IP6K9K certified. It can deliver up a 1080p resolution at 60fps (all AXIS F91 main units) or 720p at 180fps (AXIS F9111 main unit only).	\$ 1,859.00	7331021080744	0.99	5.51
There is no cable included with AXIS F2135-RE fisheye bulk 8p. AXIS TU600X cables have to be purchased separately.				
There is no mounting accessory included with AXIS F2135-RE. Mounting accessories can be purchased separately.				
AXIS F2135-R is NOT compatible with the 1st generation F-series main unit (F34, F41 or F44)				
AXIS F7225-RE is a 1080p Angled pinhole sensor part for the F-series. It has 92° Horizontal Field of View and 3.7mm focal length. AXIS F7225-RE is a rugged outdoor angled pinhole sensor. It is IP66 certified. It can deliver up a 1080p resolution at 60fps (all AXIS F91 main units) or 720p at 180fps (AXIS F9111 main unit only). AXIS F7225-RE does not come with a cable. An AXIS TU600X cable has to be purchased separately. AXIS F7225-RE comes with 1x AXIS F8202 Straight Mounting bracket	\$ 259.00	7331021076419	0.15	3.15
 AXIS F7225-RE pinhole bulk 8p is bulk pack of 8x 1080p angled pinhole sensor part for the F- series. AXIS F7225-RE has 92° Horizontal Field of View and 3.7mm focal length. AXIS F7225-RE is a rugged outdoor sensor. It is both IP66 certified. It can deliver up a 1080p resolution at 60fps (all AXIS F91 main units) or 720p at 180fps (AXIS F9111 main unit only). AXIS F7225-RE standard bulk 8P does not come with any cables. AXIS TU600X cables have to be purchased separately. AXIS F7225-RE standard bulk 8P comes with 8x AXIS F8202 Straight Mounting brackets. 	\$ 1,859.00	7331021081338	0.88	6.30

 AXIS F4105-LRE is a 1080p mini-dome sensor with IR light part for the F-series. It has 110° Horizontal Field of View and 2.8mm focal length. AXIS F4105-LRE uses detachable M12 lenses. Several M12 lenses can be purchased separately offering different types of Horizontal Field of View and Focal Length. AXIS F4105-LRE is a rugged outdoor mini- dome sensor. It is both IP66 and IP6K9K certified. It can deliver up a 1080p resolution at 60fps (all AXIS F91 main units) or 720p at 180fps (AXIS F9111 main unit only). AXIS F4105-LRE does not come with a cable. An AXIS TU600X cable has to be purchased separately. AXIS F4105-LRE does not come with any mounting accessory. Mounting accessories can be purchased separately. 	\$ 319.00	7331021076426	0.66	4.53
AXIS F4105-LRE bulk 8p is bulk pack of 8x 1080p mini-dome sensors with IR part for the F- series. AXIS F4105-LRE-RE has 110° Horizontal Field of View and 2.8 mm focal length. AXIS F4105-LRE uses detachable M12 lenses. Several M12 lenses can be purchased separately offering different types of Horizontal Field of View and Focal Length. AXIS F4105-LRE is a rugged outdoor sensor. It is both IP66 and IP6K9K certified. It can deliver up a 1080p resolution at 60fps (all AXIS F91 main units) or 720p at 180fps (AXIS F9111 main unit only). AXIS F4105-LRE standard bulk 8P do not come with any cables. AXIS TU600X cables have to be purchased separately. AXIS F4105-LRE standard bulk 8P do not come with any mounting accessories. Mounting accessories can be purchased separately.	\$ 2,439.00	7331021081345	6.17	11.22
Ultra-discreet, indoor fixed mini dome for recessed mounting in ceiling or wall. Fixed lens. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max HDTV 1080p at 30 fps with WDR. Axis Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	\$ 269.00	7331021061118	1.09	4.53

Ultra-discreet, indoor fixed mini dome for recessed mounting in ceiling or wall. Fixed lens. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max 3 MP at 30 fps with WDR. Axis Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	\$ 369.00	7331021061125	1.09	4.53
Ultra-compact, indoor fixed mini dome with dust- and vandal-resistant casing for easy mounting on wall or ceiling. Fixed lens. Multiple, individually configurable H.264 and Motion JPEG streams; max 4 MP at 30 fps with WDR. HDMI output (micro). Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	\$ 369.00	7331021049086	0.62	5.31
AXIS M3064-V is an ultra-compact, indoor fixed mini dome with dust- and IK08 vandal-resistant casing for easy mounting on wall or ceiling. Fixed lens, horizontal/vertical field of view 83°/45°. D/N functionality with automatically removable IR cut filter. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max HDTV 720p resolution at 30 fps with WDR. Zipstream for reduced bandwidth and storage. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet.	\$ 199.00	7331021066878	0.60	4.80
AXIS M3065-V is an ultra-compact, indoor fixed mini dome with dust- and IK08 vandal-resistant casing for easy mounting on wall or ceiling. Fixed lens, horizontal/vertical field of view 102°/55°. D/N functionality with automatically removable IR-cut filter. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max HDTV 1080p at 30 fps with WDR. HDMI output (micro). Zipstream for reduced bandwidth and storage. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet.	\$ 269.00	7331021066779	0.57	4.80

AXIS M3075-V is an ultra-compact, indoor fixed mini dome with dust- and IK08 vandal-resistant casing for easy mounting on wall or ceiling. Fixed lens, horizontal/vertical field of view 102°/55°. D/N functionality with automatically removable IR-cut filter. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max HDTV 1080p at 30 fps with WDR. HDMI output (micro). Zipstream for reduced bandwidth and storage. Audio detection and capture with built-in microphone. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet.	\$ 299.00	7331021066793	0.58	4.80
AXIS M3066-V is an ultra-compact, indoor fixed mini dome with dust- and IK08 vandal-resistant casing for easy mounting on wall or ceiling. Fixed lens, horizontal/vertical field of view 131°/97°. D/N functionality with automatically removable IR-cut filter. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max 4 MP at 30 fps with WDR. HDMI output (micro). Zipstream for reduced bandwidth and storage. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet.	\$ 369.00	7331021066786	0.61	4.80
Ultra-compact, indoor fixed mini dome with 6 MP sensor, fixed lens and and tamper-resistant casing for easy mounting on wall or ceiling. Provides 360°/180° overview and dewarped panorama, quad, corner, corridor or digital PTZ views in up to 30 fps. Multiple, individually configurable H.264 and Motion JPEG streams. Client dewarping also supported. Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. HDMI output (micro). Memory card slot for optional local video storage. Environment-friendly, PVC-free with recycled plastics. Power over Ethernet. Midspan not included.	\$ 469.00	7331021049123	0.79	4.53

Ultra-compact, indoor fixed mini dome with 12 MP sensor, fixed lens and and tamper-resistant casing for easy mounting on wall or ceiling. Provides 360°/180° overview in up to 30 fps and dewarped panorama, quad, corner, corridor or digital PTZ views in up to 15 fps. Multiple, individually configurable H.264 and Motion JPEG streams. Client dewarping also supported. Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm.	\$ 66	59.00	7331021054479	0.79	4.53
HDMI output (micro). Memory card slot for optional local video storage. Environment- friendly, PVC-free with recycled plastics. Power over Ethernet. Midspan not included.					
Product version for the American market. AXIS M3067-P is an ultra-compact, indoor fixed mini dome with 6 MP sensor, fixed lens and tamper-resistant casing for easy mounting on wall or ceiling. Forensic WDR, Lightfinder and D/N functionality with automatically removable IR cut filter. Provides 360°/180° overview and dewarped panorama, quad, corner, corridor or digital PTZ views in up to 30 fps with WDR, up to 60 fps without. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Memory card slot for optional local video storage. Signed firmware and secure boot ensure firmware authenticity. Environment-friendly, PVC-free with recycled plastics. Power over Ethernet.	\$45	99.00	7331021076020	0.88	4.80
 AXIS M3085-V is an ultra-compact, indoor fixed mini dome with Deep Learning Processing Unit (DLPU). Dust - and IK08 vandal-resistant casing, fixed lens, horizontal/vertical field of view 102°/55°. D/N functionality with automatically removable IR-cut filter. Lightfinder. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max 2MP at 30 fps with WDR. Zipstream for reduced bandwidth and storage. Audio and I/O with optional accessories. MicroSD memory card slot for local storage. Axis Object Analytics, video motion detection and active tampering alarm. Axis Edge Vault for increased cybersecurity. Powered by IEEE 802.3af/802.3at Type 1 Class 2 	\$29	99.00	7331021076631	0.55	4.72

 AXIS M3086-V is an ultra-compact, indoor fixed mini dome with Deep Learning Processing Unit (DLPU). Dust - and IK08 vandal-resistant casing, fixed lens, horizontal/vertical field of view 130°/93°. D/N functionality with automatically removable IR-cut filter. Lightfinder. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max 4MP at 30 fps with WDR. Zipstream for reduced bandwidth and storage. MicroSD memory card slot for local storage. Audio and I/Owith optional accessories. Axis Object Analytics, video motion detection and active tampering alarm. Axis Edge Vault for increased cybersecurity Powered by IEEE 802.3af/802.3at Type 1 Class 2 	\$ 369.00	7331021076648	0.62	4.72
AXIS M3088-V is an ultra-compact, indoor fixed mini dome with Deep Learning Processing Unit (DLPU). Dust - and IK08 vandal-resistant casing, fixed lens, horizontal/vertical field of view 109°/56°. D/N functionality with automatically removable IR-cut filter. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max 8MP at 15 fps with WDR. Zipstream for reduced bandwidth and storage. MicroSD memory card slot for local storage. Audio and I/O with optional accessories. Axis Object Analytics, video motion detection and active tampering alarm. AXIS Edge Vault for increased cybersecurity. Powered by IEEE 802.3af/802.3at Type 1 Class 2	\$ 449.00	7331021076655	0.62	4.72
Compact, day/night fixed mini dome in a vandal- resistant casing for outdoor or indoor installation. Fixed, 106° lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 30 fps or 3 MP resolution at 20 fps. Memory card slot for optional local video storage. Video motion detection, active tampering alarm and I/O for alarm/event handling. Comes with a 2 m (6.6 ft.) network cable and is powered using Power over Ethernet. Midspan not included.	\$ 649.00	7331021007956	2.38	5.91

Compact, day/night fixed mini dome in a vandal- resistant casing for outdoor or indoor installation, offering 360°/270°/180° panoramic views as well as quad and digital PTZ views. Multiple, individually configurable H.264 and Motion JPEG streams in up to 5MP resolution at 12 fps. Two-way, echo-free audio communication with built-in microphone and speaker. SIP support for IP phone system integration. Memory card slot for optional local video storage. Video motion detection, active tampering alarm and I/O for alarm/event handling. Comes with a 2 m (6.6 ft.) cable with a male RJ-45 network connector and is powered using Power over Ethernet. Midspan not included.	\$ 799.00	7331021050303	2.29	6.10
360°/180° fixed dome with 12 MP sensor and support for Forensic WDR, Lightfinder and OptimizedIR illumination. Vandal-resistant casing in flat design, for outdoor or indoor installation. Provides complete 360° overview in up to 20 fps with WDR and 30 fps with WDR disabled. Dewarped panorama, quad, corner, corridor and up to four digital PTZ views. Client- side dewarping also supported. Multiple, individually configurable H.264 and Motion JPEG streams, Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Supervised input / digital output for alarm / event handling. Memory card slot for optional local video storage. Power over Ethernet. Includes mounting bracket for wall or junction boxes. Midspan not included.	\$ 919.00	7331021061422	2.16	6.89
With its 6 MP sensor, AXIS M3077-PLVE offers excellent image quality and a complete 180° or 360° overview, indoors or out, around the clock. It features two built-in microphones allowing for audio surveillance and detection. This compact mini dome offers dewarped views such as panorama, quad, corner, and corridor views directly from the camera. It includes Axis Lightfinder and Axis Forensic WDR for true colors and great details in challenging light or near darkness. And, Axis OptimizedIR for surveillance in pitch darkness. Furthermore, enhanced security functionality prevents unauthorized access and safeguards your system.	\$ 749.00	7331021070813	2.16	6.30

Day/night, compact mini dome with flat-faced design for indoor use. Built-in IR illumination and WDR – Forensic Capture. Fixed lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	\$ 249.00	7331021050761	1.08	4.72
Day/night, compact mini dome in a vandal- resistant, outdoor-ready, flat-faced design. Built- in IR illumination and WDR – Forensic Capture. Fixed lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	\$ 299.00	7331021050778	0.99	4.72
Day/night, compact mini dome with flat-faced design for indoor use. Built-in IR illumination and WDR – Forensic Capture. Fixed lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	\$ 319.00	7331021050785	1.08	4.72
Day/night, compact mini dome in a vandal- resistant, outdoor-ready, flat-faced design. Built- in IR illumination and fixed lens. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max 4 MP resolution at 30 fps with WDR. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	\$ 469.00	7331021058330	0.84	4.57

AXIS M3115-LVE is a compact mini dome in a flat-faced, outdoor-ready, IK08 impact-resistant design with built-in IR illumination. Fixed lens, 105° field of view. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; HDTV 1080p at up to 30 fps with Forensic WDR and Lightfinder. Zipstream for reduced bandwidth and storage. Video motion detection and tampering alarm. Signed firmware and secure boot ensure firmware authenticity. Memory card slot for optional local video storage. Power over Ethernet.	\$ 349.00	7331021065765	1.12	4.88
AXIS M3116-LVE is a compact mini dome in a flat-faced, outdoor-ready, IK08 impact-resistant design with built-in IR illumination. Fixed lens, 130° field of view. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 4 MP at up to 30 fps with Forensic WDR and Lightfinder. Zipstream for reduced bandwidth and storage. Video motion detection and tampering alarm. Signed firmware and secure boot ensure firmware authenticity. Memory card slot for optional local video storage. Power over Ethernet.	\$ 449.00	7331021065772	1.12	4.88
Fixed dome with built-in IR illumination and IK10 vandal-resistant casing, designed for easy outdoor or indoor installation. Fixed lens, 100° field of view. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; HDTV 1080p at up to 30 fps with WDR. Zipstream for reduced bandwidth and storage. Video motion detection, tampering alarm and supervised digital input / digital output for alarm/event handling. HDMI output (micro). Memory card slot for optional local video storage. Power over Ethernet. Includes mounting bracket for wall/ceiling or junction boxes.	\$ 499.00	7331021064485	2.39	10.43

Fixed dome with built-in IR illumination and IK10 vandal-resistant casing, designed for easy outdoor or indoor installation. Fixed lens, wide 105°/79° horizontal/vertical field of view. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 4 MP at up to 30 fps with WDR. Zipstream for reduced bandwidth and storage. Video motion detection, tampering alarm and supervised digital input / digital output for alarm/event handling. HDMI output (micro). Memory card slot for optional local video storage. Power over Ethernet. Includes mounting bracket for wall/ceiling or junction boxes.	\$ 599.00		7331021064492	2.40	10.43
Fixed dome camera with Deep Learning Processing Unit (DLPU). Forensic WDR, Lightfinder and Optimized IR. Discreet, dust- and IK10 vandal-resistant outdoor casing. Fixed lens, 101°/ 55° horizontal/vertical field of view . Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. Max 2MP at 30 fps with WDR up to 30fps. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. MQTT support. Axis Edge Vault for added cyber security. Built in case open switch. MicroSD memory card slot for local storage. Powered by IEEE 802.3af/802.3at Type 1 Class 3. Includes mounting bracket and weather shield.	\$ 589.00	-	7331021076549	2.34	8.27

Fixed dome camera with Deep Learning Processing Unit (DLPU). Forensic WDR, Lightfinder and Optimized IR. Discreet, dust- and IK10 vandal-resistant outdoor casing. Fixed lens, 102°/ 73° horizontal/vertical field of view . Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. Max 4MP at 30 fps with WDR up to 30fps. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. MQTT support. Axis Edge Vault for added cyber security. Built in case open switch. MicroSD memory card slot for local storage. Powered by IEEE 802.3af/802.3at Type 1 Class 3. Includes mounting bracket and weather shield.	\$	689.00	7331021076556	2.35	8.27
	<u> </u>				
Compact, varifocal, D/N mini dome with dust- and vandal-resistant casing for easy indoor mounting. 3.6-6.6 mm with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 2MP for wide 16:9 view with up to 30 fps. Zipstream for reduced bandwidth and storage. Includes a Deep Learning Processing Unit (DPLU) for advanced analytics. Axis Object Analytics, video motion detection and active tampering alarm. HDMI output. Audio and I/O with compatible Axis portcast accessories. MicroSD memory card slot for local video storage. AXIS Edge Vault for increased Cyber Security	\$	439.00	7331021081512	1.17	4.92
Compact, varifocal, D/N mini dome with built-in IR illumination and dust- and vandal-resistant casing for easy indoor mounting. 3.6-6.6 mm with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 2MP for wide 16:9 view with up to 30 fps. Zipstream for reduced bandwidth and storage. Includes a Deep Learning Processing Unit (DPLU) for advanced analytics. Axis Object Analytics, video motion detection and active tampering alarm. HDMI output. Audio and I/O with compatible Axis portcast accessories. MicroSD memory card slot for local video storage. AXIS Edge Vault for increased Cyber Security	\$	479.00	7331021081529	1.17	4.92

Compact, varifocal, D/N mini dome with dust- and vandal-resistant casing for easy indoor mounting. 3-6 mm lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 4MP in 4:3, 3MP in 16:9, max 30 fps with WDR. Zipstream for reduced bandwidth and storage. Includes a Deep Learning Processing Unit (DPLU) for advanced analytics. Axis Object Analytics, video motion detection and active tampering alarm. HDMI output (micro). MicroSD memory card slot for optional local video storage. AXIS Edge Vault for increased Cyber Security	\$ 479.00	7331021072800	1.04	5.31
Compact, varifocal, D/N mini dome with built-in IR illumination and dust- and vandal-resistant casing for easy indoor mounting. 3-6 mm lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 4MP in 4:3, 3MP in 16:9, max 30 fps with WDR. Zipstream for reduced bandwidth and storage. Includes a Deep Learning Processing Unit (DPLU) for advanced analytics. Axis Object Analytics, video motion detection and active tampering alarm. HDMI output (micro). MicroSD memory card slot for optional local video storage. AXIS Edge Vault for increased Cyber Security	\$ 519.00	7331021072817	1.12	5.31
Compact, varifocal, D/N mini dome with dust- and vandal-resistant casing for easy indoor mounting. 3.6-6.6 mm with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 8MP for wide 16:9 view with up to 15 fps. Zipstream for reduced bandwidth and storage. Includes a Deep Learning Processing Unit (DPLU) for advanced analytics. Axis Object Analytics, video motion detection and active tampering alarm. HDMI output. Audio and I/O with compatible Axis portcast accessories. MicroSD memory card slot for local video storage. AXIS Edge Vault for increased Cyber Security	\$ 519.00	7331021081536	1.17	4.92

Compact, varifocal, D/N mini dome with built-in IR illumination and dust- and vandal-resistant casing for easy indoor mounting. 3.6-6.6 mm with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 8MP for wide 16:9 view with up to 15 fps. Zipstream for reduced bandwidth and storage. Includes a Deep Learning Processing Unit (DPLU) for advanced analytics. Axis Object Analytics, video motion detection and active tampering alarm. HDMI output. Audio and I/O with compatible Axis portcast accessories. MicroSD memory card slot for local video storage. AXIS Edge Vault for increased Cyber Security	\$ 559.00	7331021081543	1.08	4.92
AXIS M4308-PLE is a discreet, outdoor-ready mini dome designed to blend seamlessly into any environment. With 12 MP sensor and stereographic lens it offers outstanding images and complete 360° panoramic overview. Thanks to Sharpdome 360, this panoramic camera delivers greater sharpness at the edges of the image. AXIS Object Analytics is included and a deep learning processing unit (DLPU) enables unique opportunities to take advantage of analytics based on deep learning on the edge. It includes Axis Lightfinder and Axis Forensic WDR for true colors and great details in challenging light or near darkness. Plus, Axis OptimizedIR for surveillance in pitch darkness. Four built-in microphones and Voice Enhancer offers audio capture with great noise suppression.	999.00	7331021072534	2.34	6.30

	^				0.50
AXIS M4317-PLVE is a discreet, IK10 and IP66 outdoor-ready mini dome designed with 6 MP sensor and stereographic lens, that can deliver multiple 360° or 180° panoramic views at up to 30 fps with no blind spots. Thanks to Sharpdome 360, this panoramic camera delivers greater sharpness at the edges of the image. Built on ARTPEC-8, it offers powerful artificial intelligence and deep learning analytics on the edge. including AXIS Object Analytics, it can accurately detect and classify moving objects for more effective monitoring. The camera can stream multiple, individually configurable H.264, H.265 and Motion JPEG streams, with support for digital PTZ. AXIS M4317-PLVE comes with build-in configurable IR, making it perfect for low light situations. Signed firmware and secure boot ensure firmware authenticity. Power over Ethernet.	\$	729.00	7331021078741	2.29	6.50
AXIS M4318-PLVE is a discreet, IK10 and IP66 outdoor-ready mini dome designed with 12 MP sensor and stereographic lens, that can deliver 360° or 180° panoramic views at up to 30 fps with no blind spots. Thanks to Sharpdome 360, this panoramic camera delivers greater sharpness at the edges of the image. Built on ARTPEC-8, it offers powerful artificial intelligence and deep learning analytics on the edge. including AXIS Object Analytics, it can accurately detect and classify moving objects for more effective monitoring. The camera can stream multiple, individually configurable H.264, H.265 and Motion JPEG streams, with support for digital PTZ. AXIS M4318-PLVE comes with build-in configurable IR, making it perfect for low light situations. Signed firmware and secure boot ensure firmware authenticity. Power over Ethernet.	\$	899.00	7331021078758	2.31	6.50

AXIS M4327-P is an ultra-compact, indoor fixed mini dome with 6 MP sensor and stereographic lens, that can deliver multiple 360° or 180° panoramic views at up to 30 fps with no blind spots. Built on ARTPEC-8, it offers powerful artificial intelligence and deep learning analytics on the edge. including AXIS Object Analytics, it can accurately detect and classify moving objects for more effective monitoring. The camera can stream multiple, individually configurable H.264, H.265 and Motion JPEG streams, with support for digital PTZ. AXIS M4327-P is delivered factory-focused and features digital roll functionality for easy installation. Signed firmware and secure boot ensure firmware authenticity. Environment- friendly, PVC-free with recycled plastics. Power over Ethernet.	\$ 529.00	7331021081451	0.95	4.33
AXIS M4328-P is an ultra-compact, indoor fixed mini dome with 12 MP sensor and stereographic lens, that can deliver 360° or 180° panoramic views at up to 30 fps with no blind spots. Built on ARTPEC-8, it offers powerful artificial intelligence and deep learning analytics on the edge. including AXIS Object Analytics, it can accurately detect and classify moving objects for more effective monitoring. The camera can stream multiple, individually configurable H.264, H.265 and Motion JPEG streams, with support for digital PTZ. AXIS M4328-P is delivered factory-focused and features digital roll functionality for easy installation. Signed firmware and secure boot ensure firmware authenticity. Environment- friendly, PVC-free with recycled plastics. Power over Ethernet.	\$ 699.00	7331021081468	0.88	4.33

Day/night fixed dome with support for WDR – Forensic Capture, Lightfinder and OptimizedIR with built-in IR illumination. IK10 vandal- resistant outdoor casing. Varifocal 3-10 mm P- Iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR, and up to 60 fps with WDR disabled. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes mounting bracket for wall/ceiling or junction boxes.	\$ 749.00	7331021062009	2.80	8.46
Fixed dome with support for Forensic WDR, Lightfinder 2.0 and OptimizedIR illumination. Discreet, dust- and IK10 vandal-resistant indoor casing. Varifocal 3.4-8.9 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR. Zipstream for reduced bandwidth and storage. Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Signed firmware and secure boot ensure firmware authenticity. Memory card slot for optional local video storage. Power over Ethernet. Includes mounting bracket for wall/ceiling or junction boxes.	\$ 579.00	7331021065659	2.02	6.89

Fixed dome with support for Forensic WDR, Lightfinder 2.0 and OptimizedIR illumination. Discreet, dust- and IK10 vandal-resistant outdoor-ready casing. Varifocal 9-22 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR. Zipstream for reduced bandwidth and storage. Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Signed firmware and secure boot ensure firmware authenticity. Memory card slot for optional local video storage. Power over Ethernet. Includes mounting bracket for wall/ceiling or junction boxes.	\$ 749.00	7331021071483	2.71	7.87
AXIS P3247-LV is a day/night fixed dome with discreet, dust- and IK10 vandal-resistant indoor casing. It has support for Forensic WDR, Lightfinder 2.0, motion-adaptive exposure for minimized motion blur, and OptimizedIR illumination. Varifocal 3-8mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. 5 MP at up to 30 fps with WDR. Zipstream for reduced bandwidth and storage. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Signed firmware, secure boot and AXIS Edge Vault ensure firmware authenticity and device identity. Memory card slot for optional local video storage. Power over Ethernet. Includes mounting bracket for wall/ceiling or junction boxes.	\$ 779.00	7331021065680	2.14	6.89

AXIS P3247-LVE is a day/night fixed dome with	•		 7331021065697		44.55
IK10 vandal-resistant outdoor casing. It has support for Forensic WDR, Lightfinder 2.0,	\$	899.00		2.76	10.63
motion-adaptive exposure for minimized					
motion blur, and OptimizedIR illumination.					
Varifocal 3-8 mm P-Iris lens with remote zoom					
and focus simplifying the installation. Multiple,					
individually configurable H.264, H.265 and					
Motion JPEG streams. 5 MP at up to 30 fps with					
WDR. Zipstream for reduced bandwidth and					
storage. AXIS Object Analytics, Video motion					
detection and tampering alarm. Two-way audio					
and audio detection. Supervised digital input /					
digital output for alarm / event handling. Signed					
firmware, secure boot and AXIS Edge Vault					
ensure firmware authenticity and device					
identity. Memory card slot for optional local					
video storage. Power over Ethernet. Includes					
mounting bracket for wall or junction boxes					
and weather shield against sun, rain or snow.					
AXIS P3248-LV is a day/night fixed dome with	\$	979.00	7331021065703	2.14	6.89
	•				
discreet, dust- and IK10 vandal-resistant indoor	·				
casing. It has support for Forensic WDR,	•				
casing. It has support for Forensic WDR, Lightfinder 2.0, motion-adaptive exposure for	·				
casing. It has support for Forensic WDR, Lightfinder 2.0, motion-adaptive exposure for minimized motion blur, and OptimizedIR	·				
casing. It has support for Forensic WDR, Lightfinder 2.0, motion-adaptive exposure for minimized motion blur, and OptimizedIR illumination. Varifocal 4.3-8.6 mm P-Iris lens					
casing. It has support for Forensic WDR, Lightfinder 2.0, motion-adaptive exposure for minimized motion blur, and OptimizedIR illumination. Varifocal 4.3-8.6 mm P-Iris lens with remote zoom and focus simplifying the					
casing. It has support for Forensic WDR, Lightfinder 2.0, motion-adaptive exposure for minimized motion blur, and OptimizedIR illumination. Varifocal 4.3-8.6 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable					
casing. It has support for Forensic WDR, Lightfinder 2.0, motion-adaptive exposure for minimized motion blur, and OptimizedIR illumination. Varifocal 4.3-8.6 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. 4K					
casing. It has support for Forensic WDR, Lightfinder 2.0, motion-adaptive exposure for minimized motion blur, and OptimizedIR illumination. Varifocal 4.3-8.6 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. 4K (8MP) at up to 30 fps with WDR. Zipstream for					
casing. It has support for Forensic WDR, Lightfinder 2.0, motion-adaptive exposure for minimized motion blur, and OptimizedIR illumination. Varifocal 4.3-8.6 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. 4K (8MP) at up to 30 fps with WDR. Zipstream for reduced bandwidth and storage. AXIS Object					
casing. It has support for Forensic WDR, Lightfinder 2.0, motion-adaptive exposure for minimized motion blur, and OptimizedIR illumination. Varifocal 4.3-8.6 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. 4K (8MP) at up to 30 fps with WDR. Zipstream for reduced bandwidth and storage. AXIS Object Analytics, Video motion detection and					
casing. It has support for Forensic WDR, Lightfinder 2.0, motion-adaptive exposure for minimized motion blur, and OptimizedIR illumination. Varifocal 4.3-8.6 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. 4K (8MP) at up to 30 fps with WDR. Zipstream for reduced bandwidth and storage. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio					
casing. It has support for Forensic WDR, Lightfinder 2.0, motion-adaptive exposure for minimized motion blur, and OptimizedIR illumination. Varifocal 4.3-8.6 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. 4K (8MP) at up to 30 fps with WDR. Zipstream for reduced bandwidth and storage. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital					
casing. It has support for Forensic WDR, Lightfinder 2.0, motion-adaptive exposure for minimized motion blur, and OptimizedIR illumination. Varifocal 4.3-8.6 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. 4K (8MP) at up to 30 fps with WDR. Zipstream for reduced bandwidth and storage. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Signed					
 casing. It has support for Forensic WDR, Lightfinder 2.0, motion-adaptive exposure for minimized motion blur, and OptimizedIR illumination. Varifocal 4.3-8.6 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. 4K (8MP) at up to 30 fps with WDR. Zipstream for reduced bandwidth and storage. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Signed firmware, secure boot and AXIS Edge Vault 					
casing. It has support for Forensic WDR, Lightfinder 2.0, motion-adaptive exposure for minimized motion blur, and OptimizedIR illumination. Varifocal 4.3-8.6 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. 4K (8MP) at up to 30 fps with WDR. Zipstream for reduced bandwidth and storage. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Signed firmware, secure boot and AXIS Edge Vault ensure firmware authenticity and device					
casing. It has support for Forensic WDR, Lightfinder 2.0, motion-adaptive exposure for minimized motion blur, and OptimizedIR illumination. Varifocal 4.3-8.6 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. 4K (8MP) at up to 30 fps with WDR. Zipstream for reduced bandwidth and storage. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Signed firmware, secure boot and AXIS Edge Vault ensure firmware authenticity and device identity. Memory card slot for optional local					
 casing. It has support for Forensic WDR, Lightfinder 2.0, motion-adaptive exposure for minimized motion blur, and OptimizedIR illumination. Varifocal 4.3-8.6 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. 4K (8MP) at up to 30 fps with WDR. Zipstream for reduced bandwidth and storage. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Signed firmware, secure boot and AXIS Edge Vault ensure firmware authenticity and device identity. Memory card slot for optional local video storage. Power over Ethernet. Includes 					
 casing. It has support for Forensic WDR, Lightfinder 2.0, motion-adaptive exposure for minimized motion blur, and OptimizedIR illumination. Varifocal 4.3-8.6 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. 4K (8MP) at up to 30 fps with WDR. Zipstream for reduced bandwidth and storage. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Signed firmware, secure boot and AXIS Edge Vault ensure firmware authenticity and device identity. Memory card slot for optional local 					
 casing. It has support for Forensic WDR, Lightfinder 2.0, motion-adaptive exposure for minimized motion blur, and OptimizedIR illumination. Varifocal 4.3-8.6 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. 4K (8MP) at up to 30 fps with WDR. Zipstream for reduced bandwidth and storage. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Signed firmware, secure boot and AXIS Edge Vault ensure firmware authenticity and device identity. Memory card slot for optional local video storage. Power over Ethernet. Includes 					
 casing. It has support for Forensic WDR, Lightfinder 2.0, motion-adaptive exposure for minimized motion blur, and OptimizedIR illumination. Varifocal 4.3-8.6 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. 4K (8MP) at up to 30 fps with WDR. Zipstream for reduced bandwidth and storage. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Signed firmware, secure boot and AXIS Edge Vault ensure firmware authenticity and device identity. Memory card slot for optional local video storage. Power over Ethernet. Includes 					
casing. It has support for Forensic WDR, Lightfinder 2.0, motion-adaptive exposure for minimized motion blur, and OptimizedIR illumination. Varifocal 4.3-8.6 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. 4K (8MP) at up to 30 fps with WDR. Zipstream for reduced bandwidth and storage. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Signed firmware, secure boot and AXIS Edge Vault ensure firmware authenticity and device identity. Memory card slot for optional local video storage. Power over Ethernet. Includes					

Fixed dome with Deep Learing Processing Unit. Support for Forensic WDR, Lightfinder 2.0 and OptimizedIR illumination. Discreet, dust- and IK10 vandal-resistant outdoor-ready casing. Varifocal 3.4-8.9 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. HDTV 1080p up to 60 fps, 30fps with WDR. Zipstream for reduced bandwidth and storage. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Signed firmware, secure boot and AXIS Edge Vault ensure firmware authenticity and device identity. Memory card slot for optional local video storage. Powered by IEEE 802.3at Type 2 Class 4 (PoE+). Includes mounting bracket for wall/ceiling or junction boxes.	\$ 849.00	7331021072527	2.69	7.87
 High-performance fixed dome camera with Deep Learning Processing Unit (DLPU). Forensic WDR, Lightfinder 2.0. Discreet, dust- and IK10 vandal-resistant indoor casing. Varifocal 3.4-8.9 mm P-Iris lens with remote zoom and focus. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. HDTV 1080p stream up to 60 fps, 30fps with WDR. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. MQTT support. Axis Edge Vault for added cyber security. MicroSD memory card slot for local storage. Powered by IEEE 802.3af/802.3at Type 1 Class 2. Includes mounting bracket. 	\$ 559.00	7331021075924	2.07	6.30

 High-performance fixed dome camera with Deep Learning Processing Unit (DLPU). Forensic WDR, Lightfinder 2.0 and Optimized IR. Discreet, dust- and IK10 vandal-resistant indoor casing. Varifocal 3.4-8.9 mm P-Iris lens with remote zoom and focus. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. HDTV 1080p stream up to 60 fps, 30fps with WDR. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. MQTT support. Axis Edge Vault for added cyber security. MicroSD memory card slot for local storage. Powered by IEEE 802.3af/802.3at Type 1 Class 3. Includes mounting bracket. 	\$ 639.00	7331021075931	1.98	6.30
 High-performance fixed dome camera with Deep Learning Processing Unit (DLPU). Forensic WDR, Lightfinder 2.0 and Optimized IR. Discreet, dust- and IK10 vandal-resistant outdoor casing. Varifocal 3.4-8.9 mm P-Iris lens with remote zoom and focus. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. HDTV 1080p stream up to 60 fps, 30fps with WDR. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. MQTT support. Axis Edge Vault for added cyber security. MicroSD memory card slot for local storage. Powered by IEEE 802.3af/802.3at Type 1 Class 3. Extended temperature range. Includes mounting bracket and weather shield. 	\$ 749.00	7331021075948	2.65	7.87

Fixed dome with support for Forensic WDR and Lightfinder 2.0. Discreet, dust- and IK10 vandal-resistant indoor casing. Varifocal 3.4-8.9 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR. Zipstream for reduced bandwidth and storage. Video motion detection and tampering alarm. Signed firmware and secure boot ensure firmware authenticity. Memory card slot for optional local video storage. Power over Ethernet. Includes mounting bracket for wall/ceiling or junction boxes.	\$ 499.00	7331021065642	1.98	6.89
 High-performance fixed dome camera with Deep Learning Processing Unit (DLPU). Forensic WDR, Lightfinder 2.0 and Optimized IR. Discreet, dust- and IK10 vandal-resistant outdoor casing. Varifocal 9-22 mm P-Iris lens with remote zoom and focus. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. HDTV 1080p stream up to 60 fps, 30fps with WDR. AXIS Object Analytics, Video motion detection and tampering alarm. Two- way audio and audio detection. Supervised digital input / digital output for alarm / event handling. MQTT support. Axis Edge Vault for added cyber security. Built in case open switch. MicroSD memory card slot for local storage. Powered by IEEE 802.3af/802.3at Type 1 Class 3. Extended temperature range. Includes mounting bracket and weather shield. 	\$ 799.00	7331021075993	2.56	7.87

 High-performance fixed dome camera with Deep Learning Processing Unit (DLPU). Forensic WDR, Lightfinder 2.0 and Optimized IR. Discreet, dust- and IK10 vandal-resistant indoor casing. Varifocal 3-8 mm P-Iris lens with remote zoom and focus. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. 5MP stream in 4:3 up to 30fps. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. MQTT support. Axis Edge Vault for added cyber security. Built in case open switch. MicroSD memory card slot for local storage. Powered by IEEE 802.3af/802.3at Type 1 Class 3. Includes mounting bracket. 	\$ 799.00	7331021075955	2.20	5.71
High-performance fixed dome camera with Deep Learning Processing Unit (DLPU). Forensic WDR, Lightfinder 2.0 and Optimized IR. Discreet, dust- and IK10 vandal-resistant outdoor casing. Varifocal 3-8 mm P-Iris lens with remote zoom and focus. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. 5MP stream in 4:3 up to 30fps AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. MQTT support. Axis Edge Vault for added cyber security. Built in case open switch. MicroSD memory card slot for local storage. Powered by IEEE 802.3af/802.3at Type 1 Class 3. Extended temperature range. Includes mounting bracket and weather shield.	\$ 949.00	7331021075962	2.56	7.87

Fixed dome with support for Forensic WDR and Lightfinder 2.0. Discreet, dust- and IK10 vandal-resistant outdoor-ready casing. Varifocal 3.4-8.9 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR. Zipstream for reduced bandwidth and storage. Video motion detection and tampering alarm. Signed firmware and secure boot ensure firmware authenticity. Memory card slot for optional local video storage. Power over Ethernet. Includes mounting bracket for wall/ceiling or junction boxes.	\$ 619.00	7331021065673	2.54	10.43
 High-performance fixed dome camera with Deep Learning Processing Unit (DLPU). Forensic WDR, Lightfinder 2.0 and Optimized IR. Discreet, dust- and IK10 vandal-resistant indoor casing. Varifocal 4.3-8.6 mm P-Iris lens with remote zoom and focus. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. 8MP 4K stream in 16:9 up to 30fps. AXIS Object Analytics, Video motion detection and tampering alarm. Two- way audio and audio detection. Supervised digital input / digital output for alarm / event handling. MQTT support. Axis Edge Vault for added cyber security. Built in case open switch. MicroSD memory card slot for local storage. Powered by IEEE 802.3af/802.3at Type 1 Class 3. Includes mounting bracket. 	\$ 949.00	7331021075979	2.25	5.71

Fixed dome with support for Forensic WDR, Lightfinder 2.0 and OptimizedIR illumination. Discreet, dust- and IK10 vandal-resistant outdoor-ready casing. Varifocal 3.4-8.9 mm P- Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG	\$ 699.00	7331021065666	2.54	10.43
streams. HDTV 1080p at 30 fps with WDR. Zipstream for reduced bandwidth and storage. Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Signed firmware and secure boot ensure firmware authenticity. Memory card slot for optional local video storage. Power over Ethernet. Includes mounting bracket for wall/ceiling or junction boxes.				
High-performance fixed dome camera with Deep Learning Processing Unit (DLPU). Forensic WDR, Lightfinder 2.0 and Optimized IR. Discreet, dust- and IK10 vandal-resistant outdoor casing. Varifocal 3-8 mm P-Iris lens with remote zoom and focus. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. 8MP 4K stream in 16:9 up to 30fps. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. MQTT support. Axis Edge Vault for added cyber security. Built in case open switch. MicroSD memory card slot for local storage. Powered by IEEE 802.3af/802.3at Type 1 Class 3. Extended temperature range. Includes mounting bracket and weather shield.	\$ 1,049.00	7331021075986	2.56	7.87

Day/night fixed dome with support for WDR- Forensic Capture and Lightfinder. Discreet, IK10 vandal-resistant indoor casing. Varifocal 3 – 10 mm P-Iris lens with remote zoom and focus. Multiple, individually configurable H.264 and Motion JPEG streams. HDTV 720p at 30 fps with WDR, and up to 60 fps with WDR disabled. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Two-way audio and audio detection. Supervised input / digital output for alarm / event handling. Memory card slot for optional local video storage. Power over Ethernet, midspan not included.	\$ 599.00	7331021059245	2.05	6.89
Day/night fixed dome with support for WDR- Forensic Capture, Lightfinder and OptimizedIR with built-in IR illumination. Discreet, IK10 vandal-resistant indoor casing. Varifocal 3 – 10 mm P-Iris lens with remote zoom and focus. Multiple, individually configurable H.264 and Motion JPEG streams. HDTV 720p at 30 fps with WDR, and up to 60 fps with WDR disabled. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Two-way audio and audio detection. Supervised input / digital output for alarm / event handling. Memory card slot for optional local video storage. Power over Ethernet, midspan not included.	\$ 699.00	7331021059269	2.03	6.89
AXIS P3715-PLVE offers two channels with 2MP per channel, at a frame rate of 30 fps. With its unique peanut-shaped dome design, this multidirectional camera offers cost-effective installation and flexible positioning of both varifocal camera heads. Each head can be controlled individually, so you can capture scenes in two directions in wide angle or zoomed-in views. It features Axis Lightfinder and Axis Forensic WDR for true colors and great details in challenging or poor light. And, remote zoom and focus capabilities ensures fast and accurate installation. Furthermore, Zipstream with support for H.264 significantly lowers bandwidth and storage requirements.	\$ 969.00	7331021070097	2.79	9.06

AVIC D4705 DI VE offers two sharpeds with OMD	۴	000.00	 7004004070050	0.00	7.40
AXIS P4705-PLVE offers two channels with 2MP per channel, at a frame rate of up to 60 fps. With its unique design, this multidirectional camera offers cost-effective installation and flexible positioning of both varifocal camera heads. Each head can be controlled individually, so you can capture scenes in two directions in wide angle or zoomed-in views, with up to 2.5x zoom. It features Axis Lightfinder and Axis Forensic WDR for true colors and great details in challenging or poor light. The camera comes with a Deep Learning Processing Unit and can run analytics on both channels simultaneously. Furthermore, Zipstream with support for H.264 and H.265 significantly lowers bandwidth and storage requirements.	\$	969.00	7331021076952	2.82	7.48
AXIS P4707-PLVE offers two channels with 5MP per channel, at a frame rate of 30 fps. With its unique design, this multidirectional camera offers cost-effective installation and flexible positioning of both varifocal camera heads. Each head can be controlled individually, so you can capture scenes in two directions in wide angle or zoomed-in views, with up to 2.5x zoom. It features Axis Lightfinder and Axis Forensic WDR for true colors and great details in challenging or poor light. The camera comes with a Deep Learning Processing Unit and can run analytics on both channels simultaneously. Furthermore, Zipstream with support for H.264 and H.265 significantly lowers bandwidth and storage requirements.	\$	1,099.00	7331021076969	2.82	7.09
AXIS P3719-PLE Network Camera is a compact 15-megapixel camera with four varifocal lenses (4 x Quad HD) enabling overview and detailed surveillance. With one IP address and one network cable, the four- cameras-in-one unit provides a flexible, cost-effective solution for multidirectional surveillance. 360° IR illumination, WDR and Lightfinder technology provides excellent video quality in any light conditions. Each camera head can be individually positioned (pan, tilt, roll, and twist) along a circular track. Remote zoom and focus makes it easy to install and the clear cover, with no sharp edges, ensures undistorted views in all directions. The camera has an integrated weathershield.	\$	1,699.00	7331021064126	5.78	13.58

AXIS P3727-PLE Panoramic Camera offers 4x2 MP with 360° IR coverage. It lets you easily cover four different areas with a single camera, around the clock and even in challenging lighting. You'll be able to count on both high- quality overviews and detailed coverage thanks to the brilliant design of this cost-effective solution. And, AXIS Object Analytics on one channel, allowing you to detect and classify humans and vehicles, all tailored to your specific needs.	\$ 1,449.00	7331021074972	5.82	12.60
AXIS P3735-PLE Panoramic Camera offers 4x2 MP sensors and is perfect for 360° and 270° coverage. You'll be able to count on both high- quality overviews and detailed coverage thanks to the brilliant design of this cost-effective solution. With 360° IR illumination, the product provides excellent image quality around the clock, even in challenging lighting. With ARTPEC-8 and its deep learning processing unit, the product supports analytics and metadata on all sensors.	\$ 1,499.00	7331021080621	5.89	12.60
AXIS P3737-PLE Panoramic Camera offers 4x5 MP sensors and is perfect for 360° and 270° surveillance. You'll be able to count on both high-quality overviews and detailed coverage thanks to the brilliant design of this cost- effective solution. With 360° IR illumination, the product provides excellent image quality around the clock, even in challenging lighting. With ARTPEC-8 and its deep learning processing unit, the product supports analytics and metadata on all sensors.	\$ 1,699.00	7331021080638	5.89	12.60
AXIS P3738-PLE Panoramic Camera offers 4x4K (4x8 MP) sensors and is perfect for 360° and 270° surveillance. You'll be able to count on both high-quality overviews and detailed coverage thanks to the brilliant design of this cost-effective solution. With 360° IR illumination, the product provides excellent image quality around the clock, even in challenging lighting. With ARTPEC-8 and its deep learning processing unit, the product supports analytics and metadata on all sensors.	\$ 1,899.00	7331021080645	5.82	12.60

Product version for the American market.	\$	1,449.00	7331021076013	6.72	10.63
AXIS P3807-PVE Network Camera is a fixed	Ψ	1,440.00		V.1 Z	10.00
dome camera with multiple sensors, providing					
an easy, reliable and cost-efficient one-camera					
installation – reducing installation time, cabling					
and VMS license costs. Thanks to its excellent					
image sensors, along with Forensic WDR and					
Lightfinder technology, it provides great video					
quality in any light conditions. Its four sensors					
give a seamless 180° panoramic overview, at					
up to 30 fps in 8 MP resolution. The camera is					
easy to install as recessed, flush, pendant,					
back-to-back, and comes with adjustable pre-					
set camera positions.					
•Seamlessly stitched images					
•180° horizontal and 90° vertical coverage					
•8 MP resolution at full frame rate					
 Axis Lightfinder and Forensic WDR 					
•Axis Zipstream for reduced bandwidth and					
storage needs					
AXIS P3818-PVE delivers a 180° panoramic	\$	1,939.00	7331021071742	6.88	9.06
overview of extensive areas with ultra-high	Ψ	1,303.00	1001021071742	0.00	5.00
resolution images and incredible details up to					
30 fps. With 13 MP resolution and seamless					
stitching of all three images, it offers 180°					
horizontal and 90° vertical coverage with no					
blind spots. Including a variety of mounting					
options, it's also possible to mount two					
cameras back-to-back for a complete 360°					
overview using AXIS T94V01C Dual Camera					
Mount. Featuring edge-to-edge technology, it's					
easy to add support for audio. Additionally,					
built-in cybersecurity features prevent					
unauthorized access and safeguard your					
system.					

AXIS P3827-PVE delivers a 180° panoramic overview of extensive areas with high resolution images and incredible details up to 30 fps. With 7 MP resolution and seamless stitching of all four images, it offers 180° horizontal and 90° vertical coverage with no blind spots. Built on ARTPEC-8, it offers powerful artificial intelligence and deep learning analytics on the edge. With AXIS Object Analytics, it can accurately detect and classify moving objects for more effective monitoring. Including horizon straightening, this product will give an excellent viewing experience, enabling to set the horizon in the image. Additionally, built-in cybersecurity features prevent unauthorized access and safeguard your system. Power over Ethernet.	\$ 1,499.00	7331021077423	6.31	9.06
720p fixed dome onboard camera with male RJ- 45 network connector. Equipped with 3.6mm, F2.0 lens in ruggedized IP66/67 casing. Includes lens tool, top cover tool, allen key, and drill template.	\$ 479.00	7331021059696	0.85	4.92
AXIS P3904-R MkII (RJ45) in bulk 10-pack. 720p fixed dome onboard camera with male RJ-45 network connector.	\$ 4,559.00	7331021062733	8.33	14.17
AXIS P3904-R MkII (RJ45) in bulk 50-pack. 720p fixed dome onboard camera with male RJ-45 network connector.	\$ 22,799.00	7331021062740	32.19	16.54
Day/night fixed dome with support for WDR- Forensic Capture and Lightfinder. Discreet, IK10 vandal-resistant indoor casing. Varifocal 3 – 10 mm P-Iris lens with remote zoom and focus. Multiple, individually configurable H.264 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR, and up to 60 fps with WDR disabled. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Two-way audio and audio detection. Supervised input / digital output for alarm / event handling. Memory card slot for optional local video storage. Power over Ethernet, midspan not included.	\$ 699.00	7331021059283	2.03	6.89
720p fixed dome onboard camera with female M12 D-coded connector. Equipped with 3.6mm, F2.0 lens in ruggedized IP66/67 casing. Includes lens tool, top cover tool, allen key, and drill template.	\$ 479.00	7331021059627	0.86	4.92
AXIS P3904-R MkII (M12) in bulk 10-pack. 720p fixed dome onboard camera with female M12 D- coded connector.	\$ 4,609.00	7331021062719	8.51	14.17

Day/night fixed dome with support for WDR- Forensic Capture, Lightfinder and OptimizedIR with built-in IR illumination. Discreet, IK10 vandal-resistant indoor casing. Varifocal 3 – 10 mm P-Iris lens with remote zoom and focus. Multiple, individually configurable H.264 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR, and up to 60 fps with WDR disabled. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Two-way audio and audio detection. Supervised input / digital output for alarm / event handling. Memory card slot for optional local video storage. Power over Ethernet, midspan not included.	\$ 799.00	7331021059306	2.03	6.89
AXIS P3904-R MkII (M12) in bulk 50-pack. 720p fixed dome onboard camera with female M12 D- coded connector.	\$ 22,799.00	7331021062726	33.07	16.54
1080p fixed dome onboard camera with male RJ-45 network connector. Equipped with 3.6mm, F2.0 lens in ruggedized IP66/67 casing. Includes lens tool, top cover tool, allen key, and drill template.	\$ 589.00	7331021059634	0.85	4.92
Day/night fixed dome with support for WDR- Forensic Capture and Lightfinder. IK10 vandal- resistant outdoor casing. Varifocal 3 – 10 mm P- Iris lens with remote zoom and focus. Multiple, individually configurable H.264 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR, and up to 60 fps with WDR disabled. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Two-way audio and audio detection. Supervised input / digital output for alarm / event handling. Memory card slot for optional local video storage. Operation in -40 °C to 55 °C (-40 °F to 131 °F) powered by standard Power over Ethernet. Midspan not included. Includes mounting bracket for wall or junction boxes and weather shield against sun, rain or snow.	\$ 899.00	7331021059290	4.96	10.04
AXIS P3905-R MkII (RJ45) in bulk 10-pack. 1080p fixed dome onboard camera with male RJ-45 network connector.	\$ 5,559.00	7331021062757	8.16	14.17
AXIS P3905-R MkII (RJ45) in bulk 50-pack. 1080p fixed dome onboard camera with male RJ-45 network connector.	\$ 27,899.00	7331021062764	31.75	16.54
1080p fixed dome onboard camera with female M12 D-coded connector. Equipped with 3.6mm, F2.0 lens in ruggedized IP66/67 casing. Includes lens tool, top cover tool, allen key, and drill template.	\$ 589.00	7331021059641	0.87	4.92

AXIS P3905-R MkII (M12) in bulk 10-pack. 1080p fixed dome onboard camera with female M12 D-		5,559.00	7331021062771	8.51	14.17
coded connector.					
AXIS P3905-R Mkll (M12) in bulk 50-pack. 1080p	\$	27,899.00	7331021062788	33.69	16.54
fixed dome onboard camera with female M12 D-	Ť	21,000.00	1001021002100	00.00	10.04
coded connector.					
AXIS P3905-R Mk II (RJ45) with no lens in bulk	\$	5,359.00	7331021065093	8.29	14.17
10-pack. 1080p fixed dome onboard camera	Ť	-,			
with male RJ-45 network connector. Lenses					
sold separately.					
Note: Avoid installing lenses in dusty					
environments. To reduce the risk of dust falling					
into the sensor, hold the camera with the lens					
opening facing down.					
1080p fixed dome onboard camera with male	\$	649.00	7331021059658	0.89	4.92
RJ-45 network connector, and support for					
audio and I/O. Equipped with 3.6mm, F2.0 lens					
in ruggedized IP66/67 casing. Includes lens					
tool, top cover tool, allen key, and drill					
template.					
AXIS P3915-R MkII (RJ45) in bulk 10-pack.	\$	6,079.00	7331021062795	8.77	14.17
1080p fixed dome onboard camera with male					
RJ-45 network connector, and support for					
audio and I/O. Accessory kit not included in 10-					
pack.	^		7004004000004	00 70	40.54
AXIS P3915-R MkII (RJ45) in bulk 50-pack. 1080p fixed dome onboard camera with male	\$	30,299.00	7331021062801	33.73	16.54
RJ-45 network connector, and support for					
audio and I/O. Accessory kit not included in 50-					
pack.					
1080p fixed dome onboard camera with female	\$	649.00	7331021059665	0.91	4.92
M12 D-coded connector, and support for audio					
and I/O. Equipped with 3.6mm, F2.0 lens in					
ruggedized IP66/67 casing. Includes lens tool,					
top cover tool, allen key, and drill template.					
AXIS P3915-R Mkll (M12) in bulk 10-pack. 1080p	\$	6,079.00	7331021062818	8.82	14.17
fixed dome onboard camera with female M12 D-					
coded connector, and support for audio and					
I/O. Accessory kit not included in 10-pack.					
AXIS P3915-R MkII (M12) in bulk 50-pack. 1080p	\$	30,299.00	7331021062825	34.83	16.54
fixed dome onboard camera with female M12 D-	-				
coded connector, and support for audio and					
I/O. Accessory kit not included in 50-pack.					
AXIS P3905-R Mk II (M12) with no lens in bulk	\$	5,559.00	7331021065109	8.47	14.17
10-pack. 1080p fixed dome onboard camera	ľ	-,			
with female M12 D-coded connector. Lenses					
sold separately.					
Note: Avoid installing lenses in dusty					
environments. To reduce the risk of dust falling					
into the sensor, hold the camera with the lens					
opening facing down.					1

Full HDTV 1080p fixed dome onboard camera with male RJ-45 network connector for rolling stock and vehicles. Equipped with 2.8mm, F1.6 lens in ruggedized IP66/IP67 and IK10 rated metal casing. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Forensic WDR, Lightfinder technology and removable IR-cut filter for day/night functionality. Axis Zipstream technology for reduced bandwidth and storage needs, microSD/microSDHC/microSDXC memory card slot for optional local video storage. Includes lens tool, L-key, and drill template.	\$ 549.00	7331021069022	1.19	6.50
 Bulk 10-pack of AXIS P3925-R. Full HDTV 1080p fixed dome onboard camera with male RJ-45 network connector for rolling stock and vehicles. Equipped with 2.8mm, F1.6 lens in ruggedized IP66/IP67 and IK10 rated metal casing. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Forensic WDR, Lightfinder technology and removable IR-cut filter for day/night functionality. Axis Zipstream technology for reduced bandwidth and storage needs, microSD/microSDHC/microSDXC memory card slot for optional local video storage 	\$ 5,215.00	7331021069350	11.86	21.85
Full HDTV 1080p fixed dome onboard camera for rolling stock and vehicles with female M12 D-coded connector. Equipped with 2.8mm, F1.6 lens in ruggedized IP66/IP67 and IK10 rated metal casing. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Forensic WDR, Lightfinder technology and removable IR-cut filter for day/night functionality. Axis Zipstream technology for reduced bandwidth and storage needs, microSD/microSDHC/microSDXC memory card slot for optional local video storage. Includes lens tool, L-key, and drill template.	\$ 549.00	7331021069275	1.23	6.50

Bulk 10-pack of AXIS P3925-R. Full HDTV 1080p fixed dome onboard camera with female M12 D- coded connector for rolling stock and vehicles. Equipped with 2.8mm, F1.6 lens in ruggedized IP66/IP67 and IK10 rated metal casing. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Forensic WDR, Lightfinder technology and removable IR-cut filter for day/night functionality. Axis Zipstream technology for reduced bandwidth and storage needs, microSD/microSDHC/microSDXC memory card slot for optional local video storage.	\$ 5,215.00	7331021069282	12.04	21.85
Compact streamlined exterior onboard camera for rolling stock and vehicles with male RJ-45 network connector. The HDTV 1080p camera is equipped with two 850 nm IR LEDs, removable IR-cut filter for day/night functionality and a 6 mm F1.9 lens in a rugged IP6K9K and IK10 rated metal casing. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Forensic WDR, Lightfinder technology, Axis Zipstream technology for reduced bandwidth and storage needs, microSD/microSDHC/microSDXC memory card slot for optional local video storage. Includes lens tool, L-key, and drill template.	\$ 999.00	7331021072442	2.07	6.61
Compact streamlined exterior onboard camera for rolling stock and vehicles with female M12 D-coded connector. The HDTV 1080p camera is equipped with two 850 nm IR LEDs, removable IR-cut filter for day/night functionality and a 6 mm F1.9 lens in a rugged IP6K9K and IK10 rated metal casing. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Forensic WDR, Lightfinder technology, Axis Zipstream technology for reduced bandwidth and storage needs, microSD/microSDHC/microSDXC memory card slot for optional local video storage. Includes lens tool, L-key, and drill template.	\$ 999.00	7331021072459	2.07	6.61

Full HDTV 1080p fixed dome onboard camera for rolling stock and vehicles with male RJ-45 network connector. Invisible 940-nm IR LEDs, I/O for alarm/event handling, built in microphone and external microphone input or line input. Equipped with 2.8mm, F1.6 lens in ruggedized IP66/IP67 and IK10 rated metal casing. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Forensic WDR, Lightfinder technology and removable IR-cut filter for day/night functionality. Axis Zipstream technology for reduced bandwidth and storage needs, microSD/microSDHC/microSDXC memory card slot for optional local video storage.	\$ 599.00	7331021069015	1.19	6.50
Includes lens tool, L-key, and drill template. AXIS P3248-LVE is a day/night fixed dome with IK10 vandal-resistant outdoor casing. It has support for Forensic WDR, Lightfinder 2.0, motion-adaptive exposure for minimized motion blur, and OptimizedIR illumination. Varifocal 4.3-8.6 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. 4K (8MP) at up to 30 fps with WDR. Zipstream for reduced bandwidth and storage. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Signed firmware, secure boot and AXIS Edge Vault ensure firmware authenticity and device identity. Memory card slot for optional local video storage. Power over Ethernet.	\$ 1,099.00	7331021065710	2.76	10.63
Bulk 10-pack of AXIS P3935-RL. Full HDTV 1080p fixed dome onboard camera for rolling stock and vehicles with male RJ-45 network connector. Invisible 940-nm IR LEDs, I/O for alarm/event handling, built in microphone and external microphone input or line input. Equipped with 2.8mm, F1.6 lens in ruggedized IP66/IP67 and IK10 rated metal casing. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Forensic WDR, Lightfinder technology and removable IR-cut filter for day/night functionality. Axis Zipstream technology for reduced bandwidth and storage needs, microSD/microSDHC/microSDXC memory card slot for optional local video storage.	\$ 5,690.00	7331021069336	11.90	21.85

 Full HDTV 1080p fixed dome onboard camera for rolling stock and vehicles with female M12 D-coded connector. Invisible 940-nm IR LEDs, I/O for alarm/event handling, built in microphone and external microphone input or line input. Equipped with 2.8mm, F1.6 lens in ruggedized IP66/IP67 and IK10 rated metal casing. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Forensic WDR, Lightfinder technology and removable IR-cut filter for day/night functionality. Axis Zipstream technology for reduced bandwidth and storage needs, microSD/microSDHC/microSDXC memory card slot for optional local video storage. Includes lens tool, L-key, and drill template. 	\$ 599.00	7331021069244	1.23	6.50
Bulk 10-pack of AXIS P3935-RL. Full HDTV 1080p fixed dome onboard camera for rolling stock and vehicles with female M12 D-coded connector. Invisible 940-nm IR LEDs, I/O for alarm/event handling, built in microphone and external microphone input or line input. Equipped with 2.8mm, F1.6 lens in ruggedized IP66/IP67 and IK10 rated metal casing. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Forensic WDR, Lightfinder technology and removable IR-cut filter for day/night functionality. Axis Zipstream technology for reduced bandwidth and storage needs, microSD/microSDHC/microSDXC memory card slot for optional local video storage.	\$ 5,690.00	7331021069251	12.04	21.85
3MP compact and vandal-resistant (IK10) corner-mounted camera with 1.8mm lens for wide field of view without blind spots. Elegant brushed steel design with no visible screws. Dust- and waterproof (IP66) casing. WDR, Zipstream, SD card slot and support for portcast technology. Video motion detection and active tampering alarm. PoE Class 1. Color: Brushed stainless steel.	\$ 699.00	7331021064928	2.23	6.02
3MP compact and vandal-resistant (IK10) corner-mounted camera with 1.8mm lens for wide field of view without blind spots. Ligature- resistant design with dust- and waterproof (IP66) casing. WDR, Zipstream, SD card slot and support for portcast technology. Video motion detection and active tampering alarm. PoE Class 1. White in color.	\$ 649.00	7331021066069	1.87	6.30

Fixed dome with enhanced security features: signed firmware and secure boot ensure firmware authenticity, and a Trusted Platform Module (TPM) secures certificates and cryptographic keys. Forensic WDR, Lightfinder and OptimizedIR illumination. IK10+ vandal- resistant outdoor casing. Varifocal 4.3 – 8.6 mm P-Iris lens with remote zoom and focus for installation or monitoring. Multiple, individually configurable H.264 and Motion JPEG streams. 5 MP at 30 fps with WDR, and 4 MP at up to 60 fps with WDR disabled. Zipstream for reduced bandwidth and storage. Video motion detection, shock detection and active tampering alarm. Two-way audio and audio detection. Supervised inputs / digital outputs for alarm / event handling. Electronic image	\$ 1,349.00	7331021065024	6.22	9.84
stabilization. Memory card slot for local storage. Operation in -50 °C to 60 °C (-58 °F to 140 °F) powered by standard Power over Ethernet or 8-28V DC power with redundancy. Midspan and power supply not included. Includes mounting bracket for wall or junction boxes and weather shield against sun, rain or				
snow.				
Advanced fixed dome camera with Deep Learning Processing Unit (DLPU). Support for Forensic WDR, Lightfinder 2.0 and OptimizedIR. IR shielded dome for reduced reflections. Robust, dust- and IK10+ vandal- resistant outdoor-ready metal casing. Varifocal 4-9 mm P-Iris lens with remote zoom and focus. Electronic Image Stabilization. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. 4MP stream up to 60 fps, 30fps with WDR. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Sensors for intrusion and shock. MQTT support. AXIS Edge Vault with FIPS certified TPM for added cyber security. MicroSD memory card slot for local storage. Powered by IEEE 802.3at Type 2 Class 4 (PoE+) or 10-28V DC power with redundancy. Includes mounting bracket and weather shield.	\$ 1,199.00	7331021071674	5.73	8.27

Advanced fixed dome camera with Deep Learning Processing Unit (DLPU). Support for Forensic WDR, Lightfinder 2.0 and	\$	1,299.00	7331021075054	5.62	8.07
OptimizedIR. IR shielded dome for reduced reflections. Robust, dust- and IK10+ vandal- resistant outdoor-ready metal casing. Varifocal 11-29 mm P-Iris lens with remote					
zoom and focus. Electronic Image Stabilization. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG.					
4MP stream up to 60 fps, 30fps with WDR. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital					
output for alarm / event handling. Sensors for intrusion and shock. MQTT support. AXIS Edge Vault with FIPS certified TPM for added cyber security. MicroSD memory card slot for local					
storage. Powered by IEEE 802.3at Type 2 Class 4 (PoE+) or 10-28V DC power with redundancy. Includes mounting bracket and weather shield.					
Advanced fixed dome camera with Deep	\$	1,499.00	7331021075061	5.73	8.27
Learning Processing Unit (DLPU). Support for Forensic WDR, Lightfinder 2.0 and OptimizedIR. IR shielded dome for reduced reflections. Robust, dust- and IK10+ vandal-	•	.,			
resistant outdoor-ready metal casing. Varifocal 6-13 mm P-Iris lens with remote zoom and focus. Electronic Image Stabilization. Multiple, individually configurable streams,					
H.264/H.265 with Zipstream and Motion JPEG. 8MP stream up to 60 fps, 30fps with WDR. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio					
detection. Supervised digital input / digital output for alarm / event handling. Sensors for intrusion and shock. MQTT support. AXIS Edge Vault with FIPS certified TPM for added cyber					
security. MicroSD memory card slot for local storage. Powered by IEEE 802.3at Type 2 Class 4 (PoE+) or 10-28V DC power with redundancy. Includes mounting bracket and weather shield.					

Advanced fixed dome camera in a DNV marine	\$	1.799.00	7331021077812	6.17	8.66
certified, electropolished stainless steel (SS	Ť	,			
316L) outdoor casing, offering high corrosion					
resistance and IK10+ (50 joules) vandal					
resistance, with Deep Learning Processing Unit					
(DLPU). Support for Forensic WDR, Lightfinder					
2.0 and OptimizedIR. IR shielded dome for					
reduced reflections.					
Varifocal 6-13 mm P-Iris lens with remote zoom					
and focus. Electronic Image Stabilization.					
Multiple, individually configurable streams,					
H.264/H.265 with Zipstream and Motion JPEG.					
8MP stream up to 60 fps, 30fps with WDR.					
AXIS Object Analytics, Video motion detection					
and tampering alarm. Two-way audio and audio					
detection. Supervised digital input / digital					
output for alarm / event handling. Sensors for					
intrusion and shock. MQTT support. AXIS Edge					
Vault with FIPS certified TPM for added cyber					
security. MicroSD memory card slot for local					
storage. Operation in -50 °C to 60 °C (-58 °F to					
140 °F), powered by IEEE 802.3at Type 2 Class 4					
(PoE+) or 10-28V DC power with redundancy.					
Includes mounting bracket for wall/ceiling or					
junction boxes.					
	i				

Advanced dome camera with remote adjustment by Pan, Tilt, Roll and Zoom (PTRZ). Inlcudes a Deep Learning Processing Unit (DLPU) for advanced edge analytics. Support for Forensic WDR, Lightfinder 2.0. Robust, dust- and IK10 vandal-resistant outdoor-ready metal casing. 7331021081390 6.31 8.66 Varifocal 4-9 mm P-Iris lens with remote pan, tilt, roll, zoom and focus. Electronic Image Stabilization. Varifocal 4-9 mm P-Iris lens with remote pan, tilt, roll, zoom and focus. Electronic Image Stabilization. 1 7331021081390 6.31 8.66 4MP stream up to 60 fps, 30fps with WDR. 1
Inlcudes a Deep Learning Processing Unit (DLPU) for advanced edge analytics. Support for Forensic WDR, Lightfinder 2.0. Robust, dust- and IK10 vandal-resistant outdoor-ready metal casing. Varifocal 4-9 mm P-Iris lens with remote pan, tilt, roll, zoom and focus. Electronic Image Stabilization. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. 4MP stream up to 60 fps, 30fps with WDR. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Sensors for intrusion and shock. MQTT support. AXIS Edge Vault with FIPS certified TPM for added cyber security. MicroSD memory card slot for local
 (DLPU) for advanced edge analytics. Support for Forensic WDR, Lightfinder 2.0. Robust, dust- and IK10 vandal-resistant outdoor-ready metal casing. Varifocal 4-9 mm P-Iris lens with remote pan, tilt, roll, zoom and focus. Electronic Image Stabilization. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. 4MP stream up to 60 fps, 30fps with WDR. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Sensors for intrusion and shock. MQTT support. AXIS Edge Vault with FIPS certified TPM for added cyber security. MicroSD memory card slot for local
for Forensic WDR, Lightfinder 2.0. Robust, dust- and IK10 vandal-resistant outdoor-ready metal casing. Varifocal 4-9 mm P-Iris lens with remote pan, tilt, roll, zoom and focus. Electronic Image Stabilization. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. 4MP stream up to 60 fps, 30fps with WDR. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Sensors for intrusion and shock. MQTT support. AXIS Edge Vault with FIPS certified TPM for added cyber security. MicroSD memory card slot for local
and IK10 vandal-resistant outdoor-ready metal casing. Varifocal 4-9 mm P-Iris lens with remote pan, tilt, roll, zoom and focus. Electronic Image Stabilization. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. 4MP stream up to 60 fps, 30fps with WDR. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Sensors for intrusion and shock. MQTT support. AXIS Edge Vault with FIPS certified TPM for added cyber security. MicroSD memory card slot for local
casing. Varifocal 4-9 mm P-Iris lens with remote pan, tilt, roll, zoom and focus. Electronic Image Stabilization. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. 4MP stream up to 60 fps, 30fps with WDR. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Sensors for intrusion and shock. MQTT support. AXIS Edge Vault with FIPS certified TPM for added cyber security. MicroSD memory card slot for local
Varifocal 4-9 mm P-Iris lens with remote pan, tilt, roll, zoom and focus. Electronic Image Stabilization. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. 4MP stream up to 60 fps, 30fps with WDR. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Sensors for intrusion and shock. MQTT support. AXIS Edge Vault with FIPS certified TPM for added cyber security. MicroSD memory card slot for local
tilt, roll, zoom and focus. Electronic Image Stabilization. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. 4MP stream up to 60 fps, 30fps with WDR. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Sensors for intrusion and shock. MQTT support. AXIS Edge Vault with FIPS certified TPM for added cyber security. MicroSD memory card slot for local
Stabilization. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. 4MP stream up to 60 fps, 30fps with WDR. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Sensors for intrusion and shock. MQTT support. AXIS Edge Vault with FIPS certified TPM for added cyber security. MicroSD memory card slot for local
Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. 4MP stream up to 60 fps, 30fps with WDR. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Sensors for intrusion and shock. MQTT support. AXIS Edge Vault with FIPS certified TPM for added cyber security. MicroSD memory card slot for local
H.264/H.265 with Zipstream and Motion JPEG. 4MP stream up to 60 fps, 30fps with WDR. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Sensors for intrusion and shock. MQTT support. AXIS Edge Vault with FIPS certified TPM for added cyber security. MicroSD memory card slot for local
4MP stream up to 60 fps, 30fps with WDR. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Sensors for intrusion and shock. MQTT support. AXIS Edge Vault with FIPS certified TPM for added cyber security. MicroSD memory card slot for local
AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Sensors for intrusion and shock. MQTT support. AXIS Edge Vault with FIPS certified TPM for added cyber security. MicroSD memory card slot for local
and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Sensors for intrusion and shock. MQTT support. AXIS Edge Vault with FIPS certified TPM for added cyber security. MicroSD memory card slot for local
detection. Supervised digital input / digital output for alarm / event handling. Sensors for intrusion and shock. MQTT support. AXIS Edge Vault with FIPS certified TPM for added cyber security. MicroSD memory card slot for local
output for alarm / event handling. Sensors for intrusion and shock. MQTT support. AXIS Edge Vault with FIPS certified TPM for added cyber security. MicroSD memory card slot for local
intrusion and shock. MQTT support. AXIS Edge Vault with FIPS certified TPM for added cyber security. MicroSD memory card slot for local
Vault with FIPS certified TPM for added cyber security. MicroSD memory card slot for local
security. MicroSD memory card slot for local
storage. Powered by IEEE 802.3at Type 2 Class
4 (PoE+) or 10-28V DC power with redundancy.
Includes mounting bracket and weather shield.
Advanced dome camera with remote \$ 1,699.00 7331021081406 6.31 8.66
adjustment by Pan, Tilt, Roll and Zoom (PTRZ).
Inlcudes a Deep Learning Processing Unit
(DLPU) for advanced edge analytics. Support
for Forensic WDR, Lightfinder 2.0. Robust, dust
and IK10 vandal-resistant outdoor-ready metal
casing.
Varifocal 6-13 mm P-Iris lens with remote pan,
tilt, roll, zoom and focus. Electronic Image
Stabilization.
Multiple, individually configurable streams,
H.264/H.265 with Zipstream and Motion JPEG.
8MP stream up to 60 fps, 30fps with WDR.
AXIS Object Analytics, Video motion detection
and tampering alarm. Two-way audio and audio
detection. Supervised digital input / digital
output for alarm / event handling. Sensors for
Intrusion and shock. MQTT support. AXIS Edge
Vault with FIPS certified TPM for added cyber
security. MicroSD memory card slot for local
storage. Powered by IEEE 802.3at Type 2 Class
4 (PoE+) or 10-28V DC power with redundancy. Includes mounting bracket and weather shield.

AXIS Q3819-PVE delivers a 180° panoramic overview of extensive areas. With 14 MP resolution and seamless stitching of all four images, it offers 180° horizontal and 38° vertical coverage. It's possible to mount two cameras back-to-back for a complete 360° overview using AXIS T94V01C Dual Camera Mount. It features AXIS Object Analytics for nuanced and remarkably granular object classification. Furthermore, it includes built-in motors allowing for remote pan/tilt/roll functionality and it offers smart pairing with Axis network speakers using edge-to-edge technology. Furthermore, Axis Edge Vault protects your Axis devices on your network.	\$ 2,149.00	7331021068230	7.45	9.06
Robust stainless steel corner-mount camera replacing AXIS Q8414 (Trinity). Key fetaures: • Anti-ligature, stainless steel, IK10+, IP66, • 4MP, >90° VFoV, >120° HFoV, • 940nm LEDs for invisible IR • H.264 + H.265 with Zipstream, • Built-in michrophone, • I/O and optional line-in/out, • Option to further prevent screw-tampering	\$ 1,239.00	7331021067493	4.37	9.13
Robust stainless steel corner-mount camera replacing AXIS Q8414 (Trinity). Key fetaures: • Anti-ligature, stainless steel, IK10+, IP66, • 4MP, >90° VFoV, >120° HFoV, • 940nm LEDs for invisible IR • H.264 + H.265 with Zipstream, • Built-in michrophone, • I/O and optional line-in/out, • Option to further prevent screw-tampering	\$ 1,239.00	7331021067509	4.41	9.13
AXIS Q8414-LVS Network Camera Metal is a brushed stainless steel indoor corner camera with an anti-grip/anti-ligature design to prevent self-harm. Ideal for correctional facilities and psychiatric wards. It supports IK10+ 50 joules impact rating. It is IP66- and NEMA 4X-rated for easy and safe cleaning. Superb images day and night with Lightfinder technology and has built- in invisible IR LED (940 nm). It delivers HDTV 720p or 1.3 Megapixel video, supporting a lens with: P-Iris, varifocal 2.5–6 mm, 105°–49° horizontal angle of view, F1.2. It offers 3 masks and I/O ports. Built-in surface mounted high quality microphone.	\$ 1,299.00	7331021045101	10.36	13.39

AXIS Q8414-LVS Network Camera White is a powder coated stainless steel indoor corner camera with an anti-grip/anti-ligature design to prevent self-harm. Ideal for correctional facilities and psychiatric wards. It supports IK10+ 50 joules impact rating. It is IP66- and NEMA 4X-rated for easy and safe cleaning. Superb images day and night with Lightfinder technology and has built-in invisible IR LED (940 nm). It delivers HDTV 720p or 1.3 Megapixel video, supporting a lens with: P-Iris, varifocal 2.5–6 mm, 105°–49° horizontal angle of view, F1.2. It offers 3 masks and I/O ports. Built-in surface mounted high quality microphone.	\$ 1,299.00	7331021045118	10.36	13.39
Please check the supported countries Visit www.axis.com for supported products and application download. Discreet outdoor, HDTV / 1080p, day/night, dust- and IK10 vandal-resistant fixed dome camera with built-in AXIS License Plate Verifier application. Detect and verify vehicles in single lanes with speed up to 30 km/h (19 mph) in 2 to 7 meter distance (7 to 23 feet) to allow vehicle entry/exit into a controlled area. I/O port for direct control, built-in block and allow lists of up to 1000 license plates. License plate reading time less than 1 second. OptimizedIR, Forensic WDR, Lightfinder, shock detection, IK10, IP66/67. Operation temperature 40°C to +50°C (-40°F to 122°F). Includes mounting bracket for wall/ceiling or junction boxes. License plate verification day and night. Powered by IEEE 802.3af Type 1 Class 3 midspan (PoE). Midspan not included.	\$ 1,289.00	7331021075153	2.80	7.87

	-				
Please check the supported countries Visit www.axis.com for supported products and application download. Discreet outdoor, HDTV / 1080p, day/night, dust- and IK10 vandal-resistant fixed dome camera with built-in AXIS License Plate Verifier application. Detect and verify vehicles in single lanes with speed up to 30 km/h (19 mph) in 2 to 7 meter distance (7 to 23 feet) to allow vehicle entry/exit into a controlled area. I/O port for direct control, built-in block and allow lists of up to 1000 license plates. License plate reading time less than 1 second. OptimizedIR, Forensic WDR, Lightfinder, shock detection, IK10, IP66/67. Operation temperature - 40°C to +50°C (-40°F to 122°F). Includes mounting bracket for wall/ceiling or junction boxes. License plate verification day and night. Powered by IEEE 802.3af Type 1 Class 3 midspan (PoE). Midspan not included.	\$	1,289.00	7331021084384	2.69	7.87
AXIS M3057-PLR MkII is a 6Mp resolution fisheye rollingstock compliant camera offering excellent image quality and a complete 180° or 360° overview. It is intended to be used inside trains or buses. It comes with a M12 connector pigtail. This dome also offers dewarped views such as panorama, quad, corner, and corridor views directly from the camera. It includes Axis Lightfinder and Axis Forensic WDR for true colors and great details in challenging light or near darkness. The IR allows for surveillance in pitch darkness. Furthermore, enhanced security functionality prevents unauthorized access and safeguards your system.	\$	999.00	7331021077713	2.12	6.69
AXIS P3905-R MkIII is a 1080p fixed dome onboard camera with a male RJ-45 network connector on the pigtail. Equipped with 3.6mm, F2.0 lens in a rugged IP66/67 casing. It comes with a lens tool. AXIS P3905-R MkIII is rollingstock compliant.	\$	499.00	7331021081413	0.77	4.37
AXIS P3905-R MkIII is a 1080p fixed dome onboard camera with a M12 network connector on the pigtail. Equipped with 3.6mm, F2.0 lens in a rugged IP66/67 casing. It comes with a lens tool. AXIS P3905-R MkIII is rollingstock compliant.	\$	499.00	7331021081437	0.77	4.37

AXIS P3905-R MkIII Bulk 10PCS is a bulk pack of 10x AXIS P3905-R MkIII cameras. It is a 1080p fixed dome onboard cameras with a male RJ-45 network connector on the pigtail. AXIS P3905-R MkIII is equipped with 3.6mm, F2.0 lens in a rugged IP66/67 casing. It comes with a lens tool. AXIS P3905-R MkIII is rollingstock compliant.	\$ 4,559.00	7331021081420	7.61	15.51
AXIS P3905-R MkIII M12 Bulk 10PCS is a bulk pack of 10x AXIS P3905-R MkIII cameras. It is a 1080p fixed dome onboard cameras with a M12 network connector on the pigtail. AXIS P3905-R MkIII is equipped with 3.6mm, F2.0 lens in a rugged IP66/67 casing. It comes with a lens tool. AXIS P3905-R MkIII is rollingstock compliant.	\$ 4,559.00	7331021081444	7.61	15.51
AXIS M3905-R is a 1080p fixed dome onboard camera with a male RJ-45 network connector on the pigtail. Equipped with 3.6mm, F2.0 lens in a rugged IP66/67 casing. It comes with a lens tool. AXIS M3905-R is not rollingstock compliant.	\$ 329.00	7331021078307	0.77	4.37
AXIS M3905-R M12 is a 1080p fixed dome onboard camera with a M12 network connector on the pigtail. Equipped with 3.6mm, F2.0 lens in a rugged IP66/67 casing. It comes with a lens tool. AXIS M3905-R M12 is not rollingstock compliant.	\$ 329.00	7331021078321	0.77	4.37
AXIS M3905-R Bulk 10PCS is a bulk pack of 10x AXIS M3905-R cameras. It is a 1080p fixed dome onboard cameras with a male RJ-45 network connector on the pigtail. AXIS M3905-R is equipped with 3.6mm, F2.0 lens in a rugged IP66/67 casing. It comes with a lens tool. AXIS M3905-R is not rollingstock compliant.	\$ 2,999.00	7331021078314	7.61	15.51
AXIS M3905-R M12 Bulk 10PCS is a bulk pack of 10x AXIS M3905-R cameras. It is a 1080p fixed dome onboard cameras with a M12 network connector on the pigtail. AXIS M3905-R is equipped with 3.6mm, F2.0 lens in a rugged IP66/67 casing. It comes with a lens tool. AXIS M3905-R M12 is not rollingstock compliant.	\$ 2,999.00	7331021078338	7.61	15.51

······	 	 	_	
AXIS M4317-PLR is Onboard panoramic camera	\$ 729.00	7331021085053	2.41	25.98
for buses.				
AXIS M4317-PLR is a discreet, IK10 and IP66				
ready dome designed with 6 MP resolution and				
a stereographic lens. It can deliver multiple				
360° or 180° panoramic views at up to 30 fps				
with no blind spots. Thanks to Sharpdome 360,				
this panoramic camera delivers greater				
sharpness at the edges of the image. Built on				
ARTPEC-8, it offers powerful artificial				
intelligence and deep learning analytics on the				
edge.				
AXIS M4317-PLVE comes with build-in				
configurable IR, making it perfect for low light				
situations. Signed firmware and secure boot				
ensure firmware authenticity.				
AXIS M4317-PLR as a built-in RJ45 connector.				
AXIS M4318-PLR is a discreet, IK10 and IP66	\$ 899.00	7331021085060	2.40	25.98
ready dome designed with 12 MP resolution				
and a stereographic lens. It can deliver multiple				
360° or 180° panoramic views at up to 30 fps				
with no blind spots. Thanks to Sharpdome 360,				
this panoramic camera delivers greater				
sharpness at the edges of the image. Built on				
ARTPEC-8, it offers powerful artificial				
intelligence and deep learning analytics on the				
edge.				
AXIS M4318-PLVE comes with build-in				
configurable IR, making it perfect for low light				
situations. Signed firmware and secure boot				
ensure firmware authenticity.				
AXIS M4318-PLR as a built-in RJ45 connector.				

Advanced fixed dome camera in a DNV marine certified, NSF/ANSI Standard 169 Special Purpose Food Equipment and Devices electropolished stainless steel (SS 316L) outdoor casing, offering high corrosion resistance and IK11/ IP 66/67/68/ Nema 4X. With Deep Learning Processing Unit (DLPU). Forensic WDR, Lightfinder 2.0 and Optimized IR. Varifocal 3-8 mm P-Iris lens with remote zoom and focus. Multiple, individually configurable streams, H.264/H.265 with Zipstream and Motion JPEG. 8MP 4K stream in 16:9 up to 30fps. AXIS Object Analytics, Video motion detection and tampering alarm. Two- way audio and audio detection. Supervised digital input / digital output for alarm / event handling. MQTT support. Axis Edge Vault for added cyber security. Built in case open switch. MicroSD memory card slot for local storage. Powered by IEEE 802.3af/802.3at Type 1 Class 3. Extended temperature range. Includes mounting bracket.	\$ 1,349.00	7331021082182	4.50	7.28
High accuracy outdoor PTZ positioning camera. HDTV 1080p video, 31x optical zoom, focus recall, ½" sensor for extreme light sensitivity and Axis Lightfinder 2. Auto day/night functionality. Zipstream with H.264/ H.265, Responsive absolute positioning with high- speed and ultra-smooth pan and tilt capabilities and continuous 360° rotation. Autotracking 2, Tour recording and Active Gatekeeper. Compass ruler overlay, Privacy mask with chameleon and mosaic masking. Build in analytics. Integrated long-life silicone wiper for remote maintenance, and integrated SFP slot for long-distance fiber connection. IK10, IP66, NEMA 4X, NEMA TS2 for temperature up to 74C. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included) Compatible with AXIS PT IR Illuminator Kit C	\$ 4,299.00	7331021078826	35.94	11.81

High accuracy outdoor PTZ positioning camera. HDTV 1080p video, 31x optical zoom, focus recall, ½" sensor for extreme light sensitivity and Axis Lightfinder 2. Auto day/night functionality. Zipstream with H.264/ H.265, Responsive absolute positioning with high- speed and ultra-smooth pan and tilt capabilities and continuous 360° rotation. Autotracking 2, Tour recording and Active Gatekeeper. Compass ruler overlay, Privacy mask with chameleon and mosaic masking. Build in analytics. Integrated long-life silicone wiper for remote maintenance, and integrated SFP slot for long-distance fiber connection. IK10, IP66, NEMA 4X, NEMA TS2 for temperature up to 74C. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included) Compatible with AXIS PT IR Illuminator Kit C	\$ 4,299.00	7331021078833	35.94	11.81
 15MP indoor panoramic camera with PTZ and 10x optical zoom. Panoramic part; 3x5MP sensors for 360degrees surveillance PTZ part; HDTV 1080 (1920x1080) automatic day/night and autofocus. WDR- Forensic Capture Build in Z-wave gateway for home automation sensors. Text overlay from Z-wave sensors. H.264/265 with Zipstream, MJPEG Two-way audio, Deterrence LED, 30W PoE 802.3at or 24V, IP52, White body as standard. Surface mount or Axis PTZ standard mount. Midspan not included. 	\$ 1,199.00	7331021074354	5.45	11.81
Ceiling-mount mini PTZ dome camera with 5x Optical zoom and autofocusing, HDTV 720p (1280x720) 25/30fps in H.264 with Zipstream and Motion JPEG. IP51 protection against dust and water. Basic analytics are included. Only PoE, midspan not included. Surface ceiling mounting brackets included	\$ 499.00	7331021059894	1.32	5.31
Ceiling-mount mini PTZ dome camera with 5x Optical zoom and autofocusing, HDTV 720p (1280x720) 30fps in H.264/H.265 with Zipstream and Motion JPEG. IP51 protection against dust and water. Featuring a built-in microphone, includes built-in analytics such as scream detection. Only PoE, midspan not included. Surface ceiling mounting brackets included	\$ 549.00	7331021076174	1.30	6.30

Ceiling-mount mini PTZ dome camera with 5x Optical zoom and autofocusing, HDTV 1080p (1920x1080) 30fps in H.264/H.265 with Zipstream and Motion JPEG. IP51 protection against dust and water. Wireless I/O connectivity with Z-Wave Plus® gateway for home automation devices. Text overlay from Z- wave sensors. Featuring a built-in microphone, includes built-in analytics such as scream detection. Only PoE, midspan not included. Surface ceiling mounting brackets included.	\$ 649.00	7331021076204	1.30	5.51
Discreet PTZ with HDTV 1080p, 1920x1080, 10x optical zoom, automatic day/night and autofocus. Continues 360° pan. WDR- Forensic Capture, IP66, PoE and 24V. 30fps in H.264 and Motion JPEG, Zipstream, Scene profiles, two- way audio, 4 I/O. Surface mount or Axis PTZ standard mount. Midspan not included.	\$ 1,049.00	7331021061040	3.99	8.66
PTZ camera with 77° field of view, continues 360° pan for both indoor and outdoor with 21x optical zoom. HDTV 720p @ 60fps (1280x720) in H.264/265, Motion JPEG, Axis Zipstream, Lighfinder 2 and Focus Recall, WDR, Day & Night, IP66, IK10 and NEMA 4X classification. Advanced Gatekeeper, full-size SD-card slot, smoked and clear dome. Mounting brackets and Midspan are not included.	\$ 1,699.00	7331021067424	7.61	8.66
PTZ camera with 77° field of view, continues 360° pan for both indoor and outdoor with 21x optical zoom. HDTV 1080 and 720p @ 60fps in H.264/265, Motion JPEG, Axis Zipstream, Lighfinder 2 and Focus Recall, WDR, Day & Night, IP66, IK10 and NEMA 4X classification. Advanced Gatekeeper, full-size SD-card slot, smoked and clear dome. Mounting brackets and Midspan are not included.	\$ 1,699.00	7331021086272	7.54	8.86
Product version for the American market. PTZ camera with continues 360° pan for both indoor and outdoor with 32x optical zoom, Lightfinder 2, Autofocus and Focus Recall. HDTV 1080p @ 30/60fps (1920x1080) in Motion JPEG, H.264, H.265, and Axis Zipstream. Two- way audio, 4xl/O, 24V and PoE, Day & Night, IP66, IK10 and NEMA 4X classification. Advanced Gatekeeper, full-size SD-card slot. Mounting brackets, Midspan/Power supply and connector or cable for audio, I/O and 24V are not included.	\$ 1,899.00	7331021076006	7.14	8.86

PTZ camera with QHD 2560x1440 @60fps (4MP), 30x optical zoom with autofocus. IP66, IK10 and NEMA 4X. Zipstream with H.264/ H.265. Auto day/night, IR illumination 200M (660ft). Continuous 360° rotation. Shock detection, Tour recording and Active Gatekeeper. Compass ruler overlay, Privacy mask with chameleon and mosaic masking. Build in analytics, Fence Guard, Loitering Guard, Audio detection, Advanced Gatekeeper, Autotracker 2. Clear transparent dome cover. No mounting bracket or midspan included (several different accessories available).	\$ 2,199.00	7331021076945	7.10	9.45
Outdoor-ready 360° situational awareness camera, comprising of 4x5MP sensors @ 20fps in H.264/H.265 Zipstream and Motion JPEG. Movable sensors with exchangeable lenses. Autofocus, D/N, Autopilot for tracking. Designed to be integrated with AXIS Q605x-E and AXIS Q607x-E series camera for large area coverage and simultaneous zoomed-in view, using the one-click PTZ control feature. Full size SD-card slot. No extra equipment required, as it uses the same brackets, power supply and network cable as the connected AXIS Q60-E.	\$ 1,799.00	7331021070141	14.29	17.09
Outdoor-ready 360° situational awareness camera, comprising of 4x5MP sensors @ 20fps in H.264/H.265 Zipstream and Motion JPEG. Movable sensors with exchangeable lenses. Autofocus, D/N. Directional Audio Detection. Designed to be integrated with any AXIS Q61- series camera for large area coverage and simultaneous zoom-in view, using the one-click PTZ control feature. Full size SD-card slot. No extra equipment required, as it uses the same brackets, power supply and network cable as the connected AXIS Q61	\$ 1,799.00	7331021066816	12.90	15.75

Top performance PTZ camera with HDTV 720p @60fps 30x optical zoom for indoor use. IP52 rated. Zipstream with H.264/ H.265. Auto day/night functionality. Continuous 360° rotation and 180° tilt with E-flip. Two-way audio, I/O and external power with multi-connector cable (not included). Shock detection, Autotracking 2, tour recording and Active Gatekeeper. Compass ruler overlay, Privacy mask with mosaic. Highlight compensation. Build in analytics; object removed, loitering guard, fence detector, object counter, enter/exit detection, video motion detection. Clear and smoked transparent dome cover and High PoE midspan are included. Mounting kits for hard and drop ceilings	\$ 2,299.00	7331021069985	10.32	10.24
Top performance PTZ camera with HDTV 720p @60fps, 30x optical zoom, outdoor-ready, IP66, IK10 and NEMA 4x-rated. Zipstream with H.264/ H.265, Arctic Temperature Control enables operation and start up from -40 °C to +50 °C (- 58 °F to 122 °F). Auto day/night functionality. Continuous 360° rotation and 220° tilt with E- flip. Shock detection, Autotracking 2, tour recording and Active Gatekeeper. Compass ruler overlay, Privacy mask with mosaic. Highlight compensation. Build in analytics; object removed, loitering guard, fence detector, object counter, enter/exit detection, video motion detection. Clear transparent dome cover and High PoE midspan with fiber slot are included. No mounting bracket included (several different accessories available).	\$ 2,799.00	7331021070028	12.70	11.81
Top performance PTZ camera with HDTV 1080p @60fps 40x optical zoom for indoor use. IP52 rated. Zipstream with H.264/ H.265. Auto day/night functionality. Continuous 360° rotation and 180° tilt with E-flip. Two-way audio, I/O and external power with multi-connector cable (not included). Shock detection, Autotracking 2, tour recording and Active Gatekeeper. Compass ruler overlay, Privacy mask with mosaic. Highlight compensation. Build in analytics; object removed, loitering guard, fence detector, object counter, enter/exit detection, video motion detection. Clear and smoked transparent dome cover and High PoE midspan are included. Mounting kits for hard and drop ceilings	\$ 2,749.00	7331021067240	10.32	10.43

		 		-
Top performance PTZ camera with HDTV 1080p @60fps, 40x optical zoom, outdoor-ready, IP66, IK10 and NEMA 4x-rated. Zipstream with H.264/ H.265, Arctic Temperature Control enables operation and start up from -40 °C to +50 °C (- 58 °F to 122 °F). Auto day/night functionality. Continuous 360° rotation and 220° tilt with E- flip. Shock detection, Autotracking 2, tour recording and Active Gatekeeper. Compass ruler overlay, Privacy mask with mosaic. Highlight compensation. Build in analytics; object removed, loitering guard, fence detector, object counter, enter/exit detection, video motion detection. Clear transparent dome cover and High PoE midspan with fiber slot are included. No mounting bracket included (several different accessories available).	\$ 3,299.00	7331021067325	12.70	11.81
Top performance UHD 4K PTZ camera, 20x optical zoom, outdoor-ready, IP66, IK10 and NEMA 4x-rated. Zipstream with H.264/ H.265, Arctic Temperature Control enables operation and start up from -40 °C to +50 °C (-58 °F to 122 °F). Auto day/night functionality. Continuous 360° rotation and 220° tilt with E-flip. Shock detection, Autotracking 2, tour recording and Active Gatekeeper. Compass ruler overlay, Privacy mask with mosaic. Highlight compensation. Build in analytics; object removed, loitering guard, fence detector, object counter, enter/exit detection, video motion detection. Clear transparent dome cover and High PoE midspan with fiber slot are included. No mounting bracket included (several different accessories available).	\$ 3,449.00	7331021073722	11.99	11.61
 PTZ camera with continues 360° pan and build in IR illumination (660ft) with 32x optical zoom, Autofocus and Focus Recall. HDTV 1080p @ 60fps (1920x1080) in Motion JPEG, H.264, H.265, and Axis Zipstream. Day & Night, IP66, NEMA 4X and NEMA TS2 classification. Full- size SD-card slot. Perfect image quality in all directions without distortion. WDR, EIS, Speed dry. Includes Advanced gate keeper and analytics. Repaintable surface. Midspan with fiber slot and RJ45 input included. 	\$ 2,649.00	7331021069794	9.48	9.84

 PTZ camera with continues 360° pan and build in IR illumination (200M) with 32x optical zoom, Autofocus and Focus Recall. HDTV 1080p @ 50fps (1920x1080) in Motion JPEG, H.264, H.265, and Axis Zipstream. Day & Night, IP66, NEMA 4X and NEMA TS2 classification. Full- size SD-card slot. Perfect image quality in all directions without distortion. WDR, EIS, Speed dry. Includes Advanced gate keeper and analytics. Repaintable surface. Midspan NOT included. 	\$ 2,449.00	7331021087682	8.05	8.66
Compact, top performance 4K Comparable with SMPTE 2036 3840x2160 resolution in 30fps, (8MP). With 12x optical zoom for outdoor as well as indoor use. Day/night, Automatic defog, DNR 2D/3D and EIS. IP66, Active gatekeeper, tour recording and autotracking. Perfect image quality in all directions, without distortion, repaintable surface. Mounting brackets are not included (several different accessories available). Midspan with fiber slot included.	\$ 3,449.00	7331021051119	9.33	9.84
 PTZ for the toughest conditions. MIL specified, build in IR illumination 400M (1300ft), can be mounted face up or face down. IP66/67/68, IK10, MIL 8105 521. Camera part; ½" sensor with HDTV 1080p, 30x optical zoom, 60fps, H264 with Zipstream and Motion JPEG, WDR. Perfect image quality in all directions without distortion, window wiper. Advanced gate keeper analytics. 90W Midspan included. Color; Urban grey. 	\$ 3,499.00	7331021063327	24.80	12.60
Product version for Canadian market. PTZ for the toughest conditions. MIL specified, build in IR illumination 400M (1300ft), can be mounted face up or face down. IP66/67/68, IK10, MIL 8105 521. Camera part; ½" sensor with HDTV 1080p, 30x optical zoom, 60fps, H264 with Zipstream and Motion JPEG, WDR. Perfect image quality in all directions without distortion, window wiper. Advanced gate keeper analytics. 90W Midspan included. Color; Urban grey.	\$ 3,499.00	7331021068599	24.80	12.60

 PTZ for the toughest conditions. MIL specified, build in IR illumination 400M (1300t), can be mounted face up or face down. IP66/67/68, IK10, MIL 8105 521, NEMA TS2 for temperature up to 74C (165F), Arctic temperature control. Camera part; ½" sensor with HDTV 1080p, 30x optical zoom, 60fps, H264/H.265 with Zipstream and Motion JPEG, WDR, improved EIS. Perfect image quality in all directions without distortion, window wiper. Autotracking 2, Tour recording and Active Gatekeeper. Compass ruler overlay, Privacy mask with chameleon and mosaic masking. Highlight compensation. Build in analytics. 90W Midspan included. Color; Urban grey. No mounting bracket included (several different accessories available). 	\$ 3,699.00	7331021075863	24.03	10.83
High-end PTZ camera with HDTV 1080p @60fps, ½" RGB sensor, 31x optical Quick zoom 1sec from width to tele and Laser Focus. Outdoor-ready, IP66, IK10 and NEMA 4x-rated NEMA TS2 for temperature up to 74C (165F). Zipstream with H.264/ H.265, Arctic Temperature Control enables operation and start up from -40 °C. Auto day/night functionality, IR illumination up to 300M (980Feet). Continuous 360° rotation. Shock detection, Autotracking 2, Tour recording and Active Gatekeeper. Compass ruler overlay, Privacy mask with chameleon and mosaic masking. Highlight compensation. Build in analytics. Clear transparent dome cover and High PoE midspan with fiber slot are included. No mounting bracket included (several different accessories available).	\$ 3,249.00	7331021072398	14.55	11.50

High-end PTZ camera with UHD 4K @30fps (8MP), ½" RGB sensor, 31x optical Quick zoom 1sec from width to tele and Laser Focus. Outdoor-ready, IP66, IK10 and NEMA 4x-rated NEMA TS2 for temperature up to 74C (165F). Zipstream with H.264/ H.265, Arctic Temperature Control enables operation and	\$ 3,449.00	7331021077386	14.88	11.61
start up from -40 °C. Auto day/night functionality, IR illumination up to 200M (656Ft). Continuous 360° rotation. Shock detection, Autotracking 2, Tour recording and Active Gatekeeper. Compass ruler overlay, Privacy mask with chameleon and mosaic masking. Highlight compensation. Build in analytics. Clear transparent dome cover and High PoE midspan with fiber slot are included. No mounting bracket included (several different accessories available).				
Generic PTZ camera with 30x zoom, autofocus and HDTV 1080p resolution at 60fps for live streaming of video and audio. "Video conference" design, smooth pan and tilt, EIS. HDMI, 3G-SDI, XLR-3 for studio connectivity. Studio quality in stereo. Power supply and wall mount bracket are included.	\$ 2,149.00	7331021071032	5.38	7.87
Generic PTZ camera with 20x zoom, autofocus and UHD 4K resolution at 60fps for live streaming of video and audio. "Video conference" design, smooth pan and tilt, WDR, EIS. HDMI, 3G-SDI, XLR-3 for studio connectivity. Studio audio quality in stereo. Power supply, wall mount bracket and s/w for streaming are included.	\$ 3,299.00	7331021070912	5.56	7.87
Stainless steel, (SS-316L) top performance HDTV 1080p compliant, outdoor-ready, IP66, IK10 and NEMA 4X-rated PTZ dome camera with 40x optical zoom. Auto day/night functionality. Continuous 360° rotation and 220° tilt. HDTV 1080p (1920x1080) @60fps. Zipstream with H.264/ H.265 Shock detection, Autotracking 2, tour recording and Active Gatekeeper. Compass ruler overlay, Privacy mask with mosaic. Highlight compensation. Build in analytics; object removed, loitering guard, fence detector, object counter, enter/exit detection, video motion detection. Clear transparent dome cover. Including 7 m cable, media converter switch with 2xSFP slots for optical fiber modules, 2xRJ-45, 2xI/O and 24V in. Brackets and power adapter are not included (several different accessories available).	4,899.00	7331021075207	17.02	11.42

					·
High accuracy outdoor PTZ positioning	\$	13,999.00	7331021068421	39.68	15.75
Bispectral camera based on AXIS ARTPEC7					
platform. Thermal sensor features a 640x480					
resolution, 30 fps and 35 mm lens with 17°					
angle of view. Visual sensor have HDTV 1080p					
video resolution, 32x optical zoom, focus recall					
and is extremly light sensitive. EIS (Electronic					
Image Stabilization) on both channels ensures					
focused and stable video. Integrated long-life					
silicone wiper for remote maintenance. The					
bispectral camera supports Zipstream, ONVIF,					
H.265 and local storage. Included cybersecurity					
features are TPM-module, Axis secure boot and					
comes with signed FW. It includes Video					
motion detection and support for AXIS Camera					
Application Platform enabling installation of					
AXIS Perimeter Defender and third-party					
applications. Responsive absolute positioning					
with high-speed and ultra-smooth pan and tilt					
capabilities. Integrated SFP slot for long-					
distance fiber connection. IP66, NEMA 4X rated					
and UL listed. Ready for column-mount.					
Powered by 24 V AC/DC from external power					
supply (not included).					
This product is subject to export control					
regulations. You should always consult and					
comply with the regulations of the appropriate					
local export control authorities.					
· ·					
	<u> </u>				

High accuracy outdoor PTZ positioning Bispectral camera based on AXIS ARTPEC7 platform. Thermal sensor features a 640x480 resolution, 30 fps and 35-105 mm thermal zoom lens. Visual sensor have HDTV 1080p video resolution, 32x optical zoom, focus recall and is extremly light sensitive. EIS (Electronic Image Stabilization) on both channels ensures focused and stable video. Integrated long-life silicone wiper for remote maintenance. The bispectral camera supports Zipstream, ONVIF, H.265 and local storage. Included cybersecurity features are TPM-module, Axis secure boot and comes with signed FW. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long- distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included). This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	\$ 23,999.00	7331021068452	40.57	15.75
High accuracy outdoor PT positioning thermal camera. 384x288 resolution, 30 fps and 35 mm lens with 10.5° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high- speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long- distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	\$ 6,299.00	7331021060777	33.18	14.76

Llink comment outdoor DT position's still and	¢	40.000.00	7004004000704	22.54	44.70
 High accuracy outdoor PT positioning thermal camera. 640x480 resolution, 30 fps and 60 mm lens with 10° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities. 	\$	10,299.00	7331021060791	33.51	14.76
High accuracy outdoor PTZ positioning bispectral camera. Thermal sensor features a 384x288 resolution, 30 fps and 35 mm lens with 10.5° angle of view. Visual sensor have HDTV 1080p video resolution, 30x optical zoom, focus recall and are extremly light sensitive. Integrated long-life silicone wiper for remote maintenance. The bispectral camera supports Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included). This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	\$	9,999.00	7331021050013	41.01	15.55

		 		-
High accuracy outdoor PTZ positioning bispectral camera with IR illuminators. Thermal sensor features a 384x288 resolution, 30 fps and 35 mm lens with 10.5° angle of view. Visual sensor have HDTV 1080p video resolution, 30x optical zoom, built-in IR pass filter for sharper images in mixed lighting conditions. IR range up to 500m. Integrated long-life silicone wiper for remote maintenance. The bispectral camera supports Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high- speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long- distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included). This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	\$ 11,599.00	7331021056732	51.59	15.55
High accuracy outdoor PTZ positioning Bispectral camera. Thermal sensor features a 640x480 resolution, 30 fps and 35-105 mm thermal zoom lens. Visual sensor have HDTV 1080p video resolution, 30x optical zoom, focus recall and are extremly light sensitive. Integrated long-life silicone wiper for remote maintenance. The bispectral camera supports Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included). This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	\$ 21,999.00	7331021050075	41.45	15.55

High accuracy outdoor PTZ positioning Bispectral camera. Thermal sensor features a 640x480 resolution, 30 fps and 35 mm lens with 17° angle of view. Visual sensor have HDTV 1080p video resolution, 30x optical zoom, focus recall and are extremly light sensitive. Integrated long-life silicone wiper for remote maintenance. The bispectral camera supports Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included). This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	\$ 12,999.00	7331021050051	41.01	15.55
High accuracy outdoor PTZ positioning bispectral camera with IR illuminators. Thermal sensor features a 640x480 resolution, 30 fps and 35 mm lens with 17° angle of view. Visual sensor have HDTV 1080p video resolution, 30x optical zoom, built-in IR pass filter for sharper images in mixed lighting conditions. IR range up to 500m. Integrated long-life silicone wiper for remote maintenance. The bispectral camera supports Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high- speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long- distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included). This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	\$ 14,599.00	7331021056770	51.59	15.55

High accuracy outdoor PTZ positioning	\$	23,599.00	7331021056794	51.59	15.55
bispectral camera with IR illuminators. Thermal	Ŧ	_0,000.00		01100	
sensor features a 640x480 resolution, 30 fps					
and and 35-105 mm thermal zoom lens. Visual					
sensor have HDTV 1080p video resolution, 30x					
optical zoom, built-in IR pass filter for sharper					
images in mixed lighting conditions. IR range					
up to 500m. Integrated long-life silicone wiper					
for remote maintenance. The bispectral camera					
supports Zipstream, ONVIF, H.264 and local					
storage. It includes Video motion detection and					
support for AXIS Camera Application Platform					
enabling installation of AXIS Perimeter					
Defender and third-party applications.					
Responsive absolute positioning with high-					
speed and ultra-smooth pan and tilt					
capabilities. Integrated SFP slot for long-					
distance fiber connection. IP66, NEMA 4X rated					
and UL listed. Ready for column-mount.					
Powered by 24 V AC/DC from external power					
supply (not included). This product is subject					
to export control regulations. You should					
always consult and comply with the regulations					
of the appropriate local export control					
authorities.					

AXIS P1280-E Thermal Network Camera is a	\$	869.00	7331021072855	1.43	5.91
modular thermal camera based on a small-	Ŧ				
sized main unit (AXIS P12 Thermal) and an					
outdoor ready thermal sensor unit with a 12 m/					
39.4ft cable. The camera provides 208x156					
resolution, a 2.2 mm lens with 63° horizontal					
FOV. It supports multiple streams in H.264 and					
Motion JPEG, Axis' Zipstream technology for					
lower bandwidth and storage needs, edge					
storage using microSD card and built-in					
analytics with support for AXIS Camera					
Application Platform, which enables the usage					
of a broad range of third-party applications. The					
flexible form factor allows it to be placed in					
locations with limited space and a wide range					
of mounting accessories enables wall, ceiling					
and recessed installations. The main unit is					
powered with PoE. The sensor unit has 12					
m/39.4 ft cable.					
The product contains U.Sorigin controlled					
technology/component, the US Export					
Administration Regulations (EAR) are always					
applicable to the product. You should comply					
at all times with all applicable national and					
international (re-) export control regulations.					

AXIS P1280-E Thermal Network Camera is a	\$ 869.00	733102105459	92 1.43	5.91
modular thermal camera based on a small-				
sized main unit (AXIS P12 Thermal) and an				
outdoor ready thermal sensor unit with a 12 m/				
39.4ft cable. The camera provides 208x156				
resolution, a 4 mm lens with 35.4° horizontal				
FOV. It supports multiple streams in H.264 and				
Motion JPEG, Axis' Zipstream technology for				
lower bandwidth and storage needs, edge storage using microSD card and built-in				
analytics with support for AXIS Camera				
Application Platform, which enables the usage				
of a broad range of third-party applications. The				
flexible form factor allows it to be placed in				
locations with limited space and a wide range				
of mounting accessories enables wall, ceiling				
and recessed installations. The main unit is				
powered with PoE. The sensor unit has 12				
m/39.4 ft cable.				
The product contains U.Sorigin controlled				
technology/component, the US Export				
Administration Regulations (EAR) are always				
applicable to the product. You should comply				
at all times with all applicable national and				
international (re-) export control regulations.				
AXIS P1290-E Thermal Network Camera is a	\$ 949.00	733102106128	36 2.24	7.87
modular thermal camera based on a small-	\$ 949.00	733102106128	36 2.24	7.87
modular thermal camera based on a small- sized main unit (AXIS P12 Thermal) and an	\$ 949.00	733102106128	36 2.24	7.87
modular thermal camera based on a small- sized main unit (AXIS P12 Thermal) and an outdoor ready thermal sensor unit with a 12 m/	\$ 949.00	733102106128	36 2.24	7.87
modular thermal camera based on a small- sized main unit (AXIS P12 Thermal) and an outdoor ready thermal sensor unit with a 12 m/ 39.4ft cable and dome casing.The camera	\$ 949.00	733102106128	36 2.24	7.87
modular thermal camera based on a small- sized main unit (AXIS P12 Thermal) and an outdoor ready thermal sensor unit with a 12 m/ 39.4ft cable and dome casing.The camera provides 208x156 resolution, a 4 mm lens with	\$ 949.00	733102106128	36 2.24	7.87
modular thermal camera based on a small- sized main unit (AXIS P12 Thermal) and an outdoor ready thermal sensor unit with a 12 m/ 39.4ft cable and dome casing.The camera provides 208x156 resolution, a 4 mm lens with 35.4° horizontal FOV. It supports multiple	\$ 949.00	733102106128	36 2.24	7.87
modular thermal camera based on a small- sized main unit (AXIS P12 Thermal) and an outdoor ready thermal sensor unit with a 12 m/ 39.4ft cable and dome casing.The camera provides 208x156 resolution, a 4 mm lens with 35.4° horizontal FOV. It supports multiple streams in H.264 and Motion JPEG, Axis'	\$ 949.00	733102106128	36 2.24	7.87
modular thermal camera based on a small- sized main unit (AXIS P12 Thermal) and an outdoor ready thermal sensor unit with a 12 m/ 39.4ft cable and dome casing.The camera provides 208x156 resolution, a 4 mm lens with 35.4° horizontal FOV. It supports multiple streams in H.264 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and	\$ 949.00	733102106128	36 2.24	7.87
modular thermal camera based on a small- sized main unit (AXIS P12 Thermal) and an outdoor ready thermal sensor unit with a 12 m/ 39.4ft cable and dome casing.The camera provides 208x156 resolution, a 4 mm lens with 35.4° horizontal FOV. It supports multiple streams in H.264 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, edge storage using microSD	\$ 949.00	733102106128	36 2.24	7.87
modular thermal camera based on a small- sized main unit (AXIS P12 Thermal) and an outdoor ready thermal sensor unit with a 12 m/ 39.4ft cable and dome casing.The camera provides 208x156 resolution, a 4 mm lens with 35.4° horizontal FOV. It supports multiple streams in H.264 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, edge storage using microSD card and built-in analytics with support for	\$ 949.00	733102106128	36 2.24	7.87
modular thermal camera based on a small- sized main unit (AXIS P12 Thermal) and an outdoor ready thermal sensor unit with a 12 m/ 39.4ft cable and dome casing.The camera provides 208x156 resolution, a 4 mm lens with 35.4° horizontal FOV. It supports multiple streams in H.264 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, edge storage using microSD card and built-in analytics with support for AXIS Camera Application Platform, which	\$ 949.00	733102106128	36 2.24	7.87
modular thermal camera based on a small- sized main unit (AXIS P12 Thermal) and an outdoor ready thermal sensor unit with a 12 m/ 39.4ft cable and dome casing.The camera provides 208x156 resolution, a 4 mm lens with 35.4° horizontal FOV. It supports multiple streams in H.264 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, edge storage using microSD card and built-in analytics with support for AXIS Camera Application Platform, which enables the usage of a broad range of third-	\$ 949.00	733102106128	36 2.24	7.87
modular thermal camera based on a small- sized main unit (AXIS P12 Thermal) and an outdoor ready thermal sensor unit with a 12 m/ 39.4ft cable and dome casing.The camera provides 208x156 resolution, a 4 mm lens with 35.4° horizontal FOV. It supports multiple streams in H.264 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, edge storage using microSD card and built-in analytics with support for AXIS Camera Application Platform, which enables the usage of a broad range of third- party applications. The main unit is powered	\$ 949.00	733102106128	36 2.24	7.87
modular thermal camera based on a small- sized main unit (AXIS P12 Thermal) and an outdoor ready thermal sensor unit with a 12 m/ 39.4ft cable and dome casing.The camera provides 208x156 resolution, a 4 mm lens with 35.4° horizontal FOV. It supports multiple streams in H.264 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, edge storage using microSD card and built-in analytics with support for AXIS Camera Application Platform, which enables the usage of a broad range of third-	\$ 949.00	733102106128	36 2.24	7.87
modular thermal camera based on a small- sized main unit (AXIS P12 Thermal) and an outdoor ready thermal sensor unit with a 12 m/ 39.4ft cable and dome casing.The camera provides 208x156 resolution, a 4 mm lens with 35.4° horizontal FOV. It supports multiple streams in H.264 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, edge storage using microSD card and built-in analytics with support for AXIS Camera Application Platform, which enables the usage of a broad range of third- party applications. The main unit is powered with PoE. The sensor unit has 12 m/39.4 ft	\$ 949.00	733102106128	36 2.24	7.87
modular thermal camera based on a small- sized main unit (AXIS P12 Thermal) and an outdoor ready thermal sensor unit with a 12 m/ 39.4ft cable and dome casing.The camera provides 208x156 resolution, a 4 mm lens with 35.4° horizontal FOV. It supports multiple streams in H.264 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, edge storage using microSD card and built-in analytics with support for AXIS Camera Application Platform, which enables the usage of a broad range of third- party applications. The main unit is powered with PoE. The sensor unit has 12 m/39.4 ft cable.	\$ 949.00	733102106128	36 2.24	7.87
modular thermal camera based on a small- sized main unit (AXIS P12 Thermal) and an outdoor ready thermal sensor unit with a 12 m/ 39.4ft cable and dome casing.The camera provides 208x156 resolution, a 4 mm lens with 35.4° horizontal FOV. It supports multiple streams in H.264 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, edge storage using microSD card and built-in analytics with support for AXIS Camera Application Platform, which enables the usage of a broad range of third- party applications. The main unit is powered with PoE. The sensor unit has 12 m/39.4 ft	\$ 949.00	733102106128	36 2.24	7.87
 modular thermal camera based on a small-sized main unit (AXIS P12 Thermal) and an outdoor ready thermal sensor unit with a 12 m/39.4ft cable and dome casing.The camera provides 208x156 resolution, a 4 mm lens with 35.4° horizontal FOV. It supports multiple streams in H.264 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, edge storage using microSD card and built-in analytics with support for AXIS Camera Application Platform, which enables the usage of a broad range of third-party applications. The main unit is powered with PoE. The sensor unit has 12 m/39.4 ft cable. The product contains U.Sorigin controlled 	\$ 949.00	733102106128	36 2.24	7.87
 modular thermal camera based on a small-sized main unit (AXIS P12 Thermal) and an outdoor ready thermal sensor unit with a 12 m/39.4ft cable and dome casing.The camera provides 208x156 resolution, a 4 mm lens with 35.4° horizontal FOV. It supports multiple streams in H.264 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, edge storage using microSD card and built-in analytics with support for AXIS Camera Application Platform, which enables the usage of a broad range of third-party applications. The main unit is powered with PoE. The sensor unit has 12 m/39.4 ft cable. The product contains U.Sorigin controlled technology/component, the US Export 	\$ 949.00	733102106128	36 2.24	7.87
 modular thermal camera based on a small-sized main unit (AXIS P12 Thermal) and an outdoor ready thermal sensor unit with a 12 m/39.4ft cable and dome casing.The camera provides 208x156 resolution, a 4 mm lens with 35.4° horizontal FOV. It supports multiple streams in H.264 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, edge storage using microSD card and built-in analytics with support for AXIS Camera Application Platform, which enables the usage of a broad range of third-party applications. The main unit is powered with PoE. The sensor unit has 12 m/39.4 ft cable. The product contains U.Sorigin controlled technology/component, the US Export Administration Regulations (EAR) are always 	\$ 949.00	733102106128	36 2.24	7.87
 modular thermal camera based on a small-sized main unit (AXIS P12 Thermal) and an outdoor ready thermal sensor unit with a 12 m/39.4ft cable and dome casing.The camera provides 208x156 resolution, a 4 mm lens with 35.4° horizontal FOV. It supports multiple streams in H.264 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, edge storage using microSD card and built-in analytics with support for AXIS Camera Application Platform, which enables the usage of a broad range of third-party applications. The main unit is powered with PoE. The sensor unit has 12 m/39.4 ft cable. The product contains U.Sorigin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply 	\$ 949.00	733102106128	36 2.24	7.87
modular thermal camera based on a small- sized main unit (AXIS P12 Thermal) and an outdoor ready thermal sensor unit with a 12 m/ 39.4ft cable and dome casing.The camera provides 208x156 resolution, a 4 mm lens with 35.4° horizontal FOV. It supports multiple streams in H.264 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, edge storage using microSD card and built-in analytics with support for AXIS Camera Application Platform, which enables the usage of a broad range of third- party applications. The main unit is powered with PoE. The sensor unit has 12 m/39.4 ft cable. The product contains U.Sorigin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and	\$ 949.00	733102106128	36 2.24	7.87
modular thermal camera based on a small- sized main unit (AXIS P12 Thermal) and an outdoor ready thermal sensor unit with a 12 m/ 39.4ft cable and dome casing.The camera provides 208x156 resolution, a 4 mm lens with 35.4° horizontal FOV. It supports multiple streams in H.264 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, edge storage using microSD card and built-in analytics with support for AXIS Camera Application Platform, which enables the usage of a broad range of third- party applications. The main unit is powered with PoE. The sensor unit has 12 m/39.4 ft cable. The product contains U.Sorigin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and	\$ 949.00	733102106128	36 2.24	7.87
modular thermal camera based on a small- sized main unit (AXIS P12 Thermal) and an outdoor ready thermal sensor unit with a 12 m/ 39.4ft cable and dome casing.The camera provides 208x156 resolution, a 4 mm lens with 35.4° horizontal FOV. It supports multiple streams in H.264 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, edge storage using microSD card and built-in analytics with support for AXIS Camera Application Platform, which enables the usage of a broad range of third- party applications. The main unit is powered with PoE. The sensor unit has 12 m/39.4 ft cable. The product contains U.Sorigin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and	\$ 949.00	733102106128	36 2.24	7.87
 modular thermal camera based on a small-sized main unit (AXIS P12 Thermal) and an outdoor ready thermal sensor unit with a 12 m/ 39.4ft cable and dome casing.The camera provides 208x156 resolution, a 4 mm lens with 35.4° horizontal FOV. It supports multiple streams in H.264 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, edge storage using microSD card and built-in analytics with support for AXIS Camera Application Platform, which enables the usage of a broad range of third-party applications. The main unit is powered with PoE. The sensor unit has 12 m/39.4 ft cable. The product contains U.Sorigin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and 	\$ 949.00	733102106128	36 2.24	7.87

Outdoor thermal network camera for wall and ceiling mount, 384x288 resolution, 30 fps, and 7 mm lens with 55° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed. This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs- se@axis.com for guidance on the license application procedure.	\$ 2,799.00	7331021048515	5.95	7.48
Outdoor thermal network camera for wall and ceiling mount, 384x288 resolution, 30 fps, and 7 mm lens with 55° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, H.265, audio in, two supervised I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender with Al-based functionality and other third-party applications. IK10, IP66, IP67, NEMA 4X rated, UL listed and compliant to a number of MIL-standards (among those is MIL-STD-810H / 521.4). This product is free from PVC, BFR and CFR. NETD <40 mK @25C, F1.0 This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	\$ 2,999.00	7331021073777	3.62	5.51

Outdoor thermal network camera for wall and ceiling mount, 384x288 resolution, 30 fps, and 13 mm lens with 28° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed. This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs- se@axis.com for guidance on the license application procedure.	\$ 2,799.00	7331021048522	6.22	7.48
Outdoor thermal network camera for wall and ceiling mount, 384x288 resolution, 30 fps, and 13 mm lens with 28° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, H.265, audio in, two supervised I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender with Al-based functionality and other third-party applications. IK10, IP66, IP67, NEMA 4X rated, UL listed and compliant to a number of MIL-standards (among those is MIL-STD-810H / 521.4). This product is free from PVC, BFR and CFR. NETD <40 mK @25C, F1.0 This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	\$ 2,999.00	7331021073791	3.62	5.51

Outdoor thermal network camera for wall and ceiling mount, 384x288 resolution, 30 fps, and 19 mm lens with 19.4° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed. This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs- se@axis.com for guidance on the license application procedure.	2,799.00	7331021051867	6.22	7.48
Outdoor thermal network camera for wall and ceiling mount, 384x288 resolution, 30 fps, and 19 mm lens with 19.4° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, H.265, audio in, two supervised I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender with Al-based functionality and other third-party applications. IK10, IP66, IP67, NEMA 4X rated, UL listed and compliant to a number of MIL-standards (among those is MIL-STD-810H / 521.4). This product is free from PVC, BFR and CFR. NETD <40 mK @25C, F1.0 This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	\$ 2,999.00	7331021073814	3.62	5.51

Outdoor thermal network camera for wall and ceiling mount, 384x288 resolution, 30 fps, and 35 mm lens with 10.7° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed. This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs- se@axis.com for guidance on the license application procedure.	\$ 3,799.00	7331021048539	6.19	7.48
Outdoor thermal network camera for wall and ceiling mount, 384x288 resolution, 30 fps, and 35 mm lens with 10.5° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, H.265, audio in, two supervised I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender with Al-based functionality and other third-party applications. IK10, IP66, IP67, NEMA 4X rated, UL listed and compliant to a number of MIL-standards (among those is MIL-STD-810H / 521.4). This product is free from PVC, BFR and CFR. NETD <40 mK @25C, F1.0 This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	\$ 4,099.00	7331021073838	3.62	5.51

Outdoor thermal network camera for wall and ceiling mount, 384x288 resolution, 30 fps, and 60 mm lens with 6.2° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed. This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs- se@axis.com for guidance on the license application procedure.	\$ 5,799.00	7331021048546	6.66	7.48
Outdoor Thermal Network Camera for positioning unit, 384x288 resolution, 30 fps, and 7 mm lens with 55° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs- se@axis.com for guidance on the license application procedure.	\$ 2,999.00	7331021058712	4.45	7.68

Outdoor Thermal Network Camera for	\$	2,999.00	7331021058637	4.43	7.68
positioning unit, 384x288 resolution, 30 fps,					
and 13 mm lens with 28° angle of view. It					
supports Electronic Image Stabilization,					
Zipstream, ONVIF, H.264, PoE and local					
storage. It includes Video motion detection,					
shock detection and support for AXIS Camera					
Application Platform enabling installation of					
AXIS Perimeter Defender and third-party					
applications. IP66, NEMA 4X rated and UL					
listed.					
This product is controlled for export under EU					
Regulation (EC) № 428/2009 and Export Control					
Classification Number (ECCN) 6A003.b.4.b					
applies. Licensing requirements may affect the					
lead time for delivery and/or general order					
status. If in doubt, please contact customs-					
se@axis.com for guidance on the license					
application procedure.					
Outdoor Thermal Network Camera for	\$	2,999.00	7331021058651	4.45	7.68
positioning unit, 384x288 resolution, 30 fps,	*	_,			
and 19 mm lens with 19.4° angle of view. It					
supports Electronic Image Stabilization,					
Zipstream, ONVIF, H.264, PoE and local					
storage. It includes Video motion detection,					
shock detection and support for AXIS Camera					
Application Platform enabling installation of					
AXIS Perimeter Defender and third-party					
applications. IP66, NEMA 4X rated and UL					
listed.					
This product is controlled for export under EU					
Regulation (EC) № 428/2009 and Export Control					
Classification Number (ECCN) 6A003.b.4.b					
applies. Licensing requirements may affect the					
lead time for delivery and/or general order					
status. If in doubt, please contact customs-					
se@axis.com for guidance on the license					
application procedure.					

	-		_			
"Outdoor Thermal Network Camera for	\$	4,099.00		7331021058675	4.50	7.68
positioning unit, 384x288 resolution, 30 fps,						
and 35 mm lens with 10.7° angle of view. It						
supports Electronic Image Stabilization,						
Zipstream, ONVIF, H.264, PoE and local						
storage. It includes Video motion detection,						
shock detection and support for AXIS Camera						
Application Platform enabling installation of						
AXIS Perimeter Defender and third-party						
applications. IP66, NEMA 4X rated and UL						
listed.						
This product is controlled for export under EU						
Regulation (EC) № 428/2009 and Export Control						
Classification Number (ECCN) 6A003.b.4.b						
applies. Licensing requirements may affect the						
lead time for delivery and/or general order						
status. If in doubt, please contact customs-						
se@axis.com for guidance on the license						
application procedure."						
	¢	F 700 00		7004004050000	4 07	7.00
Outdoor Thermal Network Camera for	\$	5,799.00		7331021058699	4.87	7.68
positioning unit, 384x288 resolution, 30 fps,	\$	5,799.00		7331021058699	4.87	7.68
positioning unit, 384x288 resolution, 30 fps, and 60 mm lens with 6.2° angle of view. It	\$	5,799.00		7331021058699	4.87	7.68
positioning unit, 384x288 resolution, 30 fps, and 60 mm lens with 6.2° angle of view. It supports Electronic Image Stabilization,	\$	5,799.00		7331021058699	4.87	7.68
positioning unit, 384x288 resolution, 30 fps, and 60 mm lens with 6.2° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local	\$	5,799.00		7331021058699	4.87	7.68
positioning unit, 384x288 resolution, 30 fps, and 60 mm lens with 6.2° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection,	\$	5,799.00		7331021058699	4.87	7.68
positioning unit, 384x288 resolution, 30 fps, and 60 mm lens with 6.2° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera	\$	5,799.00		7331021058699	4.87	7.68
positioning unit, 384x288 resolution, 30 fps, and 60 mm lens with 6.2° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of	\$	5,799.00		7331021058699	4.87	7.68
positioning unit, 384x288 resolution, 30 fps, and 60 mm lens with 6.2° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party	\$	5,799.00		7331021058699	4.87	7.68
positioning unit, 384x288 resolution, 30 fps, and 60 mm lens with 6.2° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL	\$	5,799.00		7331021058699	4.87	7.68
positioning unit, 384x288 resolution, 30 fps, and 60 mm lens with 6.2° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed.	\$	5,799.00		7331021058699	4.87	7.68
positioning unit, 384x288 resolution, 30 fps, and 60 mm lens with 6.2° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is controlled for export under EU		5,799.00		7331021058699	4.87	7.68
positioning unit, 384x288 resolution, 30 fps, and 60 mm lens with 6.2° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control		5,799.00		7331021058699	4.87	7.68
positioning unit, 384x288 resolution, 30 fps, and 60 mm lens with 6.2° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b		5,799.00		7331021058699	4.87	7.68
positioning unit, 384x288 resolution, 30 fps, and 60 mm lens with 6.2° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the		5,799.00		7331021058699	4.87	7.68
positioning unit, 384x288 resolution, 30 fps, and 60 mm lens with 6.2° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order		5,799.00		7331021058699	4.87	7.68
positioning unit, 384x288 resolution, 30 fps, and 60 mm lens with 6.2° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs-		5,799.00		7331021058699	4.87	7.68
positioning unit, 384x288 resolution, 30 fps, and 60 mm lens with 6.2° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs- se@axis.com for guidance on the license		5,799.00		7331021058699	4.87	7.68
positioning unit, 384x288 resolution, 30 fps, and 60 mm lens with 6.2° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs-		5,799.00		7331021058699	4.87	7.68
positioning unit, 384x288 resolution, 30 fps, and 60 mm lens with 6.2° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs- se@axis.com for guidance on the license		5,799.00		7331021058699	4.87	7.68
positioning unit, 384x288 resolution, 30 fps, and 60 mm lens with 6.2° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs- se@axis.com for guidance on the license		5,799.00		7331021058699	4.87	7.68

Outdoor thermal network camera for wall and ceiling mount, 640x480 resolution, 30 fps, and 10mm lens with 63° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed. This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs- se@axis.com for guidance on the license application procedure.	\$ 4,999.00	7331021052338	6.28	7.48
Outdoor thermal network camera for wall and ceiling mount, 640x480 resolution, 30 fps, and 10 mm lens with 63° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, H.265, audio in, two supervised I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender with Al-based functionality and other third-party applications. IK10, IP66, IP67, NEMA 4X rated, UL listed and compliant to a number of MIL-standards (among those is MIL-STD-810H / 521.4). This product is free from PVC, BFR and CFR. NETD <30 mK @25C, F1.0 This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	\$ 5,399.00	7331021073852	3.62	5.51

Outdoor thermal network camera for wall and ceiling mount, 640x480 resolution, 30 fps, and 19 mm lens with 32° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed. This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs- se@axis.com for guidance on the license application procedure.	\$ 4,999.00	7331021052352	6.17	7.48
Outdoor thermal network camera for wall and ceiling mount, 640x480 resolution, 30 fps, and 19 mm lens with 31° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, H.265, audio in, two supervised I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender with Al-based functionality and other third-party applications. IK10, IP66, IP67, NEMA 4X rated, UL listed and compliant to a number of MIL-standards (among those is MIL-STD-810H / 521.4). This product is free from PVC, BFR and CFR. NETD <30 mK @25C, F1.0 This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	\$ 5,399.00	7331021073876	3.62	5.51

Outdoor thermal network camera for wall and ceiling mount, 640x480 resolution, 30 fps, and 35 mm lens with 17° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, H.265, audio in, two supervised I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender with Al-based functionality and other third-party applications. IK10, IP66, IP67, NEMA 4X rated, UL listed and compliant to a number of MIL-standards (among those is MIL-STD-810H / 521.4). This product is free from PVC, BFR and CFR. NETD <30 mK @25C, F1.0 This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	\$ 6,499.00	7331021073890	3.62	5.51
Outdoor thermal network camera for wall and ceiling mount, 640x480 resolution, 30 fps, and 60 mm lens with 10° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed. This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs- se@axis.com for guidance on the license application procedure.	\$ 8,099.00	7331021052390	6.50	7.48

Outdoor Thermal Network Camera for positioning unit. 640x480 resolution, 30 fps,	\$	5,399.00	7331021058736	4.54	7.68
and 10mm lens with 63° angle of view. It					
supports Electronic Image Stabilization,					
Zipstream, ONVIF, H.264, PoE and local					
storage. It includes Video motion detection,					
shock detection and support for AXIS Camera					
Application Platform enabling installation of					
AXIS Perimeter Defender and third-party					
applications. IP66, NEMA 4X rated and UL					
listed.					
This product is controlled for export under EU					
Regulation (EC) № 428/2009 and Export Control					
Classification Number (ECCN) 6A003.b.4.b					
applies. Licensing requirements may affect the					
lead time for delivery and/or general order					
status. If in doubt, please contact customs-					
se@axis.com for guidance on the license					
application procedure.					
Q1942-E PT mount 19mm	\$	5,399.00	7331021058750	4.43	7.68
Outdoor Thermal Network Camera for					
positioning unit. 640x480 resolution, 30 fps,					
and 19mm lens with 32° angle of view. It					
supports Electronic Image Stabilization,					
Zipstream, ONVIF, H.264, PoE and local					
storage. It includes Video motion detection,					
shock detection and support for AXIS Camera					
Application Platform enabling installation of					
AXIS Perimeter Defender and third-party					
applications. IP66, NEMA 4X rated and UL					
listed. This product is controlled for export under EU					
Regulation (EC) № 428/2009 and Export Control					
Classification Number (ECCN) 6A003.b.4.b					
applies. Licensing requirements may affect the					
lead time for delivery and/or general order					
status. If in doubt, please contact customs-					
se@axis.com for guidance on the license					
application procedure.					

			 		r
Outdoor Thermal Network Camera for	\$	6,499.00	7331021058774	4.48	7.68
positioning unit. 640x480 resolution, 30 fps, and 35mm lens with 17° angle of view. It	l				
supports Electronic Image Stabilization,	l				
Zipstream, ONVIF, H.264, PoE and local					
storage. It includes Video motion detection,					
shock detection and support for AXIS Camera					
Application Platform enabling installation of					
AXIS Perimeter Defender and third-party					
applications. IP66, NEMA 4X rated and UL					
listed.					
This product is controlled for export under EU					
Regulation (EC) № 428/2009 and Export Control					
Classification Number (ECCN) 6A003.b.4.b					
applies. Licensing requirements may affect the					
lead time for delivery and/or general order					
status. If in doubt, please contact customs-					
se@axis.com for guidance on the license					
application procedure.					
Outdoor Thermal Network Camera for	^				
	~	8 099 00	7331021058798	4 87	7 68
	\$	8,099.00	7331021058798	4.87	7.68
positioning unit. 640x480 resolution, 30 fps,	Þ	8,099.00	7331021058798	4.87	7.68
positioning unit. 640x480 resolution, 30 fps, and 60mm lens with 10° angle of view. It	\$	8,099.00	7331021058798	4.87	7.68
positioning unit. 640x480 resolution, 30 fps, and 60mm lens with 10° angle of view. It supports Electronic Image Stabilization,	\$	8,099.00	7331021058798	4.87	7.68
positioning unit. 640x480 resolution, 30 fps, and 60mm lens with 10° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local	\$	8,099.00	7331021058798	4.87	7.68
positioning unit. 640x480 resolution, 30 fps, and 60mm lens with 10° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection,	\$	8,099.00	7331021058798	4.87	7.68
positioning unit. 640x480 resolution, 30 fps, and 60mm lens with 10° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera	\$	8,099.00	7331021058798	4.87	7.68
positioning unit. 640x480 resolution, 30 fps, and 60mm lens with 10° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of	\$	8,099.00	7331021058798	4.87	7.68
positioning unit. 640x480 resolution, 30 fps, and 60mm lens with 10° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera	\$	8,099.00	7331021058798	4.87	7.68
positioning unit. 640x480 resolution, 30 fps, and 60mm lens with 10° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party	\$	8,099.00	7331021058798	4.87	7.68
positioning unit. 640x480 resolution, 30 fps, and 60mm lens with 10° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL	\$	8,099.00	7331021058798	4.87	7.68
positioning unit. 640x480 resolution, 30 fps, and 60mm lens with 10° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed.		8,099.00	7331021058798	4.87	7.68
positioning unit. 640x480 resolution, 30 fps, and 60mm lens with 10° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is controlled for export under EU		8,099.00	7331021058798	4.87	7.68
positioning unit. 640x480 resolution, 30 fps, and 60mm lens with 10° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the		8,099.00	7331021058798	4.87	7.68
positioning unit. 640x480 resolution, 30 fps, and 60mm lens with 10° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order		8,099.00	7331021058798	4.87	7.68
positioning unit. 640x480 resolution, 30 fps, and 60mm lens with 10° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs-		8,099.00	7331021058798	4.87	7.68
positioning unit. 640x480 resolution, 30 fps, and 60mm lens with 10° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs- se@axis.com for guidance on the license		8,099.00	7331021058798	4.87	7.68
positioning unit. 640x480 resolution, 30 fps, and 60mm lens with 10° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs-		8,099.00	7331021058798	4.87	7.68
positioning unit. 640x480 resolution, 30 fps, and 60mm lens with 10° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs- se@axis.com for guidance on the license		8,099.00	7331021058798	4.87	7.68
positioning unit. 640x480 resolution, 30 fps, and 60mm lens with 10° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs- se@axis.com for guidance on the license		8,099.00	7331021058798	4.87	7.68

Q1961-TE is an ARTPEC 8 based thermometric camera that lets you remotely monitor temperatures from -40 °C to 350 °C (-40 °F to 660 °F). It supports up to 10 configurable polygonal detection areas allowing you to monitor for specific temperature levels and change rates. With early fire detection analytics (included), it's possible to set triggers and preventively act on early signs of fire. Robust and impact-resistant (IK10 and IP66/67), it includes built-in cybersecurity features to help safeguard your system. The product is halogen free and light weight. Edge-to-edge functionality lets you connect network speakers and other Axis network devices.	\$ 4,199.00	7331021074224	3.57	10.24
Q1961-TE is an ARTPEC 8 based thermometric camera that lets you remotely monitor temperatures from -40 °C to 350 °C (-40 °F to 660 °F). It supports up to 10 configurable polygonal detection areas allowing you to monitor for specific temperature levels and change rates. With early fire detection analytics (included), it's possible to set triggers and preventively act on early signs of fire. Robust and impact-resistant (IK10 and IP66/67), it includes built-in cybersecurity features to help safeguard your system. The product is halogen free and light weight. Edge-to-edge functionality lets you connect network speakers and other Axis network devices.	\$ 4,199.00	7331021074248	3.57	10.24

Q2101-TE is an ARTPEC 8 based thermometric	\$	4,899.00	7331021081079	9.92	8.27
camera that lets you remotely monitor	Í	.,			
temperatures from -40 °C to 350 °C (-40 °F to					
660 °F).					
Robust and impact-resistant (IK10 and IP66/67),					
it includes built-in cybersecurity features to					
help safeguard your system. The product is					
halogen free. Edge-to-edge functionality lets					
you connect network speakers and other Axis					
network devices.					
Q2101-TE can be PT-mounted (PT head sold					
separately). When PT-mounted, Q2101-TE					
supports the Axis unique feature of					
Thermometric guard tour, giving you the					
possibility to configure 10 polygonal detection					
areas per preset. With up to 256 presets you					
can monitor very large and complex scenes for					
specific temperature levels and temperature					
change rates.					
With early fire detection analytics (included),					
it's possible to set triggers and preventively act					
on early signs of fire. The Early Fire Detection					
ACAP comes with a smart filtering function					
eliminating many false alarms, commonly					
originating from work vehicles such as truck,					
excavators and cars.	ĺ				
	l				
	l				
	l				

Q2101-TE is an ARTPEC 8 based thermometric	\$	4,899.00	7331021081086	9.92	8.27
camera that lets you remotely monitor	Ť	.,			
temperatures from -40 °C to 350 °C (-40 °F to					
660 °F).					
Robust and impact-resistant (IK10 and IP66/67),					
it includes built-in cybersecurity features to					
help safeguard your system. The product is					
halogen free. Edge-to-edge functionality lets					
you connect network speakers and other Axis					
network devices.					
Q2101-TE can be PT-mounted (PT head sold					
separately). When PT-mounted, Q2101-TE					
supports the Axis unique feature of					
Thermometric guard tour, giving you the					
possibility to configure 10 polygonal detection					
areas per preset. With up to 256 presets you					
can monitor very large and complex scenes for					
specific temperature levels and temperature					
change rates.					
With early fire detection analytics (included),					
it's possible to set triggers and preventively act					
on early signs of fire. The Early Fire Detection					
ACAP comes with a smart filtering function					
eliminating many false alarms, commonly					
originating from work vehicles such as truck,					
excavators and cars.	l				
	l				
	l				
	l				
	l				

Q2101-TE is an ARTPEC 8 based thermometric	\$	4,899.00	7331021081130	9.92	8.27
camera that lets you remotely monitor	Ť	.,		0.02	0.27
temperatures from -40 °C to 350 °C (-40 °F to					
660 °F).					
Robust and impact-resistant (IK10 and IP66/67),					
it includes built-in cybersecurity features to					
help safeguard your system. The product is					
halogen free. Edge-to-edge functionality lets					
you connect network speakers and other Axis					
network devices.					
Q2101-TE can be PT-mounted (PT head sold					
separately). When PT-mounted, Q2101-TE					
supports the Axis unique feature of					
Thermometric guard tour, giving you the					
possibility to configure 10 polygonal detection					
areas per preset. With up to 256 presets you					
can monitor very large and complex scenes for					
specific temperature levels and temperature					
change rates.					
With early fire detection analytics (included),					
it's possible to set triggers and preventively act					
on early signs of fire. The Early Fire Detection					
ACAP comes with a smart filtering function					
eliminating many false alarms, commonly					
originating from work vehicles such as truck,					
excavators and cars.					
excavators and cars.					

Q2101-TE is an ARTPEC 8 based thermometric	\$	4,899.00	7331021081147	9.92	8.27
camera that lets you remotely monitor	Ť	,			
temperatures from -40 °C to 350 °C (-40 °F to					
660 °F).					
Robust and impact-resistant (IK10 and IP66/67),					
it includes built-in cybersecurity features to					
help safeguard your system. The product is					
halogen free. Edge-to-edge functionality lets					
you connect network speakers and other Axis					
network devices.					
Q2101-TE can be PT-mounted (PT head sold					
separately). When PT-mounted, Q2101-TE					
supports the Axis unique feature of					
Thermometric guard tour, giving you the					
possibility to configure 10 polygonal detection					
areas per preset. With up to 256 presets you					
can monitor very large and complex scenes for					
specific temperature levels and temperature					
change rates.					
With early fire detection analytics (included),					
it's possible to set triggers and preventively act					
on early signs of fire. The Early Fire Detection					
ACAP comes with a smart filtering function					
eliminating many false alarms, commonly					
originating from work vehicles such as truck,					
excavators and cars.	ĺ				
	l				
	l				
	l				

Q2101-TE is an ARTPEC 8 based thermometric	\$	4,899.00	7331021081352	9.92	8.27
camera that lets you remotely monitor	Ť	.,		0.02	·
temperatures from -40 °C to 350 °C (-40 °F to					
660 °F).					
Robust and impact-resistant (IK10 and IP66/67),					
it includes built-in cybersecurity features to					
help safeguard your system. The product is					
halogen free. Edge-to-edge functionality lets					
you connect network speakers and other Axis					
network devices.					
Q2101-TE can be PT-mounted (PT head sold					
separately). When PT-mounted, Q2101-TE					
supports the Axis unique feature of					
Thermometric guard tour, giving you the					
possibility to configure 10 polygonal detection					
areas per preset. With up to 256 presets you					
can monitor very large and complex scenes for					
specific temperature levels and temperature					
change rates.					
With early fire detection analytics (included),					
it's possible to set triggers and preventively act					
on early signs of fire. The Early Fire Detection					
ACAP comes with a smart filtering function					
eliminating many false alarms, commonly					
originating from work vehicles such as truck,					
excavators and cars.					

AXIS Q2901-E Temperature alarm camera for wall and colling mount, IP66-rato, 336x266 resolution, 315, and 35 magle of view. Six temperature alarm zones, isothermal palates and spottation and AXIS Camera Application PAC and using service alarge. Some alarge is a subsyst applicable to the product. Subsyst and decision and AXIS Camera Application The roduct contains U.S. origin controlled technology/component, the US Export Administration Regulations. \$ 5,699.00 7331021048171 6.04 7.48		-				
it's possible to set triggers and preventively act on early signs of fire. The Early Fire Detection ACAP comes with a smart filtering function eliminating many false alarms, commonly originating from work vehicles such as truck, excavators and cars.	temperatures from -40 °C to 350 °C (-40 °F to 660 °F). Robust and impact-resistant (IK10 and IP66/67), it includes built-in cybersecurity features to help safeguard your system. The product is halogen free. Edge-to-edge functionality lets you connect network speakers and other Axis network devices. Q2101-TE can be PT-mounted (PT head sold separately). When PT-mounted, Q2101-TE supports the Axis unique feature of Thermometric guard tour, giving you the possibility to configure 10 polygonal detection areas per preset. With up to 256 presets you can monitor very large and complex scenes for specific temperature levels and temperature change rates.	\$	4,899.00	7331021081369	9.92	8.27
on early signs of fire. The Early Fire Detection ACAP comes with a smart filtering function eliminating many false alarms, commonly originating from work vehicles such as truck, excavators and cars. AXIS Q2901-E Temperature alarm camera for wall and ceiling mount, IP66-rated, 336x256 resolution, 8.3 fps, and 35° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature. It supports ONVIF, H.264, audio, local storage, I/O, PoE, shock detection, AXIS Video Motion Detection 3.0, audio detection and AXIS Camera Application Platform. \$ 5,699.00 \$ 7331021048171 6.04 7.48 7.48 The product contains U.Sorigin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and A	-					
ACAP comes with a smart filtering function eliminating many false alarms, commonly originating from work vehicles such as truck, excavators and cars. AXIS Q2901-E Temperature alarm camera for wall and ceiling mount, IP66-rated, 336x256 resolution, 8.3 fps, and 35° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature. It supports ONVIF, H.264, audio, local storage, I/O, PoE, shock detection, AXIS Video Motion Detection 3.0, audio detection and AXIS Camera Application Platform. The product contains U.Sorigin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and 						
eliminating many false alarms, commonly originating from work vehicles such as truck, excavators and cars. AXIS Q2901-E Temperature alarm camera for wall and ceiling mount, IP66-rated, 336x256 resolution, 8.3 fps, and 35° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature. It supports ONVIF, H.264, audio, local storage, I/O, PoE, shock detection, AXIS Video Motion Detection 3.0, audio detection and AXIS Camera Application Platform. The product contains U.Sorigin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and						
originating from work vehicles such as truck, excavators and cars. AXIS Q2901-E Temperature alarm camera for wall and ceiling mount, IP66-rated, 336x256 resolution, 8.3 fps, and 35° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature. It supports ONVIF, H.264, audio, local storage, I/O, PoE, shock detection, AXIS Video Motion Detection 3.0, audio detection and AXIS Camera Application Platform. 7331021048171 6.04 7.48 7.48 The product contains U.Sorigin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and 7331021048171 6.04 7.48 	5					
AXIS Q2901-E Temperature alarm camera for wall and ceiling mount, IP66-rated, 336x256 resolution, 8.3 fps, and 35° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature. It supports ONVIF, H.264, audio, local storage, I/O, PoE, shock detection, AXIS Video Motion Detection 3.0, audio detection and AXIS Camera Application Platform. 7331021048171 6.04 7.48 The product contains U.Sorigin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and \$ 5,699.00 7331021048171 6.04 7.48						
wall and ceiling mount, IP66-rated, 336x256 resolution, 8.3 fps, and 35° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature. It supports ONVIF, H.264, audio, local storage, I/O, PoE, shock detection, AXIS Video Motion Detection 3.0, audio detection and AXIS Camera Application Platform. The product contains U.Sorigin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and	excavators and cars.					
wall and ceiling mount, IP66-rated, 336x256 resolution, 8.3 fps, and 35° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature. It supports ONVIF, H.264, audio, local storage, I/O, PoE, shock detection, AXIS Video Motion Detection 3.0, audio detection and AXIS Camera Application Platform. The product contains U.Sorigin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and						
resolution, 8.3 fps, and 35° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature. It supports ONVIF, H.264, audio, local storage, I/O, PoE, shock detection, AXIS Video Motion Detection 3.0, audio detection and AXIS Camera Application Platform. The product contains U.Sorigin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and	•	\$	5,699.00	7331021048171	6.04	7.48
temperature alarm zones, isothermal palettes and spot temperature. It supports ONVIF, H.264, audio, local storage, I/O, PoE, shock detection, AXIS Video Motion Detection 3.0, audio detection and AXIS Camera Application Platform. The product contains U.Sorigin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and	-					
and spot temperature. It supports ONVIF, H.264, audio, local storage, I/O, PoE, shock detection, AXIS Video Motion Detection 3.0, audio detection and AXIS Camera Application Platform. The product contains U.Sorigin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and						
detection, AXIS Video Motion Detection 3.0, audio detection and AXIS Camera Application Platform. The product contains U.Sorigin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and	-					
audio detection and AXIS Camera Application Platform. The product contains U.Sorigin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and	H.264, audio, local storage, I/O, PoE, shock					
Platform. The product contains U.Sorigin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and						
technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and	Platform.					
applicable to the product. You should comply at all times with all applicable national and	technology/component, the US Export					
at all times with all applicable national and						

AXIS Q2901-E PT Mount Temperature alarm camera ready for pan/tilt motor head, IP66- rated, 336x256 resolution, 8.3 fps, and 35° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature. It supports ONVIF, H.264, local storage, RS422/RS485, PoE, shock detection, AXIS Video Motion Detection 3.0, and AXIS Camera Application Platform. The product contains U.Sorigin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations.	\$ 5,699.00	7331021048188	4.48	7.68
AXIS Q2901-E Temperature alarm camera for wall and ceiling mount, IP66-rated, 336x256 resolution, 8.3 fps, and 17° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature. It supports ONVIF, H.264, audio, local storage, I/O, PoE, shock detection, AXIS Video Motion Detection 3.0, audio detection and AXIS Camera Application Platform. The product contains U.Sorigin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations.	\$ 5,699.00	7331021048195	6.04	7.48
AXIS Q2901-E PT Mount Temperature alarm camera ready for pan/tilt motor head, IP66- rated, 336x256 resolution, 8.3 fps, and 17° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature. It supports ONVIF, H.264, local storage, RS422/RS485, PoE, shock detection, AXIS Video Motion Detection 3.0, and AXIS Camera Application Platform. The product contains U.Sorigin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations.	\$ 5,699.00	7331021048201	4.48	7.68

AXIS FA1080-E 2.2M 8.3 FPS is a modular thermal sensor unit to be used together with AXIS FA54 Main Unit. The thermal sensor unit provides 208x156 resolution and includes a 2.2 mm lens with 63° horizontal FOV. The flexible form factor allows it to be placed in locations with limited space and can be used with a wide range of mounting accessories to enable wall, ceiling and recessed installations. The sensor unit is outdoor-ready and has 12 m/39.4 ft cable.	\$ 699.00	7331021072435	1.28	5.91
This product contains U.Sorigin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations.				
AXIS FA1080-E 4MM 8.3 FPS is a modular thermal sensor unit to be used together with AXIS FA54 Main Unit. The thermal sensor unit provides 208x156 resolution and includes a 4 mm lens with 35.4° horizontal FOV. The flexible form factor allows it to be placed in locations with limited space and can be used with a wide range of mounting accessories to enable wall, ceiling and recessed installations. The sensor unit is outdoor-ready and has 12 m/39.4 ft cable. This product contains U.Sorigin controlled technology/component, the US Export	\$ 699.00	7331021067042	1.26	5.91
Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations.				

	 			-
AXIS FA4090-E 4MM 8.3 FPS is a modular thermal sensor unit to be used together with AXIS FA54 Main Unit. The thermal sensor unit provides 208x156 resolution and includes a 4 mm lens with 35.4° horizontal FOV. The dome housing makes it easy to install and direct the sensor unit to cover your area of interets. The sensor unit is outdoor-ready and has 12 m/39.4 ft cable. This product contains U.Sorigin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and	\$ 749.00	7331021067059	2.03	8.94
international (re-) export control regulations. Indoor plenum recessed ceiling mount kit for VB-S30D/S31D/S80xD mini-domes.	\$ 129.00	4549292071566	3.09	8.27
Comprising of fire resistant in-ceiling cage and cover - Titanium White				
Indoor surface mount ceiling cover (Silver) for VB-H47/M46 PTZ's Comprising of a metal mounting plate and "skirt" cover - Silver	\$ 69.00	4960999686721	0.60	7.64
Indoor surface mount ceiling cover (Black) for VB-H47/M46 PTZ's. Comprising of a metal mounting plate and "skirt" cover - Black	\$ 69.00	4960999688794	0.60	7.64
Indoor recessed ceiling mount kit for VB- H43(/B) & VB-M42(/B) PTZ's. Comprising of in-ceiling cage and Clear Dome - Silver	\$ 229.00	4960999914558	3.09	9.45
Indoor recessed ceiling mount kit for VB- H43(/B) & VB-M42(/B) PTZ's. Comprising of in-ceiling cage and Smoked Dome - Silver	\$ 229.00	4960999914565	3.09	9.45
Indoor surface mount wall/ceiling spacer for VB S30D/S31D/S80xD mini-domes.	\$ 59.00	4549292022582	0.50	5.51
EAC certified encapsulated AC Adapter (12V DC Power supply) with US plug	\$ 119.00		7.01	0.00
Indoor Pendant mounting Cap for VB- S30VE/S800VE mini-domes	\$ 69.00	4549292079685	1.15	6.30
Conduit Box for VB-S30VE/S800VE mini-domes	\$ 109.00	4549292078848	0.66	5.75
Indoor surface mount ceiling cover (White) for VB-H47/M46 PTZ's Comprising of a metal mounting plate and "skirt" cover - White.	\$ 69.00	4549292213157	1.10	2.99

 Indoor compact fixed box network camera. 3.5x optical zoom, auto focus, digital night mode and built-in Omni-directional microphone. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast, ADSR - Areaspecific Data Size Reduction technology. 7 inbuilt video & audio intelligent analytic functions and linked events. Powered by PoE (Power supply not included). Audio output port and inbuilt microphone, Input/Output ports and micro SD/SDHC/SDHX Card slot for Edge storage. Available in Titanium White. 	\$ 469.00	4549292078381	0.40	6.85
Indoor compact network camera with lite-PTZ operation. 3.5x optical zoom, auto focus, and digital night mode. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast. 6 in-built video & audio intelligent analytic functions. Powered by PoE (Power supply not included). Two way audio, Input/Output ports and micro SD/SDHC/SDHX Card slot for Edge storage. Available in Silver.	\$ 647.66	4549292107296	1.34	6.85
Indoor compact network camera with lite-PT operation. Fixed 2.7mm wide angle lens (95.0° AOV 16:9) and digital night mode. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast. 6 in-built video & audio intelligent analytic functions. Powered by PoE (Power supply not included). Two way audio, Input/Output ports and micro SD/SDHC/SDHX Card slot for Edge storage. Available in Silver.	\$ 618.72	4549292106978	0.60	6.85
Indoor compact PTZ minidome network camera with 3.5x optical zoom, auto focus and digital night mode. Multiple H.264, H.265 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast. Built-in video & audio intelligent analytic functions. Powered by PoE (Power supply not included). Two way audio, Input/Output ports and micro SD/SDHC/SDXC Card slot for Edge storage. Available in White.	\$ 799.00	4549292202151	1.32	6.85

Indoor PTZ network camera with 348° rotation and large aperture lens ideal for low light applications. 5x optical zoom, auto focus, day/night switching and Clear IR Mode. Multiple H.264 and Motion JPEG streams; max 1.3MP 720p resolution at 30fps. Smart Shade Control - dynamic contrast, ADSR - Area-specific Data Size Reduction technology and Motion- Adaptive Noise Reduction. 9 in-built video & audio intelligent analytic functions and linked events. Powered by PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports and SD/SDHC/SDHX Card slot for Edge storage. Only available in Black.	\$ 1,824.77	4549292065756	3.64	7.09
BLACK VERSION Indoor PTZ network camera with 340° rotation. 20x optical zoom, auto focus, and day/night switching. Multiple H.264 and Motion JPEG streams; max 1.3MP 720p resolution at 30fps. Smart Shade Control - dynamic contrast. 6 in-built video & audio intelligent analytic functions. Powered by PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports and SD/SDHC/SDHX Card slot for Edge storage. Available in Black (/B).	\$ 1,625.01	4549292106725	2.51	9.02
SILVER VERSION Indoor PTZ network camera with 340° rotation. 20x optical zoom, auto focus, and day/night switching. Multiple H.264 and Motion JPEG streams; max 1.3MP 720p resolution at 30fps. Smart Shade Control - dynamic contrast. 6 in-built video & audio intelligent analytic functions. Powered by PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports and SD/SDHC/SDHX Card slot for Edge storage. Available in Silver.	\$ 1,625.01	4549292107289	2.51	9.02
BLACK VERSION Indoor PTZ network camera with 340° rotation. 20x optical zoom, auto focus, and day/night switching. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast. 6 in-built video & audio intelligent analytic functions. Powered by PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports and SD/SDHC/SDHX Card slot for Edge storage. Available in Black (/B).	\$ 2,539.17	4549292106916	2.51	9.02

SILVER VERSION Indoor PTZ network camera with 340° rotation. 20x optical zoom, auto focus, and day/night switching. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast. 6 in-built video & audio intelligent analytic functions. Powered by PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports and SD/SDHC/SDHX Card slot for Edge storage. Available in Silver.	\$ 2,539.17	4549292106886	2.51	9.02
WHITE VERSION Indoor PTZ network camera with 340° rotation. 20x optical zoom, auto focus, and day/night switching. Multiple H.264, H.265 and Motion JPEG streams; max Full HD 1080p resolution at 60fps. Smart Shade Control - dynamic contrast. Built-in video & audio intelligent analytic functions. Powered by PoE and 12V DC. Power supply not included. Two way audio, Input/Output ports and SD/SDHC/SDXC Memory Card slot for Edge storage. Available in Titanium white and Black.	\$ 2,769.00	4549292202090	3.31	7.36
BLACK VERSION Indoor PTZ network camera with 340° rotation. 20x optical zoom, auto focus, and day/night switching. Multiple H.264, H.265 and Motion JPEG streams; max Full HD 1080p resolution at 60fps. Smart Shade Control - dynamic contrast. Built-in video & audio intelligent analytic functions. Powered by PoE and 12V DC. Power supply not included. Two way audio, Input/Output ports and SD/SDHC/SDXC Memory Card slot for Edge storage. Available in Titanium white and Black.	\$ 2,769.00	4549292202106	3.31	7.36
 WHITE VERSION Indoor PTZ network camera with 340° rotation. 20x optical zoom, auto focus, and day/night switching. Multiple H.264, H.265 and Motion JPEG streams; max 1.3MP 720p resolution at 60fps. Smart Shade Control - dynamic contrast. Built-in video & audio intelligent analytic functions. Powered by PoE and 12V DC. Power supply not included. Two way audio, Input/Output ports and SD/SDHC/SDXC Memory Card slot for Edge storage. Available in Titanium white and Black. 	\$ 1,989.00	4549292202137	3.31	7.36

BLACK VERSION Indoor PTZ network camera with 340° rotation. 20x optical zoom, auto	\$ 1,989.00	4549292202144	3.31	7.36
focus, and day/night switching. Multiple H.264, H.265 and Motion JPEG streams; max 1.3MP 720p resolution at 60fps. Smart Shade Control -				
dynamic contrast. Built-in video & audio intelligent analytic functions. Powered by PoE				
and 12V DC. Power supply not included. Two way audio, Input/Output ports and SD/SDHC/SDXC Memory Card slot for Edge				
storage. Available in Titanium white and Black.				
1 channel network video decoder. Decodes H.264 and MPEG-4 Part 2 in max. D1 resolution at 30/25 (NTSC/PAL) fps and 720p in Motion JPEG. Decodes AAC, G726 and G.711 audio streams in mono. Supports video source	\$ 539.00	7331021026179	1.72	7.48
sequencing. Power over Ethernet enabled. Includes power supply.				
AXIS P7701 BARE BOARD in 20-pack. Cannot be sold separately as single packs. No power supplies.	\$ 10,779.00	7331021032194	8.47	14.17
Bare bone 1 channel video decoder (PCB without any mechanics). Decodes H.264 and MPEG-4 Part 2 in max. D1 resolution at 30/25 (NTSC/PAL) fps and 720p in Motion JPEG. Decodes AAC, G726 and G.711 audio streams in mono. Supports video source sequencing. Power over Ethernet enabled. No power supply.	\$ 539.00	7331021032187	0.77	6.50
Network Video Decoder for easy display of video from IP cameras on big screens. With the 1080p HDMI output, Ethernet input and compact size, it is very easy to setup and use. It can display the video both as sequence or multimode and with the integrated VAPIX support, it automatically finds Axis cameras on the network for plug-and-play configuration.	\$ 399.00	7331021061965	0.75	7.87
4K Video Decoder with 8 streams in multiview, local playback of media, DC or PoE powered, with audio through audio in or HDMI plus many more features	\$ 649.00	7331021075696	1.50	6.89
Four channel video encoder supporting PAL/NTSC cameras. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Frame rate 25/30 fps in all resolutions. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Serial port for RS422/485 communication. Power over Ethernet or 12-20V DC input. MicroSD/MicroSDHC memory card slot for optional local video storage.	\$ 319.00	7331021066397	1.82	8.27

Sixteen-channel video encoder. Dual streaming H.264 and Motion JPEG on all channels. Max D1 resolution at 30/25 (NTSC/PAL) fps on all streams. Video motion detection. Active tampering alarm. Two-way audio with audio detection. SFP slot for optional fiber connection and/or network redundancy. Unit includes 4 x micro SD card slots for edge storage. PTZ support. Unit has 4 x ARTPEC chips and 4 x IP addresses. Includes power supply.	\$ 1,299.00	7331021004214	4.59	22.44
Four channel video encoder supporting PAL/NTSC and HD analog cameras. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Frame rate 25/30 fps in all resolutions up to 1080p. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, active tampering alarm and audio detection. I/O for alarm/event handling, serial port for RS422/485 communication. Power over Ethernet or 12-20V DC input. MicroSD/MicroSDHC memory card slot for optional local video storage. Two-way audio with analog or digital microphone.	\$ 429.00	7331021066403	1.84	8.27
Sixteen-channel video encoder support PAL/NTSC cameras. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Frame rate 25/30 fps in all resolutions. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. 4 serial ports for RS422/485 communication. Power over Ethernet or 12-20V DC input. MicroSD/MicroSDHC memory card slot for optional local video storage. PTZ cameras control over the serial ports.	\$ 1,079.00	7331021074835	7.10	11.22
 16-channel video encoder. Max 4K resolution at 15fp on 4x channels. The video encoder has 4x ARTPEC-7 chips and 4x IP addresses H.264, H265 and Motion JPEG on all channels. Video motion detection. Active tampering alarm. Two-way audio with audio detection. SFP slot for optional fiber connection and/or network redundancy. Unit includes 4x micro SD card slots for edge storage. PTZ support. Signed firmware and secure boot to enhance cybersecurity. It includes a power supply. 	\$ 1,399.00	7331021074910	6.75	11.42
1U 19" rack unit with three expansions slots, compatible with all Axis Blade video servers. Universal built-in power supply. One 10/100/1000Base-T output.	\$ 429.00	7331021018693	10.23	16.54

AXIS S3008 Mk II 2 TB Recorder is a compact recorder with 8 PoE ports and a gigabit uplink. With its powerful PoE switch, eight PoE class 3 devices can be connected to the recorder and the recordings are done on the internal hard drive. It is compatible with AXIS Companion, AXIS Camera Station, their mobile app, and a wide range of Axis devices. To increase reliability and security, the product supports disk encryption, contains a 2 TB surveillance class hard drive and includes 5-year limited hardware warranty. This product is not a System Controller for Body Worn Solutions.	\$ 699.00	7331021083417	4.52	7.87
AXIS S3008 Mk II 4 TB Recorder is a compact recorder with 8 PoE ports and a gigabit uplink. With its powerful PoE switch, eight PoE class 3 devices can be connected to the recorder and the recordings are done on the internal hard drive. It is compatible with AXIS Companion, AXIS Camera Station, their mobile app, and a wide range of Axis devices. To increase reliability and security, the product supports disk encryption, contains a 4 TB surveillance class hard drive and includes 5-year limited hardware warranty. This product is not a System Controller for Body Worn Solutions.	\$ 899.00	7331021083493	4.85	7.87
AXIS S3008 Mk II 8 TB Recorder is a compact recorder with 8 PoE ports and a gigabit uplink. With its powerful PoE switch, eight PoE class 3 devices can be connected to the recorder and the recordings are done on the internal hard drive. It is compatible with AXIS Companion, AXIS Camera Station, their mobile app, and a wide range of Axis devices. To increase reliability and security, the product supports disk encryption, contains a 8 TB surveillance class hard drive and includes 5-year limited hardware warranty. This product is not a System Controller for Body Worn Solutions.	\$ 1,199.00	7331021083578	5.07	7.87

AXIS S3016 8 TB Recorder is a 1U rack recorder	\$ 2,399.00	7331021078994	24.56	20.07
with an integrated PoE switch and high power budget for up to 16 devices and a maximum of PoE class 4 per port. It provides reliable recording thanks to the four surveillance-grade hard drives and different RAID levels. This high- performance recorder offers a gigabit switch for connecting network devices and a 2.5 gigabit uplink for video recordings in ultra-high definition and includes a 5-year warranty. The recorder can be used in single-site, multi-site systems and for expanding storage and network in existing systems. It is compatible with both AXIS Companion as well as AXIS Camera Station video management software and mobile app. AXIS S3016 can be installed in server racks with a post-to-post distance between 376mm (14.8in) and 499mm (19.6in). For deeper server racks, AXIS TS3901 Rail Extensions can be used when the post-to-post distance is between 499mm (19.6in) and 689mm (27.1in).	2,000.00	1551021070994	24.00	20.67
AXIS S3016 16 TB Recorder is a 1U rack recorder with an integrated PoE switch and high power budget for up to 16 devices and a maximum of PoE class 4 per port. It provides reliable recording thanks to the four surveillance-grade hard drives and different RAID levels. This high-performance recorder offers a gigabit switch for connecting network devices and a 2.5 gigabit uplink for video recordings in ultra-high definition and includes a 5-year warranty. The recorder can be used in single-site, multi-site systems and for expanding storage and network in existing systems. It is compatible with both AXIS Companion as well as AXIS Camera Station video management software and mobile app. AXIS S3016 can be installed in server racks with a post-to-post distance between 376mm (14.8in) and 499mm (19.6in). For deeper server racks, AXIS TS3901 Rail Extensions can be used when the post-to-post distance is between 499mm (19.6in) and 689mm (27.1in).	\$ 2,899.00	7331021078543	24.91	20.67

	+			-	·
AXIS S3016 32 TB Recorder is a 1U rack recorder with an integrated PoE switch and high power budget for up to 16 devices and a maximum of PoE class 4 per port. It provides reliable recording thanks to the four surveillance-grade hard drives and different RAID levels. This high-performance recorder offers a gigabit switch for connecting network devices and a 2.5 gigabit uplink for video recordings in ultra-high definition and includes a 5-year warranty. The recorder can be used in single-site, multi-site systems and for expanding storage and network in existing systems. It is compatible with both AXIS Companion as well as AXIS Camera Station video management software and mobile app. AXIS S3016 can be installed in server racks with a post-to-post distance between 376mm (14.8in) and 499mm (19.6in). For deeper server racks, AXIS TS3901 Rail Extensions can be used when the post-to-post distance is between 499mm (19.6in) and 689mm (27.1in).	\$	3,999.00	7331021078611	27.34	20.67
AXIS S3008 2 TB Recorder is a compact recorder with 8 PoE ports and a gigabit uplink. Up to 8 devices can be connected to the recorder and recording is done on the internal hard drive. It is compatible with AXIS Companion VMS, AXIS Camera Station and a wide range of Axis devices. To increase reliability and security, the product supports disk encryption, contains a 2 TB surveillance class hard drive and includes 5-year limited hardware warranty. Calculate your PoE requirements with AXIS Site Designer. This product is not a System Controller for Body Worn Solutions.	\$	649.00	7331021072640	4.43	4.72
AXIS S3008 4 TB Recorder is a compact recorder with 8 PoE ports and a gigabit uplink. Up to 8 devices can be connected to the recorder and recording is done on the internal hard drive. It is compatible with AXIS Companion VMS, AXIS Camera Station and a wide range of Axis devices. To increase reliability and security, the product supports disk encryption, contains a 4 TB surveillance class hard drive and includes 5-year limited hardware warranty. Calculate your PoE requirements with AXIS Site Designer. This product is not a System Controller for Body Worn Solutions.	\$	849.00	7331021071414	4.43	4.72

AXIS S3008 8 TB Recorder is a compact recorder with 8 PoE ports and a gigabit uplink.	\$	1,149.00	7331021073289	4.67	4.72
Up to 8 devices can be connected to the recorder and recording is done on the internal bard drive. It is compatible with AVIS					
hard drive. It is compatible with AXIS Companion VMS, AXIS Camera Station and a wide range of Axis devices. To increase					
reliability and security, the product supports					
disk encryption, contains a 8 TB surveillance class hard drive and includes 5-year limited					
hardware warranty. Calculate your PoE requirements with AXIS Site Designer. This					
product is not a System Controller for Body Worn Solutions.					
AXIS Camera Station S2108 Appliance is an	\$	1,899.00	7331021077089	9.96	11.61
affordable, all-in-one appliance including a VMS client/server, storage, and an integrated					
PoE switch - all validated to meet the demands for reliable, basic surveillance up to 1080p. It is					
preloaded with AXIS Camera Station VMS and					
all other necessary software such as Windows 10 IoT Enterprise and AXIS Recorder Toolbox. It					
includes a Trusted Platform module (TPM 2.0),					
2 TB storage, Core licenses for 8 devices and 5- year limited hardware warranty.					
year minteu natuware warranty.					
AXIS Camera Station S2208 Appliance is an	\$	2,499.00	7331021065208	19.18	18.50
eight channel compact desktop Client/Server including an integrated managed PoE switch					
validated and tested with Axis products.					
Preloaded with AXIS Camera Station software with preconfigured AXIS Camera Station					
settings and all other necessary software e.g.					
Windows 10 IoT. Includes 4 TB storage, Core licenses for 8 devices, 5-year limited hardware					
warranty on the appliance and hard drive.					
Supports up to 4k ultra HD.					
AXIS Camera Station S2212 Appliance is a	\$	3,199.00	7331021065291	19.18	18.50
twelve channel compact desktop Client/Server	Ψ	3,139.00	1331021003231	13.10	10.30
including an integrated managed PoE switch validated and tested with Axis products.					
Preloaded with AXIS Camera Station software					
with preconfigured AXIS Camera Station settings and all other necessary software e.g.					
Windows 10 IoT. Includes 6 TB storage, Core					
licenses for 12 devices, 5-year limited hardware					
warranty on the appliance and hard drive. Supports up to 4k ultra HD.					

AXIS Camera Station S2216 Appliance is a sixteen channel Client/Server for rack- mounting including an integrated managed PoE switch validated and tested with Axis products. Preloaded with AXIS Camera Station software with preconfigured AXIS Camera Station settings and all other necessary software e.g. Windows 10 IoT. Includes 8 TB storage, Core licenses for 16 devices, 5-year limited hardware warranty on the appliance and hard drives. Supports up to 4k ultra HD.	\$ 4,099.00	7331021065383	33.03	22.64
AXIS Camera Station S2224 Appliance is a twenty four channel Client/Server for rack- mounting including an integrated managed PoE switch validated and tested with Axis products. Preloaded with AXIS Camera Station software with preconfigured AXIS Camera Station settings and all other necessary software e.g. Windows 10 IoT. Includes 12 TB storage, Core licenses for 24 devices, 5-year limited hardware warranty on the appliance and hard drives. Supports up to 4k ultra HD.	\$ 4,799.00	7331021065475	34.04	22.64
AXIS Camera Station S1216 Tower is an out-of- the-box ready workstation tested and validated with Axis products for reliable surveillance up to 4K video streams. Preconfigured and preloaded with AXIS Camera Station video management software including licenses for 16 channels plus all necessary system software. Includes 5-year limited hardware warranty, on- site hardware replacement service and keep your hard drive.	\$ 3,599.00	7331021082298	22.93	17.52

AXIS Camera Station S1216 Rack 8 TB is an out- of-the-box ready recording server validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1216 Rack 8 TB is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 16 devices plus all necessary software. The AXIS Recorder Toolbox and its installation wizard will ensure every customer installation is quick and trouble- free. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide range of video surveillance devices. With an enterprise-grade hard drive, operating system stored on solid-state drive (SSD) and built-in operating system recovery, AXIS S1216 Rack 8 TB provides high-performance and reliability for your system. Furthermore, the FIPS 140-2 compliant TPM guarantees a high security level by encryption of the data at rest. Includes 5-year limited hardware warranty, on- site hardware replacement and keep your hard drive services.	\$ 4,299.00	7331021086111	40.79	24.02
AXIS Camera Station S1232 Rack 16 TB is an out-of-the-box ready recording server validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1232 Rack 16 TB is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 32 devices plus all necessary software. The AXIS Recorder Toolbox and its installation wizard will ensure every customer installation is quick and trouble- free. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide range of video surveillance devices. With redundant enterprise-grade hard drives and power supplies, operating system stored on solid-state drive (SSD) and built-in operating system recovery, AXIS S1232 Rack 16 TB provides high-performance and reliability for your system. Furthermore, the FIPS 140-2 compliant TPM guarantees a high security level by encryption of the data at rest. Includes 5- year limited hardware warranty, on-site hardware replacement and keep your hard drive services.	\$ 6,999.00	7331021080478	47.18	24.80

AXIS Camera Station S1232 Rack 32 TB is an out-of-the-box ready recording server validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1232 Rack 32 TB is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 32 devices plus all necessary software. The AXIS Recorder Toolbox and its installation wizard will ensure every customer installation is quick and trouble- free. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide range of video surveillance devices. With redundant enterprise-grade hard drives and power supplies, operating system stored on solid-state drive (SSD) and built-in operating system recovery, AXIS S1232 Rack 32 TB provides high-performance and reliability for your system. Furthermore, the FIPS 140-2 compliant TPM guarantees a high security level by encryption of the data at rest. Includes 5- year limited hardware warranty, on-site hardware replacement and keep your hard drive services.	\$ 8,299.00	7331021080485	46.30	24.02
AXIS Camera Station S1232 Tower 32 TB is an out-of-the-box ready recording server and client validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1232 Tower 32 TB is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 32 devices plus all necessary software. The AXIS Recorder Toolbox and its installation wizard will ensure every customer installation is quick and trouble-free. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide range of video surveillance devices. With redundant enterprise- grade hard drives and power supplies, operating system stored on solid-state drive (SSD) and built-in operating system recovery, AXIS S1232 Tower 32 TB provides high- performance and reliability for your system. Furthermore, the FIPS 140-2 compliant TPM guarantees a high security level by encryption of the data at rest. Includes 5-year limited hardware warranty, on-site hardware replacement and keep your hard drive services.	\$ 8,499.00	7331021079120	60.41	22.44

AXIS Camera Station S1264 Rack 24 TB is an	\$ 11,299.00	7331021079229	73.63	26.97
out-of-the-box ready recording server validated				
for reliable ultra high-definition recording. For				
quick and easy installation, AXIS S1264 Rack 24				
TB is preconfigured and preloaded with AXIS				
Camera Station video management software				
including licenses for 64 devices plus all				
necessary software. The AXIS Recorder				
Toolbox and its installation wizard will ensure				
every customer installation is quick and trouble-				
free. The system configuration can easily be				
imported from AXIS Site Designer, and AXIS				
Camera Station lets users take full advantage of				
Axis wide range of video surveillance devices.				
With redundant enterprise-grade hard drives				
and power supplies, operating system stored				
on solid-state drive (SSD) and built-in operating				
system recovery, AXIS S1264 Rack 24 TB				
provides high-performance and reliability for				
your system. Furthermore, the FIPS 140-2				
compliant TPM guarantees a high security level				
by encryption of the data at rest. Includes 5-				
year limited hardware warranty, on-site				
hardware replacement and keep your hard drive				
services.				
AXIS Camera Station S1264 Rack 64 TB is an	\$ 14,499.00	7331021079236	78.04	27.17
out-of-the-box ready recording server validated				
for reliable ultra high-definition recording. For				
quick and easy installation, AXIS S1264 Rack 64				
TB is preconfigured and preloaded with AXIS				
Camera Station video management software				
including licenses for 64 devices plus all				
necessary software. The AXIS Recorder				
Toolbox and its installation wizard will ensure				
every customer installation is quick and trouble-				
free. The system configuration can easily be				
imported from AXIS Site Designer, and AXIS				
Camera Station lets users take full advantage of				
Axis wide range of video surveillance devices.				
With redundant enterprise-grade hard drives				
and power supplies, operating system stored				
on solid-state drive (SSD) and built-in operating				
system recovery, AXIS S1264 Rack 64 TB				
provides high-performance and reliability for				
your system. Furthermore, the FIPS 140-2				
compliant TPM guarantees a high security level				
by encryption of the data at rest. Includes 5-				
year limited hardware warranty, on-site				
year limited hardware warranty, on-site hardware replacement and keep your hard drive				
year limited hardware warranty, on-site				
year limited hardware warranty, on-site hardware replacement and keep your hard drive				
year limited hardware warranty, on-site hardware replacement and keep your hard drive				
year limited hardware warranty, on-site hardware replacement and keep your hard drive				
year limited hardware warranty, on-site hardware replacement and keep your hard drive				

AXIS Camera Station S1264 Rack 144 TB is an	\$ 19,999.00	7331021079243	83.78	27.17
out-of-the-box ready recording server validated				
for reliable ultra high-definition recording. For				
quick and easy installation, AXIS S1264 Rack				
144 TB is preconfigured and preloaded with				
AXIS Camera Station video management				
software including licenses for 64 devices plus				
all necessary software. The AXIS Recorder				
Toolbox and its installation wizard will ensure				
every customer installation is quick and trouble				
free. The system configuration can easily be				
imported from AXIS Site Designer, and AXIS				
Camera Station lets users take full advantage of				
Axis wide range of video surveillance devices.				
With redundant enterprise-grade hard drives				
and power supplies, operating system stored				
on solid-state drive (SSD) and built-in operating				
system recovery, AXIS S1264 Rack 144 TB				
provides high-performance and reliability for				
your system. Furthermore, the FIPS 140-2				
compliant TPM guarantees a high security level				
by encryption of the data at rest. Includes 5-				
year limited hardware warranty, on-site				
hardware replacement and keep your hard drive				
services.				
AXIS Camera Station S1296 Rack 96 TB is an	\$ 20,499.00	7331021079250	85.10	26.97
out-of-the-box ready recording server validated	\$ 20,499.00	7331021079250	85.10	26.97
out-of-the-box ready recording server validated for reliable ultra high-definition recording. For	\$ 20,499.00	7331021079250	85.10	26.97
out-of-the-box ready recording server validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1296 Rack 96	\$ 20,499.00	7331021079250	85.10	26.97
out-of-the-box ready recording server validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1296 Rack 96 TB is preconfigured and preloaded with AXIS	\$ 20,499.00	7331021079250	85.10	26.97
out-of-the-box ready recording server validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1296 Rack 96 TB is preconfigured and preloaded with AXIS Camera Station video management software	\$ 20,499.00	7331021079250	85.10	26.97
out-of-the-box ready recording server validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1296 Rack 96 TB is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 96 devices plus all	\$ 20,499.00	7331021079250	85.10	26.97
out-of-the-box ready recording server validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1296 Rack 96 TB is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 96 devices plus all necessary software. The AXIS Recorder	\$ 20,499.00	7331021079250	85.10	26.97
out-of-the-box ready recording server validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1296 Rack 96 TB is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 96 devices plus all necessary software. The AXIS Recorder Toolbox and its installation wizard will ensure	\$ 20,499.00	7331021079250	85.10	26.97
out-of-the-box ready recording server validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1296 Rack 96 TB is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 96 devices plus all necessary software. The AXIS Recorder Toolbox and its installation wizard will ensure every customer installation is quick and trouble-	\$ 20,499.00	7331021079250	85.10	26.97
out-of-the-box ready recording server validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1296 Rack 96 TB is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 96 devices plus all necessary software. The AXIS Recorder Toolbox and its installation wizard will ensure every customer installation is quick and trouble- free. The system configuration can easily be	\$ 20,499.00	7331021079250	85.10	26.97
out-of-the-box ready recording server validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1296 Rack 96 TB is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 96 devices plus all necessary software. The AXIS Recorder Toolbox and its installation wizard will ensure every customer installation is quick and trouble- free. The system configuration can easily be imported from AXIS Site Designer, and AXIS	\$ 20,499.00	7331021079250	85.10	26.97
out-of-the-box ready recording server validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1296 Rack 96 TB is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 96 devices plus all necessary software. The AXIS Recorder Toolbox and its installation wizard will ensure every customer installation is quick and trouble- free. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of	\$ 20,499.00	7331021079250	85.10	26.97
out-of-the-box ready recording server validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1296 Rack 96 TB is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 96 devices plus all necessary software. The AXIS Recorder Toolbox and its installation wizard will ensure every customer installation is quick and trouble- free. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide range of video surveillance devices.	\$ 20,499.00	7331021079250	85.10	26.97
out-of-the-box ready recording server validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1296 Rack 96 TB is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 96 devices plus all necessary software. The AXIS Recorder Toolbox and its installation wizard will ensure every customer installation is quick and trouble- free. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide range of video surveillance devices. With redundant enterprise-grade hard drives	\$ 20,499.00	7331021079250	85.10	26.97
out-of-the-box ready recording server validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1296 Rack 96 TB is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 96 devices plus all necessary software. The AXIS Recorder Toolbox and its installation wizard will ensure every customer installation is quick and trouble- free. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide range of video surveillance devices. With redundant enterprise-grade hard drives and power supplies, operating system stored	\$ 20,499.00	7331021079250	85.10	26.97
out-of-the-box ready recording server validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1296 Rack 96 TB is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 96 devices plus all necessary software. The AXIS Recorder Toolbox and its installation wizard will ensure every customer installation is quick and trouble- free. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide range of video surveillance devices. With redundant enterprise-grade hard drives and power supplies, operating system stored on solid-state drive (SSD) and built-in operating	\$ 20,499.00	7331021079250	85.10	26.97
out-of-the-box ready recording server validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1296 Rack 96 TB is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 96 devices plus all necessary software. The AXIS Recorder Toolbox and its installation wizard will ensure every customer installation is quick and trouble- free. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide range of video surveillance devices. With redundant enterprise-grade hard drives and power supplies, operating system stored on solid-state drive (SSD) and built-in operating system recovery, AXIS S1296 Rack 96 TB	\$ 20,499.00	7331021079250	85.10	26.97
out-of-the-box ready recording server validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1296 Rack 96 TB is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 96 devices plus all necessary software. The AXIS Recorder Toolbox and its installation wizard will ensure every customer installation is quick and trouble- free. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide range of video surveillance devices. With redundant enterprise-grade hard drives and power supplies, operating system stored on solid-state drive (SSD) and built-in operating system recovery, AXIS S1296 Rack 96 TB provides high-performance and reliability for	\$ 20,499.00	7331021079250	85.10	26.97
out-of-the-box ready recording server validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1296 Rack 96 TB is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 96 devices plus all necessary software. The AXIS Recorder Toolbox and its installation wizard will ensure every customer installation is quick and trouble- free. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide range of video surveillance devices. With redundant enterprise-grade hard drives and power supplies, operating system stored on solid-state drive (SSD) and built-in operating system recovery, AXIS S1296 Rack 96 TB provides high-performance and reliability for your system. Furthermore, the FIPS 140-2	\$ 20,499.00	7331021079250	85.10	26.97
out-of-the-box ready recording server validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1296 Rack 96 TB is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 96 devices plus all necessary software. The AXIS Recorder Toolbox and its installation wizard will ensure every customer installation is quick and trouble- free. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide range of video surveillance devices. With redundant enterprise-grade hard drives and power supplies, operating system stored on solid-state drive (SSD) and built-in operating system recovery, AXIS S1296 Rack 96 TB provides high-performance and reliability for your system. Furthermore, the FIPS 140-2 compliant TPM guarantees a high security level	\$ 20,499.00	7331021079250	85.10	26.97
out-of-the-box ready recording server validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1296 Rack 96 TB is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 96 devices plus all necessary software. The AXIS Recorder Toolbox and its installation wizard will ensure every customer installation is quick and trouble- free. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide range of video surveillance devices. With redundant enterprise-grade hard drives and power supplies, operating system stored on solid-state drive (SSD) and built-in operating system recovery, AXIS S1296 Rack 96 TB provides high-performance and reliability for your system. Furthermore, the FIPS 140-2 compliant TPM guarantees a high security level by encryption of the data at rest. Includes 5-	\$ 20,499.00	7331021079250	85.10	26.97
out-of-the-box ready recording server validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1296 Rack 96 TB is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 96 devices plus all necessary software. The AXIS Recorder Toolbox and its installation wizard will ensure every customer installation is quick and trouble- free. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide range of video surveillance devices. With redundant enterprise-grade hard drives and power supplies, operating system stored on solid-state drive (SSD) and built-in operating system recovery, AXIS S1296 Rack 96 TB provides high-performance and reliability for your system. Furthermore, the FIPS 140-2 compliant TPM guarantees a high security level by encryption of the data at rest. Includes 5- year limited hardware warranty, on-site	\$ 20,499.00	7331021079250	85.10	26.97
out-of-the-box ready recording server validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1296 Rack 96 TB is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 96 devices plus all necessary software. The AXIS Recorder Toolbox and its installation wizard will ensure every customer installation is quick and trouble- free. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide range of video surveillance devices. With redundant enterprise-grade hard drives and power supplies, operating system stored on solid-state drive (SSD) and built-in operating system recovery, AXIS S1296 Rack 96 TB provides high-performance and reliability for your system. Furthermore, the FIPS 140-2 compliant TPM guarantees a high security level by encryption of the data at rest. Includes 5- year limited hardware warranty, on-site hardware replacement and keep your hard drives	\$ 20,499.00	7331021079250	85.10	26.97
out-of-the-box ready recording server validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1296 Rack 96 TB is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 96 devices plus all necessary software. The AXIS Recorder Toolbox and its installation wizard will ensure every customer installation is quick and trouble- free. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide range of video surveillance devices. With redundant enterprise-grade hard drives and power supplies, operating system stored on solid-state drive (SSD) and built-in operating system recovery, AXIS S1296 Rack 96 TB provides high-performance and reliability for your system. Furthermore, the FIPS 140-2 compliant TPM guarantees a high security level by encryption of the data at rest. Includes 5- year limited hardware warranty, on-site	\$ 20,499.00	7331021079250	85.10	26.97
out-of-the-box ready recording server validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1296 Rack 96 TB is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 96 devices plus all necessary software. The AXIS Recorder Toolbox and its installation wizard will ensure every customer installation is quick and trouble- free. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide range of video surveillance devices. With redundant enterprise-grade hard drives and power supplies, operating system stored on solid-state drive (SSD) and built-in operating system recovery, AXIS S1296 Rack 96 TB provides high-performance and reliability for your system. Furthermore, the FIPS 140-2 compliant TPM guarantees a high security level by encryption of the data at rest. Includes 5- year limited hardware warranty, on-site hardware replacement and keep your hard drive	\$ 20,499.00	7331021079250	85.10	26.97
out-of-the-box ready recording server validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1296 Rack 96 TB is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 96 devices plus all necessary software. The AXIS Recorder Toolbox and its installation wizard will ensure every customer installation is quick and trouble- free. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide range of video surveillance devices. With redundant enterprise-grade hard drives and power supplies, operating system stored on solid-state drive (SSD) and built-in operating system recovery, AXIS S1296 Rack 96 TB provides high-performance and reliability for your system. Furthermore, the FIPS 140-2 compliant TPM guarantees a high security level by encryption of the data at rest. Includes 5- year limited hardware warranty, on-site hardware replacement and keep your hard drive	\$ 20,499.00	7331021079250	85.10	26.97
out-of-the-box ready recording server validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1296 Rack 96 TB is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 96 devices plus all necessary software. The AXIS Recorder Toolbox and its installation wizard will ensure every customer installation is quick and trouble- free. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide range of video surveillance devices. With redundant enterprise-grade hard drives and power supplies, operating system stored on solid-state drive (SSD) and built-in operating system recovery, AXIS S1296 Rack 96 TB provides high-performance and reliability for your system. Furthermore, the FIPS 140-2 compliant TPM guarantees a high security level by encryption of the data at rest. Includes 5- year limited hardware warranty, on-site hardware replacement and keep your hard drive	\$ 20,499.00	7331021079250	85.10	26.97
out-of-the-box ready recording server validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1296 Rack 96 TB is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 96 devices plus all necessary software. The AXIS Recorder Toolbox and its installation wizard will ensure every customer installation is quick and trouble- free. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide range of video surveillance devices. With redundant enterprise-grade hard drives and power supplies, operating system stored on solid-state drive (SSD) and built-in operating system recovery, AXIS S1296 Rack 96 TB provides high-performance and reliability for your system. Furthermore, the FIPS 140-2 compliant TPM guarantees a high security level by encryption of the data at rest. Includes 5- year limited hardware warranty, on-site hardware replacement and keep your hard drives	\$ 20,499.00	7331021079250	85.10	26.97

AXIS Camera Station S1296 Rack 192 TB is an out-of-the-box ready recording server validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1296 Rack 192 TB is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 96 devices plus all necessary software. The AXIS Recorder Toolbox and its installation wizard will ensure every customer installation is quick and trouble- free. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide range of video surveillance devices. With redundant enterprise-grade hard drives and power supplies, operating system stored on solid-state drive (SSD) and built-in operating system recovery, AXIS S1296 Rack 192 TB provides high-performance and reliability for your system. Furthermore, the FIPS 140-2 compliant TPM guarantees a high security level by encryption of the data at rest. Includes 5- year limited hardware warranty, on-site hardware replacement and keep your hard drive services.	27,499.00	7331021079267	83.78	27.17
AXIS Camera Station S9301 Workstation is a complement to Axis recorders to enable quick set-up of a workstation meeting the demands for a reliable surveillance. The workstation is preloaded with an AXIS Camera Station client and preconfigured to minimize installation time. AXIS S9301 has validated hardware and software components for optimal surveillance experience and includes 5-year limited hardware warranty.	\$ 1,599.00	7331021081796	6.08	10.24
AXIS Camera Station S9302 Workstation is a complement to Axis recorders to enable quick set-up of a workstation meeting the demands for a reliable Ultra HD surveillance. The workstation is preloaded with an AXIS Camera Station client and preconfigured to minimize installation time. AXIS S9302 has validated hardware and software components for optimal surveillance experience and includes 5-year limited hardware warranty.	\$ 2,699.00	7331021082281	14.99	19.69

 AXIS Camera Station S1116 Recorder is an out- of-the-box ready workstation tested and validated with Axis products for reliable surveillance up to 4K video streams. Preconfigured and preloaded with AXIS Camera Station video management software including licenses for 16 channels plus all necessary system software. Includes 5-year limited hardware warranty, on-site hardware replacement service, keep your hard drive and international keyboard and mouse. 	\$ 3,599.00	7331021067011	20.64	19.88
 AXIS Camera Station S1116 Recorder is an out- of-the-box ready rack-server tested and validated with Axis products for reliable surveillance up to 4K video streams. Preconfigured and preloaded with AXIS Camera Station video management software including licenses for 16 channels plus all necessary system software.Includes 5-year limited hardware warranty, on-site hardware replacement service and keep your hard drive. 	\$ 4,099.00	7331021065970	33.51	23.35
 AXIS Camera Station S1132 Recorder is an out- of-the-box ready rack server tested and validated with Axis products for reliable surveillance up to 4K video streams. Preconfigured and preloaded with AXIS Camera Station video management software including licenses for 32 channels plus all necessary system software. Includes 5-year limited hardware warranty, on-site hardware replacement service and keep your hard drive. 	\$ 5,999.00	7331021065857	43.21	23.82

AXIS Camera Station S1132 Tower 32 TB is an out-of-the-box ready server and client validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1132 Tower 32 TB is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 32 channels plus all necessary software. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide range of video surveillance devices. With redundant enterprise-grade hard disks and power supplies, operating system stored on solid- state drive (SSD) and built-in operating system recovery, AXIS S1132 Tower 32 TB provides high-performance and reliability for your system. Includes 5-year limited hardware warranty, on-site hardware replacement service and keep your hard drive.	\$ 8,199.00	7331021072091	59.75	23.62
AXIS Camera Station S1132 Tower 64 TB is an out-of-the-box ready server and client validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1132 Tower 64 TB is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 32 channels plus all necessary software. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide range of video surveillance devices. With redundant enterprise-grade hard disks and power supplies, operating system stored on solid- state drive (SSD) and built-in operating system recovery, AXIS S1132 Tower 64 TB provides high-performance and reliability for your system. Includes 5-year limited hardware warranty, on-site hardware replacement service and keep your hard drive.	\$ 10,199.00	7331021072107	66.80	23.62
AXIS Camera Station S1148 Recorder is an out- of-the-box ready rack server tested and validated with Axis products for reliable surveillance up to 4K video streams. Preconfigured and preloaded with AXIS Camera Station video management software including licenses for 48 channels plus all necessary system software. Includes 5-year limited hardware warranty, on-site hardware replacement service and keep your hard drive.	\$ 9,199.00	7331021065864	66.58	23.82

AXIS Camera Station S1148 Recorder is an out- of-the-box ready rack server tested and validated with Axis products for reliable surveillance up to 4K video streams. Preconfigured and preloaded with AXIS Camera Station video management software including licenses for 48 channels plus all necessary system software. Includes 5-year limited hardware warranty, on-site hardware replacement service and keep your hard drive.	\$ 18,399.00	7331021065888	63.49	23.82
AXIS Camera Station S9101 Mk II Desktop Terminal is a complement to Axis recorders to enable quick set-up of a surveillance workstation. The terminal is preloaded with an AXIS Camera Station client and preconfigured to minimize installation time. AXIS S9101 Mk II has validated hardware and software components for optimal surveillance experience and includes 5-year limited hardware warranty.	\$ 1,399.00	7331021070233	5.56	10.83
AXIS Camera Station S9201 Mk II Desktop Terminal is an all-in-one desktop terminal with a 22-inch monitor for system overview, to be used with Axis recorders. The terminal is preloaded with AXIS Camera Station software and all other necessary software. Includes 3- year hardware warranty, on-site hardware replacement service and international keyboard and mouse.	\$ 1,899.00	7331021067035	27.43	20.47
 Payment for Axis Professional Services. Only valid when applied to a signed Statement of Work (SOW) with an assigned Professional Services ID (PSID). Note: Order must contain PSID to be valid. Axis Professional Services tokens are non-cancellable, non-changeable, and non-returnable. 	\$ 1,000.00		0.00	0.00

Note: One licence key new order live	¢	0.00	<u> </u>		Í
Note: One license key per order line	\$	9.00			
AXIS Device Manager Extend (ADM Extend)					
offers a unified, user-friendly interface that					
helps you proactively manage your customers'					
Axis devices and sites from anywhere.					
Featuring an intuitive dashboard and remote					
site access, you can manage thousands of Axis					
devices and it allows you to perform firmware					
updates and other tasks at scale. Additionally,					
it's an invaluable tool for troubleshooting and					
proactive planning, helping you save time and					
money. ADM Extend delivers product warranty,					
end-of-life, and hardening compliance					
information. For instance, you'll receive					
recommendations for firmware upgrades to					
help mitigate your customers device					
vulnerabilities.					
vullerabilities.					
ADM Extend is based on annual subscription					
The renewal date is time-based (12 months)					
One license per device					
One license key per order line					
Activation through a license key redeemed by					
SI in AXIS License Manager.					
Free 90-day trial period					
noo oo aay ahar ponoa					
End Customers and Authorized partners =					
world market price/device and year					
MRP (NSI), Gold and Silver Solution Partners =					
requires no license for full access					
Oingle unit a linguage for AVIO During (¢	000.00		0.00	0.00
Single unit e-license for AXIS Perimeter	\$	299.00		0.00	0.00
Defender, a scalable and flexible video					
analytics application for perimeter surveillance					
and protection. Visit www.axis.com for					
supported products and application download.					
Ten (10) unit e-license for AXIS Perimeter	\$	2,989.00		0.00	0.00
Defender, a scalable and flexible video	¥	_,		0.00	0.00
analytics application for perimeter surveillance					
and protection. Visit www.axis.com for					
supported products and application download.					

Single unit license for AXIS Perimeter Defender PTZ Autotracking. Together with a fixed camera running AXIS Perimeter defender this enable automatic control of a PTZ camera to zoom in on and follow detected objects. Please check the supported countries (https://www.axis.com/files/pods/axis_perimete r_defender_ptz_autotracking_supported_count ries.pdf) before ordering. Visit www.axis.com for supported products and application download.	6	299.00		0.00	0.00
A license document that grants installation of AXIS AVC/H.264 decoder onto 50 separate computers. Applicable for all AXIS products that supports H.264 but does not have support for audio.	\$	45.00	7331021024212	0.11	12.60
A license document that grants installation of AXIS AVC/H.264 and ACC decoder onto 50 separate computers. Applicable for all AXIS products that supports H.264 that also have support for audio.	\$	55.00	7331021024229	0.13	12.60
AXIS People Counter is a cost-efficient and scalable video analytics application for people counting. This business-improving application, installed on a network camera, enables accurate monitoring and analysis of customer flows. It is ideal for e.g. quick evaluation of marketing efforts, improving staff and store planning, or evaluating conversion rate if combined with point-of-sale data. In addition to people counting, this version can also estimate occupancy levels and detect and notify if more than one person enters within a set time interval or if people move in the wrong direction. One license key per unit.	\$	249.00		0.00	0.00

Please check the supported countries (https://www.axis.com/products/axis-license- plate-verifier/where-to-buy) before ordering. Single unit e-license for AXIS License Plate Verifier. AXIS License Plate Verifier is an AXIS Camera Application Platform software that can be used in selected Axis cameras. It supports	\$ 539.00		0.00	0.00
license plate recognition for slow-speed traffic and vehicle access control. This edge-based analytics allows for smart license plate reading at speeds of up to 70 km/h (45 mph). Visit www.axis.com for supported products and application download. One license key per unit.				
AXIS Store Reporter is a web-based tool that is used for graphical representation and reporting of statistical data gathered from Axis retail analytics applications. It is sold on a per channel basis as e-license. A license is valid for 12 months. After this period the license will have to be renewed. AXIS Store Reporter is based on Axis annual subscription. One license key per order line.	\$ 139.00	-		
ONLY REQUIRED FOR CANON NETWORK CAMERAS (excluding VB-H47W, VB-H47B, VB- M46W, VB-M46B & VB-S32D). License to view the video encoded to H.264. Each network camera contains one license for the 1st PC, additional user license is required for the 2nd PC onwards.	\$ 5.00			
ONLY REQUIRED FOR CANON NETWORK CAMERAS VB-H47W, VB-H47B, VB-M46W, VB- M46B & VB-S32D. License to view the video encoded to H.264/H.265. Each network camera contains one license for the 1st PC, additional user license is required for the 2nd PC onwards.	\$ 5.00			

One (1) AXIS Camera Station version 5.0 and up, Core Device license. Applicable for AXIS devices. AXIS Camera Station is a monitoring and recording system mid-size installations optimized to take full advantage of Axis leading network cameras and video encoders. It combines easy setup with an intuitive user interface for efficient operation, quick investigation and high definition identification. Delivered as eLicense key, One license key per order. Note: eLicenses are non-cancellable, non-changeable and non-returnable.	\$ 85	9.00	0.00	0.00
 One (1) Universal Device license applicable for AXIS Camera Station version 5.0 and up. AXIS Camera Station is a monitoring and recording system mid-size installations optimized to take full advantage of Axis leading network cameras and video encoders. It combines easy setup with an intuitive user interface for efficient operation, quick investigation and high definition identification. Delivered as eLicense key, One license key per order. Note: eLicenses are non-cancellable, non-changeable and non-returnable. 	\$ 159	2.00 	0.00	0.00
One (1) upgrade license applicable for existing licenses of AXIS Camera Station, version 1,2,3, 4. Each existing license in combination with this upgrade license enables upgrade to a AXIS Camera Station version 5 Universal Device license. Delivered as eLicense key, One license key per order. Note: eLicenses are non-cancellable, non-changeable and non-returnable.	\$ 85	9.00	0.00	0.00
This license is primarily used for replacing AXIS devices with ONVIF devices. One (1) Upgrade license and one AXIS Camera Station version 5 Core Device license upgrades to one (1) Universal Device license. Delivered as eLicense key, One license key per order. Note: eLicenses are non-cancellable, non-changeable and non-returnable.	\$ 89	9.00	0.00	0.00

Replacement front cover for AXIS D2050-VE.	\$	79.00	7331021063204	1.54	8.46
Includes anti-loss screws and sealing gaskets.					
AVIS TM2912 Domo Clear 4 Book, are standard	\$	69.00	7331021079571	0.19	2.95
AXIS TM3813 Dome Clear 4-Pack, are standard clear domes with anti-scratch hard coating.	Þ	69.00	/3310210/95/1	0.19	2.95
Compatible with AXIS M4317/M4318-PLVE. 4-					
pack.					
Original white top cover with clear dome for	\$	269.00	7331021006775	1.21	6.30
AXIS M3006, 5pcs.					
Original white top cover with clear dome for	\$	269.00	7331021006782	1.10	6.10
AXIS M3007, 5pcs.					
Standard clear domes for AXIS M3024, 5 pcs	\$	269.00	7331021045347	2.87	11.02
Standard clear domes for AXIS M3025, M3026. 5	\$	249.00	7331021045323	0.71	7.48
	^	100.00			
Standard clear dome for AXIS M3044-V/45-V/46-	\$	109.00	7331021056176	0.32	3.15
V, 5 pcs Standard clear dome with anti-scratch hard	\$	69.00	7331021065048	0.33	4.72
coating. Rubber gaskets included. Compatible	φ	09.00	7331021005040	0.33	4.72
with AXISM3057/58-PLVE. 4-piece bulk pack.					
Original white casing for AXIS M3047/48-P. 5	\$	89.00	7331021061132	0.37	11.02
pcs.					_
Spare part white casing. Cover top	\$	69.00	7331021069541	0.46	5.12
replacement part for M3067/68.					
Original white casings for AXIS M42 series.	\$	69.00	7331021069046	0.44	5.31
Easy to repaint. 4-piece bulk pack.					
Clear dome with anti-scratch hard coating.	\$	89.00	7331021069053	0.37	2.17
Compatible with AXIS M42 series. 4x domes per					
pack. Spare part AXIS M50 dome casing cover in	\$	59.00	7331021062948	0.34	6.50
white. Included in AXIS M50 dome casing cover in	φ	59.00	7551021002940	0.34	0.50
white. Included in Axis M3034/35/03 calleras.					
Spare part AXIS M501X dome, pre-mounted in	\$	39.00	7331021036741	0.35	6.50
the white top casing. Opening tool and gasket	*				
are included.					
Spare part clear dome in polycarbonate. IK09	\$	49.00	7331021065789	0.49	6.69
vandal resistant. Compatible with AXIS M5525-					
E. Single pack.					
Standard clear dome for AXIS P32-V Series, 5	\$	169.00	7331021048126	0.88	5.12
pcs					
Semi smoked domes for AXIS P32-LVE Series,	\$	169.00	7331021050860	1.28	5.12
5 pcs	¢	20.00	7224024020742	0.94	7.48
Dome Kit for AXIS P3343, AXIS P3344, AXIS P3353 and AXIS P3354 as spare part. Includes a	\$	39.00	7331021029743	0.84	7.48
clear bubble, mounted on o plastic dome cover					
and a separate smoked bubble.					
Dome kit for AXIS P3343-V, AXIS P3344-V, AXIS	\$	79.00	7331021029736	1.34	7.48
P3363-V and AXIS P3364-V as spare part.	Ť				
Includes a clear bubble, mounted on an					
aluminium dome cover and a separate smoked					
bubble.					
Dome Kit for AXIS P3343-VE, P3344-VE, AXIS	\$	79.00	7331021029767	1.34	7.48
P3363-VE and AXIS P3364-VE as spare part.					
Includes a clear bubble, mounted on an					
aluminium dome cover and a separate smoked					
bubble.					
-					

Dome kit for AXIS P3346-V, P3367-V and AXIS P3384-V as spare part. Includes a clear bubble, mounted on a zinc alloy dome cover and a separate smoked bubble.	\$ 89.00	7331021033467	1.54	7.48
Dome Kit for AXIS P3346-VE, P3367-VE, AXIS P3384-VE as spare part. Includes a clear bubble, mounted on an aluminium dome cover and a separate smoked bubble.	\$ 89.00	7331021033474	1.43	7.48
Dome kit for AXIS P3364-LV. The dome is pre- mounted in the standard white top cover casing.	\$ 79.00	7331021006843	1.21	7.48
Dome kit for AXIS P3364-LVE. The dome is pre- mounted in a standard white top cover casing.	\$ 79.00	7331021006836	1.32	7.09
Semi-smoked dome with anti-scratch hard coating for indoor and outdoor AXIS P337X-LV/- LVE cameras. 4x domes per pack.	\$ 129.00	7331021064805	0.61	5.12
Clear dome with anti-scratch hard coating for indoor and outdoor AXIS P337X-V/-VE cameras. 4x domes per pack.	\$ 129.00	7331021064812	0.61	5.12
Dome kit for AXIS P3707-PE. The dome is pre- mounted in the standard white top cover casing.	\$ 109.00	7331021054158	1.61	12.60
Dome kit for AXIS P3717-PLE and AXIS P3719- PLE. The dome is pre-mounted in the standard white top cover casing.	\$ 99.00	7331021064362	2.02	12.60
Original top cover including dome and screws for AXIS P39-R Series. 10 pieces.	\$ 269.00	7331021047006	2.07	11.02
Clear dome for AXIS P54-series.	\$ 59.00	7331021007420	0.66	7.48
Dome kit for AXIS P5512-E, 5514-E, 5515-E. Clear-/smoked dome and dome cover included.	\$ 59.00	7331021037571	1.04	11.02
4 pack white dome cover for AXIS P3925-R. Replaces the standard white dome cover.	\$ 219.00	7331021070721	2.34	11.10
Standard clear dome with anti-scratch hard coating. Compatible with selected AXIS Q61-LE cameras. Weather-resistant and chemical- resistant. Rubber gasket included. Single pack.	\$ 99.00	7331021068179	0.62	7.48
Hard coated clear dome spare part for Q6100-E.	\$ 89.00	7331021067639	1.32	16.73
Clear dome cover including dome cover ring. Compatible with legacy AXIS Q60-E/-C cameras. See axis.com for updated compatibility list.	\$ 149.00	7331021069510	1.68	8.98
Standard clear dome with anti-scratch hard coating. Compatible with AXIS Q60-E cameras. Weather-resistant and chemical-resistant. Rubber gasket, ring compass, ring support included. Single pack.	\$ 169.00	7331021076839	1.54	9.25

Standard clear dome with anti-scratch hard coating. Compatible with AXIS Q6074, 75, 78-E cameras. Weather-resistant and chemical- resistant. Replacement dome only.	\$ 69.00	7331021076853	0.53	4.72
Spare part aspheric clear dome for AXIS M4308- PLE. Includes gasket.	\$ 39.00	7331021077065	0.35	4.72
TQ9801 CLEAR DOME spare part for Q9216- SLV.	\$ 89.00	7331021071537	0.40	6.69
Clear dome for AXIS P56 Series cameras. Hard- coated clear dome for harsh environments. It's weather-resistant and chemical-resistant.	\$ 59.00	7331021075672	0.62	8.66
Standard clear domes for AXIS Q35-V Series, 5 pcs	\$ 189.00	7331021046283	0.95	5.12
Standard clear dome with anti-scratch hard coating. Compatible with AXIS Q3517-LV/-LVE. 5x domes per pack.	\$ 219.00	7331021061712	1.73	6.30
Standard clear dome for AXIS Q3505-VE. 5pcs	\$ 219.00	7331021046306	1.12	5.12
Standard clear dome with anti-scratch hard coating. Compatible with AXIS P38 and Q36 Series.	\$ 59.00	7331021053564	0.88	7.48
Standard clear dome with anti-scratch hard coating. Compatible with AXIS Q3708-PVE and Q3709-PVE. Single pack.	\$ 49.00	7331021051010	0.71	7.48
Clear dome for AXIS Q6000-E	\$ 89.00	7331021048287	1.72	16.73
HD optimized dome kit for AXIS Q603X as spare part. Includes a clear bubble mounted on dome ring and a separate smoked bubble.	\$ 99.00	7331021032880	1.70	11.42
Original clear dome in polycarbonate with anti- scratch hard coating. IK10+ vandal-resistant and high chemical resistance. Compatible with AXIS Q3517-SLVE. 2x domes per pack.	\$ 99.00	7331021065581	0.89	6.30
Stand alone smoked dome for AXIS Q60XX-E/-C series	\$ 79.00	7331021005525	0.95	11.02
Original clear dome in a special nylon blend with superior stress and chemical resistance. Compatible with AXIS Q604x-S and Q6055-S cameras. Single-pack.	\$ 79.00	7331021006829	0.60	7.48
Standard clear dome for AXIS Q8414-LVS. 5 pcs.	\$ 99.00	7331021047617	0.49	4.72
AXIS A8105-E Clear Dome is sold as spare parts to the AXIS A8105-E Network Video Door Station and comes in packs of five clear dome covers. It enables easy on-site replacement in case the original dome cover has been damaged or vandalized.	\$ 35.00	7331021053212	0.11	4.13
AXIS TA8801 Clear Dome Cover is sold as spare parts to the AXIS A8207-VE Network Video Door Station and comes in packs of five clear dome covers. It enables easy on-site replacement in case the original dome cover has been damaged or vandalized.	\$ 39.00	7331021067479	0.12	6.10

Original white casing for selected AXIS P32 indoor cameras. 4pcs bulk pack.	\$ 89.00	7331021067813	1.10	6.30
Original white casing for selected AXIS M32 and P32 outdoor cameras. Pre-assembled with anti-loss screws. 4pcs bulk pack.	\$ 109.00	7331021067820	1.37	6.30
Standard clear dome with anti-scratch hard coating. Compatible with selected AXIS P32 indoor cameras. 4pcs bulk pack.	\$ 109.00	7331021066113	1.32	7.64
Standard clear dome with anti-scratch hard coating. Compatible with selected AXIS M32 and P32 outdoor cameras. 4pcs bulk pack.	\$ 129.00	7331021066151	1.32	7.64
This is a spare part clear dome for AXIS P3715- PLVE.	\$ 39.00	7331021074583	0.68	5.51
4 pack white dome cover for AXIS P3935-LR. Replaces the standard white dome cover.	\$ 219.00	7331021070738	2.34	11.10
Outdoor spare part weathershield for AXIS P3265-LVE, P3267-LVE, P3268-LVE. The underside of the cover is specially coated with matte black anti-reflective coating to prevent reflections from external light sources. Anti- loss screws included. Bulk 2 pack.	\$ 79.00	7331021078352	0.44	5.31
Original spare part white casing for AXIS P3265- LV, P3265-V indoor cameras. 4pcs bulk pack.	\$ 89.00	7331021078369	1.10	6.30
Original spare part white casing for AXIS P3265- LVE 9 mm outdoor camera. Pre-assembled with anti-loss screws. 4pcs bulk pack.	\$ 109.00	7331021078406	1.21	6.30
Original white spare part casing for AXIS P3265- LVE 22 mm, P3267-LV, P3267-LVE, P3268-LV, P3268-LVE outdoor cameras. 4pcs bulk pack.	\$ 109.00	7331021078420	0.99	6.30
Spare part clear dome with anti-scratch hard coating. Compatible with AXIS P3265-LVE 22 mm, P3267-LV, P3267-LVE, P3268-LV, P3268- LVE. 4pcs bulk pack.	\$ 109.00	7331021079298	1.38	11.61
Complete spare part top casing for AXIS P3925- LRE including aluminum top casing with tempered glass window with antireflective coating, heater, connector board, screws and re-painting window mask.	\$ 319.00	7331021074736	1.15	6.61
Spare part mounting bracket for AXIS P3267- LV, P3268-LV. Suitable for mounting cameras over junction boxes (4" octagon, single-gang, or double-gang), and other Axis mounting accessories. 4-piece bulk pack.	\$ 59.00	7331021079311	0.77	5.71

Spare part mounting bracket for AXIS P3265- LVE 22 mm, P3267-LVE, P3268-LVE. Suitable for mounting cameras over junction boxes (4" octagon, single-gang, or double-gang), and other Axis mounting accessories. 4-piece bulk pack.	\$	109.00	7331021079328	1.65	7.87
	*	00.00	7004004070000	0.44	4.50
Clear dome spare part for AXIS P3717-PLE, AXIS P3719-PLE, AXIS P3727-PLE. The dome and the casing are included.	\$	89.00	7331021076822	2.14	4.53
Cover weathershield for P3818-PVE. Includes anti loss screws.	\$	29.00	7331021075573	1.12	7.48
Cover top replacement for Q3819-PVE including anti loss screws and holder magnet.	\$	49.00	7331021075597	1.41	8.27
Spare part mounting bracket in 5p for AXIS Q3536-LVE, AXIS Q3538-LVE.	\$	139.00	7331021078796	3.31	7.28
Spare part clear dome for AXIS Q3536-LVE, AXIS Q3538-LVE in a 5p (anti-scratch hard coating).	\$	159.00	7331021078772	1.87	10.83
Spare part weathershield in a 5p for AXIS Q3536-LVE, AXIS Q3538-LVE. Anti loss screws and gasket included.	\$	139.00	7331021078789	1.37	5.24
Spare part white dome cover for AXIS M5000 & AXIS M5000-G. Includes dome and cover, 4 SCREW TX+ 8 DOME FLANGE, and 2 spring clips.	\$	69.00	7331021077195	1.43	10.04
4 pack spare part white casing replacing original out of the box. Compatible with M3085- V, M3086-V, M3088-V.	\$	69.00	7331021079656	0.39	5.31
Standard clear dome spare part replacing original out of the box with anti-scratch hard coating. Compatible with: AXIS M3215-LVE, AXIS M3216-LVE. 4pcs bulk pack.	\$	129.00	7331021080164	1.28	11.61
AXIS TP3819-E Dome Clear, is spare part clear dome for AXIS P4705-PLVE and P4707-PLVE.	\$	29.00	7331021078130	0.35	4.72
AXIS TP3825-E Weathershield White, is a spare part (white) weathershield for AXIS P4705- PLVE and P4707-PLVE.	\$	29.00	7331021079731	0.40	6.69
Spare part standard clear dome with anti- scratch hard coating. Compatible with Q3626/8- VE.	\$	39.00	7331021083998	0.43	5.71
Spare part original white casings for AXIS M42 series. Easy to repaint. 4-piece bulk pack.	\$	59.00	7331021082595	0.44	5.12
Spare cover top casing white for AXIS M4327-P and AXIS M4328-P. Comes in 4 Pack.	\$	69.00	7331021084568	0.44	5.91
AXIS TI8903 Clear Dome is sold as spare parts to the AXIS I8116-E Network Video Intercom and comes in packs of five clear dome covers. It enables easy on-site replacement in case the original dome cover has been damaged or vandalized.	\$	69.00	7331021079434	0.13	3.94

Clear dome spare for AXIS P5676-LE. Hard- coated clear dome for harsh environments. It's weather-resistant and chemical-resistant.	\$ 59.00	7331021085022	0.66	7.28
Spare part clear dome for: AXIS P3735-PLE, AXIS P3737-PLE, AXIS P3738-PLE. The dome and cover are included.	\$ 99.00	7331021085947	2.14	
Allen-key for AXIS 209FD-R 10-pack	\$ 49.00	7331021021433	0.02	5.71
Original stainless steel mounting bracket for AXIS D2050-VE. Includes two pipe adapters, anti-loss screws, two gray cable gaskets, three black cable gaskets, and an M20 cable gland.	\$ 69.00	7331021063211	1.34	11.02
Contains 5pcs wall-and-corner mount bracket and 5pcs table-top stand. Compatible with AXIS M1045-LW, AXIS M1065-L and AXIS M1065-LW. Not compatible with AXIS M1055-L and AXIS M1075-L	\$ 49.00	7331021058262	0.71	4.72
Spare part indoor recessed mount for mounting AXIS Q60 indoor cameras in drop ceilings.	\$ 99.00	7331021040649	1.69	11.02
Mounting bracket that allows AXIS FA1125 Sensor Unit to be mounted behind a thin metal/plastic/glass panel. 5 pcs.	\$ 29.00	7331021061996	0.14	4.21
AXIS TF9904 Swivel Mount allows to mount the sensor unit in different horizontal and vertical angles. It is sold a pack of 5.	\$ 59.00	7331021005419	0.46	6.10
Original ceiling mount kit for both hard- and drop ceilings for the AXIS M501X.	\$ 15.00	7331021036758	0.22	6.50
Spare part powder coated white stainless steel back chassis with gaskets for AXIS Q8414-LVS.	\$ 199.00	7331021047594	5.93	13.39
Spare part brushed stainless steel metal back chassis with gaskets for AXIS Q8414-LVS.	\$ 199.00	7331021047600	5.80	13.39
Original stainless steel mounting bracket for AXIS T98A-VE Surveillance Cabinet series.	\$ 69.00	7331021001442	2.87	9.06
1 pair marine-grade (SS316L) stainless steel straps with TX30 screw interface for ease-of- installation. Length 570mm (22.5"). Width 14.3mm (0.57"). Thickness 0.68mm (0.03"). Compatible with a wide range of Axis pole mounts. Pole diameter range 50-150mm (2"-6") when used with AXIS T91B47 Pole Mount.	\$ 39.00	7331021063723	0.31	6.61
1 pair marine-grade (SS316L) stainless steel straps with TX30 screw interface for ease-of- installation. Length 1450mm (57"). Width 14.3mm (0.57"). Thickness 0.68mm (0.03"). Compatible with a wide range of Axis pole mounts. Pole diameter range 100-410mm (4"- 16") when used with AXIS T91B47 Pole Mount.	\$ 49.00	7331021063716	0.53	6.61

Original stainless steel straps for AXIS T91A47 110-400 mm. The straps also fit the AXIS	\$ 32.00	7331021007062	0.71	8.27
T91A67. Mounting tool (P/N 21776) is required.				
Screw Kit for AXIS P3343-VE and P3344-VE as spare part. Includes mounting screws, plugs and I/O connector.	\$ 5.00	7331021029774	0.11	7.87
Screw kit för AXIS P3343, P3343-V, P3344 and P3344-V as spare part. Includes mounting screws, plugs and I/O connector.	\$ 4.00	7331021029729	0.04	7.87
Spare part mounting brackets for AXIS M20 Series, 5-pack. Includes 5x mounting brackets with 5x Gasket C M20.	\$ 59.00	7331021059337	0.77	4.33
Standard mount bracket for AXIS M3006-V, AXIS M3007-P/-PV, AXIS M3024-LVE/3025- VE/3026-VE	\$ 29.00	7331021040663	0.20	6.50
Sparepart mounting bracket for AXIS Q1765-LE, Q1931-E, Q1932-E	\$ 39.00	7331021046412	0.35	6.50
Sparepart mounting bracket for AXIS Q3505-V. 4 pcs	\$ 129.00	7331021046269	1.72	7.87
Sparepart mounting bracket for AXIS Q3505-VE. 4 pcs	\$ 149.00	7331021046276	2.74	9.06
Sparepart mounting bracket for AXIS P32-V Series. 4 pcs	\$ 69.00	7331021046214	0.84	6.50
Sparepart mounting bracket for AXIS P32-VE Series. 4 pcs	\$ 89.00	7331021046191	1.39	6.50
Spare part mounting brackets for AXIS M3057/58-PLVE, single pack. Includes spring clips for ease-of-installation.	\$ 39.00	7331021065031	0.40	7.09
Original AXIS P33XX-VE mounting bracket for wall or hard ceilling.	\$ 29.00	7331021032767	0.65	7.48
Standard mounting bracket for AXIS Q36 Series Network Cameras.	\$ 49.00	7331021056541	1.21	7.09
4-pack of 3/4" conduit locknut. Suitable for AXIS T91B53 Telescopic Ceiling Mount.	\$ 29.00	7331021064331	0.04	2.56
Standard mounting bracket for AXIS Q3505- SVE made of stainless steel. Including gasket.	\$ 179.00	7331021050839	1.57	8.27
Standard plastic mounting bracket for AXIS P1405, P1425, P1427, P1428.	\$ 29.00	7331021050884	0.26	6.50
Spare part mounting bracket for selected AXIS M32 and P32 cameras. Suitable for mounting cameras over junction boxes (4" octagon, single-gang, or double-gang), and other Axis mounting accessories. 4-piece bulk pack.	\$ 49.00	7331021068056	0.80	5.71
Spare part mounting bracket for selected AXIS P32 outdoor cameras. Suitable for mounting cameras over junction boxes (4" octagon, single-gang, or double-gang), and other Axis mounting accessories. 4-piece bulk pack.	\$ 99.00	7331021067837	1.61	7.87

Mount bracket for Q3819-PVE. Includes conduit lid to cover conduit entry not used.	\$ 49.00		7331021075580	0.66	12.60
Spare part weather shield for AXIS M2035-LE and M2036-LE. Includes cover and holder.	\$ 79.00		7331021079823	0.37	5.63
5 pack spare part wall mount for: AXIS M1055-L and AXIS M1075-L.	\$ 19.00	Ī	7331021085282	0.44	6.30
Spare part standard mounting bracket for AXIS Q3626/8-VE Network Cameras.	\$ 49.00		7331021085008	0.76	7.68
Standard clear dome with anti-scratch hard coating. Rubber gaskets included. Compatible with AXIS P9106-V. 2-piece bulk pack.	\$ 49.00		7331021066076	0.22	4.72
Spare part skin cover for AXIS P9106-V. Brushed stainless steel finish. Easy to repaint. Magnetically attached. Suitable for both AXIS P9106-V White and Brushed Steel models.	\$ 69.00		7331021066083	0.57	6.30
Shielded RJ12 connectors for use with AXIS modular cameras. 10-pack.	\$ 39.00		7331021061736	0.18	6.50
Power supply PS-P for AXIS 215 PTZ	\$ 39.00		7331021043626	1.12	6.50
Standard power supply for AXIS FA54. IEC-C13 mains cable is not included.	\$ 59.00		7331021064300	0.62	6.50
Standard power supply for AXIS S3008 and AXIS Companion Recorder. IEC-C13 mains cable is not included. This adapter is not compatible with AXIS S3008 Mk II or AXIS W800.	\$ 109.00		7331021064294	0.88	6.50
Mains cable for AXIS One-Port Midspan, AXIS T8123/24, AXIS 291, AXIS Q7900, AXIS Video Server Rack, AXIS PoE Midspan 8-Port/16-Port, Power Supply AXIS T8412.	\$ 15.00		7331021037472	0.28	7.87
Set of patch cables for AXIS T8085 PS57 RACK MOUNT 500W 1U to connect AXIS T8646 POE+ OVER COAX BLADE	\$ 79.00		7331021047662	0.09	4.13
M16 cable gland for cable diameter of 4.5 to 10mm. IP68. 5 pcs.	\$ 19.00		7331021044227	0.12	3.94
The kit contains a complete AXIS P3367-VE enclosure, heater and cable cover. The kit could also be used for converting an indoor version of AXIS P3346, P3367, P3384 and P3365 to an outdoor VE version.	\$ 215.00		7331021005204	3.53	11.02
Kit for the AXIS P13XX-series. Content: one terminal connector 4P str 250mm BP LF and one 2P STR 3.81MM BP LF.	\$ 9.00		7331021022041	0.01	2.36
Terminal connectors for AXIS Q7404. Includes 8 pcs 2P 2.50MM, 4 pcs 4P 2.50MM and one 2P 3.81MM. In total 13 connectors.	\$ 35.00		7331021026056	0.04	2.48
AXIS M3115/16-LVE WHITE CASING 4P sold as a spare part and comes in pack of four. It enables easy on-site replacement in case the original case has been damaged.	\$ 89.00		7331021072046	0.74	6.89
Standard lens for AXIS F4005-E, AXIS F1005-E and AXIS P1214-E.	\$ 219.00		7331021056602	0.44	6.50

Spare part top part of the housing including window.	\$ 69.00	7331021050297	1.98	5.12
CS mounted Varifocal 2.8-8 mm DC-iris megapixel lens. Original lens for AXIS M1114.	\$ 149.00	7331021033269	0.37	4.72
Original CS mounted varifocal P-Iris lens 2.8- 8mm for AXIS Q1604/14 and AXIS P1355/57	\$ 149.00	7331021005983	0.33	4.72
Original CS mounted varifocal DC-Iris lens 2.8- 8mm for AXIS Q1602/04 and AXIS P1354/55	\$ 149.00	7331021005976	0.33	4.72
Standard CS mounted varifocal P-Iris lens 2.8- 8mm for AXIS Q1615.	\$ 149.00	7331021048386	0.33	4.72
Standard CS mounted varifocal P-Iris lens 2.8- 8.5mm for AXIS P1364.	\$ 159.00	7331021053458	0.33	4.72
Varifocal 2.9-8.2mm CS mounted SVGA DC-iris lens. Original lens for AXIS M1113	\$ 69.00	7331021033252	0.15	4.72
Standard lens for AXIS Q1635-E.	\$ 249.00	7331021054394	0.37	4.72
Standard C mounted varifocal DC-Iris lens 4- 13mm for AXIS Q1635.	\$ 399.00	7331021048393	0.60	4.72
Varifocal 8-50 MM, 5 MP telephoto IR-corrected lens with P-Iris. Recommended for AXIS P1367 and AXIS P1367-E.	\$ 249.00	7331021063693	0.43	4.72
Lens CS-mount 2.8 - 10 mm. F1.2 P-IRIS 2MP resolution Computar. Spare part for AXIS P1375 / -E	\$ 149.00	7331021069534	0.14	3.54
Standard lens for AXIS P3925-R and AXIS P3935-LR. 10 pack.	\$ 199.00	7331021070745	0.49	6.42
LENS M12 2.9MM F2.0 for Q6010-E and Q6100- E.	\$ 49.00	7331021071858	0.18	6.50
Spare varifocal CS lens for AXIS P1378/-LE.	\$ 199.00	7331021072473	0.33	4.72
Sunshield for AXIS Q872x-E as sparepart. Including screws and washer	\$ 299.00	7331021004641	4.61	11.42
Bracket kit for surface mounting a camera on a hard ceiling. Compatible with Q603X and P553X. Content: Bracket, screws with washers and wave springs.	\$ 29.00	7331021033184	0.19	6.50
Connectors for AXIS Q7410 as spare parts. Includes two 2pin STR 2.50MM, one 6pin STR 2.50MM and one 2pin STR 3.81MM. In total 4 connectors.	\$ 19.00	7331021022027	0.02	3.94
Spare RJ45 connector plug for AXIS Q603X-E & AXIS P55XX-E. IP67 rated.	\$ 49.00	7331021029866	0.09	5.91
Shielded outdoor network cable 5 meter. Pre mounted rubber gasket and male RJ45 connectors. For use with AXIS M11-E series, AXIS P13-E series, AXIS Q16-E series, AXIS Q1755-E, AXIS Q19-E series, AXIS P33-VE series and AXIS T92/3-E housings.	\$ 10.00	7331021029750	0.44	7.87
Cable between AXIS Q60XX-C and connection box AXIS T8605	\$ 179.00	7331021007161	1.19	9.45

Screw kit for installing AXIS P55-E Series with either AXIS T91L61 or AXIS T91G61 Wall Mounts. Single-pack includes 3x bayonet screws, 3x securing screws, 3x springs and an	\$ 39.00	7331021060388	0.11	3.94
installation guide.				
Spare part lens kit for AXIS P5544	\$ 399.00	7331021003057	0.77	9.84
Spare part window and window holder for AXIS T96B05 Outdoor Housing and AXIS P3905-RE. 5 Pcs. Includes screws.	\$ 179.00	7331021050105	0.75	6.50
Peltier element, inside and outside fan for AXIS Q60XX-C	\$ 1,079.00	7331021005013	2.20	6.50
Switching power supply, 5W with microUSB connector. Including interchangeable regional power plugs for world wide use.	\$ 39.00	7331021058071	0.54	6.50
Replacement power supply for AXIS Q7920 Video Encoder Chassis	\$ 329.00	7331021007505	3.33	8.27
Spare part top part of the AXIS T93G housing including window.	\$ 59.00	7331021050099	2.23	11.61
Replacement front window assembly for AXIS T92G Outdoor Housing and AXIS Q16-LE Fixed Box Cameras. Includes front window, adjacent IR windows, mounting screws and sealing gasket.	\$ 109.00	7331021065161	0.95	5.91
Original outdoor weathershield for AXIS T92G Outdoor Housing and AXIS Q16-LE cameras. The underside of the cover is specially coated with matte black anti-reflective coating to prevent reflections from IR LEDs and other light source. Mounting screws included.	\$ 69.00	7331021065178	1.57	8.86
Spare Camera Holder for AXIS T92G20 Outdoor Housing and for AXIS Q1645/7-LE Network Cameras. The holder makes it possible to mount AXIS P13 Network Camera Series into AXIS T92G20 Outdoor Housing.	\$ 39.00	7331021069619	0.66	7.48
Sunshield compatible with AXIS Q1765-LE, Q1931-E/32-E/41-E and Q2901-E	\$ 39.00	7331021044296	0.33	4.72
Sunshield compatible with AXIS Q1765-LE PT Mount	\$ 39.00	7331021044302	0.42	12.20
Sunshield for AXIS Q603X-E.	\$ 39.00	7331021033801	1.41	12.20
Kit for making a stand-alone AXIS Q6010-E installation without PTZ camera inside. Includes a metal cover lid, IP66-rated RJ45 push-pull connector, and a connector plug. Use this kit together with an AXIS Q6010-E network camera (not included) and the AXIS T8133 Midspan 30 W 1-port (not included).	\$ 129.00	7331021075016	1.54	10.83
Protection of front window on AXIS Q62-LE camera. Provides IK10 rating on product. Includes bracket and mounting screws.	\$ 29.00	7331021065727	0.11	4.13

Original front window assembly for AXIS Q6215- LE, IK09 rated. Includes a complete front window glass assembly with mounting screws and sealing gasket; and a wiper arm (long-life, UV-resistant silicone rubber included). Note: IR window available separately.	59.00	7331021065734	0.65	4.53
Bulk pack (4 pcs) of replacement wiper arms (rubber included) for AXIS Q62-LE. Made from long-life, UV-resistant silicone rubber.	\$ 59.00	7331021065741	0.17	4.53
Original IR window assembly for AXIS Q62-LE. Includes a complete IR Window assembly with mounting screws and sealing gasket. Note: clear front window available separately.	\$ 59.00	7331021065758	0.38	4.53
Sunshield for AXIS P134X-E, AXIS Q1755-E and AXIS Q192X-E. Includes mounting screws and Torx key.	\$ 49.00	7331021033535	1.37	7.68
Original weathershield with anti-loss screws for protecting AXIS P33 outdoor cameras from rain, snow and sun when wall mounted. The underside of the cover is specially coated with matte black anti-reflective coating to prevent reflections from IR LEDs and other light sources. This part is included with AXIS P3375- VE/-LVE Cameras.	\$ 25.00	7331021066663	0.51	7.87
Original weathershield with anti-loss screws for protecting AXIS P3807-PVE from rain, snow and sun when wall mounted.	\$ 39.00	7331021064096	0.68	12.80
Original weathershield for AXIS Q35-LVE network camera series. Screws and gasket included.	\$ 24.00	7331021061705	0.53	7.87
Weathershield with screws for protecting the dome of an AXIS Q35-VE camera from rain, snow and sun.	\$ 29.00	7331021048645	0.33	6.50
Weathershield with screws for protecting the dome of an AXIS P32-VE camera from rain, snow and sun.	\$ 29.00	7331021048638	0.31	4.72
Standard weathershield for AXIS Q3709	\$ 34.00	7331021051027	0.95	11.02
Standard weather shield for AXIS M2025/26 and AXIS Companion Bullet	\$ 24.00	7331021056183	0.20	6.50
Standard weather shield for Axis Q36 Series, protecting the dome from rain, snow and sun.	\$ 24.00	7331021052895	0.77	8.27
Weathershield for protecting wall mounted fixed dome cameras against rain, snow and sun. UV-resistant plastics and matte black anti- reflective coating on the underside to prevent reflection from IR illumination. Equipped with anti-loss screws for ease of installation. Compatible with AXIS P32-VE/-LVE fixed dome cameras.	\$ 39.00	7331021062849	0.35	7.87
Original weathershield for AXIS P3343, AXIS P3344-VE, AXIS P3363-VE and AXIS P3364-VE. Screws included.	\$ 20.00	7331021034631	0.31	7.87

Original weathershield for AXIS P3346, AXIS P3367-VE and AXIS P3384-VE. Screws	\$ 20.00	7331021034648	0.31	7.87
included. Outdoor weathershield for selected AXIS M32 and P32 cameras. The underside of the cover is specially coated with matte black anti-reflective	\$ 79.00	7331021066144	0.51	5.31
coating to prevent reflections from external light sources. Anti-loss screws included. Bulk 2 pack.				
Replacement clamp bracket mount for AXIS P3717-PLE, AXIS P3719-PLE and AXIS P3727- PLE. Pack of 10pcs.	\$ 19.00	7331021076075	0.08	3.27
Complete Front Kit for AXIS T92E20/21. Content: Front Cover, Front Glass, Gasket & Screws.	\$ 20.00	7331021032903	0.37	6.50
Sparepart including the electronics module of the AXIS T92E20 housing including fan and screws.	\$ 199.00	7331021033887	1.17	6.50
Extension front for AXIS T92E20 outdoor housing, allowing longer lenses than the standard housing. The kit includes aluminum front and extension part, window, gasket and screws.	\$ 49.00	7331021057661	0.75	6.50
Replacement front window assembly for AXIS M2025-LE, M2026-LE. The kit comes with both a black and a white front cover ring. Includes one window and sealing gasket.	\$ 29.00	7331021059344	0.22	5.63
Standard weather shield for selected AXIS P13 series. For protection from rain, snow and sun. The underside of the cover is coated with matte black anti-reflective coating, for suitable use near IR LEDs.	\$ 49.00	7331021066632	1.15	6.50
Replacement top cover with front window for selected AXIS P13-E cameras. Original weathershield is not included but available separately.	\$ 89.00	7331021066649	1.57	6.10
Standard front window kit for selected AXIS P144x-LE series. Abrasion and UV resistant for long service life. Includes cover ring, front window, and rubber gasket.	\$ 39.00	7331021067448	0.22	4.33
Standard weather shield for selected AXIS P14 series. For protection from rain, snow and sun. The underside of the cover is coated with matte black anti-reflective coating, for suitable use with camera's built-in IR LEDs.	\$ 39.00	7331021066915	0.31	4.13
Standard front window kit for selected AXIS P145x-LE series. Abrasion and UV resistant for long service life. Includes cover ring, front window, and rubber gasket.	\$ 39.00	7331021075740	0.22	5.00

Spare part front window kit for AXIS P1455-LE 29 mm and AXIS P1455-LE-3. Abrasion and UV resistant for long service life. Includes cover ring, front window, and rubber gasket.	\$ 49.00	7331021076921	0.22	
Original front glass window assembly for AXIS Q1785/86-LE, IK08 rated. Provides the clarity required for maximum utilization of the camera's zoom capacity.	\$ 89.00	7331021066465	0.40	7.09
Original front glass window assembly for AXIS Q1700-LE, IK08 rated. Provides the clarity required for maximum utilization of the camera's zoom capacity.	\$ 109.00	7331021070103	0.29	6.30
Original outdoor weathershield for AXIS Q1700- LE camera, Color: Black	\$ 59.00	7331021070110	0.44	12.20
Spare part front window for AXIS Q1765-LE	\$ 69.00	7331021046405	0.33	6.50
Original spare part fan cassette for AXIS Q7920.	\$ 109.00	7331021007482	0.73	6.50
Cabinet door for AXIS T98A Surveillance Cabinet. Stand alone. Used in T98A15-VE Cabinets.	\$ 139.00	7331021004948	2.27	14.57
Cabinet door for AXIS T98A Surveillance Cabinet. Compatible cameras: AXIS M111X-E, AXIS P13XX-E, AXIS Q16XX-E, AXIS Q17XX-E, AXIS Q191X-E, AXIS Q192X-E. Used in T98A16-VE Cabinets.	\$ 139.00	7331021004955	2.43	14.57
Cabinet door for AXIS T98A Surveillance Cabinet. Compatible cameras: AXIS P33-VE/- LVE and the outdoor bullet-style Q1765 and Q1931 cameras. Used in T98A17-VE Cabinets.	\$ 139.00	7331021004962	2.27	14.57
Cabinet door for T98A. Compatible products: AXIS T91A61 Wall bracket for use with AXIS P55 and Q60-series or fixed dome pendant kits. Used in T98A18-VE Cabinets.	\$ 139.00	7331021004979	2.47	14.57
Cabinet door for AXIS T98A. Compatible products: AXIS P54-Series. Used in T98A19-VE Cabinets.	\$ 139.00	7331021007512	2.38	14.57
Terminal connectors for AXIS P135X-series. Includes 1 pcs TERMINAL CONNECTOR 4P STR 2.50MM, 1 pcs TERMINAL CONNECTOR 2P STR 3.81MM, 2 pcs TERMINAL CONNECTOR 2P STR 2.50MM	\$ 9.00	7331021002227	0.02	2.44
2pcs RJ-45 waterproof plugs and 1pcs grounding wire for outdoor midspan T8123/4-E	\$ 29.00	7331021002159	0.04	2.76
Frontkit for AXIS Q872X-E with 60mm lens as spare part.	\$ 1,499.00	7331021004634	1.50	10.04
Frontkit for AXIS Q872X-E with 30mm lens as spare part	\$ 699.00	7331021004627	1.39	10.04
Spare part illuminator kit for AXIS Q8665-LE. NOTE: it is not possible to upgrade a Q8665-E to become LE version	\$ 1,299.00	7331021048867	11.35	12.20

Replacement front window assembly for AXIS Q8685-E/-LE. Window in clear tempered glass.	\$ 379.00	7331021063228	1.06	5.00
Includes built-in heater, wiper mechanism, and heat sink.				
Replacement wiper blades for selected AXIS Q86 and Q87 cameras. Made from long-life, UV-	\$ 59.00	7331021063235	0.09	4.21
resistant silicone rubber. 5pcs per pack.				
Light sensor box with integrated power supply for controlling IR illuminators and power AXIS Q8665-LE. Input power 120V AC.	\$ 640.00	7331021048348	16.53	16.93
Good-LE. Input power 120V AC.				
Spare part base unit for AXIS Q86-LE 24 V AC.	\$ 1,199.00	7331021053328	7.45	5.51
Spare part base unit for AXIS Q86-E 120 V AC.	\$ 1,199.00	7331021053311	7.43	5.51
Spare part top housing with germanium window for AXIS Q8631-E/32-E.	\$ 599.00	7331021053410	4.41	7.68
Spare part top housing with glass window for AXIS Q8665-E/-LE.	\$ 399.00	7331021053403	4.67	7.68
Spare parte sunshield for AXIS Q8631-E/32-E/65- E/65-LE	\$ 59.00	7331021053427	1.57	7.68
Spare part wiper blade for AXIS Q8665-E/-LE including the stainless steel holder	\$ 59.00	7331021053335	0.09	3.27
Base assembly for the AXIS Q8721-E/22-E.	\$ 699.00	7331021043879	7.05	10.24
Replacement top cover with front window for selected AXIS M11-E cameras. Original weathershield included.	\$ 129.00	7331021067622	2.98	14.17
Weathershield from UV-resistant plastics for protecting camera against rain, snow and sun.	\$ 59.00	7331021064065	1.41	10.63
Wiper arm with blade for easy replacement. Spare part.	\$ 59.00	7331021066489	0.15	4.13
Axis male connector for legacy IO port . Pitch: 2.50 mm. 2pos terminal block. 10pack.	\$ 19.00	7331021042865	0.02	3.94
Axis male connector for limited and full IO port . Pitch: 2.50 mm. 4pos terminal block. 10pack.	\$ 19.00	7331021040595	0.02	2.44
Axis male connector for extended IO port . Pitch: 2.50 mm. 6pos terminal block. 10pack	\$ 59.00	7331021042872	0.04	3.94
Axis male connector for low voltage power. Pitch: 3.81 mm. 2pos terminal block. 10pack	\$ 19.00	7331021040601	0.04	3.94
Axis male connector for low voltage power. Pitch: 3.81 mm. 3pos terminal block. 10pack	\$ 29.00	7331021042889	0.04	2.36
Axis male connector for audio. Pitch: 3.81 mm. 2+2pos terminal block. 10pack	\$ 39.00	7331021042896	0.07	3.94
Axis male connector for low voltage power. Pitch: 3.81 mm. 4pos terminal block. 10pack	\$ 29.00	7331021042711	0.07	3.94
Axis male connector for low voltage power. Pitch: 5.08 mm. 2pos terminal block. 10pack	\$ 29.00	7331021042902	0.05	2.76

Spare part internal switch for the AXIS Q8721- E/22-E Dual cameras,including brackets.	\$ 599.00	7331021040618	1.08	6.50
Sparepart foot chassis for AXIS Q1765-LE and AXIS Q193X-E. Note. This sales part does not include the mounting bracket (5506-081 AXIS T94G01S Mounting plate)	\$ 49.00	7331021046429	0.73	6.50
Adapter for connecting Q6000-E to PTZ camera	\$ 15.00	7331021049673	0.15	4.72
Spare part plastic side covers for compatible AXIS T91- and AXIS T94- series of mounting accessories. 10 pcs per pack.	\$ 29.00	7331021061392	0.19	14.96
Sparepart including the electronics module of the AXIS T92G20 housing.	\$ 119.00	7331021075269	0.19	3.15
Spare part front window kit for AXIS P3925-LRE including tempered glass window with anti- reflective coating, gasket and window holder bracket screws.	\$ 109.00	7331021074743	0.35	6.38
Spare part original outdoor weathershield for AXIS P3715-PLVE. The underside of the cover is specially coated with black anti-reflective coating to prevent reflections from external light sources. Includes gasket and anti-loss screw.	\$ 59.00	7331021072053	0.40	6.50
Original outdoor weathershield for AXIS Q1785/86-LE cameras. The underside of the cover is specially coated with matte black anti- reflective coating to prevent reflections from external light sources. Includes weathershield slider and anti-loss screw.	\$ 59.00	7331021067431	0.66	12.01
KIT WEATHER SHIELD spare part Q1700-LE E1.	\$ 109.00	7331021070783	0.84	6.30
Original front glass window assembly for AXIS Q1700-LE, IK08 rated. Provides the clarity required for maximum utilization of the camera's zoom capacity.	\$ 159.00	7331021070790	0.33	6.69
Spare top cover including wiper for AXIS Q1656 LE, AXIS Q1656-BLE	\$ 499.00	7331021074514	3.99	8.27
Spare top cover for AXIS Q1656-BE. No wiper	\$ 239.00	7331021077201	6.61	8.27
KIT WEATHER SHIELD spare part for Q1785, 6 – LE, and Q1798-LE. Additional ring for Q1798- LE.	\$ 109.00	7331021075528	0.79	6.30
Replacement front kit for AXIS Q1951-E, AXIS Q1952-E. Includes window in germanium, heater, cover and gasket.	\$ 299.00	7331021077164	0.29	5.51
Spare front glass window for AXIS Q1656-LE and AXIS Q1656-BLE. Support for wiper	\$ 99.00	7331021076976	0.68	5.12
Spare front plastic window for AXIS Q1656-BE. No support for wiper	\$ 89.00	7331021076983	0.68	5.12
Spare part weather shield for Q6315-LE. Includes anti loss screws	\$ 39.00	7331021072619	0.51	9.69

Spare part hard coated clear dome for Q6315- LE. Standard clear dome with anti-scratch hard coating. Includes dome ring, cover IR block.	\$ 79.00	7331021072602	0.83	7.95
Replacement wiper kit with wiper arm (rubber included) for AXIS Q8752-E. Made from long- life, UV-resistant silicone rubber. For a front window. It includes a wiper arm with four Fblades for an easy replacement.	\$ 109.00	7331021075122	0.18	4.13
This is a replacement top cover assembly for AXIS Q8752-E Bispectral PTZ Camera with 35 mm lens on the thermal camera.	\$ 1,299.00	7331021075108	5.14	14.37
This is a replacement top cover assembly for AXIS Q8752-E Bispectral PTZ Camera with 35- 105 mm zoom lens on the thermal camera.	\$ 2,379.00	7331021075115	5.07	14.37
Glass replacement kit sold as a spare part to AXIS I8016-LVE Network Video Intercom. It enables easy on-site replacement in case the original cover has been damaged or vandalized.	\$ 49.00	7331021071896	0.09	4.13
Spare varifocal i-CS lens for AXIS Q1656, AXIS Q1656-LE, EXCAM XF Q1645,EXCAM XF P1377 and F101-A XF P1377. Also compatible with AXIS Q1645/-LE and AXIS Q1647/-LE	\$ 299.00	7331021076471	0.25	4.92
Optional extremely light-sensitive lens. CS- Mount 4-10 mm F0.9 with P-Iris. IR-corrected. Compatible with AXIS Q1656/-B/-BE/-BLE and AXIS P1375/-E, AXIS P1377/-LE.	\$ 499.00	7331021077409	1.06	4.72
Spare part mounting bracket for AXIS M2035- LE, M2036-LE. Includes a mounting bracket and gasket for cable.	\$ 39.00	7331021079809	0.37	5.63
Spare part front window assembly for AXIS M2035-LE, M2036-LE. The kit comes with a black front cover ring. Includes a window assembly kit (light guide IR filter, window gasket).	\$ 29.00	7331021079816	0.37	5.63
Spare part cabinet door for AXIS TQ1808-VE Surveillance Cabinet. Stand alone. Can be used with any T98A surveillance cabinets if the front door wants to be replaced with a bigger front door that will allow for more components to be placed in them. Back box has had no changes.	\$ 159.00	7331021076327	3.88	11.61
Kit for making a stand-alone AXIS Q6100-E installation without PTZ camera inside. Includes a thermo plastic cover lid, IP66-rated RJ45 push-pull connector, and a connector plug. Use this kit together with an AXIS Q6100- E network camera (not included) and the AXIS High PoE Midspan 60 W (not included).	\$ 99.00	7331021081192	0.57	8.07

AXIS TP3818-E Dome Cover White, is a spare part kit including a white casing, clear dome and screws for AXIS P4705-PLVE and P4707- PLVE.	\$ 69.00	7331021078116	0.75	5.51
Lens M12 2mm F2.0 is a bulk pack of 4p replacement lenses for AXIS F2135-RE Fisheye lenses.	\$ 79.00	7331021077898	0.18	4.13
Lens M12 3.1mm F2.0 is a bulk pack of 4x replacement lenses for AXIS F2105-RE standard sensor.	\$ 79.00	7331021077881	0.18	4.13
Spare part front window kit for AXIS P1467-LE and AXIS P1468-LE. Abrasion and UV resistant for long service life. Includes cover front, window front, and rubber window gasket.	\$ 49.00	7331021082236	0.18	4.33
Spare part front window kit for AXIS P1465-LE 9 mm. Abrasion and UV resistant for long service life. Includes cover ring, front window, and rubber gasket.	\$ 49.00	7331021082243	0.13	4.53
AXIS TU6001 Conn 3-pin 3.81mm 10p is a bulk pack of 10x AXIS TU6001 Conn 3-pin 3.81mm. AXIS TU6001 Conn 3-pin is compatible with the 2nd generation of F-series Main units: F9111, F9114, and F9104-B and F9114-B AXIS TU6001 Conn 3-pin 3.81mm helps connecting AXIS F91 main units to the DC power.	\$ 9.00	7331021077942	0.13	4.13
Replacement wiper kit with wiper arm/blade (rubber included) for AXIS Q8615-E. Made from long-life, UV-resistant silicone rubber.	\$ 49.00	7331021081246	0.11	4.33
Replacement front kit for AXIS Q8615-E. Includes window, wiper arm, anti-loss screws, holder, gasket.	\$ 449.00	7331021079076	1.11	4.92
Original front window assembly for AXIS Q62- LE, IK09 rated. Includes a complete front window glass assembly with mounting screws and sealing gasket; and a wiper arm (long-life, UV-resistant silicone rubber included). Note: IR window available separately.	\$ 159.00	7331021082274	0.66	4.53
Spare part standard weather shield for Axis Q3626/8-VE, protecting the dome from rain, snow and sun.	\$ 39.00	7331021084001	0.57	7.09
Spare i-CS lens for AXIS M1135/-E MK II i-CS and AXIS M1137/-E MK II i-CS	\$ 139.00	7331021080676	0.26	3.35
10 pack spare part clamp bracket mount. Compatible with: AXIS P3735-PLE, AXIS P3737- PLE, AXIS P3738-PLE.	\$ 39.00	7331021086579		

AXIS TS3902 RAIL KIT is a full rail kit compatible with AXIS S3016 Recorder only. It allows the product to be mounted in server racks with a post to post distance between 376mm (14.8in) and 499mm (19.6in). The rail kit is not compatible with other products such as AXIS S12 Recording Server Series or AXIS S22 Appliance Series.	\$ 119.00		7331021082991	3.75	2.48
Standard power supply for AXIS S3008 Mk II. IEC-C13 mains cable is not included. This adapter is not compatible with AXIS S3008 or AXIS W800.	\$ 129.00		7331021083370	1.21	6.50
AXIS Device Microphone A is an omnidirectional microphone to enable audio recording and/or audio analytics with AXIS devices that support audio but do not include a microphone. The product is compatible with devices that support 3.5 mm audio input, like AXIS indoor Q35 series or P33 series together with AXIS TP3201 Recessed Mount.	\$ 29.00	1	7331021065130	0.13	5.91
AXIS T8351 Mk II Microphone 3.5mm is an omnidirectional microphone with a 3.5mm connector, compatible with all Axis network video products supporting a 3.5mm jack for microphone input. Flexible to install, AXIS T8351 adapts to different installation scenarios thanks to a vast range of included accessories and to its dust-and-water proof casing.	\$ 109.00		7331021064959	0.31	4.13
AXIS T8355 Digital Microphone is an omnidirectional microphone compatible with Axis network product with digital in and ring power supporting both a 3.5mm jack and audio terminal block for microphone input. Axis T8355 could be placed up to 100m (328 ft) away from Axis network products, generating flexibility for installation without deterioration of the audio signal.	\$ 139.00		7331021064966	0.33	4.13
Casing with built-in microphone for selected AXIS P32-LV cameras. Color: Axis white.	\$ 49.00		7331021067806	0.44	6.02
Accessory casing with built-in microphone for AXIS P3267-LV, AXIS P3268-LV,M3215-LVE, M3216-LVE includes microphone and casing with mic hole coming in Axis white.	\$ 69.00		7331021079274	0.33	6.02

AXIS Device Microphone B is an omnidirectional microphone to enable audio recording and/or audio analytics with AXIS devices that support audio but do not include a microphone. The product includes a Terminal Block to 3.5 mm Audio Extension allowing it to be installed together with our latest AXIS P32 series. AXIS TU1001 -VE is an outdoor analog	\$	39.00	7331021069886 7331021075535	0.13	5.91
microphone which has to be connected over 3,5mm jack to an AXIS camera or AXIS device with Audio IN support. AXIS TU1001 -VE is IK10 and IP66 rated to withstand challenges in outdoor environments. AXIS TU1001 -VE can be wall or celling mounted.					
AXIS TU1002-VE Microphone Kit, is an IP66, IK10 enclosure with embedded microphone. AXIS TU1002-VE fits a metallic mesh windscreen as well as dual weatherproofing membranes.The product is designed to fit an AXIS C8033 Audio Bridge, that combined with AXIS TU1002-VE will form a network microphone solution.	\$	159.00	7331021072305	2.25	5.51
TU1001 -V is an indoor analog microphone for single gang box. TU1001 -V is IK10 rated.	\$	139.00	7331021075542	0.30	4.13
PoE Splitter 5 V can be used together with a network device that has no built-in support for Power over Ethernet (PoE). The product splits PoE into seperate 5 V DC and data outputs. The product is IEEE 802.3af compliant.	\$	59.00	7331021071360	0.39	2.95
802.3af compliant power injector for standard Cat 5 network cables. Maximum cable length is 328ft/100m. Supporting up to eight Axis Network cameras/video servers. Metal casing.	\$	649.00	7331021022423	9.94	12.60
802.3af compliant power injector for standard Cat 5 network cables. Maximum cable length is 328ft/100m. Supporting up to sixteen Axis Network cameras/video servers. Metal casing.	\$	859.00	7331021022454	9.70	12.60
Provides power over Ethernet to Axis network video products with built-in PoE support. AXIS T8120 is IEEE 802.3af compliant, ensuring compatibility with all Axis PoE Class 1-3 products. The midspan can be installed on a wall or shelf.	69	59.00	7331021003408	0.93	5.71
Provides power over Ethernet to Axis network video products with built-in PoE support. AXIS T8120 is IEEE 802.3af compliant, ensuring compatibility with all Axis PoE Class 1-3 products. The midspan can be installed on a wall or shelf. 10 pcs.	\$	569.00	7331021003583	9.99	14.17

Media converter switch . 2 RJ45 ports and 2 SFP slots for optical fiber connection (SFP modules not included). Two I/O ports and a combined communication and powering port for the camera. Temp spec40 °C to 75 °C (-40 °F to 167 °F). 12 V DC power input. Shelf or DIN- rail mount. 24 V DC power in.	\$ 479.00	7331021058965	1.41	6.30
Single port midspan for Power over Ethernet Plus (PoE+) IEEE 802.3at Type 2 Class 4 products	\$ 79.00	7331021074071	0.84	3.74
AXIS 30 W Midspan AC/DC is ideal for installations where mains power is not an option. By means of either 10-28 V DC or 24 V AC power input the midspan can provide up to IEEE 802.3at (30 W) to a network device. AXIS 30W Midspan AC/DC 24 V is plug-and-play and offers a wide compatibility with AXIS products.	\$ 109.00	7331021074712	0.66	3.31
AXIS 90 W Midspan AC/DC is ideal for installations where mains power is not an option. By means of either 20-26.4 V DC or 24 V AC power input the midspan can provide both IEEE 802.3bt (90 W & 60 W) and AXIS High PoE 60 W to a network device. AXIS 90W Midspan AC/DC is plug-and-play and offers a wide compatibility with AXIS products.	\$ 209.00	7331021074729	1.28	3.54
AXIS 30 W Outdoor Midspan is an outdoor ready IP66-/IP67-rated midspan compliant with IEEE802.3af and 802.3at. With built in 6kV surge protection. Delivers up to 30W. Temperature specification: 40°C to 65°C (-40°F to 149°F) for 30W.	\$ 269.00	7331021069473	3.71	6.89
Small Form Factor Pluggable (SFP) transceiver module. Single mode 1310nm, 10km. Industrial grade.	\$ 109.00	7331021055704	0.09	4.13
Small Form Factor Pluggable (SFP) transceiver module. Multi mode 850nm, 550m. Industrial grade.	\$ 89.00	7331021055711	0.09	4.13
Small Form Factor Pluggable (SFP) transceiver module. Ethernet RJ-45 . Industrial grade	\$ 99.00	7331021055728	0.14	4.13
High PoE 1-port midspan 60W. Compliant with 802.3.at and PoE 802.3af.	\$ 159.00	7331021047402	1.23	8.46
Industrial midspan with extended temperature range, PoE 60W and dual DC 12/24 V DC power input for redundancy. Operating temperature - 40 to +75 degC or -40 to +167 °F. DIN and wall mount included.	\$ 269.00	7331021061149	1.19	4.53

AXIS TU8002-E is an outdoor ready IP66-rated midspan with up to 90 W power budget. The product is ideal for environmental challenging installations of PTZ and other devices with high power needs. The midspan support both IEEE802.3bt and HighPoE.	\$ 369.00	7331021077553	5.79	9.25
60W PoE midspan for 24V AC input.	\$ 159.00	7331021004665	1.23	3.74
DIN power supply. 12V DC, 2.1 A. For use in T98A to power cameras, media converters etc.	\$ 109.00	7331021045170	0.56	3.54
DIN power supply. 24V DC, 4.2 A. For use in AXIS Surveillance Cabinets to power cameras, media converters etc.	\$ 159.00	7331021061309	0.99	5.51
24V DC power supply with 240 W output power.	\$ 249.00	7331021061323	3.04	4.49
PoE splitter. Can deliver both 12 and 24 V DC (user selectable) from High PoE 60W midspan. Useful to power and connect non-PoE devices like IP cameras, magnetic locks for access control systems, WiFi AP, thin clients etc.	\$ 129.00	7331021052536	0.84	3.54
Power supply for AXIS Q86, Q87 & T99A product lines. 480W 24V 20A for DIN rail mounting.	\$ 319.00	7331021066342	3.09	5.71
Power supply for AXIS T8504-R Industrial PoE Switch. 240W 56V 5A for DIN rail mounting.	\$ 269.00	7331021066991	2.71	4.09
Power over Ethernet extender repeates the data signal and forward the PoE to the camera, PoE+ compliant it is compatible with all Axis cameras. No additional power supply is required. The maximum total distance between switch and camera depends on the power input and the power required by the camera, but all cameras can be at least extended to 200 meter connection.	\$ 199.00	7331021003972	0.22	7.09
AXIS T8129-E Outdoor PoE Extender repeats the data signal and PoE to the camera. AXIS T8129-E is PoE+ compliant with all Axis cameras and does not require an additional power supply. The maximum total distance between switch and camera depends on the power input and the power required by the camera, but all cameras can be at least extended to 200 meter connection.	\$ 299.00	7331021061071	0.39	3.35
Audio and I/O extension cable for AXIS P33 Series. Includes 4 pin terminal connector 2.5mm Female to Male, 2 x stereo plug 3.5mm Male to Female. 5 meter.	\$ 39.00	7331021027145	0.86	6.50

				1
AXIS Long range PoE Extender kit offers a smart and easy-to-install solution for extending the range of your network and PoE up to 1000m (3280ft.). Connect the product in-line with the CAT5e or CAT6 cable and power and data are forwarded to your Axis network devices. AXIS Long range PoE Extender kit supports both IEEE 802.3af and IEEE 802.3at compliant devices and can withstand challenging temperatures. The product is NEMA TS2 compatible.	\$ 539.00	7331021068636	0.75	4.72
AXIS Digital Audio Extension Kit enables AXIS T8355 Digital Microphone to extend to distances up to 100m (328 ft).	\$ 19.00	7331021065635	0.16	4.13
Audio extension cable for Axis 3.5mm mono microphones. Length 5m (197 in).	\$ 19.00	7331021065628	0.23	4.13
PoE+ managed gigabit network switch, optimized for Axis network products. 2 SFP/RJ45 uplink ports and 16 PoE+ ports with 250W power supply. Built in DCHP server for plug-and-play camera setup. Easy system configuration for effective installation of Axis network products.	\$ 749.00	7331021055308	8.33	11.81
PoE+ managed gigabit network switch, optimized for Axis network products. 2 SFP/RJ45 uplink ports and 24 PoE+ ports with 370W power supply. Built in DCHP server for plug-and-play camera setup. Easy system configuration for effective installation of Axis network products.	\$ 949.00	7331021061873	8.36	20.47
3.5mm audio jack extension for Axis Network Video products with terminal block audio connection.	\$ 10.00	7331021066854	0.10	4.13
Multi-connector cable for power (12VDC), audio and I/O port. 1m (40 in)	\$ 89.00	7331021040588	0.64	7.09
Pair of Ethernet over COAX adapters that enable use of COAX cables for PoE applications, supports IEEE802.3af/at. Powered by either PoE or power supply, dependent on power requirement at the device end. Diagnosics LEDs for power and link status in both base and device unit. Connectors: BNC and RJ45 connector and power input (for optional power supply). The package contains one base unit and one device unit.	\$ 549.00	7331021001619	0.49	6.89
Multi-connector cable for power (12VDC), audio and I/O port. 5m (197 in)	\$ 109.00	7331021040571	1.70	7.87
Single Base unit of Ethernet over COAX adapter. The package contains one base unit.	\$ 279.00	7331021001756	0.26	6.50
Multi-connector cable for AC/DC power, audio in/out and I/O connectivity. 2.5m (8.2 ft)	\$ 89.00	7331021046238	0.95	7.01
Single Device unit of Ethernet over COAX adapter. The package contains one device unit.	\$ 279.00	7331021001657	0.26	6.50

	•				1
Multi-connector cable for power, audio and I/O connectivity. 1m (3.3 ft)	\$	119.00	7331021048379	0.49	4.72
AXIS T8643 PoE+ over Coax Compact enables legacy coax cabling to be kept when converting an analog system to digital. The design allows for improved installation and cable management as it can easily be integrated in housings and backboxes. It delivers standard Power over Ethernet (PoE) and centrally- sourced power through existing coax cabling.	\$	279.00	7331021063686	0.33	6.30
Multi-connector cable for power, audio and I/O connectivity. 5m (16.4 ft)	\$	149.00	7331021048362	1.23	7.48
AXIS T8645 PoE+ over Coax Compact Kit enables legacy coax cabling to be kept when converting an analog system to digital, and comprises AXIS T8641 PoE+ Over Coax Base and AXIS T8643 PoE+ over Coax Compact. It delivers standard Power over Ethernet (PoE) and centrally-sourced power through existing coax cabling. The compact design of the AXIS T8643 PoE+ over Coax Compact allows for improved installation and cable management as it can easily be integrated in housings and backboxes.	\$	549.00	7331021063839	0.72	7.87
Ethernet over COAX blade (6ch) that enable use of COAX cables for PoE applications, supports IEEE802.3af/at. For use with Axis video encoder chassis together with our AXIS T8082 or AXIS T8085 power supplies. Requires one AXIS T8642 POE+ OVER COAX DEVICE for every channel at the camera end.	\$	749.00	7331021043947	0.97	6.69
A Kit that contains one (1) AXIS T8646 POE+ OVER COAX BLADE and six (6) AXIS T8642 POE+ OVER COAX DEVICE for a complete 6 channel solution.	\$	1,829.00	7331021043930	2.25	14.76
Outdoor CAT6 Ethernet cable for outdoor AXIS PTZ and panoramic cameras. IP66-rated male push pull connector on one end, IP20 rated male RJ45 connector on the other end. Length: 5m (16ft). Color: black.	\$	89.00	7331021032309	0.88	7.87
Outdoor CAT6 Ethernet cable for outdoor AXIS PTZ and panoramic cameras. IP66-rated male push pull connector on one end, IP20 rated male RJ45 connector on the other end. Length: 15m (50ft). Color: black.	\$	159.00	7331021007499	2.06	11.02
Cable between AXIS Q60XX-C and connection box AXIS T8605. Lenght: 12m (39ft).	\$	269.00	7331021006591	1.98	15.75

	•		 		
Heavy duty power cable, 22m (72ft) in length, 3- wire, 12AWG, jacket diameter 10mm (0.4in). Suitable for outdoor installation. UL20626 up to 90'C (194'F) ambient temperature. Designed for use with AXIS Positioning Cameras and Positioning Units, such as AXIS Q8685-E. Material: TPE insulation, copper wire, PVC-free and halogen-free. Color: Black.	\$	209.00	7331021055667	8.09	8.74
Female/female RJ45 coupler. For indoor use. Perfect when you need to extend a pre- terminated cable.	\$	11.00	7331021003743	0.04	4.72
Female/female RJ45 coupler. Slim and compact size. For indoor use. Perfect when you need to extend a pre-terminated cable.	\$	19.00	7331021005211	0.04	23.62
Electrical safety kit for AXIS T98A in countries where the mains power is 120 V DC. Included products: Surge protector class 2, Fuse/main switch, terminal blocks and an intrusion door switch.	\$	229.00	7331021038158	1.17	4.92
Pre-assembled T98A Surveilance cabinet with following system compoents: (1) Breaker and surge protection, (2), 12 VDC DIN PSU, (3)AXIS T8604 Media Converter, (4) Internal cables and mounts. Tested and verified with Axis cameras.	\$	969.00	7331021043404	11.68	12.87
 Pre-assembled T98A Surveilance cabinet with following system compoents: (1) Breaker and surge protection, (2), 12 VDC DIN PSU, (3)AXIS T8604 Media Converter, (4) Internal cables and mounts. Tested and verified with Axis cameras. 	\$	969.00	7331021043411	11.68	12.87
Pre-assembled T98A Surveilance cabinet with following system compoents: (1) Breaker and surge protection, (2), 12 VDC DIN PSU, (3)AXIS T8604 Media Converter, (4) Internal cables and mounts. Tested and verified with Axis cameras.	\$	899.00	7331021043428	11.68	12.87
 Pre-assembled T98A18-VE Surveilance cabinet with following system compoents: (1) Breaker and surge protection, (2), 12 VDC DIN PSU, (3) AXIS T8604 Media Converter, (4) Power cable and DIN clip for midspan AXIS T8124, (5) Internal cables and mounts. Tested and verified with Axis cameras. 	\$	969.00	7331021043435	11.68	12.87

Pre-assembled T98A Surveilance cabinet with following system compoents: (1) Breaker and surge protection, (2), 12 VDC DIN PSU, (3)AXIS T8604 Media Converter, (4) Internal cables and mounts. Tested and verified with Axis cameras.	\$ 969.00	7331021043442	11.68	12.87
24VAC power adapter for outdoor use. Output max 63VA.	\$ 159.00	7331021015289	3.57	10.63
24V DC power supply 250W with extended temperature (-40 to +75C (-40 to 167F)).	\$ 429.00	7331021055537	3.15	8.27
AC/DC to DC power converter for AXIS Q35-VE, 24 V AC or 12/24 V DC input. Backbox designed to match perfectly with camera.	\$ 199.00	7331021044494	1.43	8.07
AXIS TU8001 Ethernet Surge Protector helps reduce downtime, service and maintenance of your system by shielding your PoE devices against transient voltage spikes in the Ethernet cable. The product protects up to 10 kV surge, with data rates up to 1 Gbps. AXIS TU8001 is IEC 61643-21 complaint and can handle extended temperature ranges. Its compact form factor is ideal for surface or DIN-rail installations, in e.g. electrical cabinets. A high- quality product validated to work seamlessly with Axis devices.	\$ 69.00	7331021075849	0.22	2.17
Protect your Ethernet networks device, i.e. cameras, switches, midspans, etc, from lighting. Protects up to 10KV surge, IP66 and UL certified.	\$ 109.00	7331021054899	0.88	3.58
Rugged, male D-coded M12 connector compatible with AXIS M31XX-R M12 and Connector M12 Female 4P . Field installable with screw-in contacts. 10 pcs	\$ 159.00	7331021025059	0.86	6.50
10-pin system connector for power, audio and I/O.	\$ 39.00	7331021046948	0.11	4.72
RJ45 Field Connector (10 PCS) for easy assembly in the field without the need for special tools. Due to its compact size, it has a wide compatibility with Axis devices, like AXIS P32 Series or Network Cable Coupler IP66. Ready to be used with CAT6a ethernet cabling, AWG 26-22. Suitable for IEEE 802.3af, 802.3at, 802.3bt and Axis HighPoE solution.	\$ 129.00	7331021070578	0.27	5.51
AXIS Stereo-to-mono Adapter. Spare part to AXIS F44 Dual Audio Input Main Unit. Allows two microphones or line inputs to be connected to AXIS F44 Dual Audio Input.	\$ 29.00	7331021055469	0.22	4.13

AXIS Power Cable 24V 7m (23ft) helps extending the operating temperature of AXIS Q6010 / Q6100 -E up to -50° (-58°F) when installed in extreme cold environments.The power cable requires a 24V DC mains adapter (Not included).	\$ 39.00	7331021074590	0.62	6.50
AXIS TD8902 SFP+ Module LC.SR.X is an enhanced small form-factor pluggable (SFP+) transceiver that supplies network devices, such as a switches or routers, with a fiber optic network connection. It is industrial grade with a wide temperature range, and it includes link-loss that enable network redundancy. Complying with SFP+ Multisource Agreement (MSA), it is easy to install into compliant ports at any time without interrupting the online operation of the host equipment. Short wavelength (850 nm) VCSEL laser diodes enable data transmission up to 400 m on a multimode 50/125 µm optical fiber.	\$ 109.00	7331021080546	0.77	1.97
Small Form Factor Pluggable (SFP+) transceiver module. Single mode 1310nm, 10km. Industrial grade.	\$ 149.00	7331021080539	0.77	1.97
Power supply for D8208-R Industrial PoE++ Switch, 480W and for DIN rail mounting.	\$ 399.00	7331021080553	4.81	7.68
bt. compliant 60 W Midspan with additional SFP port	\$ 209.00	7331021082793	1.68	4.33
AXIS TU8004 is a single port 90 W midspan, compliant with IEEE 802.3bt and High PoE devices. Power over Ethernet (PoE) offers an easy, fast and cost-effective solution for powering network products. In a single network cable, a PoE midspan injects power and data to the network device with built-in PoE support. No need to replace existing Ethernet switches and cabling infrastructure. The midspan can be installed on a wall, shelf or DIN rail with AXIS T91A03 DIN Rail Clip A. Note: AXIS TU6011 Mains Cable is sold separately.	\$ 209.00	7331021085367	1.19	3.66

AXIS Surveillance Card 64 GB is a high endurance microSDXC [™] card optimized for video surveillance. It has support for health status monitoring with Axis cameras. The card enables flexible edge recording solutions with de-centralized video recording, eliminating the need of an onsite server, DVR or NVR. Optimizes bandwidth usage as video is recorded onboard each camera even when bandwidth is limited or absent. Combined with Axis Zipstream technology, even high quality video or longer retention times can be used effectively. Includes SD card adapter.	\$ 39.00	7331021056909	0.02	4.33
AXIS Surveillance Card 64 GB is a high endurance microSDXC™ card optimized for video surveillance. It has support for health status monitoring with Axis cameras. The card enables flexible edge recording solutions with de-centralized video recording, eliminating the need of an onsite server, DVR or NVR. Optimizes bandwidth usage as video is recorded onboard each camera even when bandwidth is limited or absent. Combined with Axis Zipstream technology, even high quality video or longer retention times can be used effectively. Includes SD card adapter. 10pack.	\$ 380.00	7331021056916	0.02	4.33
AXIS Surveillance Card 128 GB is a high endurance microSDXC [™] card optimized for video surveillance. It has support for health status monitoring with Axis cameras. The card enables flexible edge recording solutions with de-centralized video recording, eliminating the need of an onsite server, DVR or NVR. Optimizes bandwidth usage as video is recorded onboard each camera even when bandwidth is limited or absent. Combined with Axis Zipstream technology, even high quality video or longer retention times can be used effectively. Includes SD card adapter.	\$ 79.00	7331021063853	0.02	2.95
The 10 pack variant of the AXIS Surveillance Card 128 GB, a high endurance microSDXC™ card optimized for video surveillance. It has support for health status monitoring with Axis cameras.	\$ 765.00	7331021066366	0.18	0.39

AXIS Surveillance Card 256 GB is a high endurance microSDXC [™] card optimized for video surveillance. It has support for health status monitoring with Axis cameras. The card enables flexible edge recording solutions with de-centralized video recording, eliminating the need of an onsite server, DVR or NVR. Optimizes bandwidth usage as video is recorded onboard each camera even when bandwidth is limited or absent. Combined with Axis Zipstream technology, even high quality video or longer retention times can be used effectively. Includes SD card adapter.	\$ 139.00	7331021070844	0.02	4.72
AXIS Surveillance Card 256 GB (10pcs) are high endurance microSDXC [™] cards optimized for video surveillance. They have support for health status monitoring with Axis cameras. The cards enable flexible edge recording solutions with de-centralized video recording, eliminating the need of an onsite server, DVR or NVR. Optimizes bandwidth usage as video is recorded onboard each camera even when bandwidth is limited or absent. Combined with Axis Zipstream technology, even high quality video or longer retention times can be used effectively. Includes SD card adapters.	\$ 1,350.00	7331021070851	0.18	4.72
AXIS Surveillance Card 512 GB is a high endurance microSDXC [™] card optimized for video surveillance. It has support for health status monitoring with Axis cameras. The card enables flexible edge recording solutions with de-centralized video recording, eliminating the need of an onsite server, DVR or NVR. Optimizes bandwidth usage as video is recorded onboard each camera even when bandwidth is limited or absent. Combined with Axis Zipstream technology, even high quality video or longer retention times can be used effectively. Includes SD card adapter.	\$ 199.00	7331021076433	0.03	2.76

AXIS Surveillance Card 512 GB (10pcs) are high endurance microSDXC [™] cards optimized for video surveillance. They have support for health status monitoring with Axis cameras. The cards enable flexible edge recording solutions with de-centralized video recording, eliminating the need of an onsite server, DVR or NVR. Optimizes bandwidth usage as video is recorded onboard each camera even when bandwidth is limited or absent. Combined with Axis Zipstream technology, even high quality video or longer retention times can be used effectively. Includes SD card adapters.	\$ 1,940.00	7331021076440	0.22	3.15
AXIS Surveillance Card 1 TB is a high endurance microSDXC [™] card optimized for video surveillance. It has support for health status monitoring with Axis cameras. The card enables flexible edge recording solutions with de-centralized video recording, eliminating the need of an onsite server, DVR or NVR. Optimizes bandwidth usage as video is recorded onboard each camera even when bandwidth is limited or absent. Combined with Axis Zipstream technology, even high quality video or longer retention times can be used effectively. Includes SD card adapter.	\$ 429.00	7331021076457	0.03	2.76
AXIS Surveillance Card 1 TB (10pcs) are high endurance microSDXC [™] cards optimized for video surveillance. They have support for health status monitoring with Axis cameras. The cards enable flexible edge recording solutions with de-centralized video recording, eliminating the need of an onsite server, DVR or NVR. Optimizes bandwidth usage as video is recorded onboard each camera even when bandwidth is limited or absent. Combined with Axis Zipstream technology, even high quality video or longer retention times can be used effectively. Includes SD card adapters.	\$ 4,190.00	7331021076464	0.22	3.15
Surveillance Hard Drive 4TB is a 3.5-inch internal drive designed and tested for 24/7 reliable video surveillance. It is optimized for high-definition continuous or event triggered recordings and high write-cycle workloads. Suitable for storage expansion of compatible appliances, it enables for flexible storage solutions. Storage needs can be estimated with AXIS Site Designer 2 and appropriate recommendation will be provided.	\$ 259.00	7331021068643	1.76	5.91

				1
Surveillance Hard Drive 6TB is a 3.5-inch internal drive designed and tested for 24/7 reliable video surveillance. It is optimized for high-definition continuous or event triggered recordings and high write-cycle workloads. Suitable for storage expansion of compatible appliances, it enables for flexible storage solutions. Storage needs can be estimated with AXIS Site Designer 2 and appropriate recommendation will be provided.	\$ 389.00	7331021068650	1.85	5.91
Enterprise Hard Drive 4 TB is a 3.5-inch internal hard drive designed and tested for 24/7 reliable video surveillance. It is optimized for ultra-high- definition continuous or event-triggered recording at high workloads. Enterprise Hard Drive 4 TB can be added to an existing RAID array composed of drives of the same capacity. It is suitable for storage expansion of most products in AXIS S11 Series and AXIS S12 Series. Storage needs can be estimated with AXIS Site Designer and appropriate recommendation will be provided. Enterprise Hard Drive 4 TB is sold together with the HDD tray.	\$ 359.00	7331021077959	2.10	7.09
Enterprise Hard Drive 8 TB is a 3.5-inch internal hard drive designed and tested for 24/7 reliable video surveillance. It is optimized for ultra-high- definition continuous or event-triggered recording at high workloads. Enterprise Hard Drive 8 TB can be added to an existing RAID array composed of drives of the same capacity. It is suitable for storage expansion of most products in AXIS S11 Series and AXIS S12 Series. Storage needs can be estimated with AXIS Site Designer and appropriate recommendation will be provided. Enterprise Hard Drive 8 TB is sold together with the HDD tray.	\$ 569.00	7331021077966	2.24	7.09
Professional 22 button keypad for quick navigation between workspaces, camera views and PTZ. Connects to the workstation over USB. Includes a 2 meter USB cable for connection to the workstation. AXIS T8312 Keypad is supported in ACS ver. 3.3 or later.	\$ 469.00		2.31	7.48
Four port media converter switch with 2 RJ45 ports and 2 SFP slots for optical fiber connection (SFP modules not inluded). Shelf or DIN-rail mount. Temp spec: -40°C to +75°C (- 40°F to 167°F).	\$ 429.00	7331021037694	0.86	8.27

Four port media converter switch with 2 RJ45 ports and 2 SFP slots for optical fiber connection (SFP modules not inluded). Shelf or DIN-rail mount. Temp spec: -40°C to +75°C (- 40°F to 167°F). 24 V DC power in.	\$ 429.00	7331021058958	1.54	6.30
Indoor PIR detector especially made for Axis cameras to enhance motion detection. Easy plug and play connectivity to Axis I/O camera port.	\$ 39.00	7331021049918	0.60	6.50
Outdoor PIR detector especially made for Axis cameras to enhance motion detection. Easy plug and play connectivity to Axis I/O camera port.	\$ 129.00	7331021049925	0.82	6.50
PIR Motion Sensor for Axis Wireless I/O using Z-wave technology.	\$ 49.00	7331021062023	0.25	2.95
Door/window sensor for Axis Wireless I/O using Z-wave technology.	\$ 49.00	7331021062047	0.15	2.36
Panic button for Axis Wireless I/O using Z-wave technology.	\$ 49.00	7331021062061	0.26	2.95
Power on/off plug for Axis Wireless I/O using Z- wave technology.	\$ 49.00	7331021062085	0.44	2.95
AXIS T8353A Microphone 3.5mm is an omnidirectional microphone with a 3.5mm adaptor, compatible with all Axis network video products supporting a 3.5mm jack for microphone input. AXIS T8353A Microphone offers great details and resolution, the capsule has a neutral sonic character and is very natural sounding. The discreet microphone is very reliable even in demanding environments.	\$ 469.00	7331021005228	0.13	4.13
Mounting accessory for AXIS T8353 Microphones	\$ 19.00	7331021041257	0.00	2.36
Camera installation made easy. Battery driven Wi-Fi access point with PoE+ to camera for use with AXIS Installation application on your iOS or Android device.	\$ 649.00	7331021046702	6.86	15.75
Kit including AXIS T8415 Wireless Installation Tool, one extra AXIS Installation Tool Battery 12V3.4Ah and one AXIS Installation Bag.	\$ 749.00	7331021049642	12.96	16.54
Multi-connector cable for power, audio and I/O. Used for Indoor AXIS P55-series and Indoor Q60-series PTZ Dome Network Camera.	\$ 119.00	7331021031647	1.74	11.02
Durable soft bag to carry the AXIS T8415 Wireless Installation Tool, with space for extra battery, charger, network cables etc.	\$ 49.00	7331021049635	1.68	6.30
Additional battery for AXIS T8415 Wireless Installation Tool.	\$ 109.00	7331021048669	3.88	5.71
Power supply PS-P T-C for AXIS Q1755 and AXIS Q7404	\$ 39.00	7331021026360	1.21	6.50
Charging adaptor for AXIS T8415 Wireless Installation Tool.	\$ 49.00	7331021048652	0.40	4.72

Network I/O and audio module. Eight digital ports configurable as inputs or outputs. Two- way audio configurable to simplex, half or full duplex. Built-in pre-amp, phantom power and gain control for a balanced microphone. Line and speaker output. Serial port RS-232/422/485. Power over Ethernet enabled. Includes power supply.	\$ 379.00	7331021030367	1.85	7.48
AXIS D3110 gives sensor and audio capabilities to network video systems or other IoT systems that do not have them or need additional ones. The product comes with 2x Audio IN, Audio Out, 8x Configurable I/Os, Relay and RS485/422. The product can be Powered over Ethernet or through DC. AXIS D3110 supports MQTT, Vapix® and SIP. The product comes with Built-in cybersecurity functionality preventing unauthorized access.	\$ 379.00	7331021075139	1.32	6.30
Power supply with extended temperature specification -40°C to +75°C (-40°F to +167°F) providing 12 V DC to units such as AXIS T8604 and AXIS Q7424-R.	\$ 99.00	7331021003897	1.43	6.50
Compact IP66-rated female/female RJ45 cable coupler. Perfect when you need to extend a pre- terminated outdoor cable.	\$ 29.00	7331021037618	0.14	5.12
Power supply for AXIS P1311/43/44 and AXIS Q7401 as a spare part.	\$ 39.00	7331021003316	0.78	6.50
Power supply for the AXIS T8640 Coax Over Ethernet Adapter. If connected to the base end COAX adapter part, it powers up the connection, the device end unit and the PoE camera and thereby removes the need for a separate midspan. Can also be connected to the device end, to secure enought power (max 30W) to the connected PoE camera (COAX cable quality/long distance).	\$ 59.00	7331021001688	0.77	8.07
Indoor mains power supply. Output 24V DC 1.5A. Available for USA, AU, CN markets. As of August 2021 EU, UK, JP markets will be available again.	\$ 69.00	7331021035737	1.10	6.50
Power supply for AXIS Q60XX-C series -40 to +75C (-40 to 167F). In 90-264V AC 47-63Hz. Out 12,5V DC 85W.	\$ 429.00	7331021004870	3.42	8.27
Power supply 500W for use with AXIS T8646 POE+ OVER COAX BLADE in a 1U rack.	\$ 1,239.00	7331021044128	5.71	0.00

IR-illuminator for AXIS P334X-VE cameras. POE IEEE802.3af compliant. Operating temperature - 40 °C to 55 °C (-40 °F to 131 °F). IP66-, Nema 4X rated, vandal resistant. Premounted 5m network cable cable with gaskets.	\$ 379.00	7331021033900	2.06	14.37
IR LED illuminator for Axis network cameras. Included interchangeable diverging lenses providing 10°, 35°, 60° & 80° beam angles. Beam distance ranges 36m to 144m (118 ft to 472 ft). Made of IK09 impact-resistant aluminium and polycarbonate. IP66 and NEMA 4X ratings. Operating temperature -50°C to 50°C (-58 °F to 122 °F). 12/24 V DC or AC input.	\$ 479.00	7331021062160	2.73	5.91
PoE powered IR LED illuminator for Axis network cameras. Included interchangeable diverging lenses providing 10°, 35°, 60° & 80° beam angles. Beam distance ranges 36m to 144m (118 ft to 472 ft). Made of IK09 impact- resistant aluminium and polycarbonate. IP66 and NEMA 4X ratings. Operating temperature - 50°C to 50°C (-58 °F to 122 °F). PoE+ IEEE 802.3at required.	\$ 479.00	7331021062177	2.73	5.91
White LED illuminator for Axis network cameras. Included interchangeable diverging lenses providing 10°, 35°, 60° & 80° beam angles. Beam distance ranges 25 m to 110 m (80 ft to 360 ft). Made of IK09 impact resistant aluminium and polycarbonate. IP66 and NEMA 4X ratings. Operating temperature -50°C to 50°C (-58 °F to 122 °F). 12/24 V DC or AC input	\$ 479.00	7331021062214	2.73	5.91
PoE powered white LED illuminator for Axis network cameras. Included interchangeable diverging lenses providing 10°, 35°, 60° & 80° beam angles. Beam distance ranges 25 m to 110 m (80 ft to 360 ft). Made of IK09 impact resistant aluminium and polycarbonate. IP66 and NEMA 4X ratings. Operating temperature - 50°C to 50°C (-58 °F to 122 °F). PoE+ IEEE 802.3at required.	\$ 479.00	7331021062221	2.73	5.91
IR LED illuminator for Axis network cameras. Included interchangeable diverging lenses providing 10°, 35°, 60° & 80° beam angles. Beam distance ranges 70m to 350m (230ft to 1150 ft). Made of IK09 impact-resistant aluminium and polycarbonate. IP66 and NEMA 4X ratings. Operating temperature -50°C to 50°C (-58 °F to 122 °F). 12/24 V DC or AC input.	\$ 859.00	7331021062184	4.76	5.91

Do E now and ID I ED illuminator for Avia	¢	050.00	700400400404	4.70	7.00
PoE powered IR LED illuminator for Axis network cameras. Included interchangeable diverging lenses providing 10°, 35°, 60° & 80° beam angles. Beam distance ranges 70m to 350m (230ft to 1150 ft). Made of IK09 impact- resistant aluminium and polycarbonate. IP66 and NEMA 4X ratings. Operating temperature - 50°C to 50°C (-58 °F to 122 °F). PoE+ IEEE 802.3at required.	\$	859.00	7331021062191	4.76	7.68
White LED illuminator for Axis network cameras. Included interchangeable diverging lenses providing 10°, 35°, 60° & 80° beam angles. Beam distance ranges 35m to 180m (115ft to 590ft). Made of IK09 impact-resistant aluminium and polycarbonate. IP66 and NEMA 4X ratings. Operating temperature -50°C to 50°C (-58 °F to 122 °F). 12/24 V DC or AC input.	\$	859.00	7331021062238	4.76	7.68
PoE powered white LED illuminator for Axis network cameras. Included interchangeable diverging lenses providing 10°, 35°, 60° & 80° beam angles. Beam distance ranges 35m to 180m (115ft to 590ft). Made of IK09 impact- resistant aluminium and polycarbonate. IP66 and NEMA 4X ratings. Operating temperature - 50°C to 50°C (-58 °F to 122 °F).PoE+ IEEE 802.3at required.	\$	799.00	7331021062245	4.76	7.68
IR LED illuminator for Axis network cameras. Included interchangeable diverging lenses providing 10°-140° beam angles. Beam distance ranges 105m to 500m (345ft to 1640ft). Made of IK09 impact-resistant aluminium and polycarbonate. IP66 and NEMA 4X ratings. Operating temperature -50°C to 50°C (-58 °F to 122 °F). 12/24 V DC or AC input.	\$	1,289.00	7331021062207	7.72	7.24
Accessory lens providing 120° beam angle, beam distance is 15 m (49 ft). Compatible with AXIS T90B25 W-LED.	\$	29.00	7331021044449	0.06	4.72
Accessory lens providing 120° beam angle, beam distance 20 m (66 ft). Compatible with AXIS T90B20 IR-LED.	\$	29.00	7331021044463	0.06	4.72
Accessory lens providing 120° beam angle, beam distance 20 m (66 ft). Compatible with AXIS T90B35 W-LED.	\$	39.00	7331021044456	0.10	4.72
Accessory lens compatible with AXIS T90B30 IR LED providing 120° beam angle, beam distance 30 m (98 ft). Also compatible with AXIS T90B40 IR-LED (two lenses are required as the illuminator has two panels). The beam angle can be adjusted between 120° and 180°, with a beam distance stretching from 65 m to 45 m (213 ft to 148 ft). This sales part includes one lens.		39.00	7331021044470	0.10	4.72
Accessory lens providing 120° beam angle	\$	39.00	7331021062665	0.11	4.72

The remote control is compatible with all Axis T90B illuminators and provides the possibility to adjust settings of light intensity, photocell sensitivity and more conveniently from the ground level. No lift or ladder required. The remote control feature can be disabled after the installation is finalized to avoid tampering.	\$ 39.00	7331021044425	0.08	0.00
Mounting bracket for AXIS T90 illuminators.	\$ 39.00	7331021062252	1.06	5.35
Mounting bracket for AXIS T90 illuminators.	\$ 49.00	7331021062269	0.88	5.12
Mounting bracket for AXIS T90 illuminators.	\$ 69.00	7331021062276	1.98	5.59
Intrusion door switch for AXIS T98A,	\$ 29.00	7331021003781	0.20	6.50
connection to I/O port. AXIS Dome Intrusion Switch C can be placed in compatible Axis dome cameras and devices to trigger an event upon removal of the casing. Connects directly to the I/O port.	\$ 19.00	7331021067844	0.15	4.13
Angled C13 mains cable for use when limited space. Open ends for installation in terminal blocks etc. Use when installing midspan into AXIS T98A Surveillance cabinet.	\$ 19.00	7331021046887	0.18	11.81
AXIS Fixed Box IR Illuminator Kit A for AXIS P1375-E. For mounting on AXIS P13 Series camera. Range of reach 50 m (164 ft) or more depending on the scene. Powered by AXIS P13 Series camera. Requires Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 4 midspan power for AXIS P13 Series camera.	\$ 109.00	7331021064645	0.66	7.09
Illuminator Kit for AXIS P13 Series and AXIS Q1656-BE. Offers both and 850nm or 940nm wavelength. Powered by the camera. Camera requires Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 4 midspan power for AXIS P13 Series and AXIS Q1656-BE camera. AXIS TQ1901-E IR ILLUMINATOR KIT is included in AXIS Q1656-LE and AXIS Q1656- BLE	\$ 159.00	7331021074521	0.77	3.54
AXIS I/O Indication LED is an easy to install signaling accessory for all AXIS devices that support 12 V I/O and can be setup through the event handling of the device to address desired deterrence or privacy concerns. The LED comes with IP44 rating. Up to three LEDs could be installed with AXIS devices that support 50 mA load on their I/O ports. This product comes in a 4-pack.	\$ 69.00	7331021067486	0.20	4.13

AXIS Camera Heater Power Supply helps	\$	109.00	7331021071339	1.37	6.50
extending the operating temperature of AXIS Q6010 / Q6100 -E up to -50°C (-58°F) when installed in extreme cold environments.	·				
Illuminator Kit compatible with: AXIS P1375-E, AXIS P1377-LE, AXIS P1378-LE, AXIS Q1656- BE, AXIS Q1656-BLE, AXIS Q1656-LE. Offers IR with White light module – 840nm with white leds. Powered by the camera. Camera requires Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 4 midspan. Note there is a similar illuminator kit for same cameras: 02194-001 and the difference is only the White light, where: 02194-001 – IR with IR modules – 840nm with 940nm.	\$	159.00	7331021074538	0.77	1.97
4 pack accessory casing to prevent tampering. Offer a secure way by a screw to increase the tamper resistance by replacing standard cover with the new Tamper Cover. It require special tools (resitorx) to open the cover. Allen key, TX6 screw, cover, cover top hatch come in the package. Compatible with M3085-V, M3086-V, M3088-V.	\$	79.00	7331021079458	0.38	4.13
4 pack accessory casing to prevent tampering. Offer a secure way by a screw to increase the tamper resistance by replacing standard cover with the new Tamper Cover. It require special tools (resitorx) to open the cover. Allen key, TX6 screw, cover, cover top hatch come in the package. Compatible with M4216-LV/V.	\$	59.00	7331021079557	0.58	4.33
Wireless communication kit for AXIS M1075-L Box Camera. The kit includes a wireless adapter and a power injector for AXIS M1075-L Box Camera. This allows the camera to communicate with 2.4 GHz and 5 GHz frequency. The wireless adapter supports 802.11ac/b/g/n. The power injector is powered by 100-240 V AC (50-60 Hz). Requires ethernet cable.	\$	69.00	7331021080447	0.88	5.71

AXIS D4100-E Network Strobe Siren helps deter intruders and improve operations with the power of light and sound. Flexible to configure with a combination of RGBA light patterns and sounds up to 110 dB. Easy to setup through two configurable I/O ports, VAPIX, MQTT or SIP. Power over Ethernet. IP66 and IK10 outdoor ready, vandal-resistant casing. Includes mounting bracket for wall/ceiling or junction boxes.	\$ 429.00	7331021069459	2.69	7.68
AXIS D2110-VE Security Radar, 24.05–24.25 GHz, FMCW, for wall mounting outdoor. Reliable 180 degrees horizontal field of detection 24/7 with built-in analytics including classification of humans and vehicles. Complement to video surveillance enables filtering on distance, customized detection zones, and auto-tracking for PTZ cameras. Trigger events to activate camera recording, audio notification or light source for deterrence. Open API for software integration, microSD/SDHC memory card slot for edge storage, 30W PoE out to power an additional device, 4 input/output ports, 24 V DC relay port. Powered by PoE+ (IEEE 802.3at, Type 2 Class 4) or DC 8-28V. IP66, IK08 and NEMA 4. Operating conditions -40°C to 60°C (-40°F to 140°F).	\$ 1,699.00	7331021065017	9.15	15.63
AXIS D2210-VE Security Radar, White front. 61.0–61.5 GHz, FMCW, for pole and wall mount. Reliable 95 degrees horizontal field of detection 24/7 with built-in analytics including classification of humans and vehicles. Optimized for both area monitoring and traffic monitoring. Complement to video surveillance enables filtering on distance, customized detection zones, Radar Autotracking and Radar Autotracking for PTZ cameras. Trigger events to activate camera recording, audio notification or light source for deterrence. Integrated dynamic LEDs for deterrence. Open API for software integration, microSD/SDHC memory card slot for edge storage. 30W PoE out to power an additional device, 1 input and 1 output ports, 24 V DC. Powered by PoE (IEEE 802.3bt, Type 3 Class 6) or DC 8-28V. IP66, IK08 and NEMA 4. Operating conditions -40°C to 60°C (-40°F to 140°F).	\$ 1,199.00	7331021086753	6.00	10.04

AXIS D2210-VE Security Radar, Black front. 61.0–61.5 GHz, FMCW, for pole and wall mount. Reliable 95 degrees horizontal field of detection 24/7 with built-in analytics including classification of humans and vehicles. Optimized for both area monitoring and traffic monitoring. Complement to video surveillance enables filtering on distance, customized detection zones, Radar Autotracking and Radar Autotracking for PTZ cameras. Trigger events to activate camera recording, audio notification or light source for deterrence. Integrated dynamic LEDs for deterrence. Open API for software integration, microSD/SDHC memory card slot for edge storage. 30W PoE out to power an additional device, 1 input and 1 output ports, 24 V DC. Powered by PoE (IEEE 802.3bt, Type 3 Class 6) or DC 8-28V. IP66, IK08 and NEMA 4. Operating conditions -40°C to 60°C (-40°F to 140°F).	\$ 1,199.00	7331021083646	6.00	10.04
AXIS D8004 Unmanged PoE Switch is a 4 channel 10/100 Mbps PoE+ switch with plug & play installation. The unmanaged switch comes with a 60 W power budget and is perfect as an entry-level switch for small systems with PoE requirements.	\$ 109.00	7331021072565	1.92	6.10
Outdoor 4-port managed PoE switch for surveillance applications. 4 PoE ports with up to 60W PoE per port and one SFP port for uplink. Robust metal enclosure with wide temperature range, IP67 and surge protection for demanding installations. Managed switch for remote configuration and management.	\$ 1,299.00	7331021063488	6.44	9.45
AXIS T8504-R Industrial PoE Switch is a 4-port managed industrial PoE++ Gigabit switch. In addition, the switch is equipped with 2 x RJ45 and 2x SFP data ports that allows for extra devices to be connected. The switch uses the same intuitive administrator interface as AXIS T85 PoE Network Switch Series, is ruggedized with a wide temperature range and NEMA TS2 compliant.	\$ 749.00	7331021066199	2.23	8.27
AXIS D8208-R Industrial PoE Switch is a 8-port managed industrial PoE++ Gigabit switch. In addition, the switch is equipped with 2 x RJ45 and 2x SFP data ports that allows for extra devices to be connected. The switch uses the same intuitive administrator interface as AXIS T85 PoE Network Switch Series, is ruggedized with a wide temperature range and NEMA TS2 compliant.	\$ 1,099.00	7331021080225	3.48	6.69

PoE+ managed fanless gigabit network switch,	\$ 449.00	7331021061828	6.22	14.17
optimized for Axis network products. 2 SFP/RJ45 uplink ports and 8 PoE+ ports with 130W power supply. Built in DCHP server for plug-and-play camera setup. Easy system configuration for effective installation of Axis network products				14.17
AXIS P8221 in 10-pack/bulk. Cannot be sold separately as single pack. NO midspans. Power supplies not included.	\$ 3,779.00	7331021030312	11.79	14.17
AXIS T6101 MKII Audio and I/O Interface enabling external two-way audio and configurable supervised inputs / digital outputs for Axis cameras even when they do not have such functionality built-in. Powered by standard Power over Ethernet and PoE passthrough to camera. Allows the connected camera to provide one stream for audio and video, without the need for any additional IP address.	\$ 129.00	7331021079335	0.26	3.31
AXIS T6112 MKII Audio and I/O Interface combines AXIS T6101 MKII Audio and I/O Interface with two microphones in a discreet casing suitable for indoor installation on wall or ceiling. Powered by standard Power over Ethernet and PoE passthrough to camera. Two- way audio and configurable supervised inputs / digital outputs for Axis cameras even when they do not have such functionality built-in. Allows the connected camera to provide one stream for audio and video, without the need for any additional IP address.	\$ 179.00	7331021079342	0.66	5.51
AXIS TW1100 Clip Mount 5P 5 pack mount for the Klick Fast adaptor on the Axis body worn cameras. The clip mount is an easy to use, versatile mount suitable for many types of clothing.	\$ 109.00	7331021073005	0.60	7.87
AXIS TW1101 MOLLE Mount 5P. 5 pack mount for the Klick Fast adaptor on the Axis body worn cameras. The MOLLE mount is especially suitable for the MOLLE system found on tactical equipment and such.	\$ 79.00	7331021073012	0.37	8.66
AXIS TW1102 Magnet Mount 5P 5 pack mount for the Klick Fast adaptor on the AXIS W100 Body Worn Camera. The magnet mount is a rugged, versatile mount suitable for many types of clothing	\$ 469.00	7331021073029	1.83	5.12

AXIS TW1103 Chest Harness Mount 5P 5 pack mount for the Klick Fast adaptor on the Axis body worn cameras. The chest harness mount holds the camera independent of choice of clothing.	()	189.00	7331021073036	1.63	6.50
5 pack mount for the Klick Fast adaptor on the Axis body worn cameras. The magnet mount is a rugged, versatile mount suitable for many types of clothing. This updated version perfectly follows the shape of the camera and has an improved stability to the camera.	\$	439.00	7331021077287	1.79	3.54
5 pack mount for the Klick Fast adaptor on the Axis body worn camera. The harness center mount holds the camera independent of choice of clothing. It features a large, soft mount pad, centered on the body, and its elastic bands makes it easy to adjust and comfortable to wear.	\$	349.00	7331021079700	2.43	12.99
For flexible and light wearing of the AXIS W110 Body Worn Camera on any fabric. Comes in 5- pack.	\$	129.00	7331021081680	0.34	2.76
AXIS W110 Body Worn Camera mount for secure wearing compatible with all Klick Fast mounts. Comes in 5-pack.	\$	149.00	7331021081697	0.48	4.13
As an accessory to the Axis body worn cameras the AXIS TW1200 Body Worn Mini Bullet Sensor is designed to offer a flexible recording position. It supports the Picatinny mounting system, making it compatible with many kinds of available gear, and especially suitable for helmets. AXIS TW1200 offers the same optical performance as the body worn camera with sharp images even in challenging conditions. Mounting options are included.	\$	219.00	7331021069572	0.36	5.71
As an accessory to the Axis body worn cameras the AXIS TW1201 Body Worn Mini Cube Sensor is designed to offer a flexible on-chest recording position. Its less prominent form factor, very low weight and flexible magnet mount makes it suitable to wear on lighter clothing, like a t-shirt or even on the lapel of a blazer, and is perfect for usage outside law enforcement. AXIS TW1201 offers the same optical performance as the body worn camera with sharp images even in challenging conditions. Magnet mount included.	\$	189.00	7331021075238	0.21	3.23

As an accessory to the Axis body worn camera the AXIS TW1201 Body Worn Mini Cube Sensor is designed to offer a flexible on-chest recording position. Its less prominent form factor, very low weight and flexible magnet mount makes it suitable to wear on lighter clothing, like a t-shirt or even on the lapel of a blazer, and is perfect for usage outside law enforcement. AXIS TW1201 offers the same optical performance as the body worn camera with sharp images even in challenging conditions. Magnet mount included.	\$ 189.00		7331021075450	0.21	3.23
5 pack adhesive picatinny rail to mount the AXIS TW1200 Body Worn Mini Bullet Sensor on general equipment.	\$ 69.00		7331021071254	0.25	4.33
5 pack replacement cable holder to securely connect the AXIS TW1200 Body Worn Mini Bullet Sensor cable to the Axis body worn cameras.	\$ 34.00		7331021071247	0.19	4.33
5 pack replacement lens protector for AXIS TW1200 Body Worn Mini Bullet Sensor.	\$ 79.00		7331021071261	0.14	4.33
Demonstration kit consisting of 3 mounts, 1 of each AXIS TW1101, AXIS TW1102 and AXIS TW1103.	\$ 159.00		7331021074477	1.01	9.45
5 pack mount for the AXIS TW1201 Body Worn Mini Cube Sensor. The magnet mount is a light and versatile mount suitable for many types of clothing and positions.	\$ 99.00	•	7331021075467	0.24	4.57
The AXIS 1906 Battery Replacement kit includes everything needed to safely replace the battery in the AXIS W100 Body Worn Camera or the AXIS W101 Body Worn Camera. Included in the kit are 5x replacement batteries, a plastic camera opening tool, a Torx T6 and spare screws.	\$ 399.00		7331021082564	1.06	6.50

The AXIS TW8100 Rack Mount is an accessory that makes it possible to conveniently place multiple AXIS W800 System Controller:s in a 19- inch rack. This mount therefore enables easy placement of the Axis body worn system's controllers in a server room with controlled physical access and operational environment. The TW8100 Rack Mount is flexible and allows both horizontal and vertical placement of devices. In horizontal placement, up to 2 pcs of W800 System Controller are supported and will occupy 2U in height. In vertical placement, up to 6 pcs of controllers are supported and will occupy only 5U in height. NB: Vertical mounting is only compatible with the AXIS W800 System Controller of revision 2 (R2).	\$ 169.00	7331021075870	7.41	22.05
AXIS W100 Body Worn Camera is an easy-to- use, lightweight and robust body worn camera with an operating time of over 12 hours at 1080p. It delivers sharp images even in challenging conditions and has dual microphones for excellent audio and noise suppression. AXIS W100 features the Klick Fast System, making it compatible with most available mounting options, the TW1100 Clip Mount is included. In addition, Axis Zipstream technology allows users to store as much footage as they require without compromising image quality. The camera also features a GPS/GNSS receiver for location data, Bluetooth Low Energy 4.1, IEEE 802.11b/g/n, and a 6-axis gyro and accelerometer. Docking stations and system controller are sold separately.	\$ 649.00	7331021066960	0.64	6.22
24 pack of AXIS W100 Body Worn Camera. Mounts, docking stations and system controller are sold separately.	\$ 14,999.00	7331021077300	11.33	13.78

AXIS W101 Body Worn Camera is a robust and	\$ 699.00	7331021075436	0.64	4.72
AXIS W101 Body Worn Camera is a robust and easy-to-use body worn camera featuring the KlickFast mounting system. It delivers clear audio with noise suppression and exceedingly sharp images in every frame. Axis Zipstream technology lowers bandwidth and storage requirements without compromising video quality. AXIS W101 offers over 12 hours of battery time at 1080p and charging with any USB-C® charger. Recording is activated automatically upon unholstering and person down. And the location of the camera is continuously recorded with the built-in GNSS receiver (location tracking). Built-in Bluetooth®, and network technologies provide wireless communication with, for example, the AXIS Body Worn Assistant mobile app. TW1100 Clip Mount included; docking stations and system controller are sold separately.	\$ 699.00	/3310210/5436	0.64	4.72
AXIS W101 Body Worn Camera is a robust and easy-to-use body worn camera featuring the KlickFast mounting system. It delivers clear audio with noise suppression and exceedingly sharp images in every frame. Axis Zipstream technology lowers bandwidth and storage requirements without compromising video quality. AXIS W101 offers over 12 hours of battery time at 1080p and charging with any USB-C® charger. Recording is activated automatically upon unholstering and person down. And the location of the camera is continuously recorded with the built-in GNSS receiver (location tracking). Built-in Bluetooth®, and network technologies provide wireless communication with, for example, the AXIS Body Worn Assistant mobile app. TW1100 Clip Mount included; docking stations and system controller are sold separately.	\$ 699.00	7331021075443	0.64	4.72
24 pack of AXIS W101 Body Worn Camera, Black:沪 Mounts, docking stations and system controller are sold separately.	\$ 16,199.00	7331021077447	11.55	13.78

AXIS W110 Body Worn Camera is made for a safer workplace and is used to deter, protect, and document events. It's sleek and friendly design opens for use in all segments outside law enforcement. With a compact formfactor and low weight together with innovative mounts using strong magnets for flexible mounting. AXIS W110 offers excellent image and audio quality with exceedingly sharp images and clear audio for forensic usability. Built-in Bluetooth®, and network technologies provide wireless communication with, for example, live streaming with AXIS Body Worn Live or the AXIS Body Worn Assistant mobile app. Recording can be activated automatically using Bluetooth® beacons.	\$ 599.00	7331021083790	0.35	4.33
AXIS W110 Body Worn Camera is made for a safer workplace and is used to deter, protect, and document events. It's sleek and friendly design opens for use in all segments outside law enforcement. With a compact formfactor and low weight together with innovative mounts using strong magnets for flexible mounting. AXIS W110 offers excellent image and audio quality with exceedingly sharp images and clear audio for forensic usability. Built-in Bluetooth®, and network technologies provide wireless communication with, for example, live streaming with AXIS Body Worn Live or the AXIS Body Worn Assistant mobile app. Recording can be activated automatically using Bluetooth® beacons.	\$ 599.00	7331021083783	0.35	4.33
AXIS W110 Body Worn Camera is made for a safer workplace and is used to deter, protect, and document events. It's sleek and friendly design opens for use in all segments outside law enforcement. With a compact formfactor and low weight together with innovative mounts using strong magnets for flexible mounting. AXIS W110 offers excellent image and audio quality with exceedingly sharp images and clear audio for forensic usability. Built-in Bluetooth®, and network technologies provide wireless communication with, for example, live streaming with AXIS Body Worn Live or the AXIS Body Worn Assistant mobile app. Recording can be activated automatically using Bluetooth® beacons.	\$ 2,995.00	7331021085633	1.21	3.94

AXIS W110 Body Worn Camera is made for a safer workplace and is used to deter, protect, and document events. It's sleek and friendly design opens for use in all segments outside law enforcement. With a compact formfactor and low weight together with innovative mounts using strong magnets for flexible mounting. AXIS W110 offers excellent image and audio quality with exceedingly sharp images and clear audio for forensic usability. Built-in Bluetooth®, and network technologies provide wireless communication with, for example, live streaming with AXIS Body Worn Live or the AXIS Body Worn Assistant mobile app. Recording can be activated automatically using Bluetooth® beacons.	\$ 2,995.00	7331021085657	1.21	3.94
 1-year license for AXIS Body Worn Live, used to stream live video, audio and metadata from our body worn cameras. Secure and reliable, it supports informed decision making by operators and provides an added sense of safety for the camera wearers. AXIS Body Worn Live has several layers of security and the transmission is protected by full end-to-end encryption, ensuring that customer owns their encryption keys. It offers 24-hour data retention, and stream gap retrieval ensures that the customer never miss a thing despite any temporary connection dropout. Being a web-based application it's compatible with PCs, tablets and Android mobile devices and works independently of the user's choice of video or evidence management system. Note: One license key per order line 	\$ 199.00			

 AXIS Case Insight securely gathers evidence in an easy-to-manage, centralized location. All types of digital evidence can be uploaded and it's easy to collaborate with internal investigators and share information externally. With automatic redaction of faces, it's easy to protect sensitive information and ensure the public's privacy remains intact. Designed with cybersecurity in mind, it offers end-to-end encryption of videos from the AXIS W100 Body Worn Camera. Audit trail functionality records every change made to the files ensuring your evidence can hold up in court. This end-to-end solution with integration possibilities automatically collects evidence from Axis body worn cameras. Furthermore, with all hardware, software, and hosting from Axis, users can benefit from one, complete solution from one, trusted supplier. Includes access and unlimited storage for Body Worn Camera videos from one camera during one year. Additional storage for other evidence are sold separately. NB: A reference key is required to place an order. Please go to https://axis.com/bodyworn- registration 	\$ 948.			
NB: Only for existing Case Insight users. Case Insight Additional Storage provides 1 TB of storage in AXIS Case Insight for non-body worn digital evidence material during one year. This could be almost any video file, image file or even document. Such material is either uploaded from inside Case Insight or through a Public Upload portal from anyone with a mobile phone. All digital evidence material can efficiently be organized in cases and easily shared both internally and externally. NB: A reference key is required to place an order. Please go to https://axis.com/bodyworn- registration	\$ 948.	00		

	 	-	
 NB: For customers requiring CJIS storage AXIS Case Insight securely gathers evidence in an easy-to-manage, centralized location. All types of digital evidence can be uploaded and it's easy to collaborate with internal investigators and share information externally. With automatic redaction of faces, it's easy to protect sensitive information and ensure the public's privacy remains intact. Designed with cybersecurity in mind, it offers end-to-end encryption of videos from the AXIS W100 Body Worn Camera. Audit trail functionality records every change made to the files ensuring your evidence can hold up in court. This end-to-end solution with integration possibilities automatically collects evidence from Axis body worn cameras. Furthermore, with all hardware, software, and hosting from Axis, users can benefit from one, complete solution from one, trusted supplier. Includes access and unlimited storage for Body Worn Camera videos from one camera during one year. Additional storage for other evidence are sold separately. NB: A reference key is required to place an order. Please go to https://axis.com/bodyworn- registration 	\$ 948.00		
NB: For customers requiring CJIS storage NB: Only for existing Case Insight users Case Insight Additional Storage provides 1 TB of storage in AXIS Case Insight for non-body worn digital evidence material during one year. This could be almost any video file, image file or even document. Such material is either uploaded from inside Case Insight or through a Public Upload portal from anyone with a mobile phone. All digital evidence material can efficiently be organized in cases and easily shared both internally and externally. NB: A reference key is required to place an order. Please go to https://axis.com/bodyworn- registration	\$ 948.00		

NB: For users in Canada AXIS Case Insight securely gathers evidence in an easy-to-manage, centralized location. All types of digital evidence can be uploaded and it's easy to collaborate with internal investigators and share information externally. With automatic redaction of faces, it's easy to protect sensitive information and ensure the public's privacy remains intact. Designed with cybersecurity in mind, it offers end-to-end encryption of videos from the AXIS W100 Body Worn Camera. Audit trail functionality records every change made to the files ensuring your evidence can hold up in court. This end-to-end solution with integration possibilities automatically collects evidence from Axis body worn cameras. Furthermore, with all hardware, software, and hosting from Axis, users can benefit from one, complete solution from one, trusted supplier. Includes access and unlimited storage for Body Worn Camera videos from one camera during one year. Additional storage for other evidence	\$ 948.00			
	\$ 948.00			
Case Insight Additional Storage provides 1 TB of storage in AXIS Case Insight for non-body worn digital evidence material during one year. This could be almost any video file, image file or even document. Such material is either uploaded from inside Case Insight or through a Public Upload portal from anyone with a mobile phone. All digital evidence material can efficiently be organized in cases and easily shared both internally and externally. NB: A reference key is required to place an order. Please go to https://axis.com/bodyworn- registration				

AXIS W800 System Controller is the central integration and management point of the body worn solution. It ensures a high speed and supervised data offloading from the cameras and has built in temporary storage. A single AXIS W800 supports up to five docking stations and 40 cameras and larger body worn systems can easily be extended with additional system controllers. Power adaptor and mounting bracket are included.	\$ 1,199.00	7331021071834	4.19	8.86
AXIS W700 Docking Station 1 Bay charges the battery and ensures easy data offloading of a single body worn camera. Power adaptor included.	\$ 109.00	7331021068001	1.08	3.94
AXIS W701 Docking Station 8 Bay charges the batteries and ensures easy data offloading of up to eight body worn cameras. Power adaptor included.	\$ 599.00	7331021068025	3.53	5.51
AXIS W702 Docking Station 1 Bay charges the battery and ensures easy data offloading of a single AXIS W110 body worn camera. Power adaptor included.	\$ 109.00	7331021080911	1.03	11.81
AXIS W703 Docking Station 8 Bay charges the batteries and ensures easy data offloading of up to eight AXIS W110 body worn cameras. Power adaptor included.	\$ 599.00	7331021080980	3.68	5.31
AXIS W400 Body Worn Activation Kit automatically activates recording by all body worn cameras in the same system when a lightbar or siren is activated, or a panic button is pressed, ensuring there is always evidence captured of escalated events.	\$ 499.00	7331021085992	1.72	6.30

Depth inches	Height inches
6.50	7.40
4.45	5.39
4.33	1.26
5.20	5.20
5.20	5.20
5.20	5.20
4.29	5.20
4.29	5.20
4.29	5.20

4.29	5.20
4.29	5.20
4.29	5.20
3.11	5.39
6.69	7.09
3.11	5.39
6.69	7.09
3.11	5.39
6.69	7.09
3.11	5.39
6.69	7.09
4.29	5.20
4.29	5.20
4.29	5.20
4.29	5.20
4.29	5.20
4.29	5.20
4.29	5.20
4.29	5.20

5.98	2.01
0.39	0.12
6.57	0.87
4.29	1.18
3.90	0.79
5.04	1.38
3.35	1.18
3.35	1.18
7.56	0.28
8.70	5.91
8.70	5.91
5.91	3.90
5.91	8.70
12.20	6.10
12.20	6.10
12.20	6.10
12.20	6.10
12.20	6.10
12.20	6.10

16.1410.2447.0115.989.846.695.319.453.354.924.411.1812.206.1012.206.1012.206.109.6513.587.5610.837.5610.837.5610.832.763.945.918.666.307.366.307.366.307.366.307.366.307.366.576.89		
9.84 6.69 5.31 9.45 3.35 4.92 4.41 1.18 12.20 6.10 12.20 6.10 12.20 6.10 9.65 13.58 7.56 10.83 7.56 10.83 2.76 3.94 5.91 8.66 6.30 7.36 6.30 7.36 6.30 7.36	16.14	10.24
5.31 9.45 3.35 4.92 4.41 1.18 12.20 6.10 12.20 6.10 12.20 6.10 9.65 13.58 7.56 10.83 7.56 10.83 2.76 3.94 5.91 8.66 6.30 7.36 6.30 7.36 6.30 7.36 6.30 7.36	47.01	15.98
3.35 4.92 4.41 1.18 12.20 6.10 12.20 6.10 12.20 6.10 9.65 13.58 7.56 10.83 7.56 10.83 2.76 3.94 5.91 8.66 6.30 7.36 6.30 7.36 6.30 7.36	9.84	6.69
4.41 1.18 12.20 6.10 12.20 6.10 12.20 6.10 12.20 6.10 9.65 13.58 7.56 10.83 7.56 10.83 2.76 3.94 5.91 8.66 6.30 7.36 6.30 7.36 6.30 7.36	5.31	9.45
12.20 6.10 12.20 6.10 12.20 6.10 12.20 6.10 9.65 13.58 7.56 10.83 7.56 10.83 2.76 3.94 5.91 8.66 6.30 7.36 6.30 7.36 6.30 7.36	3.35	4.92
12.20 6.10 12.20 6.10 9.65 13.58 7.56 10.83 7.56 10.83 2.76 3.94 5.91 8.66 6.30 7.36 6.30 7.36 6.30 7.36 6.30 7.36	4.41	1.18
12.20 6.10 9.65 13.58 7.56 10.83 7.56 10.83 2.76 3.94 5.91 8.66 6.30 7.36 6.30 7.36 6.30 7.36 6.30 7.36	12.20	6.10
9.65 13.58 7.56 10.83 7.56 10.83 2.76 3.94 5.91 8.66 6.30 7.36 6.30 7.36 6.30 7.36 6.30 7.36	12.20	6.10
7.56 10.83 7.56 10.83 2.76 3.94 5.91 8.66 6.30 7.36 6.30 7.36 6.30 7.36 6.30 7.36 6.30 7.36	12.20	6.10
7.56 10.83 2.76 3.94 5.91 8.66 6.30 7.36 6.30 7.36 6.30 7.36 6.30 7.36	9.65	13.58
2.76 3.94 5.91 8.66 6.30 7.36 6.30 7.36 6.30 7.36 6.30 7.36	7.56	10.83
5.91 8.66 6.30 7.36 6.30 7.36 6.30 7.36 6.30 7.36	7.56	10.83
6.30 7.36 6.30 7.36 6.30 7.36 6.30 7.36	2.76	3.94
6.30 7.36 6.30 7.36 6.30 7.36	5.91	8.66
6.30 7.36 6.30 7.36	6.30	7.36
6.30 7.36	6.30	7.36
	6.30	7.36
6.57 6.89	6.30	7.36
	6.57	6.89

6.57	6.81
7.91	6.89
6.30	7.40
6.30	7.40
6.30	7.40
6.30	7.40
7.01	14.80
7.09	15.00
9.80	15.71

9.80	15.71
8.70	14.61
7.56	10.63
7.56	10.83
7.56	10.83
7.56	10.83
2.76	3.94
3.27	4.72
10.83	0.28
9.37	2.09
2.76	3.94
2.76	3.94
4.33	10.47
4.33	10.47
4.33	10.47
4.33	10.47
4.33	10.47

4.33	1.22
4.41	1.22
4.41	1.22
5.31	4.33
4.41	1.22
4.33	5.20
4.41	1.22
4.41	1.22
4.33	1.18
4.33	1.22
6.69	3.74
5.87	1.38
4.65	2.76
4.33	10.51
4.33	10.51
4.33	10.47
4.33	10.47

4.29	10.51
4.29	10.51
4.33	1.22
4.33	1.22
4.33	1.22
3.86	1.38
5.00	2.99
4.02	0.98
4.02	0.98
4.02	0.98
4.02	0.98

3.94	7.87
5.31	9.45
4.61	9.33
2.09	0.79
3.90	5.91
5.71	2.09
3.31	1.10
3.31	4.69
2.80	0.79
1.89	0.39
2.80	3.90
2.80	3.90
4.41	1.18
4.41	1.18
4.09	10.79
4.21	1.18
4.29	1.18
4.29	1.18

4.291.184.295.204.295.204.291.186.420.986.420.986.4610.636.4610.636.380.986.380.986.576.776.5010.836.501.974.411.224.3310.514.3310.51
4.29 5.20 4.29 1.18 6.42 0.98 6.42 0.98 6.46 10.63 6.46 10.63 6.38 0.98 6.38 0.98 6.57 6.77 6.50 10.83 6.50 1.97 4.41 1.22 4.33 10.51
4.29 1.18 6.42 0.98 6.42 0.98 6.46 10.63 6.46 10.63 6.38 0.98 6.38 0.98 6.57 6.77 6.50 10.83 6.50 1.97 4.41 1.22 4.33 10.51
6.42 0.98 6.42 0.98 6.46 10.63 6.46 10.63 6.38 0.98 6.38 0.98 6.57 6.77 6.50 10.83 6.50 1.97 4.41 1.22 4.33 10.51
6.42 0.98 6.46 10.63 6.46 10.63 6.38 0.98 6.38 0.98 6.57 6.77 6.50 10.83 6.50 1.97 4.41 1.22 4.33 10.51 4.33 10.51
6.46 10.63 6.46 10.63 6.38 0.98 6.38 0.98 6.57 6.77 6.50 10.83 6.50 1.97 4.41 1.22 4.41 1.22 4.33 10.51 4.33 10.51
6.46 10.63 6.38 0.98 6.38 0.98 6.57 6.77 6.50 10.83 6.50 1.97 4.41 1.22 4.41 1.22 4.33 10.51
6.38 0.98 6.38 0.98 6.38 0.98 6.57 6.77 6.50 10.83 6.50 1.97 4.41 1.22 4.41 1.22 4.33 10.51
6.38 0.98 6.57 6.77 6.50 10.83 6.50 1.97 4.41 1.22 4.41 1.22 4.33 10.51 4.33 10.51
6.57 6.77 6.50 10.83 6.50 1.97 4.41 1.22 4.41 1.22 4.33 10.51 4.33 10.51
6.50 10.83 6.50 1.97 4.41 1.22 4.41 1.22 4.33 10.51 4.33 10.51
6.50 1.97 4.41 1.22 4.41 1.22 4.33 10.51 4.33 10.51
4.41 1.22 4.41 1.22 4.33 10.51 4.33 10.51
4.41 1.22 4.33 10.51 4.33 10.51
4.33 10.51 4.33 10.51
4.33 10.51
4.33 13.82
4.33 13.82

4.33	5.63
4.41	10.47
4.37	1.22
12.80	13.86
12.80	13.86
12.80	1.18
12.80	13.86
4.02	0.98
2.01	0.98

0.00	0.00
2.17	0.04
2.17	0.04
1.57	0.20
1.57	2.36
4.13	5.91
1.18	0.39
3.62	2.48
0.02	2.40
7.52	4.92

4.72	2.17
1.57	2.36
6.69	8.27
2.17	3.35
1.18	1.57
4.49	3.66
4.49	3.66
6.81	1.46
7.09	10.71
4.41	7.87
0.20	0.28
9.37	2.09
9.37	2.09
7.01	2.01
4.96	1.06
4.96	10.63
4.96	1.06
4.96	1.06
4.96	1.06

5.91
5.91
5.91
5.91
5.91
0.39
0.39
1.06
0.39
0.39
0.39
5.51
4.72
4.72
1.06
1.06
2.09
10.00
8.31

2.52	2.72
6.30	7.91
2.40	2.40
3.90	2.40
7.72	2.40
7.72	2.40
5.91	3.54
7.72	2.40
7.72	2.40

	,
7.80	9.57
7.80	9.57
5.51	5.71
5.91	5.91
5.31	2.80
5.51	6.50

4.29	6.69
5.71	4.49
12.99	11.81
4.69	5.51
7.09	8.31
4.02	10.00
13.82	3.31
10.63	3.54
8.11	4.21
8.11	4.21
8.11	4.21
8.11	4.21
8.27	6.30
8.27	6.30
3.74	3.74

12.40	6.10
9.84	13.98
5.51	3.27
5.51	3.27
4.13	10.83
15.16	3.15
6.69	4.33
4.72	1.69

	-
5.91	1.57
4.13	2.48
6.10	6.50
4.92	1.38
4.92	1.81

6.30	4.13
4.33	1.89
4.13	1.54
9.45	2.36
8.66	2.17
12.01	0.59
7.01	1.57
5.91	1.57
6.50	2.76
6.50	2.56

11.73	1.18
5.91	1.50
9.45	1.97
9.45	3.15
9.45	3.15
10.04	3.54

6.65	4.33
5.12	2.52
19.69	15.55
9.45	3.54
9.45	3.54

8.66	2.95
16.93	9.45

9.45	3.15
9.65	3.15
15.55	6.10

	· · · · · · · · · · · · · · · · · · ·
6.30	3.54
6.10	2.68
0.10	2.00
6.50	2.17

6.50	2.17
4.33	1.57
6.61	1.57

7.09	1.77
6.30	1.18
6.50	0.79
12.20	2.36
5.12	1.18
6.30	0.79
6.69	0.79
4.53	2.05
6.89	0.98

5.91	0.39
6.10	1.38
5.91	0.08
5.51	0.00
6.69	1.18
9.65	1.18
6.10	1.38
5.91	1.46
5.91	1.46
7.09	1.77
7.09	1.77
7.09	1.77
7.09	1.77
9.45	3.94
9.45	3.94
7.09	1.77
9.25	3.15
0.20	0.10
9.45	3.15
A 17	
9.45	3.15

9.45	3.15
6.10	1.38
9.57	3.15
9.57	3.15
9.57	3.15
9.57	3.15
7.09	1.77
7.09	1.57
5.12	3.74
5.12	3.74
5.12	3.74
5.12	3.74

- / -	
5.12	3.74
5.12	3.74
0.12	0.74
5.12	3.74
0.1.2	•
5.12	3.74
6.69	4.92
5.12	3.74
4.76	3.70
5.12	3.74
- 10	
5.12	3.74
6.89	5.71
0.03	ə. <i>t</i> i
5.12	3.74
V.12	0.14
7.09	1.57
9.45	3.15
9.45 5.91	0.20
5.91	0.20
5.91	0.59
5.91	0.59
5.91	0.12
5.91	0.12

8.31 6.61 10.24 5.91 17.32 5.71 17.32 5.71 15.16 19.88 15.35 20.28 4.53 4.53 5.31 1.38 5.91 1.46		
17.32 5.71 17.32 5.71 15.16 19.88 15.35 20.28 4.53 4.53 5.31 1.38	8.31	
15.16 19.88 15.35 20.28 4.53 4.53 5.31 1.38		
15.35 20.28 4.53 4.53 5.31 1.38		
4.53 4.53 5.31 1.38		
5.31 1.38	15.35	
		4.53
5.91 1.46	5.31	1.38
	5.91	1.46

7.28	4.72
7.09	5.91
5.51	1.38
6.89	1.57
3.94	1.18
7.09	1.18
9.84	5.12
7.01	1.46
9.06	3.74

8.27	1.57
10.24	2.36
6.30	1.97

8.66	8.74
8.27	1.57
10.24	2.56

4.65	1.14
5.91	1.50
5.91	1.50
4.72	1.18
4.72	1.18
6.89	1.18
2.05	0.59
5.91	1.18

5.91	1.18
6.50	3.15
21.46	1.57
10.24	2.36
8.46	3.74
21.65	8.66

21.65	8.66
21.26	7.28
27.95	10.63
22.56	8.86
7.48	5.51
15.20	5.04

15.20	5.04
15.20	5.04
19.69	6.89
16.54	3.66
14.88	6.65
14.88	6.65

14.88	6.65
14.88	6.65
14.88	6.65
12.40	14.57
8.66	1.97
5.31	3.74
5.12	3.74

6.10	1.38
12.80	3.94
16.14	10.83
7.87	3.15
7.87	1.57
15.16	6.10
15.16	6.10
7.28	6.30
15.98	4.72
10.24	2.17
13.39	4.33
14.37	3.94
6.89	1.97

	40.04
6.89	10.24
14.96	3.35
20.67	5.71
15.16	6.10
15.16	6.10
5.12	7.48
14.57	1.57
8.66	4.33
8.66	4.33
5.12	7.48
10.04	5.31
10.04	0.01
6.54	2.28
7.48	5.12
7.40	5.12
7.68	4.33
9.45	4.13
6.89	10.24

8.27	7.87
26.38	3.35
6.30	7.68
7.09	5.12
7.28	4.72
7.28	7.28
7.95	5.39
9.84	4.13
7.28	4.72
6.69	6.69
5.12	3.74
5.51	4.13
3.94	4.33
4.33	4.33
4.33	4.33
8.86	4.33

6.22	6.22	
5.91	4.33	
8.35	6.22	
8.35	6.22	
11.57	2.76	
11.57	2.76	
7.56	7.83	
7.56	7.83	
10.43	2.76	
12.60	13.39	
8.46	6.69	
19.69	8.46	
8.35	6.22	
8.35	6.22	

7.09 5.12 8.35 6.22 8.46 6.69 14.96 3.94 6.69 3.74 6.69 3.74 6.69 3.74 9.06 5.31 9.84 4.13 10.04 5.31		
8.46 6.69 14.96 3.94 6.69 3.74 6.69 3.74 6.69 3.74 8.94 5.24 9.06 5.31 9.84 4.13	7.09	5.12
14.96 3.94 6.69 3.74 6.69 3.74 6.69 3.74 8.94 5.24 9.06 5.31 9.84 4.13		
6.69 3.74 6.69 3.74 6.69 3.74 8.94 5.24 9.06 5.31 9.84 4.13	8.46	6.69
6.69 3.74 6.69 3.74 8.94 5.24 9.06 5.31 9.84 4.13		
8.94 5.24 9.06 5.31 9.84 4.13	6.69	3.74
9.06 5.31	6.69	3.74
9.84 4.13	8.94	5.24
	9.06	5.31
10.04 5.31	9.84	4.13
	10.04	5.31

8.03	2.91
10.43	6.18
11.57	2.91
11.61	2.76
7.87	2.56
9.45	3.15
4.72	1.77
4.72	1.77
4.13	4.72

12.20	4.53
8.66	4.61
5.71	3.74
7.48	3.35
7.09	6.30
5.31	5.31
4.33	4.33
4.33	5.91
7.28	4.72
7.28	4.72
15.75	8.66
12.60	3.94
1.97	0.79

	,
4.13	1.57
26.38	19.49
6.06	2.95
11.34	14.96
10.43	8.46
16.34	11.22
22.44	7.48
4.13	4.33

4.72 1.38 23.62 22.44	
23.62 22.44	
4.13 1.57	
4.13 1.57	
4.13 1.57	
8.66 6.10	
6.30 3.15	
4.33 1.57	
4.33 1.57	
3.15 0.79	
3.15 0.79	
3.15 0.79	

4.72	2.36
2.36	1.38
2.36	1.77
6.10	1.38
3.03	1.97
4.33	2.76
4.33	2.76
5.91	1.57
5.12	3.74
5.12	3.74
7.87	0.08
6.10	1.38
3.15	5.51

7.09	1.77
6.89	3.94
6.89	3.74
6.89	3.74
7.48	2.24
5.91	3.15
6.89	3.54
4.33	2.17
10.24	2.95

10.24	2.95
11.22	4.02
11.22	4.13
9.69	7.95
11.22	1.77
10.04	1.57
12.80	5.91
7.48	3.62

17.13	10.83
17.52	9.06
15.55	1.57
17.13	11.22
8.46	3.74
12.99	7.09

6.69	2.60
0.00	2.00
10.63	11.42
16.93	11.02
16.93	11.02
39.96	4.72
15.75	1.77
31 50	4 53
31.50	4.03

45.67	6.69
7.28	7.68
13.39	2.56
40.75	2.56
41.93	4.33
31.69	3.35
51.05	5.55
13.98	8.07

10.24	3.15
9.06	3.54
14.37	6.69
10.43	6.30
9.45	3.15
12.01	3.66
5.12	3.74
5.12	3.74
12.60	10.24
12.60	8.46
12.40	8.07

7.68	4.33
4.92	0.39
4.45	2.28
6.10	5.51
6.30	6.30
7.28	0.98
4.92	1.97
11.22	6.30
1.18	6.89

E 04	E 40
5.91 8.66	5.12
4.72	4.53
6.30	7.87
9.45	3.15
7.28	7.68
6.89	0.98
7.09	1.57
9.45	2.36
7.48	7.09
9.45	4.13

10.43	7.68
11.02	2.17
10.24	2.76
12.40	3.15
12.40	4.33
11.42	5.31
11.81	4.92
9.45	3.15

13.58	4.72
8.78	4.33
5.91	2.68
5.91	2.00
44 00	
11.22	3.35
11.22	3.35
11.22	3.35
11.22	3.35
11.22	3.35
11.22	3.35
11.22	3.35
18.90	7.68
18.90	7.68
18.90	7.68
18.90	7.68
18.90	7.68
18.90	7.68

8.66 2.36 8.46 2.36 7.48 3.15 7.48 3.15 10.24 2.36 9.65 4.53 12.01 4.13 10.24 8.27		
7.48 3.15 7.48 3.15 7.48 3.15 10.24 2.36 9.65 4.53 12.01 4.13	8.66	2.36
7.48 3.15 10.24 2.36 9.65 4.53 12.01 4.13	8.46	2.36
10.24 2.36 9.65 4.53 12.01 4.13		
9.65 4.53 12.01 4.13	7.48	3.15
12.01 4.13	10.24	2.36
	9.65	4.53
10.24 8.27		
	10.24	8.27

10.43	8.27
14.37	12.01
10.43	10.63
12.80	7.28
10.04	8.11
11.22	9.65
15.35	8.86
7.09	1.57
3.35	0.39
9.45	3.15
5.12	3.74
5.12	3.74
4.92	1.38

9.45 3.15 3.15 1.18 8.07 3.03 8.50 4.13 10.04 5.31 9.45 10.04 5.12 3.74 5.12 3.74
8.07 3.03 8.50 4.13 10.04 5.31 9.45 10.04 5.12 3.74
8.50 4.13 10.04 5.31 9.45 10.04 5.12 3.74
10.04 5.31 9.45 10.04 5.12 3.74
9.45 10.04 5.12 3.74
5.12 3.74
5.12 3.74
4.72 1.57
5.20 3.74
6.10 1.38
5.12 1.65

5.12	1.77
22.64	2.76
7.28	4.72
6.10	1.38
7.09	1.57
7.09	1.57
6.10	1.38
5.12	3.74
7.09	1.77
7.48	2.95
7.48	2.95
35.43	2.95

35.43	2.95
8.66	3.54
5.12	1.18
4.53	1.97
7.68	1.97
7.68	1.97
10.43	3.35
11.42	3.35
8.86	6.89

11.42	3.35
6.30	5.91
6.30	6.10
7.48	3.54
6.89	1.18
8.86	1.97
10.04	3.23
9.06	6.89

8.86	6.69
7.00	3.15
7.28	3.15
7.28	3.35
1.20	3.35
4.53	2.09
4.53	2.09
=	
7.09	2.36
7.09	1.38
7.09	1.46
1.00	··••
0.40	
8.19	3.07
-	
8.86	2.68
4.53	2.09
7.55	2.05

7.09	1.18
13.98	5.91
9.45	2.64
10.63	7.68
31.50	4.65
7.09	2.56
7.09	3.35
8.74	2.87
12.60	8.35
7.09	4.33

8.86	6.89
6.30	5.91
6.89	1.38
6.89	1.38
10.87	1.85
3.74	0.79
3.15	0.39
7.28	2.24
4.65	1.77

4.72	1.77
4.72	1.77
4.65	1.77
4.72	1.77
9.25	3.74

12.99	3.94
10.63	7.48
5.75	2.20
11.85	1.85
12.60	8.27
11.61	2.76
9.84	2.36

10.91	2.28
	-
7.87	2.91
11.81	7.68
11.81	9.25

25.98	22.05
14.76	28.74
11.02	20.47
7.87	1.97
7.28	4.53
29.13	10.43

27.17	1.57
8.66	1.97
8.66	1.97
12.99	1.38
12.99	1.38

0.00	0.00
21.65	5.71
10.83	11.61

19.69	5.24	
9.45	10.63	
13.78	10.24	

13.78	10.24
7.68	3.94

14.37	10.43
14.57	10.45
9.65	7.87
9.65	7.87
9.65	7.87
9.65	7.87
9.65	7.87
9.65	7.87
9.65	7.87
9.65	7.87
9.65	7.87
9.65	7.87
9.65	7.87
9.65	7.87
9.65	7.87
9.65	7.87
9.65	7.87
9.65	7.87
9.65	7.87
9.65	7.87
9.65	7.87
9.65	7.87
9.65	7.87
9.65	7.87
9.65	7.87
9.65	7.87
9.65	7.87

	·	
15.24	12.05	
11.42	10.63	
24.49	4.02	

24.49	4.02
10.47	7.36
12.99	1.38
12.33	1.50

10.35	2.56
6.89	1.50
5.31	1.77
7.09	1.22

6.89	1.46
23.62	9.84

10.24	7.09

15.35	8.46
15.35	0.40
1	
20.47	12.60

25.98 5.12	12.20
5.51	3.54

5.12	3.54
5.12	3.54
5.51	3.54

7.87	3.35
7.87	3.35
7.87	3.35

7.87	3.35
7.68	3.35
7.87	3.35
7.87	3.35
7.87	3.35

		1
14.17	5.51	
14.17	5.71	

13.78	5.51
7.87	3.35

7.68 3.35 21.65 11.02 7.87 3.35	7.87	3.35
21.65 11.02		
21.65 11.02		
21.65 11.02		
21.65 11.02		
21.65 11.02		
21.65 11.02		
7.87 3.35	21.65	11.02
	7.87	3.35

		1
14.17	5.51	
14.17	5.71	

14.17	5.51	
6.69	5.12	

6.69	5.12
23.62	7.87
23.02	1.01
6.81	4.57
0.01	
6.81	4.57
23.62	7.87
23.62	7.87

-		
6.38	5.20	
0.00		
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	

-		
6.38	5.20	
0.00		
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	

-		
6.38	5.20	
0.00		
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	
6.38	5.20	

11.81	3.35
6.50	2.76
7.87	2.36

10.71	3.62	
10.71	3.62	

22.64	8.50
21.06	8.66

22.64	8.50
21.06	8.66

10.24	3.94	
10.24	3.94	

21.26	8.66	
21.26	8.66	

21.26	8.66	
21.26	8.66	

21.65	8.66
21.65	8.66
10.01	0.01
10.24	3.94
10.24	3.94
10.24	3.94

21.26	8.66	
21.26	8.66	

21.26	8.66	
21.26	8.66	
	0.00	

12.20	5.51
12.20	5.51
12.40	5.55
12.40	5.55
12.40	5.55
12.40	5.55
12.40	5.55
12.40	5.55
12.40	5.55
12.40	5.55
12.40	5.55
12.40	5.55
12.40	5.55
12.40	5.55
12.40	5.55
12.40	5.55
12.40	5.55
12.40	5.55
12.40	5.55
12.40	5.55
12.40	5.55
12.40	5.55
12.40	5.55
12.40	5.55

40.57		
10.24	6.30	
12.48	5.59	
	1	

10 I		
10.35	6.38	
5.51	6.22	

5.51	6.22
12.40	5.51
12.40	5.51
12.40	5.51
12.40	5.51
12.40	5.51
12.40	5.51
12.40	5.51
12.40	5.51
12.40	5.51
12.40	5.51
12.40	5.51
12.40	5.51
12.40	5.51
12.40	5.51
12.40	5.51
12.40	5.51
12.40	5.51
12.40	5.51
12.40	5.51
12.40	5.51
12.40	5.51
12.40	5.51
12.40	5.51
12.40	5.51
12.40	5.51
12.40	5.51

5.71	6.30
12.40	5.51
12.40	5.51
12.40	5.51
12.40	5.51
12.40	5.51
12.40	5.51
12.40	5.51
12.40	5.51
12.40	5.51
12.40	5.51
12.40	5.51
12.40	5.51
12.40	5.51
12.40	5.51
12.40	5.51
12.40	5.51
12.40	5.51
12.40	5.51
12.40	5.51
12.40	5.51
12.40	5.51
12.40	5.51
12.40	5.51
12.40	5.51
12.40	5.51
12.40	5.51
12.40	5.51
12.40	5.51
12.40	5.51
12.40	5.51

5.71	6.30
7 48	4.06
7.48	4.06
7.48	4.06
7.48	4.06
7.48	4.06
7.48	4.06
7.48	4.06
7.48	4.06
7.48	4.06
7.48	4.06
7.48	4.06
7.48	4.06
7.48	4.06
7.48	4.06
7.48	4.06
7.48	4.06
7.48	4.06
7.48	4.06
7.48	4.06
7.48	4.06
7.48	4.06
7.48	4.06
7.48	4.06
7.48	4.06
7.48	4.06
7.48	4.06
7.48	4.06
7.48	4.06
7.48	4.06
7.48	4.06
7.48	4.06

27.95	11.02
7.48	4.06
7.48	4.06
7.48	4.06

10.63	3.74
27.56	11.02
	1.7.1
10.63	3.74

27.56	11.02
27.50	11.02
10.63	3.94

10.63	3.94	
10.05	5.54	

21.06	8.66

8.66

21.06	8.66

8.27	11.81

12.20	6.30
0.25	2.94
9.25	3.94
9.25	3.94
9.25	3.94
9.25	3.94
9.25	3.94
9.25	3.94
9.25	3.94
9.25	3.94
9.25	3.94
9.25	3.94
9.25	3.94
9.25	3.94
9.25	3.94
9.25	3.94
9.25	3.94
9.25	3.94
9.25	3.94
9.25	3.94
9.25	3.94
9.25	3.94
9.25	3.94
9.25	3.94
9.25	3.94
9.25	3.94
9.25	3.94
9.25	3.94
9.25	3.94
9.25	3.94
9.25	3.94
9.25	3.94
9.25	3.94
9.25	3.94
9.25	3.94
9.25	3.94

47.07	
17.87	9.25
16.14	9.25
16.14	9.25
16.14	9.25
16.14	9.25
16.14	9.25
16.14	9.25
16.14	9.25
16.14	9.25
16.14	9.25
16.14	9.25
16.14	9.25
16.14	9.25
16.14	9.25
16.14	9.25
16.14	9.25
16.14	9.25
16.14	9.25
16.14	9.25
16.14	9.25
16.14	9.25
16.14	9.25
16.14	9.25
16.14	9.25
16.14	9.25
16.14	9.25
16.14	9.25
16.14	9.25
16.14	9.25
16.14	9.25
16.14	9.25
16.14	9.25

16.14	9.25	
-		

15.55	9.45

15.55 8.27	

15.55	8.27	
6.69	2.76	

6.30	2.76
7.48	2.95
7.87	2.36
7.28	1.57

6.89	11.61
10.04	2.36

9.84	5.91
3.27	1.77
3.27	1.77
6.89	3.15

7.09	2.76
4 33	3 15
4.33	3.15
4.33	3.15
4.33	3.15
4.33	3.15
4.33	3.15
4.33	3.15
4.33	3.15
4.33	3.15
4.33	3.15
4.33	3.15
4.33	3.15
4.33	3.15
4.33	3.15
4.33	3.15
4.33	3.15
4.33	3.15
4.33	3.15
4.33	3.15
4.33	3.15
4.33	3.15
4.33	3.15
4.33	3.15
4.33	3.15
4.33	3.15
4.33	3.15
4.33	3.15
4.33	3.15

6.89	3.15	
4.76	1.57	

	4 == 1	1
4.76	1.57	
4 70	4 57	
4.72	1.57	
4.72	1.57	
4.72	1.57	
4.72	1.57	
4.72	1.57	
4.72	1.57	
4.72	1.57	
4.72	1.57	
4.72	1.57	
4.72	1.57	
4.72	1.57	
4.72	1.57	
4.72	1.57	
4.72	1.57	
4.72	1.57	
4.72	1.57	
4.72	1.57	
4.72	1.57	
4.72	1.57	
4.72	1.57	
4.72	1.57	
4.72	1.57	
4.72	1.57	
4.72	1.57	
4.72	1.57	
4.72	1.57	
4.72	1.57	
4.72	1.57	

7.40	4.07
7.48	1.97
7.48	1.97
7.40	1.97

·	· · · · · · · · · · · · · · · · · · ·
7.48	1.97
4.72	1.30
9.45	3.07

5.12	2.87
15.55	8.07
5.31	5.31

5.31	5.31
4.53	2.95
4.33	3.54
4.33	3.54

4.33	3.54
4.33	3.54
4.92	2.95

4.92	2.95
4.33	3.54
4.33	3.54

4.33	3.54
4.33	3.54
7.68	5.12

7.87	5.31
6.89	3.54
6.30	3.54

5.51	4.72	
5.51	4.72	
5.51	4.72	
5.51	4.84	

4.33	4.65
4.33	4.65
7.87	5.24

7.87	5.24
7.87	5.71

7.87	3.54
5.31	3.54
5.31	3.54

4.92	3.15
4.92	3.15
5.31	3.54

5.31	3.54
6.30	3.54

6.89 3.74 6.89 3.74
6.89 3.74
6.89 3.74
6.89 3.74
6.89 3.74
6.89 3.74
6.89 3.74
6.89 3.74
6.89 3.74
6.89 3.74
6.89 3.74
6.89 3.74
6.89 3.74
6.89 3.74
6.89 3.74
6.89 3.74
6.89 3.74
6.89 3.74
6.89 3.74
6.89 3.74
6.89 3.74
6.89 3.74
6.89 3.74
6.89 3.74
6.89 3.74
6.89 3.74
6.89 3.74
6.89 3.74

4.92	3.74	
4.92	3.74	
4.92	3.74	
4.92	3.74	
4.92	3.74	
4.92	3.74	
4.92	3.74	
4.92	3.74	
4.92	3.74	
4.92	3.74	
4.92	3.74	
4.92	3.74	
4.92	3.74	
4.92	3.74	
4.92	3.74	
4.92	3.74	
4.92	3.74	
4.92	3.74	
4.92	3.74	
4.92	3.74	
4.92	3.74	
4.92	3.74	
4.92	3.74	

8.46	9.45	
6.34	5.20	

40 40	E 94	
10.43	5.31	
6.34	5.20	
	0.20	
	0.20	

7.87	5.31
6.34	5.20
6.34	5.20
6.34	5.20
6.34	5.20
6.34	5.20
6.34	5.20
6.34	5.20
6.34	5.20
6.34	5.20
6.34	5.20
6.34	5.20
6.34	5.20
6.34	5.20
6.34	5.20
6.34	5.20
6.34	5.20
6.34	5.20
6.34	5.20
6.34	5.20
6.34	5.20
6.34	5.20
6.34	5.20
6.34	5.20
6.34	5.20
6.34	5.20
6.34	5.20
6.34	5.20
6.34	5.20
6.34	5.20
6.34	5.20
6.34	5.20

40.00		
10.63	5.51	
6 30	5 12	
6.30	5.12	
6.30	5.12	
6.30	5.12	
6.30	5.12	
6.30	5.12	
6.30	5.12	
6.30	5.12	
6.30	5.12	
6.30	5.12	
6.30	5.12	
6.30	5.12	
6.30	5.12	
6.30	5.12	
6.30	5.12	
6.30	5.12	
6.30	5.12	
6.30	5.12	
6.30	5.12	
6.30	5.12	

6.30	5.12
10.63	5.51

6.34	5.20
8.27	5.91

6.38	6.38	
0.30	0.30	
8.27	- 04	
	591	
0.27	5.91	
0.27	5.91	
0.27	5.91	
0.27	5.91	
0.27	5.91	
0.27	5.91	
0.27	5.91	
0.27	5.91	
0.27	5.91	
0.27	5.91	
0.27	5.91	
0.21	5.91	
0.21	5.91	
0.21	5.91	
0.21	5.91	
0.21	5.91	
0.21	5.91	
0.21	5.91	
0.21	5.91	
0.21	5.91	
0.21	5.91	

7.87	5.31
6.42	6.46

7.87	5.31	
8.27	5.91	
8.27	5.91	
8.27	5.91	
8.27	5.91	
8.27	5.91	
8.27	5.91	
8.27	5.91	
8.27	5.91	
8.27	5.91	
8.27	5.91	
8.27	5.91	
8.27	5.91	
8.27	5.91	
8.27	5.91	
8.27	5.91	
8.27	5.91	
8.27	5.91	
8.27	5.91	
8.27	5.91	
8.27	5.91	
8.27	5.91	
8.27	5.91	
8.27	5.91	
8.27	5.91	

6.34	5.20
6.34	5.20
7.48	4.33

9.45	4.72
9.06	4.33
12.60	5.00

13.78	4.53
13.58	4.72
13.58	4.72
13.58	4.72

10.63	11.81	
9.06	10.63	

-	
9.06	10.63
6.69	3.74
0.09	3.74
21.65	11.02
25.20	11.42
25.20	11.42
6.34	5.20
6.69	3.74
21.65	11.02
21.00	11.02
	1

6.34	5.20
25.20	11.42
6.69	3.74
0.03	0.74
9.45	12.01
9.45	12.01
21.65	11.02
25.20	11.42
20.20	11.44
6.69	3.74

21.65	11.02
25.20	11.42
21.65	11.02
6.69	3.74
21.65	11.02
25.20	11.42
6.69	3.74
21.65	11.02
25.20	11.42
21.65	11.02

4.72	3.35
14.37	11.02
4.72	3.35

44.4-	11.02
5.51	3.74
5.51	3.74

4.72	3.35
7.87	5.31
14.37	11.02

4.72	3.35
14.37	11.02
7.09	4.61
7.09	4.33

0.04	40.00
9.84	12.60
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67

9.25	10.47
0.45	40.07
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67
9.45	10.67

8.66	10.83

10.43 7.48
10.43 7.48

9.06	13.19
9.00	13.19
•	
9.65	4.53
9.65	4.53
10.24	8.07

10.24	8.07
10.24	5.31

10.24	5.31
6.69	3.94
6.30	3.19
6.30	3.19

11.22	7.80
11.22	7.80
6.30	3.19
6.30	3.19
11.22	7.80
11.22	7.80

29.92	4.29
29.92	3.94

7.40	E 40
7.48	5.12
16.93	25.98

16.93	25.98
11.81	8.27
6.89	4.33
5.51	6.30

6.30	6.30
8.66	9.65
8.86	17.40
8.86	15.35

A /-	10.00
9.45	12.60
17.09	11.34
15.75	11.42

10.24	16.93
11.81	17.32
10.43	16.73

11.81	17.32
11.61	17.52
-	_
9.84	15.35

8.66	14.37
9.65	15.35
15.75	16.93
15.75	16.93

14.96	14.96	
11.50	14.25	

11.61	14.45
8.74	14.72
•	=
8.66	14.57
11.42	16.14
11.42	10.14

20.47	25.98

20.47	25.98
44 = 0	00 T (
14.76	28.74

14.76	28.74	
20.47	26.38	

20.47	26.38
20.47	26.28
20.47	26.38
20.47	26.38
20.47	26.38
20.47	26.38
20.47	26.38
20.47	26.38
20.47	26.38
20.47	26.38
20.47	26.38
20.47	26.38
20.47	26.38
20.47	26.38
20.47	26.38
20.47	26.38
20.47	26.38
20.47	26.38
20.47	26.38
20.47	26.38
20.47	26.38
20.47	26.38
20.47	26.38
20.47	26.38
20.47	26.38
20.47	26.38
20.47	26.38
20.47	26.38
20.47	26.38
20.47	26.38
20.47	26.38
20.47	26.38
20.47	26.38
20.47	26.38
20.47	26.38
20.47	26.38

<u> </u>	
20.47	26.38
20.47	
	26.20
20.47	26.38
20.47	26.38
20.41	26.38
20.47	26.38
20.47	26.38
20.41	26.38
20.41	26.38
20.41	26.38
20.41	26.38
20.41	26.38
20.41	26.38
20.41	26.38
20.41	26.38
20.41	26.38
20.41	26.38
20.41	26.38
20.41	26.38
20.41	26.38
20.41	26.38
20.41	26.38
20.41	26.38
20.41	26.38
20.41	26.38
20.41	26.38
20.41	26.38
20.41	26.38
20.41	26.38
20.41	26.38
20.41	26.38
20.41	26.38
20.41	26.38
20.41	26.38
20.41	26.38
20.41	26.38
20.41	26.38

20.47	26.38

11.81	3.15	

	T
11.81	3.35
8.86	5.12
8.86	5.12
8.86	5.12
8.86	5.12
8.86	5.12
8.86	5.12
8.86	5.12
8.86	5.12
8.86	5.12
8.86	5.12
8.86	5.12
8.86	5.12
8.86	5.12
8.86	5.12
8.86	5.12
8.86	5.12
8.86	5.12
8.86	5.12
8.86	5.12
8.86	5.12
8.86	5.12
8.86	5.12
8.86	5.12
8.86	5.12
8.86	5.12
8.86	5.12
8.86	5.12
8.86	5.12
8.86	5.12

16.14	9.45	,
10.28	6.30	

16.14	9.45	,
10.28	6.30	

		,
16.14	9.45	
10.28	6.30	

		,
16.14	9.45	
10.28	6.30	

	I	
16.14	9.45	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	

15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	

15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	

16.14	9.45	,
10.28	6.30	

16.14	9.45	,
10.28	6.30	

40.00		
10.28	6.30	
16.14	9.45	
16.14	9.45	
16.14	9.45	
16.14	9.45	
16.14	9.45	
16.14	9.45	
16.14	9.45	
16.14	9.45	
16.14	9.45	
16.14	9.45	
16.14	9.45	
16.14	9.45	
16.14	9.45	
16.14	9.45	
16.14	9.45	
16.14	9.45	
16.14	9.45	
16.14	9.45	
16.14	9.45	
16.14	9.45	
16.14	9.45	
16.14	9.45	
16.14	9.45	

15.35	7.28	
45.25	= 00	
15.35	7.28	
15.35	7.28	
15.55	7.28	
15.55	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
19.39	7.28	
19.39	7.28	
19.39	7.28	
19.39	7.28	
19.39	7.28	
19.39	7.28	
19.39	7.28	
19.39	7.28	
19.39	7.28	
19.39	7.28	
19.39	7.28	
19.39	7.28	
19.39	7.28	
19.39	7.28	
19.39	7.28	
19.39	7.28	
19.39	7.28	

15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	
15.35	7.28	

5.51	6.50
5.51	6.50

22.05	9.06	

22.05	9.06	

22.05	9.06	

22.05	9.06	

22.05	9.06	

22.05	9.06	
22.05	9.00	
16.14	9.45	

15.35	7.28
16.14	9.45
15.35	7.28

11.81	3.15	1
11.01	3.13	
44.04	2.45	
11.81	3.15	
11.81	3.15	
11.81	3.15	
11.81	3.15	
11.81	3.15	
11.81	3.15	
11.81	3.15	
11.81	3.15	
11.81	3.15	
11.81	3.15	
11.81	3.15	
11.81	3.15	
11.81	3.15	
11.81	3.15	
11.81	3.15	
11.81	3.15	
11.81	3.15	
11.81	3.15	
11.81	3.15	

	1
7.76	5.12
	9.06
2.99	7.48
2.99	7.48
9.45	9.45
9.45	9.45
5.51	5.51
0.00	0.00
6.30	5.24
5.75	3.66
7.64	7.48

5.24	4.53
6.85	5.31
6.85	5.31
6.85	5.31

8.86	8.07
7.36	8.27
7.36	8.27
7.36	8.27

7.36	8.27
9.02	8.27
9.02	8.27
9.02	8.27

-	-	r
9.02	8.27	
9.84	4.13	
21.65	11.02	
9.45	3.15	
4.92	2.56	
6.30	2.76	
6.69	2.95	

7.48	2.95
6.69	2.95
20.47	3.35
20.47	3.54
21.65	5.51

9.06	4.53
9.06	4.53
9.06	4.53

	1
20.67	7.48
20.67	7 49
20.67	7.48
20.67	7.48
20.67	7.48
20.67	7.48
20.67	7.48
20.67	7.48
20.67	7.48
20.67	7.48
20.67	7.48
20.67	7.48
20.67	7.48
20.67	7.48
20.67	7.48
20.67	7.48
20.67	7.48
20.67	7.48
20.67	7.48
20.67	7.48
20.67	7.48
20.67	7.48
20.67	7.48
20.67	7.48
20.67	7.48
20.67	7.48
20.67	7.48
20.67	7.48
20.67	7.48
20.67	7.48
20.67	7.48
20.67	7.48

20.67	7.48
7.48	8.66
7.48	8.66
7.48	8.66
7.48	8.66
7.48	8.66
7.48	8.66
7.48	8.66
7.48	8.66
7.48	8.66
7.48	8.66
7.48	8.66
7.48	8.66
7.48	8.66
7.48	8.66
7.48	8.66
7.48	8.66
7.48	8.66
7.48	8.66
7.48	8.66
7.48	8.66

	· · · · · · · · · · · · · · · · · · ·
7.48	8.66
14.37	10.43
14.37	10.43

30.51	8.07	
30.51	8.07	
20.87	14.96	

37.01	10.24
05.00	44.00
35.83	11.02
35.83	11.02
35.83	11.02
35.83	11.02
35.83	11.02
35.83	11.02
35.83	11.02
35.83	11.02
35.83	11.02
35.83	11.02
35.83	11.02
35.83	11.02
35.83	11.02
35.83	11.02
35.83	11.02
35.83	11.02
35.83	11.02
35.83	11.02
35.83	11.02
35.83	11.02
35.83	11.02
35.83	11.02
35.83	11.02
35.83	11.02
35.83	11.02
35.83	11.02
35.83	11.02
35.83	11.02
35.83	11.02
35.83	11.02
35.83	11.02

36.61	11.02
31.89	16.54
31.89	16.54
31.89	16.54
31.89	16.54
31.89	16.54
31.89	16.54
31.89	16.54
31.89	16.54
31.89	16.54
31.89	16.54
31.89	16.54
31.89	16.54
31.89	16.54
31.89	16.54
31.89	16.54
31.89	16.54
31.89	16.54
31.89	16.54
31.89	16.54
31.89	16.54
31.89	16.54
31.89	16.54
31.89	16.54
31.89	16.54
31.89	16.54
31.89	16.54
31.89	16.54
31.89	16.54
31.89	16.54
31.89	16.54
31.89	16.54
31.89	16.54
31.89	16.54
31.89	16.54
31.89	16.54
31.89	16.54

37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78

37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78
37.01	13.78

07.04	444-
37.01	14.17
21.65	5.71
	0.71
	0.11
	0.11
	0.11
	0.11
16.14	11.42

14.17
8.39
11.81
11.81

30.51	17.91
30.51	17.91
35.83	11.81

35.83	11.81
7.48	12.01
32.87	8.27
0.00	0.00

0.00	0.00
0.00	0.00

0.00	0.00
9.06	0.08
9.06	0.08
0.00	0.00

0.00	0.00
0.00	0.00

0.00	0.00
0.00	0.00
0.00	0.00
0.00	0.00

10.51	
12.01	3.35
9.84	1.18
6.30	7.87
6.10	5.51
10.04	5.31
9.84	4.13
14.57	1.57
5.12	3.74
10.24	2.17
4.13	4.33
5.12	5.31
14.37	3.94
7.48	2.95
9.45	3.15
6.89	1.97
5.12	7.48
5.12	7.48
9.84	4.13
9.84	4.13
9.84	4.13

9.84	4.13
9.84	4.13
9.84	4.13
9.45	3.94
5.51	3.54
5.51	3.54
12.80	4.13
13.78	4.72
10.04	5.31
7.48	4.33
10.04	5.31
7.56	7.83
7.28	4.72
17.32	3.35
8.94	5.24
9.06	5.31

7.28	7.28
4.72	3.74
6.30	1.77
9.17	4.13
5.17	4.10
- 10	
5.12	7.48
26.38	3.35
5.12	7.48
7.28	4.72
7.20	4.72
7.28	4.72
17.13	3.54
11.42	9.06
6.30	7.87
0.30	1.01
10.04	5.31
9.84	4.13
	-
5.12	3.74
J.12	3.14
0.40	
6.10	1.38
4.33	1.38

0.05	6.00
8.35	6.22
8.35	6.22
11.57	2.76
11.57	2.76
9.06	3.54
7.56	7.83
8.03	2.91
8.35	6.22
8.35	6.22
8.35	6.22
11.57	2.91
5.51	3.74
5.71	3.23

8.07	6.50
12.60	13.39
7.87	3.15
9.06	3.74
7.40	7.48
14.96	3.94
11.02	0.98
10.43	6.18
5.51	5.31
11.61	2.76
7.87	2.56
9.45	3.15
5.71	3.74
5.31	5.31
4.33	4.33
5.71	1.38

7.28	4.92
9.06	0.20
7.09	2.17
5.12	3.74
10.83	2.20
6.10	1.38
4.72	2.36
7.09	1.57
10.24	8.07
10.24	8.07
13.78	4.33
6.46	0.83
6.46	0.83

10.04	0.79
5.91	0.20
5.91	0.20
8.46	3.94
7.09	1.57
7.09	1.57
7.28	3.94
4.53	13.78
7.48	2.95
7.48	2.95
6.50	1.77
9.84	4.13
7.48	8.07
2.36	1.46
8.27	8.27
•-=-	
- ^^	4
7.09	1.77
5.71	3.23
8.07	6.50

8.27	3.94
9.06	2.48
9.45	3.15
7.09	2.56
5.12	3.74
7.09	4.33
7.09	1.57
9.45	3.15
7.09	1.77
7.09	1.77
5.91	1.97
11.02	0.59
6.69	0.08
10.04	5.31
3.15	0.39
3.74	0.79
8.86	4.33
9.45	3.35

6.30	15.35
5.12	3.74
5.12	3.74
5.12	3.74
5.12	3.74
5.12	3.74
5.12	3.74
5.12	3.74
5.12	3.74
5.12	3.74
4.72	4.72
9.45	3.03
7.09	1.77
4.72	3.54
33.46	11.02
7.09	1.57
2.36	0.39
7.87	0.08
11.81	0.79
9.84	0.79

5.91	1.97
0.04	0.07
9.84	8.27
9.45	3.15
9.45	3.15
7.09	1.77
12.80	3.94
19.29	6.10
8.27	2.95
19.29	6.10
7.28	4.72
8.86	2.17
4.72	2.36
10.83	8.27
11.02	2.24
6.10	1.18

4.53	1.57
4.53	1.57
4.53	1.57
20.47	7.68
9.06	3.94
8.07	3.94
8.86	4.33
7.48	2.95
5.12	3.74
10.04	5.31
7.09	1.77
12.80	3.94
7.87	2.76
5.91	0.08

5.91	0.08
8.03	2.91
4.92	1.57
7.09	1.57
16.46	3.66
7.09	1.77
9.06	2.44
16.54	2.95
14.96	5.12
6.69	1.97
10.24	2.36
5.71	2.95

6.30	1.18
6.69	1.57
7.09	5.91
7.09	1.57
9.45	3.15
12.60	2.36
12.60	2.36
12.60	2.36
12.60	2.36
12.60	1.97
3.94	0.39
4.33	0.83
6.30	2.09
6.30	2.09
20.67	8.86

6.30	3.94
5.98	1.34
16.93	7.48
10.24	7.87
10.24	7.87
20.87	5.91
20.87	5.71
20.87	5.71
4.33	2.09
5.51	7.87
10.24	5.91
15.16	4.72
6.10	1.38
2.36	0.39
3.94	0.39
2.36	0.39
2.36	0.39
3.74	0.39
6.89	0.79
6.69	0.08
4.72	0.47

9.45	3.15
7.09	1.57
6.89	1.38
5.12	3.15
5.31	1.06
9.25	3.07
9.45	3.35
8.27	3.15
6.30	5.51
6.69	0.79
22.05	8.66
22.05	8.66
6.30	5.91
3.94	2.36
6.30	1.38
6.30	1.38
9.84	1.97

7.95	5.39
6.02	1.57
10.63	6.42
10.63	6.42
5.91	1.38
5.12	3.74
5.12	3.74
9.06	2.48
9.06	2.48
15.75	6.10
8.66	1.77

9.06	3.74
5.91	1.38
5.91	1.38
6.69	1.97
4.53	1.69
5.91	1.50
1.97	1.57
6.30	3.94
4.53	1.57
10.63	3.15
4.72	2.36

18.70	2.44
9.45	3.15
4.33	1.18
5.91	1.57
5.91	1.57
6.61	2.44
6.61	2.44

4.13	1.50
6.02	3.19
0.02	5.19
40.04	0.00
10.04	2.36
5.91	1.50
0.01	
5.31	1.57
20.47	4.33
20.47	4.33
8.07	1.97
8.07	1.97
21.65	11.02
21.00	11.02

9.45	3.35
8.27	2.17
0.27	2
7.48	1.77
8.66	2.17
0.00	
11.02	3.35
	0.00
6.10	1.38
6.10	1.38
6.10	1.38
2.76	4.72
•	=
6.30	1.57

4.92	11.81
9.06	3.82
5.51	2.76
4.33	3.54
12.20	4.33
7.87	1.97
6.69	5.71
7.60	9.84
7.00	5.04
4.72	1.57
5.91	1.57
9.45	3.15

6.69	1.38
5.91	1.30
5.91	1.30
20.67	3.54
11.81	3.54
5.91	1.30
11.02	2.17
5.12	1.18
8.86	4.33
9.45	3.15
10.98	2.24
9.45	3.15

2.36	12.20
4.33	1.18
7.48	2.95
5.51	1.18
10.43	2.17
6.69	2.17
8.86	4.33
10.04	5.31
11.81	1.97

8.74	5.16
3.15	0.79
3.94	0.39
7.87	3.35
14.88	6.65
14.88	6.65
14.88	6.65
14.88	6.65

14.88	6.65
7.87	12.20
12.80	3.94
7.48	3.15
7.40	5.15
4.33	1.57
9.17	1.77
9.45	3.15
5.45	0.15
7.48	1.57
3.54	1.97
	1.38
6.10	
6.10	
6.10	
6.10	
6.10	

7.48	2.95
4.13	0.79
4.13	0.79
7.68	5.51
7.00	5.51
8.07	3.54
8.66	2.36

1.38
1.38
2.24
1.57

2.95	2.17
2.95	2.17
2.36	0.59

4.53	1.97
2.36	0.59
4.53	1.97
9.06	3.15

9.06	6.30
8.66	6.30
10.04	4.72
5.91	1.38

9.45	3.35
7.48	2.95
7.48	2.95
3.15	4.53
2.56	3.35
3.15	4.53
2.95	4.53
6.10	1.38
3.94	0.20
9.45	8.07
15.75	10.63
10.04	5.31
15.55	5.31
9.25	6.10
9.45	3.15
5.45	

9.84	4.13
6.10	2.76
9.45	3.15
6.10	1.18
9.45	3.15
5.71	2.17
9.45	3.15
12.80	3.94
0.00	0.00

8.86	3.15
9.65	4.72
9.65	4.72
9.65	4.72
9.65	4.72
9.65	4.72

12.01	4.53
12.20	4.53
12.01	4.53
13.19	10.47
9.06	0.71
9.06	0.71
9.06	0.71
9.06	0.71
9.06	0.71

0.00	0.00
7.28	3.35
6.69	1.18
15.55	1.26
7.09	1.57
6.10	1.18
15.75	0.59
6.50	1.81
0.00	
4.72	1.97
5.51	1.38

7.48	2.95
3.54	4.72
5.16	4.13
5.91	4.33
7.87	2.05

7.09	3.74
10.51	7.87
8.86	7.68

8.86	7.68
9.25	2.56
14.76	4.13
10.04	3.35
10.63	3.35

12.99	3.54
12.99	3.54
21.65	11.02
5.04	1.38
9.06	2.17
0.00	2,
4.72	1.77
5.12	1.38
7.09	3.94
7.09	3.94
	L

9.45	3.15
3.74	2.95
8.27	3.94
3.46	4.61
5.91	1.42
6.10	1.57
5.20	1.57

5.20	1.57
5.91	1.57
5.91	1.57
5.91	1.57
6.50	3.35
5.94	1.50
4.33	1.97

18.11	3.15
4.84	1.57
14.96	5.12

6.10	1.57	
6.10	1.57	
14.57	4.33	

3.94	1.77
3.94	1.77
9.06	3.35

9.06	3.35

L		l

7.68	5.31
11.65	1.97
17.52	3.54
4.33	1.97
18.11	3.54
7.09	3.94